

TEST DATA OF TEPS65F05

Regulated DC Power Supply
October.3. 2023

Approved by : _____ Satoshi Uetani

Design Manager

Prepared by : _____ Riku Nishimura

Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)

COSEL

Model	TEPS65F05
Item	Input Current (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A


2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0	0.005	0.008	0.010
1	0.130	0.087	0.079
2	0.234	0.148	0.135
3	0.330	0.206	0.187
4	0.424	0.262	0.238
5	0.513	0.316	0.287
6	0.603	0.369	0.335
8	0.781	0.477	0.432
10	0.962	0.584	0.530
11	1.056	0.639	0.578
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	TEPS65F05
Item	Efficiency (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0	-	-	-
1	88.3	84.0	82.3
2	88.3	87.2	86.0
3	89.4	88.5	87.6
4	90.2	89.6	88.9
5	91.3	90.7	90.1
6	91.5	91.8	91.1
8	91.2	91.8	91.8
10	90.2	91.7	91.7
11	89.5	91.6	91.8
--	-	-	-

Note: Slanted line shows the range of the rated load current.




COSEL

Model	TEPS65F05	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>0.109</td><td>0.049</td><td>0.043</td></tr> <tr> <td>1</td><td>0.444</td><td>0.349</td><td>0.341</td></tr> <tr> <td>2</td><td>0.493</td><td>0.394</td><td>0.381</td></tr> <tr> <td>3</td><td>0.517</td><td>0.419</td><td>0.404</td></tr> <tr> <td>4</td><td>0.532</td><td>0.433</td><td>0.418</td></tr> <tr> <td>5</td><td>0.542</td><td>0.443</td><td>0.427</td></tr> <tr> <td>6</td><td>0.552</td><td>0.450</td><td>0.433</td></tr> <tr> <td>8</td><td>0.570</td><td>0.464</td><td>0.445</td></tr> <tr> <td>10</td><td>0.585</td><td>0.473</td><td>0.454</td></tr> <tr> <td>11</td><td>0.590</td><td>0.476</td><td>0.457</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.109	0.049	0.043	1	0.444	0.349	0.341	2	0.493	0.394	0.381	3	0.517	0.419	0.404	4	0.532	0.433	0.418	5	0.542	0.443	0.427	6	0.552	0.450	0.433	8	0.570	0.464	0.445	10	0.585	0.473	0.454	11	0.590	0.476	0.457	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.109	0.049	0.043																																																			
1	0.444	0.349	0.341																																																			
2	0.493	0.394	0.381																																																			
3	0.517	0.419	0.404																																																			
4	0.532	0.433	0.418																																																			
5	0.542	0.443	0.427																																																			
6	0.552	0.450	0.433																																																			
8	0.570	0.464	0.445																																																			
10	0.585	0.473	0.454																																																			
11	0.590	0.476	0.457																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	TEPS65F05	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	TEPS65F05	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	_____		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	264 [V]	
DEN-AN	Figure C-1	Both phases	0.03	0.07	0.08	Operation
		One of phases	0.05	0.11	0.13	Stand by
IEC62368-1	Figure C-2	Both phases	0.03	0.07	0.08	Operation
		One of phases	0.05	0.11	0.13	Stand by
	Figure C-3	Both phases	0.03	0.07	0.08	Operation
		One of phases	0.05	0.11	0.13	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	TEPS65F05
Item	Line Regulation
Object	+5V10A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	5.069	-
100	5.069	5.068
115	5.070	5.068
200	5.070	5.068
230	5.070	5.067
264	5.070	5.067
280	5.070	5.067
--	-	-
--	-	-


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	TEPS65F05
Item	Load Regulation
Object	+5V10A

 Temperature 25°C
 Testing Circuitry Figure A

- 1.Graph
- △ — Input Volt. 100V
 - - - □ - - Input Volt. 200V
 - - ○ - - Input Volt. 230V



Note: Slanted line shows the range of the rated load current.


2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0	5.071	5.069	5.070
1	5.071	5.071	5.071
2	5.071	5.071	5.071
3	5.071	5.071	5.071
4	5.071	5.071	5.070
5	5.071	5.071	5.070
6	5.071	5.070	5.070
8	5.071	5.070	5.070
10	5.069	5.069	5.068
11	5.067	5.067	5.064
--	--	--	--

Item	Ripple-Noise
Object	+5V10A

 Temperature 25°C
 Testing Circuitry Figure B

- 1.Graph
- Input Voltage 230V
 Load 100%




COSEL

Model	TEPS65F05	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+5V10A		

Input Volt. 230 V

Cycle 1000 ms



Load 0%(0A) \longleftrightarrow
Load 100%(10A)

200[mV/div]

1[ms/div]

20[ms/div]

Load 50%(5A) \longleftrightarrow
Load 100%(10A)

200[mV/div]

1[ms/div]

20[ms/div]

Load 0%(0A) \longleftrightarrow
Load 50%(5A)

200[mV/div]


1[ms/div]

20[ms/div]

COSEL


Model	TEPS65F05	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+24V2.75A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		442.0	1.5	443.5	11.2	1.2	
230 V		421.5	1.0	422.5	84.3	1.3	




COSEL

Model	TEPS65F05
Item	Hold-Up Time
Object	+5V10A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	18	-
100	27	11
115	38	16
200	129	60
230	173	83
264	232	113
280	264	128
--	-	-
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	TEPS65F05	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+5V10A																																																					
1.Graph	<p>Graph showing Instantaneous Compensation Time [ms] vs Load Current [A] for three input voltages: 100V, 200V, and 230V. The Y-axis is logarithmic from 1 to 1000 ms. The X-axis ranges from 0 to 12 A. Data points are connected by dashed lines. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [ms]</th> <th>Input Volt. 200V [ms]</th> <th>Input Volt. 230V [ms]</th> </tr> </thead> <tbody> <tr><td>1</td><td>~146</td><td>~627</td><td>~833</td></tr> <tr><td>2</td><td>~74</td><td>~322</td><td>~430</td></tr> <tr><td>3</td><td>~48</td><td>~216</td><td>~289</td></tr> <tr><td>4</td><td>~35</td><td>~162</td><td>~217</td></tr> <tr><td>5</td><td>~27</td><td>~130</td><td>~175</td></tr> <tr><td>6</td><td>~21</td><td>~107</td><td>~142</td></tr> <tr><td>8</td><td>~13</td><td>~79</td><td>~107</td></tr> <tr><td>10</td><td>~8</td><td>~61</td><td>~83</td></tr> <tr><td>11</td><td>~6</td><td>~55</td><td>~74</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100V [ms]	Input Volt. 200V [ms]	Input Volt. 230V [ms]	1	~146	~627	~833	2	~74	~322	~430	3	~48	~216	~289	4	~35	~162	~217	5	~27	~130	~175	6	~21	~107	~142	8	~13	~79	~107	10	~8	~61	~83	11	~6	~55	~74	--	-	-	-							
Load Current [A]	Input Volt. 100V [ms]	Input Volt. 200V [ms]	Input Volt. 230V [ms]																																																			
1	~146	~627	~833																																																			
2	~74	~322	~430																																																			
3	~48	~216	~289																																																			
4	~35	~162	~217																																																			
5	~27	~130	~175																																																			
6	~21	~107	~142																																																			
8	~13	~79	~107																																																			
10	~8	~61	~83																																																			
11	~6	~55	~74																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1</td><td>146</td><td>627</td><td>833</td></tr> <tr><td>2</td><td>74</td><td>322</td><td>430</td></tr> <tr><td>3</td><td>48</td><td>216</td><td>289</td></tr> <tr><td>4</td><td>35</td><td>162</td><td>217</td></tr> <tr><td>5</td><td>27</td><td>130</td><td>175</td></tr> <tr><td>6</td><td>21</td><td>107</td><td>142</td></tr> <tr><td>8</td><td>13</td><td>79</td><td>107</td></tr> <tr><td>10</td><td>8</td><td>61</td><td>83</td></tr> <tr><td>11</td><td>6</td><td>55</td><td>74</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	-	-	-	1	146	627	833	2	74	322	430	3	48	216	289	4	35	162	217	5	27	130	175	6	21	107	142	8	13	79	107	10	8	61	83	11	6	55	74	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
1	146	627	833																																																			
2	74	322	430																																																			
3	48	216	289																																																			
4	35	162	217																																																			
5	27	130	175																																																			
6	21	107	142																																																			
8	13	79	107																																																			
10	8	61	83																																																			
11	6	55	74																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	TEPS65F05
Item	Overcurrent Protection
Object	+5V10A

1. Graph



Note: Slanted line shows the range of the rated load current.

Overcurrent protection is Hiccup mode.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
5.00	12.48	12.11
4.75	-	-
4.50	-	-
4.00	-	-
3.50	-	-
3.00	-	-
2.50	-	-
2.00	-	-
1.50	-	-
1.00	-	-
0.50	-	-
0.00	-	-



Model	TEPS65F05	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	+5V10A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-10	5.094	5.093	5.092
25	5.070	5.069	5.067
50	5.053	5.052	5.051

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+5V10A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-10	62	64
25	63	65
50	63	65

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+5V10A	

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-10	5.79	5.79
25	5.79	5.79
50	5.71	5.71

COSEL




Figure A




Figure B

COSEL

