

TEST DATA OF TEPS65F12

Regulated DC Power Supply
October.3. 2023

Approved by : Satoshi Uetani
Design Manager

Prepared by : Riku Nishimura
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)



<p>Model TEPS65F12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Input Current (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p> </p> <p> △ Input Volt. 100V □ Input Volt. 200V ○ Input Volt. 230V </p>		2.Values																																																			
<p style="text-align: center;">Input Current [A]</p> <p style="text-align: center;">Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.005</td><td>0.008</td><td>0.009</td></tr> <tr><td>0.55</td><td>0.164</td><td>0.110</td><td>0.099</td></tr> <tr><td>1.09</td><td>0.291</td><td>0.185</td><td>0.169</td></tr> <tr><td>1.64</td><td>0.414</td><td>0.261</td><td>0.237</td></tr> <tr><td>2.18</td><td>0.531</td><td>0.330</td><td>0.301</td></tr> <tr><td>2.73</td><td>0.645</td><td>0.401</td><td>0.364</td></tr> <tr><td>3.27</td><td>0.755</td><td>0.468</td><td>0.426</td></tr> <tr><td>4.36</td><td>0.973</td><td>0.599</td><td>0.545</td></tr> <tr><td>5.45</td><td>1.194</td><td>0.729</td><td>0.664</td></tr> <tr><td>6.00</td><td>1.310</td><td>0.794</td><td>0.723</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.005	0.008	0.009	0.55	0.164	0.110	0.099	1.09	0.291	0.185	0.169	1.64	0.414	0.261	0.237	2.18	0.531	0.330	0.301	2.73	0.645	0.401	0.364	3.27	0.755	0.468	0.426	4.36	0.973	0.599	0.545	5.45	1.194	0.729	0.664	6.00	1.310	0.794	0.723	--	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.00	0.005	0.008	0.009																																																		
0.55	0.164	0.110	0.099																																																		
1.09	0.291	0.185	0.169																																																		
1.64	0.414	0.261	0.237																																																		
2.18	0.531	0.330	0.301																																																		
2.73	0.645	0.401	0.364																																																		
3.27	0.755	0.468	0.426																																																		
4.36	0.973	0.599	0.545																																																		
5.45	1.194	0.729	0.664																																																		
6.00	1.310	0.794	0.723																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					






<p>Model TEPS65F12</p>		<p>Temperature 25°C</p>																																																				
<p>Item Efficiency (by Load Current)</p>		<p>Testing Circuitry Figure A</p>																																																				
<p>Object _____</p>																																																						
<p>1.Graph</p> <p> △ Input Volt. 100V</p> <p> □ Input Volt. 200V</p> <p> ○ Input Volt. 230V</p>		<p>2.Values</p>																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.55</td><td>89.8</td><td>86.2</td><td>84.7</td></tr> <tr><td>1.09</td><td>89.9</td><td>89.7</td><td>87.7</td></tr> <tr><td>1.64</td><td>90.6</td><td>89.4</td><td>88.8</td></tr> <tr><td>2.18</td><td>91.1</td><td>90.9</td><td>90.2</td></tr> <tr><td>2.73</td><td>91.8</td><td>91.7</td><td>91.2</td></tr> <tr><td>3.27</td><td>92.3</td><td>92.4</td><td>91.9</td></tr> <tr><td>4.36</td><td>92.4</td><td>93.1</td><td>93.0</td></tr> <tr><td>5.45</td><td>91.9</td><td>93.5</td><td>93.3</td></tr> <tr><td>6.00</td><td>91.5</td><td>93.5</td><td>93.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.55	89.8	86.2	84.7	1.09	89.9	89.7	87.7	1.64	90.6	89.4	88.8	2.18	91.1	90.9	90.2	2.73	91.8	91.7	91.2	3.27	92.3	92.4	91.9	4.36	92.4	93.1	93.0	5.45	91.9	93.5	93.3	6.00	91.5	93.5	93.5	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.55	89.8	86.2	84.7																																																			
1.09	89.9	89.7	87.7																																																			
1.64	90.6	89.4	88.8																																																			
2.18	91.1	90.9	90.2																																																			
2.73	91.8	91.7	91.2																																																			
3.27	92.3	92.4	91.9																																																			
4.36	92.4	93.1	93.0																																																			
5.45	91.9	93.5	93.3																																																			
6.00	91.5	93.5	93.5																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						



<p>Model TEPS65F12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item</p>	<p>Power Factor (by Load Current)</p>																																																				
<p>Object</p>	<p>_____</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.138</td><td>0.057</td><td>0.048</td></tr> <tr><td>0.55</td><td>0.452</td><td>0.351</td><td>0.343</td></tr> <tr><td>1.09</td><td>0.503</td><td>0.397</td><td>0.386</td></tr> <tr><td>1.64</td><td>0.529</td><td>0.425</td><td>0.410</td></tr> <tr><td>2.18</td><td>0.545</td><td>0.439</td><td>0.423</td></tr> <tr><td>2.73</td><td>0.558</td><td>0.450</td><td>0.432</td></tr> <tr><td>3.27</td><td>0.568</td><td>0.457</td><td>0.439</td></tr> <tr><td>4.36</td><td>0.588</td><td>0.473</td><td>0.453</td></tr> <tr><td>5.45</td><td>0.602</td><td>0.484</td><td>0.463</td></tr> <tr><td>6.00</td><td>0.606</td><td>0.489</td><td>0.467</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.138	0.057	0.048	0.55	0.452	0.351	0.343	1.09	0.503	0.397	0.386	1.64	0.529	0.425	0.410	2.18	0.545	0.439	0.423	2.73	0.558	0.450	0.432	3.27	0.568	0.457	0.439	4.36	0.588	0.473	0.453	5.45	0.602	0.484	0.463	6.00	0.606	0.489	0.467	--	-	-	-
Load Current [A]	Power Factor																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.00	0.138	0.057	0.048																																																		
0.55	0.452	0.351	0.343																																																		
1.09	0.503	0.397	0.386																																																		
1.64	0.529	0.425	0.410																																																		
2.18	0.545	0.439	0.423																																																		
2.73	0.558	0.450	0.432																																																		
3.27	0.568	0.457	0.439																																																		
4.36	0.588	0.473	0.453																																																		
5.45	0.602	0.484	0.463																																																		
6.00	0.606	0.489	0.467																																																		
--	-	-	-																																																		
<p>1.Graph</p> <p> —△— Input Volt. 100V - - -□- - - Input Volt. 200V - · - ○ - · - Input Volt. 230V </p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																					



Model		TEPS65F12	
Item		Temperature	25°C
Object		Testing Circuitry	Figure A





COSEL		
Model	TEPS65F12	
Item	Leakage Current	Temperature 25°C Testing Circuitry Figure C
Object	_____	

1.Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	264 [V]	
DEN-AN	Figure C-1	Both phases	0.03	0.07	0.08	Operation
		One of phases	0.04	0.11	0.12	Stand by
IEC62368-1	Figure C-2	Both phases	0.03	0.07	0.08	Operation
		One of phases	0.04	0.11	0.12	Stand by
	Figure C-3	Both phases	0.03	0.07	0.08	Operation
		One of phases	0.04	0.11	0.12	Stand by

The value for "One of phases" is the reference value only.

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



COSEL																																		
Model	TEPS65F12																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V5.45A																																	
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>12.106</td> <td>-</td> </tr> <tr> <td>100</td> <td>12.106</td> <td>12.104</td> </tr> <tr> <td>115</td> <td>12.106</td> <td>12.104</td> </tr> <tr> <td>200</td> <td>12.106</td> <td>12.103</td> </tr> <tr> <td>230</td> <td>12.105</td> <td>12.103</td> </tr> <tr> <td>264</td> <td>12.106</td> <td>12.103</td> </tr> <tr> <td>280</td> <td>12.106</td> <td>12.103</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.106	-	100	12.106	12.104	115	12.106	12.104	200	12.106	12.103	230	12.105	12.103	264	12.106	12.103	280	12.106	12.103	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	12.106	-																																
100	12.106	12.104																																
115	12.106	12.104																																
200	12.106	12.103																																
230	12.105	12.103																																
264	12.106	12.103																																
280	12.106	12.103																																
--	-	-																																
--	-	-																																



COSEL																																																					
Model	TEPS65F12																																																				
Item	Load Regulation	Temperature 25°C Testing Circuitry Figure A																																																			
Object	+12V5.45A																																																				
<p>1.Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V - · - ○ - · - - Input Volt. 230V </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.112</td><td>12.113</td><td>12.113</td></tr> <tr><td>0.55</td><td>12.110</td><td>12.110</td><td>12.110</td></tr> <tr><td>1.09</td><td>12.110</td><td>12.109</td><td>12.109</td></tr> <tr><td>1.64</td><td>12.110</td><td>12.109</td><td>12.109</td></tr> <tr><td>2.18</td><td>12.109</td><td>12.109</td><td>12.109</td></tr> <tr><td>2.73</td><td>12.108</td><td>12.109</td><td>12.109</td></tr> <tr><td>3.27</td><td>12.107</td><td>12.107</td><td>12.109</td></tr> <tr><td>4.36</td><td>12.107</td><td>12.107</td><td>12.107</td></tr> <tr><td>5.45</td><td>12.106</td><td>12.106</td><td>12.106</td></tr> <tr><td>6.00</td><td>12.105</td><td>12.105</td><td>12.105</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	12.112	12.113	12.113	0.55	12.110	12.110	12.110	1.09	12.110	12.109	12.109	1.64	12.110	12.109	12.109	2.18	12.109	12.109	12.109	2.73	12.108	12.109	12.109	3.27	12.107	12.107	12.109	4.36	12.107	12.107	12.107	5.45	12.106	12.106	12.106	6.00	12.105	12.105	12.105	--	--	--	--
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.00	12.112	12.113	12.113																																																		
0.55	12.110	12.110	12.110																																																		
1.09	12.110	12.109	12.109																																																		
1.64	12.110	12.109	12.109																																																		
2.18	12.109	12.109	12.109																																																		
2.73	12.108	12.109	12.109																																																		
3.27	12.107	12.107	12.109																																																		
4.36	12.107	12.107	12.107																																																		
5.45	12.106	12.106	12.106																																																		
6.00	12.105	12.105	12.105																																																		
--	--	--	--																																																		
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																																			
Object	+12V5.45A																																																				
<p>1.Graph</p> <p>Input Voltage 230V Load 100%</p> <p style="text-align: center;">50[mV/div]</p> <p style="text-align: center;">40[μs/div]</p>																																																					





Model		TEPS65F12	
Item		Dynamic Load Response	
Object		+12V5.45A	
		Temperature	25°C
		Testing Circuitry	Figure A



Input Volt. 230 V Response. $t_1=t_2=50\mu\text{s}$. Typ
 Cycle 1000 ms





Load 0%(0A) ←→
 Load 100%(5.45A)



Load 50%(2.725A) ←→
 Load 100%(5.45A)




Load 0%(0A) ←→
 Load 50%(2.725A)






Model	TEPS65F12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V5.45A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		445.5	2.5	448.0	7.9	3.1
230 V		423.5	2.0	425.5	62.9	3.3






Model	TEPS65F12
Item	Hold-Up Time
Object	+12V5.45A

Temperature 25°C
 Testing Circuitry Figure A

1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	13	-
100	19	7
115	28	11
200	96	45
230	128	61
264	173	85
280	196	94
--	-	-
--	-	-



<p>Model TEPS65F12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Instantaneous Interruption Compensation</p>																																																					
<p>Object +12V5.45A</p>																																																					
<p>1.Graph</p> <p> </p> <p> △ Input Volt. 100V □ Input Volt. 200V ○ Input Volt. 230V </p> <p style="transform: rotate(-90deg); position: absolute; left: -50px; top: 50%; transform: translateY(-50%);">Instantaneous Compensation Time [ms]</p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.55</td><td>113</td><td>477</td><td>635</td></tr> <tr><td>1.09</td><td>55</td><td>243</td><td>326</td></tr> <tr><td>1.64</td><td>36</td><td>162</td><td>217</td></tr> <tr><td>2.18</td><td>26</td><td>121</td><td>163</td></tr> <tr><td>2.73</td><td>20</td><td>96</td><td>130</td></tr> <tr><td>3.27</td><td>15</td><td>80</td><td>108</td></tr> <tr><td>4.36</td><td>10</td><td>57</td><td>80</td></tr> <tr><td>5.45</td><td>6</td><td>45</td><td>62</td></tr> <tr><td>6.00</td><td>5</td><td>39</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.55	113	477	635	1.09	55	243	326	1.64	36	162	217	2.18	26	121	163	2.73	20	96	130	3.27	15	80	108	4.36	10	57	80	5.45	6	45	62	6.00	5	39	55	--	-	-	-
Load Current [A]	Time [ms]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.00	-	-	-																																																		
0.55	113	477	635																																																		
1.09	55	243	326																																																		
1.64	36	162	217																																																		
2.18	26	121	163																																																		
2.73	20	96	130																																																		
3.27	15	80	108																																																		
4.36	10	57	80																																																		
5.45	6	45	62																																																		
6.00	5	39	55																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



COSEL																																												
Model	TEPS65F12	Temperature	25°C																																									
Item	Overcurrent Protection	Testing Circuitry	Figure A																																									
Object	+12V5.45A																																											
<p>1.Graph</p> <div style="text-align: right;"> <p>— Input Volt. 100V</p> <p>— Input Volt. 230V</p> </div> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Overcurrent protection is Hiccup mode.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>6.39</td><td>6.70</td></tr> <tr><td>11.4</td><td>-</td><td>-</td></tr> <tr><td>10.8</td><td>-</td><td>-</td></tr> <tr><td>9.6</td><td>-</td><td>-</td></tr> <tr><td>8.4</td><td>-</td><td>-</td></tr> <tr><td>7.2</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>-</td><td>-</td></tr> <tr><td>4.8</td><td>-</td><td>-</td></tr> <tr><td>3.6</td><td>-</td><td>-</td></tr> <tr><td>2.4</td><td>-</td><td>-</td></tr> <tr><td>1.2</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	12.0	6.39	6.70	11.4	-	-	10.8	-	-	9.6	-	-	8.4	-	-	7.2	-	-	6.0	-	-	4.8	-	-	3.6	-	-	2.4	-	-	1.2	-	-	0.0	-	-
Output Voltage [V]	Load Current [A]																																											
	Input Volt. 100[V]	Input Volt. 230[V]																																										
12.0	6.39	6.70																																										
11.4	-	-																																										
10.8	-	-																																										
9.6	-	-																																										
8.4	-	-																																										
7.2	-	-																																										
6.0	-	-																																										
4.8	-	-																																										
3.6	-	-																																										
2.4	-	-																																										
1.2	-	-																																										
0.0	-	-																																										

COSEL

COSEL			
Model	TEPS65F12		
Item	Ambient Temperature Drift	Testing Circuitry Figure A	
Object	+12V5.45A		
1.Values		Load 100%	
Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-10	12.111	12.110	12.110
25	12.109	12.108	12.108
50	12.099	12.097	12.097
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A	
Object	+12V5.45A		
1.Values			
Ambient Temperature[°C]	Input Voltage [V]		
	Load 50%	Load 100%	
-10	64	65	
25	65	67	
50	65	67	
Item	Overvoltage Protection	Testing Circuitry Figure A	
Object	+12V5.45A		
1.Values		Load 0%	
Ambient Temperature[°C]	Operating Point [V]		
	Input Volt. 100V	Input Volt. 230V	
-10	14.16	14.16	
25	14.16	14.16	
50	14.16	14.16	




Figure A




Figure B




Figure C-1 (DEN-AN)




Figure C-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure C-3 (IEC62368-1 refer to IEC60990 Fig.5)