



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|--------------|
| Model | TSD-1000-356 |
|-------|--------------|

| No. | P a r t s | | Q' ty of Device | Failure rate [10 ⁻⁶ /H] | Re f e r e n c e |
|--|------------------------|---------------------|-----------------|------------------------------------|------------------|
| 1 | I C | M o n o l i t h i c | 0 | 0.0000 | |
| 2 | | H y b r i d | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 0 | 0.0000 | |
| 4 | D i o d e s | | 0 | 0.0000 | |
| 5 | LED•Optocouplers | | 0 | 0.0000 | |
| 6 | R e s i s t o r s | | 40 | 0.1240 | |
| 7 | C a p a c i t o r s | | 56 | 0.4648 | |
| 8 | Transformer•Choke Coil | | 5 | 0.1150 | |
| 9 | C o n n e c t o r s | | 297 | 0.2005 | |
| 1 0 | O t h e r s | | 3 | 0.0090 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 0.9133 | |

| | | |
|---------------------|------|-----------|
| M T B F | [H] | 1,095,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |