



# TEST DATA OF TSD-600-□□□

## Noise Filter

Dec. 12 , 2023

Approved by : Kazunari Asano  
Design Manager

Prepared by : Yuichi Matsuto  
Design Engineer

**COSEL CO.,LTD.**





## CONTENTS

1.Attenuation Characteristics .....	1
2.Leakage Current .....	4
3.Figure of Testing Circuitry .....	5
(Final Page 6)	



**coSEL**

Model	TSD-600-□□□
Item	Attenuation Characteristics
Object	_____

Temperature 25°C  
Testing Circuitry Figure A


**coSEL**

Model	TSD-600-□□□
Item	Attenuation Characteristics
Object	_____

Temperature 25°C  
Testing Circuitry Figure A

**COSEL**

Model	TSD-600-□□□	Temperature	25°C
Item	Attenuation Characteristics	Testing Circuitry	Figure A
Object	_____		





Model	TSD-600-□□□	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object			

## 1. Results


[mA]

Model	Standards	Voltage system	Input Volt.					Note
			200[V]	250[V]	400[V]	480[V]	500[V]	
TSD-600-105	UL60939	Δ-connection	20.00	25.00	39.00			Δ-connection's rated voltage is 400V(440Vmax)
		Y-connection	0.05	0.05	0.10	0.13	0.14	
TSD-600-215	UL60939	Δ-connection	38.00	46.00	74.50			Δ-connection's rated voltage is 400V(440Vmax)
		Y-connection	0.13	0.15	0.25	0.31	0.32	
TSD-600-665	UL60939	Δ-connection	64.50	78.75	129.00			Δ-connection's rated voltage is 400V(440Vmax)
		Y-connection	0.06	0.08	0.13	0.15	0.16	
TSD-600-136	UL60939	Δ-connection	70.00	87.50	140.00			Δ-connection's rated voltage is 400V(440Vmax)
		Y-connection	0.15	0.18	0.30	0.36	0.38	
TSD-600-186	UL60939	Δ-connection	74.12	92.65	148.24			Δ-connection's rated voltage is 400V(440Vmax)
		Y-connection	0.18	0.23	0.36	0.45	0.46	

## 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**coSEL**



Attenuation =  $20\log(U_{01}/U_{02})$  [dB]  
 $U_{01}$  : Voltage in state without filters  
 $U_{02}$  : Voltage in state which added filters  
N.A. : Network Analyzer





Figure A - 1 Differential mode attenuation measurement



Attenuation =  $20\log(U_{01}/U_{02})$  [dB]  
 $U_{01}$  : Voltage in state without filters  
 $U_{02}$  : Voltage in state which added filters  
N.A. : Network Analyzer




Figure A - 2 Common mode attenuation measurement


**COSEL**

Figure B - 1 Leakage current measurement ( UL60939 Δ-connection)




Figure B - 2 Leakage current measurement ( UL60939 Y-connection)