

TEST DATA OF TUHS5F24

Regulated DC Power Supply

Approved by : Nobuyuki Shiraishi
Nobuyuki Shiraishi Design Manager

Prepared by : Takayuki Yamamoto
Takayuki Yamamoto Design Engineer


COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current) · · · · ·	1
2.Input Power (by Load Current) · · · · ·	2
3.Efficiency (by Input Voltage) · · · · ·	3
4.Efficiency (by Load Current) · · · · ·	4
5.Power Factor (by Input Voltage) · · · · ·	5
6.Power Factor (by Load Current) · · · · ·	6
7.Inrush Current · · · · ·	7
8.Leakage Current · · · · ·	8
9.Line Regulation · · · · ·	9
10.Load Regulation · · · · ·	10
11.Dynamic Load Response · · · · ·	11
12.Ripple Voltage (by Load Current) · · · · ·	12
13.Ripple-Noise · · · · ·	13
14.Ripple Voltage (by Ambient Temperature) · · · · ·	14
15.Ambient Temperature Drift · · · · ·	15
16.Output Voltage Accuracy · · · · ·	16
17.Time Lapse Drift · · · · ·	17
18.Rise and Fall Time · · · · ·	18
19.Hold-Up Time · · · · ·	19
20.Instantaneous Interruption Compensation · · · · ·	20
21.Minimum Input Voltage for Regulated Output Voltage · · · · ·	21
22.Overcurrent Protection · · · · ·	22
23.Oversupply Protection · · · · ·	23
24.Figure of Testing Circuitry · · · · ·	24


(Final Page 25)

Model	TUHS5F24	Temperature Testing Circuitry 25°C Figure A																																																				
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.005</td><td>0.003</td><td>0.003</td></tr> <tr><td>0.04</td><td>0.033</td><td>0.022</td><td>0.020</td></tr> <tr><td>0.08</td><td>0.053</td><td>0.035</td><td>0.032</td></tr> <tr><td>0.12</td><td>0.072</td><td>0.047</td><td>0.043</td></tr> <tr><td>0.16</td><td>0.091</td><td>0.058</td><td>0.053</td></tr> <tr><td>0.20</td><td>0.109</td><td>0.069</td><td>0.063</td></tr> <tr><td>0.22</td><td>0.118</td><td>0.074</td><td>0.068</td></tr> <tr><td>0.24</td><td>0.127</td><td>0.080</td><td>0.073</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.00	0.005	0.003	0.003	0.04	0.033	0.022	0.020	0.08	0.053	0.035	0.032	0.12	0.072	0.047	0.043	0.16	0.091	0.058	0.053	0.20	0.109	0.069	0.063	0.22	0.118	0.074	0.068	0.24	0.127	0.080	0.073																	
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																			
0.00	0.005	0.003	0.003																																																			
0.04	0.033	0.022	0.020																																																			
0.08	0.053	0.035	0.032																																																			
0.12	0.072	0.047	0.043																																																			
0.16	0.091	0.058	0.053																																																			
0.20	0.109	0.069	0.063																																																			
0.22	0.118	0.074	0.068																																																			
0.24	0.127	0.080	0.073																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.005</td><td>0.003</td><td>0.003</td></tr> <tr><td>0.04</td><td>0.033</td><td>0.022</td><td>0.020</td></tr> <tr><td>0.08</td><td>0.053</td><td>0.035</td><td>0.032</td></tr> <tr><td>0.12</td><td>0.072</td><td>0.047</td><td>0.043</td></tr> <tr><td>0.16</td><td>0.091</td><td>0.058</td><td>0.053</td></tr> <tr><td>0.20</td><td>0.109</td><td>0.069</td><td>0.063</td></tr> <tr><td>0.22</td><td>0.118</td><td>0.074</td><td>0.068</td></tr> <tr><td>0.24</td><td>0.127</td><td>0.080</td><td>0.073</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.005	0.003	0.003	0.04	0.033	0.022	0.020	0.08	0.053	0.035	0.032	0.12	0.072	0.047	0.043	0.16	0.091	0.058	0.053	0.20	0.109	0.069	0.063	0.22	0.118	0.074	0.068	0.24	0.127	0.080	0.073	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.005	0.003	0.003																																																			
0.04	0.033	0.022	0.020																																																			
0.08	0.053	0.035	0.032																																																			
0.12	0.072	0.047	0.043																																																			
0.16	0.091	0.058	0.053																																																			
0.20	0.109	0.069	0.063																																																			
0.22	0.118	0.074	0.068																																																			
0.24	0.127	0.080	0.073																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	TUHS5F24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 200V - · -○--- Input Volt. 230V</p>  <table border="1"> <caption>Data points from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.16</td><td>0.17</td><td>0.18</td></tr> <tr><td>0.04</td><td>1.37</td><td>1.47</td><td>1.46</td></tr> <tr><td>0.08</td><td>2.45</td><td>2.54</td><td>2.58</td></tr> <tr><td>0.12</td><td>3.55</td><td>3.61</td><td>3.65</td></tr> <tr><td>0.16</td><td>4.66</td><td>4.69</td><td>4.72</td></tr> <tr><td>0.20</td><td>5.79</td><td>5.78</td><td>5.81</td></tr> <tr><td>0.22</td><td>6.35</td><td>6.33</td><td>6.36</td></tr> <tr><td>0.24</td><td>6.99</td><td>6.93</td><td>6.96</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)	0.00	0.16	0.17	0.18	0.04	1.37	1.47	1.46	0.08	2.45	2.54	2.58	0.12	3.55	3.61	3.65	0.16	4.66	4.69	4.72	0.20	5.79	5.78	5.81	0.22	6.35	6.33	6.36	0.24	6.99	6.93	6.96															
Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)																																																			
0.00	0.16	0.17	0.18																																																			
0.04	1.37	1.47	1.46																																																			
0.08	2.45	2.54	2.58																																																			
0.12	3.55	3.61	3.65																																																			
0.16	4.66	4.69	4.72																																																			
0.20	5.79	5.78	5.81																																																			
0.22	6.35	6.33	6.36																																																			
0.24	6.99	6.93	6.96																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.16</td><td>0.17</td><td>0.18</td></tr> <tr><td>0.04</td><td>1.37</td><td>1.47</td><td>1.46</td></tr> <tr><td>0.08</td><td>2.45</td><td>2.54</td><td>2.58</td></tr> <tr><td>0.12</td><td>3.55</td><td>3.61</td><td>3.65</td></tr> <tr><td>0.16</td><td>4.66</td><td>4.69</td><td>4.72</td></tr> <tr><td>0.20</td><td>5.79</td><td>5.78</td><td>5.81</td></tr> <tr><td>0.22</td><td>6.35</td><td>6.33</td><td>6.36</td></tr> <tr><td>0.24</td><td>6.99</td><td>6.93</td><td>6.96</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.16	0.17	0.18	0.04	1.37	1.47	1.46	0.08	2.45	2.54	2.58	0.12	3.55	3.61	3.65	0.16	4.66	4.69	4.72	0.20	5.79	5.78	5.81	0.22	6.35	6.33	6.36	0.24	6.99	6.93	6.96	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.16	0.17	0.18																																																			
0.04	1.37	1.47	1.46																																																			
0.08	2.45	2.54	2.58																																																			
0.12	3.55	3.61	3.65																																																			
0.16	4.66	4.69	4.72																																																			
0.20	5.79	5.78	5.81																																																			
0.22	6.35	6.33	6.36																																																			
0.24	6.99	6.93	6.96																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	TUHS5F24
Item	Efficiency (by Input Voltage)
Object	—


1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	80.9	81.9
85	81.1	82.9
100	81.2	83.6
120	81.2	84.1
200	79.4	83.9
230	78.4	83.5
264	77.0	82.8
280	75.9	82.3
--	-	-

Note: Slanted line shows the range of the rated input voltage.




Model	TUHS5F24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p>  <p>The graph plots Efficiency [%] on the y-axis (40 to 90) against Load Current [A] on the x-axis (0.00 to 0.30). Three data series are shown: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show efficiency increasing with load current. A vertical slanted line is drawn from approximately 0.20A to 0.23A on the x-axis, representing the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.04</td><td>70.7</td><td>65.7</td><td>65.8</td></tr> <tr> <td>0.08</td><td>79.0</td><td>76.0</td><td>74.8</td></tr> <tr> <td>0.12</td><td>81.7</td><td>80.2</td><td>79.5</td></tr> <tr> <td>0.16</td><td>83.0</td><td>82.3</td><td>81.7</td></tr> <tr> <td>0.20</td><td>83.5</td><td>83.6</td><td>83.1</td></tr> <tr> <td>0.22</td><td>83.6</td><td>83.9</td><td>83.5</td></tr> <tr> <td>0.24</td><td>83.6</td><td>84.3</td><td>83.9</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.04	70.7	65.7	65.8	0.08	79.0	76.0	74.8	0.12	81.7	80.2	79.5	0.16	83.0	82.3	81.7	0.20	83.5	83.6	83.1	0.22	83.6	83.9	83.5	0.24	83.6	84.3	83.9	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.04	70.7	65.7	65.8																																																			
0.08	79.0	76.0	74.8																																																			
0.12	81.7	80.2	79.5																																																			
0.16	83.0	82.3	81.7																																																			
0.20	83.5	83.6	83.1																																																			
0.22	83.6	83.9	83.5																																																			
0.24	83.6	84.3	83.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	TUHS5F24																																
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object	—	—																															
1. Graph																																	
		2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.508</td><td>0.560</td></tr> <tr> <td>85</td><td>0.488</td><td>0.539</td></tr> <tr> <td>100</td><td>0.463</td><td>0.512</td></tr> <tr> <td>120</td><td>0.438</td><td>0.483</td></tr> <tr> <td>200</td><td>0.371</td><td>0.411</td></tr> <tr> <td>230</td><td>0.357</td><td>0.393</td></tr> <tr> <td>264</td><td>0.342</td><td>0.377</td></tr> <tr> <td>280</td><td>0.336</td><td>0.369</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.508	0.560	85	0.488	0.539	100	0.463	0.512	120	0.438	0.483	200	0.371	0.411	230	0.357	0.393	264	0.342	0.377	280	0.336	0.369	--	-	-
Input Voltage [V]	Power Factor																																
	Load 50%	Load 100%																															
75	0.508	0.560																															
85	0.488	0.539																															
100	0.463	0.512																															
120	0.438	0.483																															
200	0.371	0.411																															
230	0.357	0.393																															
264	0.342	0.377																															
280	0.336	0.369																															
--	-	-																															
Note: Slanted line shows the range of the rated input voltage.																																	

Model	TUHS5F24	Temperature Testing Circuitry 25°C Figure A																																																				
Item	Power Factor (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V</th> <th>Input Volt. 200V</th> <th>Input Volt. 230V</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.30</td><td>0.25</td><td>0.25</td></tr> <tr><td>0.05</td><td>0.40</td><td>0.32</td><td>0.32</td></tr> <tr><td>0.10</td><td>0.45</td><td>0.38</td><td>0.38</td></tr> <tr><td>0.15</td><td>0.48</td><td>0.38</td><td>0.38</td></tr> <tr><td>0.20</td><td>0.50</td><td>0.40</td><td>0.40</td></tr> <tr><td>0.24</td><td>0.52</td><td>0.40</td><td>0.40</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V	0.00	0.30	0.25	0.25	0.05	0.40	0.32	0.32	0.10	0.45	0.38	0.38	0.15	0.48	0.38	0.38	0.20	0.50	0.40	0.40	0.24	0.52	0.40	0.40																									
Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V																																																			
0.00	0.30	0.25	0.25																																																			
0.05	0.40	0.32	0.32																																																			
0.10	0.45	0.38	0.38																																																			
0.15	0.48	0.38	0.38																																																			
0.20	0.50	0.40	0.40																																																			
0.24	0.52	0.40	0.40																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.303</td><td>0.250</td><td>0.247</td></tr> <tr><td>0.04</td><td>0.406</td><td>0.327</td><td>0.314</td></tr> <tr><td>0.08</td><td>0.444</td><td>0.357</td><td>0.341</td></tr> <tr><td>0.12</td><td>0.470</td><td>0.377</td><td>0.361</td></tr> <tr><td>0.16</td><td>0.489</td><td>0.392</td><td>0.375</td></tr> <tr><td>0.20</td><td>0.505</td><td>0.405</td><td>0.389</td></tr> <tr><td>0.22</td><td>0.512</td><td>0.411</td><td>0.393</td></tr> <tr><td>0.24</td><td>0.521</td><td>0.416</td><td>0.399</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.303	0.250	0.247	0.04	0.406	0.327	0.314	0.08	0.444	0.357	0.341	0.12	0.470	0.377	0.361	0.16	0.489	0.392	0.375	0.20	0.505	0.405	0.389	0.22	0.512	0.411	0.393	0.24	0.521	0.416	0.399	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.303	0.250	0.247																																																			
0.04	0.406	0.327	0.314																																																			
0.08	0.444	0.357	0.341																																																			
0.12	0.470	0.377	0.361																																																			
0.16	0.489	0.392	0.375																																																			
0.20	0.505	0.405	0.389																																																			
0.22	0.512	0.411	0.393																																																			
0.24	0.521	0.416	0.399																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	TUHS5F24	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	_____		





Model	TUHS5F24	Temperature Testing Circuitry Figure B	25°C
Item	Leakage Current		
Object	_____		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.004	0.005	0.005	Operation
	One of phases	0.003	0.007	0.008	Stand by
IEC60950-1	Both phases	0.002	0.004	0.004	Operation
	One of phases	0.003	0.006	0.007	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of


AC input and by choosing the larger one.

There is no FG in TUHS series and it is a reinforced insulation power supply of the class 2.

Model	TUHS5F24
Item	Line Regulation
Object	+24V0.22A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	24.130	24.121
85	24.130	24.121
100	24.130	24.121
120	24.130	24.121
200	24.133	24.124
230	24.131	24.123
264	24.131	24.123
280	24.130	24.122
--	-	-

Note: Slanted line shows the range of the rated input voltage.

Model	TUHS5F24	Temperature Testing Circuitry 25°C Figure A																																																				
Item	Load Regulation																																																					
Object	+24V0.22A																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 200V - - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [V]</th> <th>200V [V]</th> <th>230V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>24.15</td><td>24.15</td><td>24.15</td></tr> <tr><td>0.05</td><td>24.15</td><td>24.15</td><td>24.15</td></tr> <tr><td>0.10</td><td>24.15</td><td>24.15</td><td>24.15</td></tr> <tr><td>0.15</td><td>24.15</td><td>24.15</td><td>24.15</td></tr> <tr><td>0.20</td><td>24.15</td><td>24.15</td><td>24.15</td></tr> <tr><td>0.21</td><td>24.15</td><td>24.15</td><td>24.15</td></tr> <tr><td>0.22</td><td>24.15</td><td>24.15</td><td>24.15</td></tr> </tbody> </table>	Load Current [A]	100V [V]	200V [V]	230V [V]	0.00	24.15	24.15	24.15	0.05	24.15	24.15	24.15	0.10	24.15	24.15	24.15	0.15	24.15	24.15	24.15	0.20	24.15	24.15	24.15	0.21	24.15	24.15	24.15	0.22	24.15	24.15	24.15																					
Load Current [A]	100V [V]	200V [V]	230V [V]																																																			
0.00	24.15	24.15	24.15																																																			
0.05	24.15	24.15	24.15																																																			
0.10	24.15	24.15	24.15																																																			
0.15	24.15	24.15	24.15																																																			
0.20	24.15	24.15	24.15																																																			
0.21	24.15	24.15	24.15																																																			
0.22	24.15	24.15	24.15																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>24.136</td><td>24.136</td><td>24.132</td></tr> <tr><td>0.04</td><td>24.134</td><td>24.137</td><td>24.134</td></tr> <tr><td>0.08</td><td>24.132</td><td>24.134</td><td>24.132</td></tr> <tr><td>0.12</td><td>24.129</td><td>24.132</td><td>24.130</td></tr> <tr><td>0.16</td><td>24.127</td><td>24.129</td><td>24.128</td></tr> <tr><td>0.20</td><td>24.123</td><td>24.126</td><td>24.125</td></tr> <tr><td>0.22</td><td>24.121</td><td>24.124</td><td>24.123</td></tr> <tr><td>0.24</td><td>24.119</td><td>24.122</td><td>24.120</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	24.136	24.136	24.132	0.04	24.134	24.137	24.134	0.08	24.132	24.134	24.132	0.12	24.129	24.132	24.130	0.16	24.127	24.129	24.128	0.20	24.123	24.126	24.125	0.22	24.121	24.124	24.123	0.24	24.119	24.122	24.120	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	24.136	24.136	24.132																																																			
0.04	24.134	24.137	24.134																																																			
0.08	24.132	24.134	24.132																																																			
0.12	24.129	24.132	24.130																																																			
0.16	24.127	24.129	24.128																																																			
0.20	24.123	24.126	24.125																																																			
0.22	24.121	24.124	24.123																																																			
0.24	24.119	24.122	24.120																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL




Model	TUHS5F24																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																						
Object	+24V0.22A																																							
1. Graph																																								
<p>Input Volt. 100V Input Volt. 230V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>115</td><td>180</td></tr> <tr> <td>0.04</td><td>5</td><td>5</td></tr> <tr> <td>0.08</td><td>10</td><td>5</td></tr> <tr> <td>0.12</td><td>10</td><td>5</td></tr> <tr> <td>0.16</td><td>15</td><td>10</td></tr> <tr> <td>0.20</td><td>25</td><td>10</td></tr> <tr> <td>0.22</td><td>30</td><td>10</td></tr> <tr> <td>0.24</td><td>30</td><td>10</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 230 [V]	0.00	115	180	0.04	5	5	0.08	10	5	0.12	10	5	0.16	15	10	0.20	25	10	0.22	30	10	0.24	30	10	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 230 [V]																																						
0.00	115	180																																						
0.04	5	5																																						
0.08	10	5																																						
0.12	10	5																																						
0.16	15	10																																						
0.20	25	10																																						
0.22	30	10																																						
0.24	30	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p>																																								
<p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	TUHS5F24																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure C																																						
Object	+24V0.22A																																							
1. Graph																																								
<p>Input Volt. 100V Input Volt. 230V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>130</td> <td>200</td> </tr> <tr> <td>0.04</td> <td>5</td> <td>10</td> </tr> <tr> <td>0.08</td> <td>10</td> <td>10</td> </tr> <tr> <td>0.12</td> <td>15</td> <td>10</td> </tr> <tr> <td>0.16</td> <td>15</td> <td>10</td> </tr> <tr> <td>0.20</td> <td>25</td> <td>10</td> </tr> <tr> <td>0.22</td> <td>30</td> <td>10</td> </tr> <tr> <td>0.24</td> <td>30</td> <td>10</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 230 [V]	0.00	130	200	0.04	5	10	0.08	10	10	0.12	15	10	0.16	15	10	0.20	25	10	0.22	30	10	0.24	30	10	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 100 [V]	Input Volt. 230 [V]																																						
0.00	130	200																																						
0.04	5	10																																						
0.08	10	10																																						
0.12	15	10																																						
0.16	15	10																																						
0.20	25	10																																						
0.22	30	10																																						
0.24	30	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple-Noise [mVp-p]</p> <p>T1</p> <p>T2</p>																																								
Fig. Complex Ripple Wave Form																																								

Model	TUHS5F24	Testing Circuitry Figure C																																			
Item	Ripple Voltage (by Ambient Temp.)																																				
Object	+24V0.22A																																				
1.Graph		2.Values																																			
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C] for TUHS5F24 at Load 100%.</p> <p>Legend:</p> <ul style="list-style-type: none"> - - - □ - - - Input Volt. 100V — △ — Input Volt. 200V <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>-45</td><td>20</td><td>10</td></tr> <tr><td>-40</td><td>20</td><td>10</td></tr> <tr><td>-20</td><td>25</td><td>10</td></tr> <tr><td>0</td><td>25</td><td>10</td></tr> <tr><td>25</td><td>30</td><td>10</td></tr> <tr><td>50</td><td>30</td><td>10</td></tr> <tr><td>70</td><td>35</td><td>10</td></tr> <tr><td>80</td><td>40</td><td>15</td></tr> <tr><td>85</td><td>40</td><td>15</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	-45	20	10	-40	20	10	-20	25	10	0	25	10	25	30	10	50	30	10	70	35	10	80	40	15	85	40	15	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																			
-45	20	10																																			
-40	20	10																																			
-20	25	10																																			
0	25	10																																			
25	30	10																																			
50	30	10																																			
70	35	10																																			
80	40	15																																			
85	40	15																																			
--	-	-																																			
--	-	-																																			
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																					

Model	TUHS5F24
Item	Ambient Temperature Drift
Object	+24V0.22A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-45	24.162	24.164	24.165
-40	24.166	24.169	24.169
-20	24.173	24.176	24.176
0	24.162	24.166	24.166
25	24.121	24.124	24.123
50	24.069	24.074	24.074
70	24.014	24.021	24.021
80	24.002	24.009	24.009
85	23.992	24.000	23.999
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	TUHS5F24	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+24V0.22A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 80°C

Input Voltage : 85 - 264V

Load Current : 0 - 0.22A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	85	0	24.182	±95	±0.4
Minimum Voltage	80	85	0.22	23.993		

COSEL

Model	TUHS5F24
Item	Time Lapse Drift
Object	+24V0.22A

1. Graph



2. Values

Time since start [H]	Output Voltage [V]
0.0	24.121
0.5	24.107
1.0	24.107
2.0	24.106
3.0	24.106
4.0	24.106
5.0	24.106
6.0	24.106
7.0	24.106
8.0	24.106


* The characteristic of AC230V is equal.

COSEL

Model	TUHS5F24
Item	Rise and Fall Time
Object	+24V0.22A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		31.3	0.8	32.1	23.0	25.8	
230 V		30.8	0.8	31.6	180.0	26.3	



Model	TUHS5F24
Item	Hold-Up Time
Object	+24V0.22A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	28	7
85	38	13
100	57	23
120	88	38
200	268	132
230	360	180
264	481	244
280	544	277
--	-	-


This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

Model	TUHS5F24	Temperature Testing Circuitry 25°C Figure A																																																				
Item	Instantaneous Interruption Compensation																																																					
Object	+24V0.22A																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>0.05</td><td>~80</td><td>~80</td><td>~900</td></tr> <tr><td>0.10</td><td>~60</td><td>~60</td><td>~700</td></tr> <tr><td>0.15</td><td>~45</td><td>~45</td><td>~550</td></tr> <tr><td>0.20</td><td>~30</td><td>~30</td><td>~350</td></tr> <tr><td>0.25</td><td>~20</td><td>~20</td><td>~250</td></tr> </tbody> </table>	Load Current [A]	100V [ms]	200V [ms]	230V [ms]	0.05	~80	~80	~900	0.10	~60	~60	~700	0.15	~45	~45	~550	0.20	~30	~30	~350	0.25	~20	~20	~250																													
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																			
0.05	~80	~80	~900																																																			
0.10	~60	~60	~700																																																			
0.15	~45	~45	~550																																																			
0.20	~30	~30	~350																																																			
0.25	~20	~20	~250																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.04</td><td>85</td><td>542</td><td>722</td></tr> <tr><td>0.08</td><td>71</td><td>451</td><td>601</td></tr> <tr><td>0.12</td><td>57</td><td>360</td><td>481</td></tr> <tr><td>0.16</td><td>43</td><td>268</td><td>361</td></tr> <tr><td>0.20</td><td>30</td><td>177</td><td>240</td></tr> <tr><td>0.22</td><td>23</td><td>132</td><td>180</td></tr> <tr><td>0.24</td><td>15</td><td>82</td><td>114</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.04	85	542	722	0.08	71	451	601	0.12	57	360	481	0.16	43	268	361	0.20	30	177	240	0.22	23	132	180	0.24	15	82	114	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.04	85	542	722																																																			
0.08	71	451	601																																																			
0.12	57	360	481																																																			
0.16	43	268	361																																																			
0.20	30	177	240																																																			
0.22	23	132	180																																																			
0.24	15	82	114																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	TUHS5F24
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+24V0.22A

Testing Circuitry Figure A

1. Graph




2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-45	39	61
-40	37	60
-20	34	58
0	33	58
25	33	58
50	33	58
70	33	58
80	33	58
85	33	58
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	TUHS5F24	Temperature Testing Circuitry 25°C Figure A
Item	Overcurrent Protection	
Object	+24V0.22A	

1. Graph




Note: Slanted line shows the range of the rated load current.

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
24.0	0.30	0.39
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Model	TUHS5F24
Item	Oversupply Protection
Object	+24V0.22A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-45	29.36	29.74
-40	29.46	29.81
-20	29.82	30.09
0	30.29	30.53
25	30.63	31.02
50	30.99	31.31
70	31.26	31.52
80	31.52	31.62
85	31.62	31.68
--	-	-
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)

COSEL




Figure C