

# TEST DATA OF TUNS700F28

Regulated DC Power Supply  
May 28, 2015

Approved by : Takayuki Fukuda  
Takayuki Fukuda Design Manager

Prepared by : Kousuke Takarada  
Kousuke Takarada Design Engineer

**COSEL CO.,LTD.**

## CONTENTS


1.Input Current (by Load Current) .....	1
2.Input Power (by Load Current) .....	2
3.Efficiency (by Input Voltage) .....	3
4.Efficiency (by Load Current) .....	4
5.Power Factor (by Input Voltage) .....	5
6.Power Factor (by Load Current) .....	6
7.Inrush Current .....	7
8.Leakage Current .....	8
9.Line Regulation .....	9
10.Load Regulation .....	10
11.Dynamic Load Response .....	11
12.Ripple Voltage (by Load Current) .....	12
13.Ripple-Noise .....	13
14.Ripple Voltage (by Ambient Temperature) .....	14
15.Ambient Temperature Drift .....	15
16.Output Voltage Accuracy .....	16
17.Time Lapse Drift .....	17
18.Rise and Fall Time .....	18
19.Hold-Up Time .....	19
20.Instantaneous Interruption Compensation .....	20
21.Minimum Input Voltage for Regulated Output Voltage .....	21
22.Overcurrent Protection .....	22
23.Overvoltage Protection .....	23
24.Figure of Testing Circuitry .....	24,25

(Final Page 25)

Model	TUNS700F28
Item	Input Current (by Load Current)
Object	_____

## 1.Graph

—△— Input Volt. 100V  
 - - -□--- Input Volt. 200V  
 - - ○--- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	0.240	0.440	0.504
5.0	1.738	0.962	0.904
10.0	3.268	1.672	1.500
15.0	4.860	2.418	2.136
20.0	6.480	3.185	2.794
25.0	8.140	3.970	3.466
27.5	9.000	4.370	3.810
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	TUNS700F28	Temperature Testing Circuitry 25°C Figure A
Item	Input Power (by Load Current)	
Object	_____	
1.Graph	<p>—△— Input Volt. 100V      - - □ - - Input Volt. 200V      - - ○ - - Input Volt. 230V</p> <p>The graph plots Input Power [W] on the Y-axis (0 to 1000) against Load Current [A] on the X-axis (0 to 30). Three curves are shown for different input voltages: 100V (solid line with triangle markers), 200V (dashed line with square markers), and 230V (dash-dot line with circle markers). All curves show a linear increase in power with load current. A slanted line is drawn across the graph, starting from approximately (5, 150) and ending at (25, 850), representing the rated load current range.</p>	2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	3.0	2.8	2.9
5.0	168.9	164.0	163.0
10.0	323.1	315.0	313.0
15.0	481.0	468.0	466.0
20.0	643.0	623.0	620.0
25.0	809.0	781.0	776.0
27.5	895.0	861.0	857.0
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.


**COSEL**

Model TUNS700F28

Item Efficiency (by Input Voltage)

Object \_\_\_\_\_

## 1. Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C  
 Testing Circuitry Figure A

## 2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	85.8	84.2
85	86.0	84.8
100	86.9	86.4
120	87.5	87.4
200	89.3	89.5
230	89.7	89.9
264	90.2	90.3
280	90.4	90.5
--	-	-


**COSEL**

Model	TUNS700F28																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V        - - -□- Input Volt. 200V        - - ○- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>5</td><td>82.7</td><td>85.1</td><td>85.7</td></tr> <tr><td>10</td><td>86.4</td><td>88.6</td><td>89.2</td></tr> <tr><td>15</td><td>87.1</td><td>89.5</td><td>89.9</td></tr> <tr><td>20</td><td>86.9</td><td>89.7</td><td>90.2</td></tr> <tr><td>25</td><td>86.4</td><td>89.5</td><td>89.9</td></tr> <tr><td>27.5</td><td>85.9</td><td>89.3</td><td>89.7</td></tr> </tbody> </table>			Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	5	82.7	85.1	85.7	10	86.4	88.6	89.2	15	87.1	89.5	89.9	20	86.9	89.7	90.2	25	86.4	89.5	89.9	27.5	85.9	89.3	89.7																							
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																			
5	82.7	85.1	85.7																																																			
10	86.4	88.6	89.2																																																			
15	87.1	89.5	89.9																																																			
20	86.9	89.7	90.2																																																			
25	86.4	89.5	89.9																																																			
27.5	85.9	89.3	89.7																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>5.0</td><td>82.7</td><td>85.1</td><td>85.7</td></tr> <tr><td>10.0</td><td>86.4</td><td>88.6</td><td>89.2</td></tr> <tr><td>15.0</td><td>87.1</td><td>89.5</td><td>89.9</td></tr> <tr><td>20.0</td><td>86.9</td><td>89.7</td><td>90.2</td></tr> <tr><td>25.0</td><td>86.4</td><td>89.5</td><td>89.9</td></tr> <tr><td>27.5</td><td>85.9</td><td>89.3</td><td>89.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	5.0	82.7	85.1	85.7	10.0	86.4	88.6	89.2	15.0	87.1	89.5	89.9	20.0	86.9	89.7	90.2	25.0	86.4	89.5	89.9	27.5	85.9	89.3	89.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
5.0	82.7	85.1	85.7																																																			
10.0	86.4	88.6	89.2																																																			
15.0	87.1	89.5	89.9																																																			
20.0	86.9	89.7	90.2																																																			
25.0	86.4	89.5	89.9																																																			
27.5	85.9	89.3	89.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	TUNS700F28
Item	Power Factor (by Input Voltage)
Object	—

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
80	0.993	0.994
85	0.993	0.995
100	0.991	0.996
120	0.990	0.994
200	0.958	0.984
230	0.933	0.974
264	0.896	0.961
270	0.894	0.959
280	0.386	0.438

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	TUNS700F28	Temperature 25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry Figure A																																																			
Object																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul>																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.183</td><td>0.042</td><td>0.032</td></tr> <tr><td>2.5</td><td>0.944</td><td>0.704</td><td>0.600</td></tr> <tr><td>5.0</td><td>0.974</td><td>0.854</td><td>0.784</td></tr> <tr><td>10.0</td><td>0.990</td><td>0.943</td><td>0.907</td></tr> <tr><td>15.0</td><td>0.992</td><td>0.969</td><td>0.949</td></tr> <tr><td>20.0</td><td>0.994</td><td>0.978</td><td>0.966</td></tr> <tr><td>25.0</td><td>0.996</td><td>0.984</td><td>0.974</td></tr> <tr><td>27.5</td><td>0.996</td><td>0.985</td><td>0.977</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.183	0.042	0.032	2.5	0.944	0.704	0.600	5.0	0.974	0.854	0.784	10.0	0.990	0.943	0.907	15.0	0.992	0.969	0.949	20.0	0.994	0.978	0.966	25.0	0.996	0.984	0.974	27.5	0.996	0.985	0.977	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	0.183	0.042	0.032																																																		
2.5	0.944	0.704	0.600																																																		
5.0	0.974	0.854	0.784																																																		
10.0	0.990	0.943	0.907																																																		
15.0	0.992	0.969	0.949																																																		
20.0	0.994	0.978	0.966																																																		
25.0	0.996	0.984	0.974																																																		
27.5	0.996	0.985	0.977																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		




Note: Slanted line shows the range of the rated load current.

**COSEL**

Model TUNS700F28

Item Inrush Current

Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure A



Model	TUNS700F28	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

### 1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240[V]	
IEC60950-1	Both phases	0.16	0.33	0.40	Operation
	One of phase	0.30	0.63	0.77	stand by

The value for "One phase" is the reference value only.

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSSEL**

Model TUNS700F28


Item Line Regulation

Object +28V25A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph

---□--- Load 50%  
 —△— Load 100%



Note: Slanted line shows the range of the rated input voltage.

## 2. Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	28.006	28.005
85	28.006	28.005
100	28.006	28.005
120	28.006	28.005
200	28.006	28.005
230	28.006	28.005
264	28.006	28.005
280	28.006	28.006
--	-	-

**COSEL**

Model TUNS700F28

Item Load Regulation

Object +28V25A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	28.010	28.010	28.010
5.0	28.006	28.006	28.006
10.0	28.006	28.006	28.006
15.0	28.006	28.006	28.006
20.0	28.005	28.005	28.005
25.0	28.005	28.005	28.005
27.5	28.005	28.005	28.005
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model TUNS700F28

Item Dynamic Load Response


Object +28V 25A

Temperature 25°C  
Testing Circuitry Figure AInput Volt. 100V  
Cycle 1000ms


Load Current 25A / 100us

Min.Load (0A)↔  
Load 100%(25A)

1 V/div




400 us/div




40 ms/div

Min.Load (0A)↔  
Load 50%(12.5A)

1 V/div




400 us/div




40 ms/div

Load 10% (2.5A)↔  
Load 100% (25A)

1 V/div



400 us/div



40 ms/div

**COSEL**

Model	TUNS700F28	Temperature Testing Circuitry 25°C Figure C																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+28V25A																																							
1.Graph																																								
<p>—△— Input Volt. 100V ---○--- Input Volt. 200V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input 100V)</th> <th>Ripple Voltage [mV] (Input 200V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>40</td><td>40</td></tr> <tr><td>5</td><td>60</td><td>60</td></tr> <tr><td>10</td><td>60</td><td>60</td></tr> <tr><td>15</td><td>60</td><td>60</td></tr> <tr><td>20</td><td>65</td><td>60</td></tr> <tr><td>25</td><td>65</td><td>60</td></tr> <tr><td>30</td><td>350</td><td>350</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (Input 100V)	Ripple Voltage [mV] (Input 200V)	0	40	40	5	60	60	10	60	60	15	60	60	20	65	60	25	65	60	30	350	350														
Load Current [A]	Ripple Voltage [mV] (Input 100V)	Ripple Voltage [mV] (Input 200V)																																						
0	40	40																																						
5	60	60																																						
10	60	60																																						
15	60	60																																						
20	65	60																																						
25	65	60																																						
30	350	350																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>35</td><td>35</td></tr> <tr><td>5.0</td><td>60</td><td>55</td></tr> <tr><td>10.0</td><td>60</td><td>60</td></tr> <tr><td>15.0</td><td>60</td><td>60</td></tr> <tr><td>20.0</td><td>65</td><td>60</td></tr> <tr><td>25.0</td><td>60</td><td>60</td></tr> <tr><td>27.5</td><td>65</td><td>65</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	35	35	5.0	60	55	10.0	60	60	15.0	60	60	20.0	65	60	25.0	60	60	27.5	65	65	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.0	35	35																																						
5.0	60	55																																						
10.0	60	60																																						
15.0	60	60																																						
20.0	65	60																																						
25.0	60	60																																						
27.5	65	65																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p> <p>Fig. Complex Ripple Wave Form</p>																																								

**COSEL**


Model TUNS700F28

Item Ripple-Noise

Object +28V25A

Temperature 25°C  
Testing Circuitry Figure C

## 1. Graph



## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	45	45
5.0	70	65
10.0	70	70
15.0	70	75
20.0	75	75
25.0	75	75
27.5	80	80
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.



T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

Model	TUNS700F28
Item	Ripple Voltage (by Ambient Temp.)
Object	+28V25A

Testing Circuitry Figure C

## 1. Graph



## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	90	95
-40	80	90
-20	80	80
0	70	70
25	60	60
50	60	60
75	60	60
85	60	60
100	55	55
105	55	55
--	-	-


Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	TUNS700F28
Item	Ambient Temperature Drift
Object	+28V25A

## 1.Graph

—△— Input Volt. 100V  
 - -□--- Input Volt. 200V  
 - -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-50	27.838	27.841	27.843
-40	27.867	27.871	27.873
-20	27.917	27.921	27.922
0	27.963	27.966	27.967
25	28.005	28.005	28.005
50	28.019	28.020	28.020
70	28.033	28.035	28.036
75	28.044	28.047	28.050
--	-	-	-
--	-	-	-
--	-	-	-



Model	TUNS700F28
Item	Output Voltage Accuracy
Object	+28V25A

Testing Circuitry Figure A

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 70°C

Input Voltage : 85 - 264V

Load Current : 0 - 25A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	70	85	0	28.038	±86	±0.3
Minimum Voltage	-40	85	25	27.867		

**COSEL**

Model	TUNS700F28
Item	Time Lapse Drift
Object	+28V25A

## 1. Graph



\* The characteristic of AC200V is equal.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values


Time since start [H]	Output Voltage [V]
0.0	28.002
0.5	28.004
1.0	28.004
2.0	28.005
3.0	28.005
4.0	28.005
5.0	28.005
6.0	28.005
7.0	28.005
8.0	28.005

**COSEL**

Model	TUNS700F28
Item	Rise and Fall Time
Object	+28V25A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		527.0	11.0	538.0	33.5	9.2	
230 V		493.0	11.0	504.0	33.8	9.1	



**COSEL**


Model	TUNS700F28	Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time																																	
Object	+28V25A																																	
1.Graph		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>80</td><td>56</td><td>24</td></tr> <tr><td>85</td><td>55</td><td>26</td></tr> <tr><td>100</td><td>56</td><td>26</td></tr> <tr><td>120</td><td>56</td><td>26</td></tr> <tr><td>200</td><td>56</td><td>26</td></tr> <tr><td>230</td><td>56</td><td>26</td></tr> <tr><td>264</td><td>56</td><td>26</td></tr> <tr><td>280</td><td>60</td><td>26</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	56	24	85	55	26	100	56	26	120	56	26	200	56	26	230	56	26	264	56	26	280	60	26	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
80	56	24																																
85	55	26																																
100	56	26																																
120	56	26																																
200	56	26																																
230	56	26																																
264	56	26																																
280	60	26																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**

Model TUNS700F28

Item Instantaneous Interruption Compensation

Object +28V25A

Temperature 25°C  
Testing Circuitry Figure A


2.Values

Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	-	-	-
5.0	142	142	142
10.0	71	71	71
15.0	46	46	46
20.0	31	34	34
25.0	26	26	26
27.5	21	24	24
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

Model	TUNS700F28
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+28V25A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-50	72	72
-40	72	72
-20	72	71
0	72	72
25	73	74
50	73	75
70	73	76
75	73	75
--	-	-
--	-	-
--	-	-


**COSEL**

Model TUNS700F28

Item Overcurrent Protection

Object +28V25A

## 1. Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 20V to 0V.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
28.0	24.85	24.87
26.6	30.66	30.67
25.2	31.16	31.16
22.4	32.01	32.00
20.0	32.72	32.67
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-


**COSEL**

Model TUNS700F28

Item Overvoltage Protection

Object +28V25A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-50	37.16	37.16
-40	37.16	37.16
-20	37.27	37.27
0	37.39	37.39
25	37.45	37.45
50	37.45	37.45
70	37.44	37.45
75	37.45	37.45
--	-	-
--	-	-
--	-	-





Figure B ( DEN-AN )






Figure B ( IEC60950-1 )



C10 : TUNS700F12  $2200\mu F$  ( $0 \leq T_c \leq 100$ )  
 $2200\mu F \times 3$  ( $-40 \leq T_c < 0$ )  
 TUNS700F28  $1000\mu F$  ( $0 \leq T_c \leq 100$ )  
 $1000\mu F \times 3$  ( $-40 \leq T_c < 0$ )  
 TUNS700F48  $470\mu F$  ( $0 \leq T_c \leq 100$ )  
 $470\mu F \times 3$  ( $-40 \leq T_c < 0$ )

Tc:Base Plate Temp.

Figure C



L1,L2 : ADM-25-12-060T(Ueno)  
 C1,C2 :  $1.5\mu F$  275V Film Capacitor  
 C3 :  $1.5\mu F$  275V Film Capacitor  $\times 2$   
 C4,C5,C9 :  $2200\mu F$  Ceramic Capacitor  
 C6,C7 :  $0.68\mu F$  450V Film Capacitor  $\times 2$   
 C8 :  $390\mu F$  450V Electrolytic Capacitor  $\times 2$   
 C10 : TUNS700F12  $2200\mu F$  25V Electrolytic Capacitor  
 TUNS700F28  $1000\mu F$  50V Electrolytic Capacitor  
 TUNS700F48  $470\mu F$  63V Electrolytic Capacitor

C11 : TUNS700F12  $10\mu F$  Ceramic Capacitor  
 TUNS700F28  $4.7\mu F$  Ceramic Capacitor  
 TUNS700F48  $2.2\mu F$  Ceramic Capacitor

Figure D