

# TEST DATA OF TUXS150F50

Regulated DC Power Supply  
November 06, 2015

Approved by : Yoshimichi Hirokawa  
Yoshimichi Hirokawa Design Manager

Prepared by : Tomoki Sodeno  
Tomoki Sodeno Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1. Input Current (by Load Current) . . . . .	1
2. Input Power (by Load Current) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Current) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Current) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Current) . . . . .	12
13. Ripple-Noise . . . . .	13
14. Ripple Voltage (by Ambient Temperature) . . . . .	14
15. Ambient Temperature Drift . . . . .	15
16. Output Voltage Accuracy . . . . .	16
17. Time Lapse Drift . . . . .	17
18. Rise and Fall Time . . . . .	18
19. Hold-Up Time . . . . .	19
20. Instantaneous Interruption Compensation . . . . .	20
21. Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22. Overcurrent Protection . . . . .	22
23. Overvoltage Protection . . . . .	23
24. Figure of Testing Circuitry . . . . .	24 25

(Final Page 25)

Model	TUXS150F50	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Input Current (by Load Current)																																																						
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 100V      - -□--- Input Volt. 200V      - ·○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.091</td><td>0.153</td><td>0.173</td></tr> <tr><td>0.6</td><td>0.393</td><td>0.249</td><td>0.247</td></tr> <tr><td>1.2</td><td>0.697</td><td>0.385</td><td>0.354</td></tr> <tr><td>1.8</td><td>1.004</td><td>0.530</td><td>0.476</td></tr> <tr><td>2.4</td><td>1.314</td><td>0.678</td><td>0.602</td></tr> <tr><td>3.0</td><td>1.632</td><td>0.831</td><td>0.732</td></tr> <tr><td>3.3</td><td>1.792</td><td>0.906</td><td>0.798</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.0	0.091	0.153	0.173	0.6	0.393	0.249	0.247	1.2	0.697	0.385	0.354	1.8	1.004	0.530	0.476	2.4	1.314	0.678	0.602	3.0	1.632	0.831	0.732	3.3	1.792	0.906	0.798																						
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																				
0.0	0.091	0.153	0.173																																																				
0.6	0.393	0.249	0.247																																																				
1.2	0.697	0.385	0.354																																																				
1.8	1.004	0.530	0.476																																																				
2.4	1.314	0.678	0.602																																																				
3.0	1.632	0.831	0.732																																																				
3.3	1.792	0.906	0.798																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.091</td><td>0.153</td><td>0.173</td></tr> <tr><td>0.6</td><td>0.393</td><td>0.249</td><td>0.247</td></tr> <tr><td>1.2</td><td>0.697</td><td>0.385</td><td>0.354</td></tr> <tr><td>1.8</td><td>1.004</td><td>0.530</td><td>0.476</td></tr> <tr><td>2.4</td><td>1.314</td><td>0.678</td><td>0.602</td></tr> <tr><td>3.0</td><td>1.632</td><td>0.831</td><td>0.732</td></tr> <tr><td>3.3</td><td>1.792</td><td>0.906</td><td>0.798</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.091	0.153	0.173	0.6	0.393	0.249	0.247	1.2	0.697	0.385	0.354	1.8	1.004	0.530	0.476	2.4	1.314	0.678	0.602	3.0	1.632	0.831	0.732	3.3	1.792	0.906	0.798	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.0	0.091	0.153	0.173																																																				
0.6	0.393	0.249	0.247																																																				
1.2	0.697	0.385	0.354																																																				
1.8	1.004	0.530	0.476																																																				
2.4	1.314	0.678	0.602																																																				
3.0	1.632	0.831	0.732																																																				
3.3	1.792	0.906	0.798																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.



Model	TUXS150F50	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	—																																																					
1.Graph	<p>—△— Input Volt. 100V        - - □ - - Input Volt. 200V        - - ○ - - Input Volt. 230V</p> <p>The graph plots Input Power [W] on the Y-axis (0 to 200) against Load Current [A] on the X-axis (0.0 to 3.0). Three curves are shown for different input voltages: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show a linear increase in power with load current. A slanted line is drawn across the graph, starting from approximately (0.5, 10) and ending at (3.0, 170), indicating the range of the rated load current.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>4.7</td><td>5.0</td><td>5.2</td></tr> <tr><td>0.6</td><td>35.8</td><td>36.7</td><td>37.4</td></tr> <tr><td>1.2</td><td>66.7</td><td>67.1</td><td>67.5</td></tr> <tr><td>1.8</td><td>97.8</td><td>97.5</td><td>97.9</td></tr> <tr><td>2.4</td><td>129.1</td><td>128.1</td><td>128.3</td></tr> <tr><td>3.0</td><td>161.1</td><td>159.1</td><td>159.0</td></tr> <tr><td>3.3</td><td>177.0</td><td>174.7</td><td>174.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	4.7	5.0	5.2	0.6	35.8	36.7	37.4	1.2	66.7	67.1	67.5	1.8	97.8	97.5	97.9	2.4	129.1	128.1	128.3	3.0	161.1	159.1	159.0	3.3	177.0	174.7	174.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	4.7	5.0	5.2																																																			
0.6	35.8	36.7	37.4																																																			
1.2	66.7	67.1	67.5																																																			
1.8	97.8	97.5	97.9																																																			
2.4	129.1	128.1	128.3																																																			
3.0	161.1	159.1	159.0																																																			
3.3	177.0	174.7	174.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	TUXS150F50
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	90.5	92.2
85	90.8	92.5
100	91.2	93.2
120	91.4	93.7
200	91.7	94.2
230	91.9	94.3
264	91.9	94.4
280	92.1	94.6
--	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model	TUXS150F50	Temperature	25°C																																																					
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																					
Object	<hr/>																																																							
1.Graph	—△— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V																																																							
<p>The graph shows efficiency increasing from approximately 84% at 0.7A to 93% at 3.0A for 100V. For 200V, efficiency is around 92%. For 230V, efficiency is around 93%. A slanted line marks the rated load current range between approximately 1.0A and 2.0A.</p>			2.Values																																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.6</td><td>84.0</td><td>82.4</td><td>81.1</td></tr> <tr><td>1.2</td><td>89.9</td><td>89.6</td><td>89.1</td></tr> <tr><td>1.8</td><td>91.9</td><td>92.2</td><td>92.0</td></tr> <tr><td>2.4</td><td>92.9</td><td>93.6</td><td>93.5</td></tr> <tr><td>3.0</td><td>93.2</td><td>94.2</td><td>94.3</td></tr> <tr><td>3.3</td><td>93.3</td><td>94.3</td><td>94.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	0.6	84.0	82.4	81.1	1.2	89.9	89.6	89.1	1.8	91.9	92.2	92.0	2.4	92.9	93.6	93.5	3.0	93.2	94.2	94.3	3.3	93.3	94.3	94.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	-	-	-																																																					
0.6	84.0	82.4	81.1																																																					
1.2	89.9	89.6	89.1																																																					
1.8	91.9	92.2	92.0																																																					
2.4	92.9	93.6	93.5																																																					
3.0	93.2	94.2	94.3																																																					
3.3	93.3	94.3	94.4																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								

**COSEL**

Model	TUXS150F50
Item	Power Factor (by Input Voltage)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph

 - - - □ - - Load 50%  
 —△— Load 100%


## 2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
80	0.980	0.991
85	0.976	0.990
100	0.968	0.989
120	0.957	0.983
200	0.901	0.958
230	0.868	0.945
264	0.819	0.917
280	0.557	0.722
--	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model	TUXS150F50	Temperature 25°C Testing Circuitry Figure A																																																						
Item	Power Factor (by Load Current)																																																							
Object	—	2.Values																																																						
1.Graph	<p>—△— Input Volt. 100V      - - □- - Input Volt. 200V      - - ○- - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Power Factor (100V)</th> <th>Power Factor (200V)</th> <th>Power Factor (230V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.510</td><td>-</td><td>-</td></tr> <tr><td>0.6</td><td>0.911</td><td>0.738</td><td>0.661</td></tr> <tr><td>1.2</td><td>0.958</td><td>0.873</td><td>0.829</td></tr> <tr><td>1.8</td><td>0.976</td><td>0.922</td><td>0.896</td></tr> <tr><td>2.4</td><td>0.984</td><td>0.945</td><td>0.927</td></tr> <tr><td>3.0</td><td>0.989</td><td>0.958</td><td>0.945</td></tr> </tbody> </table>	Load Current [A]	Power Factor (100V)	Power Factor (200V)	Power Factor (230V)	0.0	0.510	-	-	0.6	0.911	0.738	0.661	1.2	0.958	0.873	0.829	1.8	0.976	0.922	0.896	2.4	0.984	0.945	0.927	3.0	0.989	0.958	0.945																											
Load Current [A]	Power Factor (100V)	Power Factor (200V)	Power Factor (230V)																																																					
0.0	0.510	-	-																																																					
0.6	0.911	0.738	0.661																																																					
1.2	0.958	0.873	0.829																																																					
1.8	0.976	0.922	0.896																																																					
2.4	0.984	0.945	0.927																																																					
3.0	0.989	0.958	0.945																																																					
2.Values		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.510</td><td>0.163</td><td>0.131</td></tr> <tr><td>0.6</td><td>0.911</td><td>0.738</td><td>0.661</td></tr> <tr><td>1.2</td><td>0.958</td><td>0.873</td><td>0.829</td></tr> <tr><td>1.8</td><td>0.976</td><td>0.922</td><td>0.896</td></tr> <tr><td>2.4</td><td>0.984</td><td>0.945</td><td>0.927</td></tr> <tr><td>3.0</td><td>0.989</td><td>0.958</td><td>0.945</td></tr> <tr><td>3.3</td><td>0.990</td><td>0.965</td><td>0.953</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.510	0.163	0.131	0.6	0.911	0.738	0.661	1.2	0.958	0.873	0.829	1.8	0.976	0.922	0.896	2.4	0.984	0.945	0.927	3.0	0.989	0.958	0.945	3.3	0.990	0.965	0.953	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Power Factor																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	0.510	0.163	0.131																																																					
0.6	0.911	0.738	0.661																																																					
1.2	0.958	0.873	0.829																																																					
1.8	0.976	0.922	0.896																																																					
2.4	0.984	0.945	0.927																																																					
3.0	0.989	0.958	0.945																																																					
3.3	0.990	0.965	0.953																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note:	Slanted line shows the range of the rated load current.																																																							

**COSSEL**

Model TUXS150F50

Item Inrush Current

Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure AInput  
Current  
[20A/div]


Input Voltage 100 V

Frequency 50 Hz

Load 100 %

Primary inrush current 15.9 A

Secondary inrush current 6.1 A





Model	TUXS150F50	Temperature Testing Circuitry 25°C Figure B
Item	Leakage Current	
Object	_____	

### 1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
DEN-AN	Both phases	0.13	0.27	0.32	Operation
	One of phases	0.23	0.45	0.55	Stand by
IEC60950-1	Both phases	0.09	0.19	0.23	Operation
	One of phases	0.22	0.44	0.53	Stand by

The value for "One of phases" is the reference value only.

### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

Model	TUXS150F50																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+50V3A																																	
1.Graph																																		
<p style="text-align: center;"> <span style="margin-right: 20px;">--- □ --- Load 50%</span> <span>— ▲ — Load 100%</span> </p>																																		
2.Values																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2" style="text-align: center; padding: 5px;">Input Voltage [V]</th> <th colspan="2" style="text-align: center; padding: 5px;">Output Voltage [V]</th> </tr> <tr> <th style="text-align: center; padding: 5px;">Load 50%</th> <th style="text-align: center; padding: 5px;">Load 100%</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; padding: 5px;">80</td><td style="text-align: center; padding: 5px;">49.911</td><td style="text-align: center; padding: 5px;">49.908</td></tr> <tr> <td style="text-align: center; padding: 5px;">85</td><td style="text-align: center; padding: 5px;">49.914</td><td style="text-align: center; padding: 5px;">49.920</td></tr> <tr> <td style="text-align: center; padding: 5px;">100</td><td style="text-align: center; padding: 5px;">49.915</td><td style="text-align: center; padding: 5px;">49.923</td></tr> <tr> <td style="text-align: center; padding: 5px;">120</td><td style="text-align: center; padding: 5px;">49.916</td><td style="text-align: center; padding: 5px;">49.924</td></tr> <tr> <td style="text-align: center; padding: 5px;">200</td><td style="text-align: center; padding: 5px;">49.913</td><td style="text-align: center; padding: 5px;">49.924</td></tr> <tr> <td style="text-align: center; padding: 5px;">230</td><td style="text-align: center; padding: 5px;">49.915</td><td style="text-align: center; padding: 5px;">49.924</td></tr> <tr> <td style="text-align: center; padding: 5px;">264</td><td style="text-align: center; padding: 5px;">49.916</td><td style="text-align: center; padding: 5px;">49.924</td></tr> <tr> <td style="text-align: center; padding: 5px;">280</td><td style="text-align: center; padding: 5px;">49.917</td><td style="text-align: center; padding: 5px;">49.926</td></tr> <tr> <td style="text-align: center; padding: 5px;">--</td><td style="text-align: center; padding: 5px;">-</td><td style="text-align: center; padding: 5px;">-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	80	49.911	49.908	85	49.914	49.920	100	49.915	49.923	120	49.916	49.924	200	49.913	49.924	230	49.915	49.924	264	49.916	49.924	280	49.917	49.926	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
80	49.911	49.908																																
85	49.914	49.920																																
100	49.915	49.923																																
120	49.916	49.924																																
200	49.913	49.924																																
230	49.915	49.924																																
264	49.916	49.924																																
280	49.917	49.926																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**

Model	TUXS150F50	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Load Regulation																																																						
Object	+50V3A																																																						
1.Graph	<p>—▲— Input Volt. 100V</p> <p>- - □ - - Input Volt. 200V</p> <p>- · ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (100V)</th> <th>Output Voltage [V] (200V)</th> <th>Output Voltage [V] (230V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>49.918</td><td>49.915</td><td>49.925</td></tr> <tr><td>0.6</td><td>49.917</td><td>49.914</td><td>49.922</td></tr> <tr><td>1.2</td><td>49.917</td><td>49.914</td><td>49.920</td></tr> <tr><td>1.8</td><td>49.916</td><td>49.914</td><td>49.918</td></tr> <tr><td>2.4</td><td>49.916</td><td>49.914</td><td>49.918</td></tr> <tr><td>3.0</td><td>49.923</td><td>49.924</td><td>49.924</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (100V)	Output Voltage [V] (200V)	Output Voltage [V] (230V)	0.0	49.918	49.915	49.925	0.6	49.917	49.914	49.922	1.2	49.917	49.914	49.920	1.8	49.916	49.914	49.918	2.4	49.916	49.914	49.918	3.0	49.923	49.924	49.924																										
Load Current [A]	Output Voltage [V] (100V)	Output Voltage [V] (200V)	Output Voltage [V] (230V)																																																				
0.0	49.918	49.915	49.925																																																				
0.6	49.917	49.914	49.922																																																				
1.2	49.917	49.914	49.920																																																				
1.8	49.916	49.914	49.918																																																				
2.4	49.916	49.914	49.918																																																				
3.0	49.923	49.924	49.924																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>49.918</td><td>49.915</td><td>49.925</td></tr> <tr><td>0.6</td><td>49.917</td><td>49.914</td><td>49.922</td></tr> <tr><td>1.2</td><td>49.917</td><td>49.914</td><td>49.920</td></tr> <tr><td>1.8</td><td>49.916</td><td>49.914</td><td>49.918</td></tr> <tr><td>2.4</td><td>49.916</td><td>49.914</td><td>49.918</td></tr> <tr><td>3.0</td><td>49.923</td><td>49.924</td><td>49.924</td></tr> <tr><td>3.3</td><td>49.924</td><td>49.925</td><td>49.926</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	49.918	49.915	49.925	0.6	49.917	49.914	49.922	1.2	49.917	49.914	49.920	1.8	49.916	49.914	49.918	2.4	49.916	49.914	49.918	3.0	49.923	49.924	49.924	3.3	49.924	49.925	49.926	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.0	49.918	49.915	49.925																																																				
0.6	49.917	49.914	49.922																																																				
1.2	49.917	49.914	49.920																																																				
1.8	49.916	49.914	49.918																																																				
2.4	49.916	49.914	49.918																																																				
3.0	49.923	49.924	49.924																																																				
3.3	49.924	49.925	49.926																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

# COSEL



**COSEL**

Model	TUXS150F50	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+50V3A																																							
1. Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0 to 3 A. Two curves are plotted: one for Input Volt. 100V (solid line with open circles) and one for Input Volt. 200V (dashed line with open circles). Both curves show a slight increase in ripple voltage as load current increases. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>11</td><td>12</td></tr> <tr><td>0.3</td><td>46</td><td>46</td></tr> <tr><td>0.6</td><td>54</td><td>54</td></tr> <tr><td>1.2</td><td>44</td><td>40</td></tr> <tr><td>1.8</td><td>54</td><td>46</td></tr> <tr><td>2.4</td><td>56</td><td>58</td></tr> <tr><td>3.0</td><td>65</td><td>67</td></tr> <tr><td>3.3</td><td>75</td><td>71</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	0.0	11	12	0.3	46	46	0.6	54	54	1.2	44	40	1.8	54	46	2.4	56	58	3.0	65	67	3.3	75	71	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																						
0.0	11	12																																						
0.3	46	46																																						
0.6	54	54																																						
1.2	44	40																																						
1.8	54	46																																						
2.4	56	58																																						
3.0	65	67																																						
3.3	75	71																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>11</td><td>12</td></tr> <tr><td>0.3</td><td>46</td><td>46</td></tr> <tr><td>0.6</td><td>54</td><td>54</td></tr> <tr><td>1.2</td><td>44</td><td>40</td></tr> <tr><td>1.8</td><td>54</td><td>46</td></tr> <tr><td>2.4</td><td>56</td><td>58</td></tr> <tr><td>3.0</td><td>65</td><td>67</td></tr> <tr><td>3.3</td><td>75</td><td>71</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	11	12	0.3	46	46	0.6	54	54	1.2	44	40	1.8	54	46	2.4	56	58	3.0	65	67	3.3	75	71	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.0	11	12																																						
0.3	46	46																																						
0.6	54	54																																						
1.2	44	40																																						
1.8	54	46																																						
2.4	56	58																																						
3.0	65	67																																						
3.3	75	71																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																								


COSEL

Model TUXS150F50

Item Ripple-Noise

Object +50V3A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	19	25
0.3	52	60
0.6	78	72
1.2	63	60
1.8	64	60
2.4	73	69
3.0	84	83
3.3	90	92
--	-	-
--	-	-
--	-	-



T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

**COSEL**

Model	TUXS150F50
Item	Ripple Voltage (by Ambient Temp.)
Object	+50V3A

## 1.Graph



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	62	81
-20	76	69
0	64	73
25	67	65
100	44	66
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.





Fig. Complex Ripple Wave Form

**COSEL**

Model	TUXS150F50
Item	Ambient Temperature Drift
Object	+50V3A

- 1.Graph
- △— Input Volt. 100V
  - - □ - - Input Volt. 200V
  - - ○ - - Input Volt. 230V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-50	49.584	49.595	49.600
-40	49.646	49.656	49.661
-20	49.752	49.762	49.766
0	49.831	49.838	49.842
25	49.923	49.924	49.924
50	49.966	49.969	49.971
75	49.980	49.979	49.978
85	49.976	49.973	49.971
100	49.949	49.942	49.940
105	49.934	49.927	49.922
--	-	-	-



Model	TUXS150F50	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+50V3A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 85 - 264V

Load Current : 0 - 3A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	85	264	3	49.977	±162	±0.3
Minimum Voltage	-40	85	0	49.654		

**COSEL**

Model	TUXS150F50
Item	Time Lapse Drift
Object	+50V3A

## 1. Graph



Input Volt. 100V  
Load 100%

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Time since start [H]	Output Voltage [V]
0.0	49.897
0.5	49.923
1.0	49.923
2.0	49.923
3.0	49.923
4.0	49.923
5.0	49.923
6.0	49.923
7.0	49.923
8.0	49.923

**COSEL**


Model TUXS150F50

Temperature 25°C  
Testing Circuitry Figure A

Item Rise and Fall Time


Object +50V3A

## 1. Graph




## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		304.5	10.0	314.5	86.1	18.1	
100 %		304.5	10.0	314.5	45.8	9.1	




**COSEL**

Model	TUXS150F50																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+50V3A																																	
1.Graph																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>119</td><td>59</td></tr> <tr> <td>85</td><td>118</td><td>59</td></tr> <tr> <td>100</td><td>119</td><td>59</td></tr> <tr> <td>120</td><td>119</td><td>59</td></tr> <tr> <td>200</td><td>119</td><td>58</td></tr> <tr> <td>230</td><td>118</td><td>59</td></tr> <tr> <td>264</td><td>118</td><td>59</td></tr> <tr> <td>280</td><td>118</td><td>58</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	119	59	85	118	59	100	119	59	120	119	59	200	119	58	230	118	59	264	118	59	280	118	58	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
80	119	59																																
85	118	59																																
100	119	59																																
120	119	59																																
200	119	58																																
230	118	59																																
264	118	59																																
280	118	58																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**


**COSEL**

Model	TUXS150F50																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+50V3A																																							
1.Graph																																								
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>--□-- Load 50%</li> <li>—△— Load 100%</li> </ul>																																								
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								
Testing Circuitry Figure A																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>67</td><td>66</td> </tr> <tr> <td>-40</td><td>67</td><td>66</td> </tr> <tr> <td>-20</td><td>67</td><td>66</td> </tr> <tr> <td>0</td><td>67</td><td>66</td> </tr> <tr> <td>25</td><td>67</td><td>66</td> </tr> <tr> <td>50</td><td>68</td><td>66</td> </tr> <tr> <td>75</td><td>68</td><td>66</td> </tr> <tr> <td>85</td><td>68</td><td>66</td> </tr> <tr> <td>100</td><td>68</td><td>66</td> </tr> <tr> <td>105</td><td>68</td><td>66</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	67	66	-40	67	66	-20	67	66	0	67	66	25	67	66	50	68	66	75	68	66	85	68	66	100	68	66	105	68	66	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-50	67	66																																						
-40	67	66																																						
-20	67	66																																						
0	67	66																																						
25	67	66																																						
50	68	66																																						
75	68	66																																						
85	68	66																																						
100	68	66																																						
105	68	66																																						
--	-	-																																						

**COSEL**

Temperature 25°C  
Testing Circuitry Figure A


## 2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
50.0	3.01	3.02	3.02
47.5	2.97	2.98	2.98
45.0	3.97	3.93	3.93
40.0	0.00	0.00	0.00
35.0	0.00	0.00	0.00
30.0	0.00	0.00	0.00
25.0	0.00	0.00	0.00
20.0	0.00	0.00	0.00
15.0	0.00	0.00	0.00
10.0	0.00	0.00	0.00
5.0	0.00	0.00	0.00
0.0	0.00	0.00	0.00

**COSEL**

Model	TUXS150F50
Item	Overvoltage Protection
Object	+50V3A

## 1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-50	59.35	59.35
-40	59.47	59.47
-20	59.53	59.53
0	59.64	59.64
25	59.76	59.76
50	59.77	59.77
75	59.77	59.77
85	59.77	59.77
100	59.77	59.77
105	59.77	59.77
--	-	-




Figure A




Figure B ( DEN-AN )





Figure B ( IEC60950-1 )

COSEL



- L1,L2 : SCR-040-0R8A100JH(NEC TOKIN)
- TH1 : 12D2-15LCS(SEMITEC)
- C1,C2 : LE684-MX(OKAYA)
- C3 : LE105-MX(OKAYA)
- C4,C5 : DE1E3KX222M(MURATA)
- C6 : EKXJ421ELL151MM50S(Nippon Chemi-con)
- C7 : AFS450V474K(OKAYA)
- C10,C11 : PCR1J101MCL1GS(NICHICON)
- C12 : GRM31CR72A225K(MURATA)

Figure C