

# TEST DATA OF TUXS200F32

Regulated DC Power Supply  
October 21, 2016

Approved by : Junichi Hatagishi  
Junichi Hatagishi                                  Design Manager

Prepared by : Hiroyuki Shoji  
Hiroyuki Shoji                                  Design Engineer

**COSEL CO.,LTD.**

## CONTENTS


1.Input Current (by Load Current) . . . . .	1
2.Input Power (by Load Current) . . . . .	2
3.Efficiency (by Input Voltage) . . . . .	3
4.Efficiency (by Load Current) . . . . .	4
5.Power Factor (by Input Voltage) . . . . .	5
6.Power Factor (by Load Current) . . . . .	6
7.Inrush Current . . . . .	7
8.Leakage Current . . . . .	8
9.Line Regulation . . . . .	9
10.Load Regulation . . . . .	10
11.Dynamic Load Response . . . . .	11
12.Ripple Voltage (by Load Current) . . . . .	12
13.Ripple-Noise . . . . .	13
14.Ripple Voltage (by Ambient Temperature) . . . . .	14
15.Ambient Temperature Drift . . . . .	15
16.Output Voltage Accuracy . . . . .	16
17.Time Lapse Drift . . . . .	17
18.Rise and Fall Time . . . . .	18
19.Hold-Up Time . . . . .	19
20.Instantaneous Interruption Compensation . . . . .	20
21.Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22.Overcurrent Protection . . . . .	22
23.Overvoltage Protection . . . . .	23
24.Figure of Testing Circuitry . . . . .	24 25

(Final Page 25)

**COSSEL**

Model	TUXS200F32
Item	Input Current (by Load Current)
Object	_____

Temperature 25°C  
 Testing Circuitry Figure A



## 2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.125	0.224	0.253
1.24	0.508	0.343	0.340
2.48	0.906	0.518	0.484
3.72	1.319	0.711	0.642
4.96	1.739	0.906	0.806
6.20	2.170	1.107	0.982
6.82	2.389	1.209	1.075
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**


Model	TUXS200F32																																																					
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V        - - -□--- Input Volt. 200V        - - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.1</td><td>5.5</td><td>5.4</td></tr> <tr><td>1.24</td><td>46.2</td><td>46.8</td><td>47.6</td></tr> <tr><td>2.48</td><td>87.6</td><td>87.6</td><td>87.9</td></tr> <tr><td>3.72</td><td>129.3</td><td>128.3</td><td>128.5</td></tr> <tr><td>4.96</td><td>171.5</td><td>169.5</td><td>169.5</td></tr> <tr><td>6.20</td><td>214.6</td><td>211.2</td><td>211.1</td></tr> <tr><td>6.82</td><td>236.4</td><td>232.4</td><td>232.0</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)	0.00	5.1	5.5	5.4	1.24	46.2	46.8	47.6	2.48	87.6	87.6	87.9	3.72	129.3	128.3	128.5	4.96	171.5	169.5	169.5	6.20	214.6	211.2	211.1	6.82	236.4	232.4	232.0																			
Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)																																																			
0.00	5.1	5.5	5.4																																																			
1.24	46.2	46.8	47.6																																																			
2.48	87.6	87.6	87.9																																																			
3.72	129.3	128.3	128.5																																																			
4.96	171.5	169.5	169.5																																																			
6.20	214.6	211.2	211.1																																																			
6.82	236.4	232.4	232.0																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.1</td><td>5.5</td><td>5.4</td></tr> <tr><td>1.24</td><td>46.2</td><td>46.8</td><td>47.6</td></tr> <tr><td>2.48</td><td>87.6</td><td>87.6</td><td>87.9</td></tr> <tr><td>3.72</td><td>129.3</td><td>128.3</td><td>128.5</td></tr> <tr><td>4.96</td><td>171.5</td><td>169.5</td><td>169.5</td></tr> <tr><td>6.20</td><td>214.6</td><td>211.2</td><td>211.1</td></tr> <tr><td>6.82</td><td>236.4</td><td>232.4</td><td>232.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	5.1	5.5	5.4	1.24	46.2	46.8	47.6	2.48	87.6	87.6	87.9	3.72	129.3	128.3	128.5	4.96	171.5	169.5	169.5	6.20	214.6	211.2	211.1	6.82	236.4	232.4	232.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	5.1	5.5	5.4																																																			
1.24	46.2	46.8	47.6																																																			
2.48	87.6	87.6	87.9																																																			
3.72	129.3	128.3	128.5																																																			
4.96	171.5	169.5	169.5																																																			
6.20	214.6	211.2	211.1																																																			
6.82	236.4	232.4	232.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	TUXS200F32
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	91.0	91.2
85	91.3	91.7
100	91.7	92.6
120	92.0	93.3
200	92.0	94.1
230	91.8	94.2
264	91.8	94.5
280	92.0	94.4
--	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	TUXS200F32
Item	Efficiency (by Load Current)
Object	_____



Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
1.24	86.1	84.9	83.4
2.48	90.7	90.7	90.4
3.72	92.2	92.9	92.8
4.96	92.7	93.8	93.8
6.20	92.6	94.1	94.2
6.82	92.5	94.0	94.2
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	TUXS200F32
Item	Power Factor (by Input Voltage)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
80	0.984	0.992
85	0.982	0.992
100	0.973	0.990
120	0.957	0.987
200	0.882	0.954
230	0.832	0.934
264	0.781	0.889
280	0.450	0.628
--	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSSEL**

Model	TUXS200F32																																																					
Item	Power Factor (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.407</td><td>0.123</td><td>0.093</td></tr> <tr><td>1.24</td><td>0.909</td><td>0.682</td><td>0.609</td></tr> <tr><td>2.48</td><td>0.967</td><td>0.845</td><td>0.790</td></tr> <tr><td>3.72</td><td>0.980</td><td>0.902</td><td>0.871</td></tr> <tr><td>4.96</td><td>0.987</td><td>0.935</td><td>0.914</td></tr> <tr><td>6.20</td><td>0.990</td><td>0.954</td><td>0.934</td></tr> <tr><td>6.82</td><td>0.991</td><td>0.962</td><td>0.938</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.407	0.123	0.093	1.24	0.909	0.682	0.609	2.48	0.967	0.845	0.790	3.72	0.980	0.902	0.871	4.96	0.987	0.935	0.914	6.20	0.990	0.954	0.934	6.82	0.991	0.962	0.938	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.407	0.123	0.093																																																			
1.24	0.909	0.682	0.609																																																			
2.48	0.967	0.845	0.790																																																			
3.72	0.980	0.902	0.871																																																			
4.96	0.987	0.935	0.914																																																			
6.20	0.990	0.954	0.934																																																			
6.82	0.991	0.962	0.938																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


COSEL

Model TUXS200F32

Item Inrush Current

Temperature 25°C  
Testing Circuitry Figure A


Object \_\_\_\_\_

Input  
Current  
[20A/div]

-50                                  50                                  150                                  250                                  350                                  450  
Time [50ms/div]

Input Voltage 100 V  
Frequency 50 Hz  
Load 100 %

Primary inrush current 15.4 A  
Secondary inrush current 7.6 A





Model	TUXS200F32	Temperature Testing Circuitry Figure B	25°C
Item	Leakage Current		
Object	_____		

### 1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
DEN-AN	Both phases	0.17	0.34	0.41	Operation
	One of phases	0.27	0.54	0.65	Stand by
IEC60950-1	Both phases	0.14	0.29	0.36	Operation
	One of phases	0.28	0.56	0.68	Stand by

The value for "One of phases" is the reference value only.

### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	TUXS200F32
Item	Line Regulation
Object	+32V6.2A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



Note: Slanted line shows the range of the rated input voltage.


## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	32.042	32.044
85	32.044	32.044
100	32.045	32.045
120	32.046	32.045
200	32.046	32.045
230	32.046	32.045
264	32.047	32.045
280	32.047	32.045
--	-	-

**COSSEL**

Model	TUXS200F32
Item	Load Regulation
Object	+32V6.2A

Temperature 25°C  
 Testing Circuitry Figure A




## 2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	32.048	32.048	32.048
1.24	32.047	32.047	32.047
2.48	32.047	32.047	32.047
3.72	32.046	32.046	32.046
4.96	32.046	32.046	32.045
6.20	32.045	32.045	32.045
6.82	32.043	32.043	32.043
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL




**COSEL**

Model	TUXS200F32
Item	Ripple Voltage (by Load Current)
Object	+32V6.2A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	30	24
1.24	24	27
2.48	29	37
3.72	32	32
4.96	39	40
6.20	49	44
6.82	51	47
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line  
T2: Due to Switching




Fig. Complex Ripple Wave Form

**COSEL**


Model	TUXS200F32																																						
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure A																																					
Object	+32V6.2A																																						
1. Graph																																							
		2. Values																																					
<p>—△— Input Volt. 100V ---○--- Input Volt. 200V</p> <table> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>33</td><td>29</td></tr> <tr><td>1.24</td><td>34</td><td>34</td></tr> <tr><td>2.48</td><td>36</td><td>45</td></tr> <tr><td>3.72</td><td>42</td><td>41</td></tr> <tr><td>4.96</td><td>49</td><td>55</td></tr> <tr><td>6.20</td><td>60</td><td>49</td></tr> <tr><td>6.82</td><td>69</td><td>53</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.00	33	29	1.24	34	34	2.48	36	45	3.72	42	41	4.96	49	55	6.20	60	49	6.82	69	53	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																						
	Input Volt. 100 [V]	Input Volt. 200 [V]																																					
0.00	33	29																																					
1.24	34	34																																					
2.48	36	45																																					
3.72	42	41																																					
4.96	49	55																																					
6.20	60	49																																					
6.82	69	53																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
<p>Fig. Complex Ripple Wave Form</p>																																							

**COSEL**

Model	TUXS200F32
Item	Ripple Voltage (by Ambient Temp.)
Object	+32V6.2A

## Testing Circuitry Figure A

## 1.Graph




Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	86	118
-20	35	62
0	31	48
25	30	49
50	28	43
75	27	40
85	27	37
100	23	35
--	-	-
--	-	-
--	-	-



**COSEL**

Model	TUXS200F32
Item	Ambient Temperature Drift
Object	+32V6.2A



Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-50	31.930	31.931	31.929
-40	31.954	31.963	31.967
-20	31.989	31.995	31.999
0	32.016	32.020	32.022
25	32.045	32.045	32.045
50	32.045	32.045	32.045
75	32.043	32.041	32.040
85	32.038	32.036	32.035
100	32.030	32.028	32.028
105	32.026	32.026	32.026
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	TUXS200F32
Item	Output Voltage Accuracy
Object	+32V6.2A

Testing Circuitry Figure A

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 100 - 230V

Load Current : 0 - 6.2A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	50	230	6.2	32.045	±46	±0.1
Minimum Voltage	-40	100	6.2	31.954		

**COSEL**


Model	TUXS200F32	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+32V6.2A																								
1. Graph																									
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>																									
2. Values																									
<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>32.025</td></tr> <tr><td>0.5</td><td>32.045</td></tr> <tr><td>1.0</td><td>32.045</td></tr> <tr><td>2.0</td><td>32.045</td></tr> <tr><td>3.0</td><td>32.045</td></tr> <tr><td>4.0</td><td>32.045</td></tr> <tr><td>5.0</td><td>32.045</td></tr> <tr><td>6.0</td><td>32.045</td></tr> <tr><td>7.0</td><td>32.045</td></tr> <tr><td>8.0</td><td>32.045</td></tr> </tbody> </table>				Time since start [H]	Output Voltage [V]	0.0	32.025	0.5	32.045	1.0	32.045	2.0	32.045	3.0	32.045	4.0	32.045	5.0	32.045	6.0	32.045	7.0	32.045	8.0	32.045
Time since start [H]	Output Voltage [V]																								
0.0	32.025																								
0.5	32.045																								
1.0	32.045																								
2.0	32.045																								
3.0	32.045																								
4.0	32.045																								
5.0	32.045																								
6.0	32.045																								
7.0	32.045																								
8.0	32.045																								

**COSEL**

Model	TUXS200F32
Item	Rise and Fall Time
Object	+32V6.2A


Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		306.0	9.5	315.5	93.6	10.4	
100 %		306.0	9.5	315.5	44.9	9.5	




**COSEL**

Model	TUXS200F32
Item	Hold-Up Time
Object	+32V6.2A

Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values


Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
80	94	42
85	94	42
100	94	42
120	93	42
200	94	42
230	94	42
264	94	42
280	93	42
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	TUXS200F32
Item	Instantaneous Interruption Compensation
Object	+32V6.2A

Temperature 25°C  
 Testing Circuitry Figure A



## 2. Values

Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
1.24	212	213	212
2.48	111	112	112
3.72	74	76	76
4.96	56	56	56
6.20	42	42	42
6.82	16	16	16
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	TUXS200F32
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+32V6.2A

## Testing Circuitry Figure A

## 1.Graph




Note: Slanted line shows the range of the rated ambient temperature.

## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-50	66	62
-40	66	60
-20	65	59
0	65	59
25	65	59
50	66	60
75	66	64
85	65	67
100	66	68
105	66	68
--	-	-

**COSEL**

Model	TUXS200F32
Item	Overcurrent Protection
Object	+32V6.2A

Temperature 25°C  
Testing Circuitry Figure A

Note: Slanted line shows the range of the rated load current.

## 2. Values

Output Voltage [V]	Load Current [A]		
	100[V]	200[V]	230[V]
32.0	7.34	7.30	7.22
30.4	7.47	7.30	7.25
28.8	7.47	7.30	7.25
25.6	0.00	0.00	0.00
22.4	0.00	0.00	0.00
19.2	0.00	0.00	0.00
16.0	0.00	0.00	0.00
12.8	0.00	0.00	0.00
9.6	0.00	0.00	0.00
6.4	0.00	0.00	0.00
3.2	0.00	0.00	0.00
0.0	0.00	0.00	0.00

Model	TUXS200F32																																							
Item	Overvoltage Protection																																							
Object	+32V6.2A																																							
1.Graph																																								
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V (Solid Line with open triangles)</li> <li>Input Volt. 230V (Dashed Line with open squares)</li> </ul>																																								
Testing Circuitry Figure A																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>37.18</td><td>37.14</td> </tr> <tr> <td>-40</td><td>37.18</td><td>37.16</td> </tr> <tr> <td>-20</td><td>37.30</td><td>37.30</td> </tr> <tr> <td>0</td><td>37.38</td><td>37.40</td> </tr> <tr> <td>25</td><td>37.44</td><td>37.44</td> </tr> <tr> <td>50</td><td>37.48</td><td>37.48</td> </tr> <tr> <td>75</td><td>37.48</td><td>37.48</td> </tr> <tr> <td>85</td><td>37.46</td><td>37.46</td> </tr> <tr> <td>100</td><td>37.46</td><td>37.46</td> </tr> <tr> <td>105</td><td>37.44</td><td>37.44</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 230[V]	-50	37.18	37.14	-40	37.18	37.16	-20	37.30	37.30	0	37.38	37.40	25	37.44	37.44	50	37.48	37.48	75	37.48	37.48	85	37.46	37.46	100	37.46	37.46	105	37.44	37.44	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 100[V]	Input Volt. 230[V]																																						
-50	37.18	37.14																																						
-40	37.18	37.16																																						
-20	37.30	37.30																																						
0	37.38	37.40																																						
25	37.44	37.44																																						
50	37.48	37.48																																						
75	37.48	37.48																																						
85	37.46	37.46																																						
100	37.46	37.46																																						
105	37.44	37.44																																						
--	-	-																																						

Note: Slanted line shows the range of the rated ambient temperature.




Figure A

Data Acquisition/Control Unit




Figure B ( DEN-AN )





Figure B ( IEC60950-1 )



L1,L2 : SCR22-060-1R0A075J(NEC TOKIN)  
 TH1 : 12D2-15LCS(SEMITEC)  
 C1,C2,C3 : LE105-MX(OKAYA)  
 C4,C5 : DE1E3KX332M(MURATA)  
 C6 : EKXJ421ELL151MM50S(Nippon Chemi-Con)  
 C7 : AFS450V105K(OKAYA)  
 C10,C11 : PCR1H181MCL1GS(NICHICON)  
 C12 : GRM31CR72A225K(MURATA)

Figure C