



# M T B F

(MIL-HDBK217F NOTICE 2)

Model	UMA30F-36
-------	-----------

No.	P a r t s		Q' ty of Device	Failure rate [10 <sup>-6</sup> /H]	Reference
1	I C	M o n o l i t h i c	2	3.5060	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		2	1.4540	
4	D i o d e s		9	0.5340	
5	LED•Optocouplers		2	0.8950	
6	R e s i s t o r s		38	0.1610	
7	C a p a c i t o r s		20	2.4750	
8	Transformer•Choke Coil		5	0.3540	
9	C o n n e c t o r s		217	0.0100	
1 0	O t h e r s		5	0.0360	
Total Failure Rate [10 <sup>-6</sup> /H]				9.4250	

M T B F	[H]	106,100
Ambient Temperature	[°C]	50.0
Load Factor	[%]	100



# M T B F

(E I A J R C R - 9 1 0 2)

Model	UMA30F-36
-------	-----------

No.	P a r t s		Q' ty of Device	Failure rate [10 <sup>-6</sup> /H]	R e f e r e n c e
1	I C	M o n o l i t h i c	2	0.0980	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		2	0.1001	
4	D i o d e s		9	0.2272	
5	LED•Optocouplers		2	0.1400	
6	R e s i s t o r s		38	0.3274	
7	C a p a c i t o r s		20	0.2167	
8	Transformer•Choke Coil		5	0.1150	
9	C o n n e c t o r s		217	0.0563	
1 0	O t h e r s		5	0.0780	
Total Failure Rate [10 <sup>-6</sup> /H]				1.3587	

M T B F	[H]	736,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—