



TEST DATA OF UMA60F-7R5

Regulated DC Power Supply
September 4, 2023

Approved by : Takashi Kajii
Design Manager

Prepared by : Akihisa Mukai
Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)


COSEL

Model	UMA60F-7R5
Item	Input Current (by Load Current)
Object	+7.5V5.5A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]
0.0	0.013	0.025	0.028
1.1	0.177	0.113	0.102
2.2	0.320	0.197	0.178
3.3	0.462	0.279	0.253
4.4	0.605	0.363	0.327
5.5	0.748	0.446	0.404
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


COSEL

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Efficiency [%]		
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]
0.0	-	-	-
1.1	87.2	86.3	85.6
2.2	86.5	87.0	86.1
3.3	86.1	86.5	85.9
4.4	85.8	86.4	86.1
5.5	85.6	86.1	85.7
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	UMA60F-7R5
Item	Power Factor (by Load Current)
Object	+7.5V5.5A



 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Power Factor		
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]
0.0	0.028	0.020	0.020
1.1	0.467	0.370	0.360
2.2	0.523	0.423	0.411
3.3	0.546	0.450	0.436
4.4	0.558	0.462	0.448
5.5	0.565	0.470	0.455
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


COSEL

Model	UMA60F-7R5	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	+7.5V5.5A		



Input Voltage 230 V
 Frequency 50 Hz
 Load 100 %

Primary inrush current 47.5 A
 Secondary inrush current 2.5 A





Model	UMA60F-7R5	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	+7.5V5.5A		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			115 [V]	230 [V]	264 [V]	
IEC60601-1	Figure C-1	Both phases	0.05	0.11	0.13	Operation
		One of phases	0.10	0.21	0.25	Stand by
IEC62368-1	Figure C-2	Both phases	0.05	0.11	0.13	Operation
		One of phases	0.10	0.21	0.25	Stand by
	Figure C-3	Both phases	0.05	0.11	0.13	Operation
		One of phases	0.10	0.21	0.25	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	UMA60F-7R5
Item	Line Regulation
Object	+7.5V5.5A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	7.599	-
100	7.599	-
115	7.599	7.575
132	7.599	7.576
170	7.599	7.577
200	7.599	7.577
230	7.599	7.577
264	7.599	7.578
--	-	-


COSEL

Model	UMA60F-7R5	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+7.5V5.5A																																																					
1.Graph	<p>—△— Input Volt. 115V - - -□- - Input Volt. 230V - - -○- - Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Volt. 115V [V]</th> <th>Output Volt. 230V [V]</th> <th>Output Volt. 264V [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>7.618</td><td>7.619</td><td>7.616</td></tr> <tr><td>1.1</td><td>7.610</td><td>7.610</td><td>7.610</td></tr> <tr><td>2.2</td><td>7.603</td><td>7.603</td><td>7.603</td></tr> <tr><td>3.3</td><td>7.595</td><td>7.595</td><td>7.595</td></tr> <tr><td>4.4</td><td>7.586</td><td>7.587</td><td>7.587</td></tr> <tr><td>5.5</td><td>7.575</td><td>7.578</td><td>7.578</td></tr> </tbody> </table>			Load Current [A]	Output Volt. 115V [V]	Output Volt. 230V [V]	Output Volt. 264V [V]	0.0	7.618	7.619	7.616	1.1	7.610	7.610	7.610	2.2	7.603	7.603	7.603	3.3	7.595	7.595	7.595	4.4	7.586	7.587	7.587	5.5	7.575	7.578	7.578																							
Load Current [A]	Output Volt. 115V [V]	Output Volt. 230V [V]	Output Volt. 264V [V]																																																			
0.0	7.618	7.619	7.616																																																			
1.1	7.610	7.610	7.610																																																			
2.2	7.603	7.603	7.603																																																			
3.3	7.595	7.595	7.595																																																			
4.4	7.586	7.587	7.587																																																			
5.5	7.575	7.578	7.578																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>7.618</td><td>7.619</td><td>7.616</td></tr> <tr><td>1.1</td><td>7.610</td><td>7.610</td><td>7.610</td></tr> <tr><td>2.2</td><td>7.603</td><td>7.603</td><td>7.603</td></tr> <tr><td>3.3</td><td>7.595</td><td>7.595</td><td>7.595</td></tr> <tr><td>4.4</td><td>7.586</td><td>7.587</td><td>7.587</td></tr> <tr><td>5.5</td><td>7.575</td><td>7.578</td><td>7.578</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]	0.0	7.618	7.619	7.616	1.1	7.610	7.610	7.610	2.2	7.603	7.603	7.603	3.3	7.595	7.595	7.595	4.4	7.586	7.587	7.587	5.5	7.575	7.578	7.578	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]																																																			
0.0	7.618	7.619	7.616																																																			
1.1	7.610	7.610	7.610																																																			
2.2	7.603	7.603	7.603																																																			
3.3	7.595	7.595	7.595																																																			
4.4	7.586	7.587	7.587																																																			
5.5	7.575	7.578	7.578																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+7.5V5.5A	Testing Circuitry	Figure B																																																			
1.Graph	<p>Input Voltage 230V Load 100%</p>																																																					

COSEL

Model	UMA60F-7R5	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+7.5V5.5A		

Input Volt. 230 V
 Cycle 1000 ms




COSEL

Model	UMA60F-7R5
Item	Rise and Fall Time
Object	+7.5V5.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		28.3	5.8	34.1	262.0	14.3	
100 %		28.3	7.8	36.1	125.5	12.0	




COSEL

Model	UMA60F-7R5
Item	Hold-Up Time
Object	+7.5V5.5A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	29	-
100	43	-
115	59	35
132	80	45
170	138	70
200	196	100
230	264	130
264	355	175
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

COSEL

Model	UMA60F-7R5	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+7.5V5.5A																																																					
1.Graph	<p>—△— Input Volt. 115V - - □ - - Input Volt. 230V - - ○ - - Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>115V [ms]</th> <th>230V [ms]</th> <th>264V [ms]</th> </tr> </thead> <tbody> <tr><td>1.1</td><td>156</td><td>759</td><td>990</td></tr> <tr><td>2.2</td><td>76</td><td>335</td><td>448</td></tr> <tr><td>3.3</td><td>48</td><td>221</td><td>297</td></tr> <tr><td>4.4</td><td>34</td><td>161</td><td>216</td></tr> <tr><td>5.5</td><td>24</td><td>121</td><td>166</td></tr> </tbody> </table>			Load Current [A]	115V [ms]	230V [ms]	264V [ms]	1.1	156	759	990	2.2	76	335	448	3.3	48	221	297	4.4	34	161	216	5.5	24	121	166																											
Load Current [A]	115V [ms]	230V [ms]	264V [ms]																																																			
1.1	156	759	990																																																			
2.2	76	335	448																																																			
3.3	48	221	297																																																			
4.4	34	161	216																																																			
5.5	24	121	166																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.1</td><td>156</td><td>759</td><td>990</td></tr> <tr><td>2.2</td><td>76</td><td>335</td><td>448</td></tr> <tr><td>3.3</td><td>48</td><td>221</td><td>297</td></tr> <tr><td>4.4</td><td>34</td><td>161</td><td>216</td></tr> <tr><td>5.5</td><td>24</td><td>121</td><td>166</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]	0.0	-	-	-	1.1	156	759	990	2.2	76	335	448	3.3	48	221	297	4.4	34	161	216	5.5	24	121	166	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]																																																			
0.0	-	-	-																																																			
1.1	156	759	990																																																			
2.2	76	335	448																																																			
3.3	48	221	297																																																			
4.4	34	161	216																																																			
5.5	24	121	166																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					





Model	UMA60F-7R5	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+7.5V5.5A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 115V	Input Volt. 230V	Input Volt. 264V
-20	7.563	7.568	7.568
25	7.575	7.578	7.578
40	7.574	7.577	7.577

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+7.5V5.5A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	33	52
25	33	53
40	32	53

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+7.5V5.5A	

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 115V	Input Volt. 264V
-20	9.58	9.59
25	9.62	9.58
40	9.72	9.82

COSEL





Figure B




Figure C-1 (IEC60601-1)

COSEL




Figure C-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure C-3 (IEC62368-1 refer to IEC60990 Fig.5)