



TEST DATA OF VAF1003 (200V INPUT)

Regulated DC Power Supply

Oct. 29, 1999

Approved by : M. Nakata
Design Manager

Prepared by : T. Yamashina
Design Engineer

コーセル株式会社
COSEL CO., LTD.




C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流(負荷特性)	
3. Input Power (by Load Current)	3
入力電力(負荷特性)	
4. Efficiency (by Input Voltage)	4
効率(入力電圧特性)	
5. Efficiency (by Load Current)	5
効率(負荷特性)	
6. Power Factor (by Input Voltage)	6
力率(入力電圧特性)	
7. Power Factor (by Load Current)	7
力率(負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保護	
10. Load Regulation	10
静的負荷変動	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Rise and Fall Time	13
立ち上り、立ち下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Time Lapse Drift	16
経時ドリフト	
17. Output Voltage Accuracy	17
定電圧精度	
18. Figure of Testing Circuitry	18
測定回路図	

(Final Page 19)

COSEL

Model	VAF1003
Item	Line Regulation 静的入力変動
Object	+3.3V2A



Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

COSEL

Model	VAF1003	Temperature	25°C																																																			
Item	Input Current (by Load Current) 入力電流（負荷特性）	Testing Circuitry	Figure A																																																			
Object																																																						
1. Graph	<p>—△— Input Volt. 170V —□— Input Volt. 200V —○— Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170[V] [A]</th> <th>Input Volt. 200[V] [A]</th> <th>Input Volt. 264[V] [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.022</td><td>0.022</td><td>0.022</td></tr> <tr><td>0.4</td><td>0.046</td><td>0.044</td><td>0.040</td></tr> <tr><td>0.8</td><td>0.066</td><td>0.061</td><td>0.057</td></tr> <tr><td>1.2</td><td>0.090</td><td>0.083</td><td>0.072</td></tr> <tr><td>1.6</td><td>0.109</td><td>0.100</td><td>0.087</td></tr> <tr><td>2.0</td><td>0.131</td><td>0.118</td><td>0.100</td></tr> <tr><td>2.2</td><td>0.141</td><td>0.128</td><td>0.108</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170[V] [A]	Input Volt. 200[V] [A]	Input Volt. 264[V] [A]	0.0	0.022	0.022	0.022	0.4	0.046	0.044	0.040	0.8	0.066	0.061	0.057	1.2	0.090	0.083	0.072	1.6	0.109	0.100	0.087	2.0	0.131	0.118	0.100	2.2	0.141	0.128	0.108																			
Load Current [A]	Input Volt. 170[V] [A]	Input Volt. 200[V] [A]	Input Volt. 264[V] [A]																																																			
0.0	0.022	0.022	0.022																																																			
0.4	0.046	0.044	0.040																																																			
0.8	0.066	0.061	0.057																																																			
1.2	0.090	0.083	0.072																																																			
1.6	0.109	0.100	0.087																																																			
2.0	0.131	0.118	0.100																																																			
2.2	0.141	0.128	0.108																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.022</td><td>0.022</td><td>0.022</td></tr> <tr><td>0.4</td><td>0.046</td><td>0.044</td><td>0.040</td></tr> <tr><td>0.8</td><td>0.066</td><td>0.061</td><td>0.057</td></tr> <tr><td>1.2</td><td>0.090</td><td>0.083</td><td>0.072</td></tr> <tr><td>1.6</td><td>0.109</td><td>0.100</td><td>0.087</td></tr> <tr><td>2.0</td><td>0.131</td><td>0.118</td><td>0.100</td></tr> <tr><td>2.2</td><td>0.141</td><td>0.128</td><td>0.108</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	0.022	0.022	0.022	0.4	0.046	0.044	0.040	0.8	0.066	0.061	0.057	1.2	0.090	0.083	0.072	1.6	0.109	0.100	0.087	2.0	0.131	0.118	0.100	2.2	0.141	0.128	0.108	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0.0	0.022	0.022	0.022																																																			
0.4	0.046	0.044	0.040																																																			
0.8	0.066	0.061	0.057																																																			
1.2	0.090	0.083	0.072																																																			
1.6	0.109	0.100	0.087																																																			
2.0	0.131	0.118	0.100																																																			
2.2	0.141	0.128	0.108																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF1003	Temperature	25°C																																																							
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Testing Circuitry	Figure A																																																							
Object	<hr/>																																																									
1. Graph	<p style="text-align: center;"> —△— Input Volt. 170V —□— Input Volt. 200V —○— Input Volt. 264V </p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170V [W]</th> <th>Input Volt. 200V [W]</th> <th>Input Volt. 264V [W]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.20</td><td>1.30</td><td>1.60</td></tr> <tr><td>0.4</td><td>2.90</td><td>3.10</td><td>3.40</td></tr> <tr><td>0.8</td><td>4.40</td><td>4.50</td><td>5.10</td></tr> <tr><td>1.2</td><td>6.40</td><td>6.50</td><td>6.80</td></tr> <tr><td>1.6</td><td>8.00</td><td>8.20</td><td>8.60</td></tr> <tr><td>2.0</td><td>10.10</td><td>10.10</td><td>10.20</td></tr> <tr><td>2.2</td><td>11.00</td><td>11.10</td><td>11.20</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 170V [W]	Input Volt. 200V [W]	Input Volt. 264V [W]	0.0	1.20	1.30	1.60	0.4	2.90	3.10	3.40	0.8	4.40	4.50	5.10	1.2	6.40	6.50	6.80	1.6	8.00	8.20	8.60	2.0	10.10	10.10	10.20	2.2	11.00	11.10	11.20																							
Load Current [A]	Input Volt. 170V [W]	Input Volt. 200V [W]	Input Volt. 264V [W]																																																							
0.0	1.20	1.30	1.60																																																							
0.4	2.90	3.10	3.40																																																							
0.8	4.40	4.50	5.10																																																							
1.2	6.40	6.50	6.80																																																							
1.6	8.00	8.20	8.60																																																							
2.0	10.10	10.10	10.20																																																							
2.2	11.00	11.10	11.20																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.20</td><td>1.30</td><td>1.60</td></tr> <tr><td>0.4</td><td>2.90</td><td>3.10</td><td>3.40</td></tr> <tr><td>0.8</td><td>4.40</td><td>4.50</td><td>5.10</td></tr> <tr><td>1.2</td><td>6.40</td><td>6.50</td><td>6.80</td></tr> <tr><td>1.6</td><td>8.00</td><td>8.20</td><td>8.60</td></tr> <tr><td>2.0</td><td>10.10</td><td>10.10</td><td>10.20</td></tr> <tr><td>2.2</td><td>11.00</td><td>11.10</td><td>11.20</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	1.20	1.30	1.60	0.4	2.90	3.10	3.40	0.8	4.40	4.50	5.10	1.2	6.40	6.50	6.80	1.6	8.00	8.20	8.60	2.0	10.10	10.10	10.20	2.2	11.00	11.10	11.20	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.0	1.20	1.30	1.60																																																							
0.4	2.90	3.10	3.40																																																							
0.8	4.40	4.50	5.10																																																							
1.2	6.40	6.50	6.80																																																							
1.6	8.00	8.20	8.60																																																							
2.0	10.10	10.10	10.20																																																							
2.2	11.00	11.10	11.20																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF1003	Temperature	25°C																																
Item	Efficiency (by Input Voltage) 効率（入力電圧特性）	Testing Circuitry	Figure A																																
Object																																			
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p> <table border="1"> <caption>Data extracted from Figure 1 graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>150</td><td>61.8</td><td>66.8</td></tr> <tr><td>160</td><td>61.8</td><td>66.1</td></tr> <tr><td>170</td><td>60.7</td><td>66.1</td></tr> <tr><td>180</td><td>61.8</td><td>66.1</td></tr> <tr><td>200</td><td>60.7</td><td>66.1</td></tr> <tr><td>220</td><td>59.6</td><td>66.1</td></tr> <tr><td>240</td><td>56.6</td><td>65.5</td></tr> <tr><td>260</td><td>55.6</td><td>64.8</td></tr> <tr><td>280</td><td>55.6</td><td>64.8</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	150	61.8	66.8	160	61.8	66.1	170	60.7	66.1	180	61.8	66.1	200	60.7	66.1	220	59.6	66.1	240	56.6	65.5	260	55.6	64.8	280	55.6	64.8		
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																	
150	61.8	66.8																																	
160	61.8	66.1																																	
170	60.7	66.1																																	
180	61.8	66.1																																	
200	60.7	66.1																																	
220	59.6	66.1																																	
240	56.6	65.5																																	
260	55.6	64.8																																	
280	55.6	64.8																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>61.8</td><td>66.8</td></tr> <tr><td>160</td><td>61.8</td><td>66.1</td></tr> <tr><td>170</td><td>60.7</td><td>66.1</td></tr> <tr><td>180</td><td>61.8</td><td>66.1</td></tr> <tr><td>200</td><td>60.7</td><td>66.1</td></tr> <tr><td>220</td><td>60.7</td><td>66.1</td></tr> <tr><td>240</td><td>59.6</td><td>66.1</td></tr> <tr><td>264</td><td>56.6</td><td>65.5</td></tr> <tr><td>280</td><td>55.6</td><td>64.8</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	150	61.8	66.8	160	61.8	66.1	170	60.7	66.1	180	61.8	66.1	200	60.7	66.1	220	60.7	66.1	240	59.6	66.1	264	56.6	65.5	280	55.6	64.8
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
150	61.8	66.8																																	
160	61.8	66.1																																	
170	60.7	66.1																																	
180	61.8	66.1																																	
200	60.7	66.1																																	
220	60.7	66.1																																	
240	59.6	66.1																																	
264	56.6	65.5																																	
280	55.6	64.8																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	VAF1003	Temperature	25°C																																																			
Item	Efficiency (by Load Current) 効率(負荷特性)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1. Graph	<p>The graph plots Efficiency [%] on the Y-axis (20 to 80) against Load Current [A] on the X-axis (0 to 2.5). Three data series are shown for different input voltages: 170V (triangles), 200V (squares), and 264V (circles). All three curves show an increasing trend in efficiency as load current increases. A slanted line is drawn across the graph, representing the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 170V [%]</th> <th>Input Volt. 200V [%]</th> <th>Input Volt. 264V [%]</th> </tr> </thead> <tbody> <tr> <td>0.4</td> <td>46.2</td> <td>43.2</td> <td>39.4</td> </tr> <tr> <td>0.8</td> <td>60.6</td> <td>59.3</td> <td>52.3</td> </tr> <tr> <td>1.2</td> <td>62.6</td> <td>61.7</td> <td>58.9</td> </tr> <tr> <td>1.6</td> <td>66.9</td> <td>65.2</td> <td>62.2</td> </tr> <tr> <td>2.0</td> <td>66.1</td> <td>66.1</td> <td>65.5</td> </tr> <tr> <td>2.2</td> <td>66.8</td> <td>66.2</td> <td>65.6</td> </tr> </tbody> </table>			Load Current [A]	Input Volt. 170V [%]	Input Volt. 200V [%]	Input Volt. 264V [%]	0.4	46.2	43.2	39.4	0.8	60.6	59.3	52.3	1.2	62.6	61.7	58.9	1.6	66.9	65.2	62.2	2.0	66.1	66.1	65.5	2.2	66.8	66.2	65.6																							
Load Current [A]	Input Volt. 170V [%]	Input Volt. 200V [%]	Input Volt. 264V [%]																																																			
0.4	46.2	43.2	39.4																																																			
0.8	60.6	59.3	52.3																																																			
1.2	62.6	61.7	58.9																																																			
1.6	66.9	65.2	62.2																																																			
2.0	66.1	66.1	65.5																																																			
2.2	66.8	66.2	65.6																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>0.4</td> <td>46.2</td> <td>43.2</td> <td>39.4</td> </tr> <tr> <td>0.8</td> <td>60.6</td> <td>59.3</td> <td>52.3</td> </tr> <tr> <td>1.2</td> <td>62.6</td> <td>61.7</td> <td>58.9</td> </tr> <tr> <td>1.6</td> <td>66.9</td> <td>65.2</td> <td>62.2</td> </tr> <tr> <td>2.0</td> <td>66.1</td> <td>66.1</td> <td>65.5</td> </tr> <tr> <td>2.2</td> <td>66.8</td> <td>66.2</td> <td>65.6</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.4	46.2	43.2	39.4	0.8	60.6	59.3	52.3	1.2	62.6	61.7	58.9	1.6	66.9	65.2	62.2	2.0	66.1	66.1	65.5	2.2	66.8	66.2	65.6	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0.4	46.2	43.2	39.4																																																			
0.8	60.6	59.3	52.3																																																			
1.2	62.6	61.7	58.9																																																			
1.6	66.9	65.2	62.2																																																			
2.0	66.1	66.1	65.5																																																			
2.2	66.8	66.2	65.6																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF1003	Temperature	25°C																															
Item	Power Factor (by Input Voltage) 力率(入力電圧特性)	Testing Circuitry	Figure A																															
Object																																		
1. Graph	<p style="text-align: center;">□ Load 50% △ Load 100%</p>																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>0.44</td><td>0.48</td></tr> <tr><td>160</td><td>0.44</td><td>0.48</td></tr> <tr><td>170</td><td>0.44</td><td>0.48</td></tr> <tr><td>180</td><td>0.43</td><td>0.48</td></tr> <tr><td>200</td><td>0.44</td><td>0.48</td></tr> <tr><td>220</td><td>0.43</td><td>0.48</td></tr> <tr><td>240</td><td>0.44</td><td>0.48</td></tr> <tr><td>264</td><td>0.44</td><td>0.48</td></tr> <tr><td>280</td><td>0.44</td><td>0.48</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	150	0.44	0.48	160	0.44	0.48	170	0.44	0.48	180	0.43	0.48	200	0.44	0.48	220	0.43	0.48	240	0.44	0.48	264	0.44	0.48	280	0.44	0.48
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
150	0.44	0.48																																
160	0.44	0.48																																
170	0.44	0.48																																
180	0.43	0.48																																
200	0.44	0.48																																
220	0.43	0.48																																
240	0.44	0.48																																
264	0.44	0.48																																
280	0.44	0.48																																

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	VAF1003	Temperature	25°C																																																							
Item	Power Factor (by Load Current) 力率(負荷特性)	Testing Circuitry	Figure A																																																							
Object																																																										
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 170V (△) Input Volt. 200V (□) Input Volt. 264V (○) <p>Approximate data points from graph:</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>170V [PF]</th> <th>200V [PF]</th> <th>264V [PF]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.31</td><td>0.31</td><td>0.27</td></tr> <tr><td>0.5</td><td>0.37</td><td>0.37</td><td>0.32</td></tr> <tr><td>1.0</td><td>0.39</td><td>0.39</td><td>0.35</td></tr> <tr><td>1.5</td><td>0.42</td><td>0.42</td><td>0.37</td></tr> <tr><td>2.0</td><td>0.45</td><td>0.45</td><td>0.40</td></tr> <tr><td>2.5</td><td>0.46</td><td>0.46</td><td>0.39</td></tr> </tbody> </table>			Load Current [A]	170V [PF]	200V [PF]	264V [PF]	0.0	0.31	0.31	0.27	0.5	0.37	0.37	0.32	1.0	0.39	0.39	0.35	1.5	0.42	0.42	0.37	2.0	0.45	0.45	0.40	2.5	0.46	0.46	0.39																											
Load Current [A]	170V [PF]	200V [PF]	264V [PF]																																																							
0.0	0.31	0.31	0.27																																																							
0.5	0.37	0.37	0.32																																																							
1.0	0.39	0.39	0.35																																																							
1.5	0.42	0.42	0.37																																																							
2.0	0.45	0.45	0.40																																																							
2.5	0.46	0.46	0.39																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.31</td><td>0.31</td><td>0.27</td></tr> <tr><td>0.4</td><td>0.37</td><td>0.35</td><td>0.31</td></tr> <tr><td>0.8</td><td>0.39</td><td>0.37</td><td>0.34</td></tr> <tr><td>1.2</td><td>0.42</td><td>0.39</td><td>0.36</td></tr> <tr><td>1.6</td><td>0.43</td><td>0.41</td><td>0.38</td></tr> <tr><td>2.0</td><td>0.45</td><td>0.43</td><td>0.39</td></tr> <tr><td>2.2</td><td>0.46</td><td>0.44</td><td>0.39</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	0.31	0.31	0.27	0.4	0.37	0.35	0.31	0.8	0.39	0.37	0.34	1.2	0.42	0.39	0.36	1.6	0.43	0.41	0.38	2.0	0.45	0.43	0.39	2.2	0.46	0.44	0.39	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Power Factor																																																									
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																							
0.0	0.31	0.31	0.27																																																							
0.4	0.37	0.35	0.31																																																							
0.8	0.39	0.37	0.34																																																							
1.2	0.42	0.39	0.36																																																							
1.6	0.43	0.41	0.38																																																							
2.0	0.45	0.43	0.39																																																							
2.2	0.46	0.44	0.39																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL


Model	VAF1003	Temperature	25°C																																
Item	Hold-Up Time 出力保持時間	Testing Circuitry	Figure A																																
Object	+3.3V2A																																		
1. Graph																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>150</td><td>125</td><td>62</td></tr> <tr> <td>160</td><td>143</td><td>72</td></tr> <tr> <td>170</td><td>162</td><td>82</td></tr> <tr> <td>180</td><td>183</td><td>93</td></tr> <tr> <td>200</td><td>227</td><td>117</td></tr> <tr> <td>220</td><td>277</td><td>143</td></tr> <tr> <td>240</td><td>331</td><td>172</td></tr> <tr> <td>264</td><td>402</td><td>211</td></tr> <tr> <td>280</td><td>452</td><td>239</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	150	125	62	160	143	72	170	162	82	180	183	93	200	227	117	220	277	143	240	331	172	264	402	211	280	452	239
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
150	125	62																																	
160	143	72																																	
170	162	82																																	
180	183	93																																	
200	227	117																																	
220	277	143																																	
240	331	172																																	
264	402	211																																	
280	452	239																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	VAF1003	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障	Testing Circuitry	Figure A																																																			
Object	+3.3V 2A																																																					
1. Graph		2. Values																																																				
<p>The graph plots Instantaneous Compensation Time [mS] on a logarithmic y-axis (from 1 to 1000) against Load Current [A] on the x-axis (from 0 to 2.5). Three data series are shown for Input Volt. 170 V (triangles), Input Volt. 200 V (squares), and Input Volt. 264 V (circles). All series show a decreasing trend as load current increases. A slanted line is drawn through the data points, representing the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.4</td><td>293</td><td>418</td><td>718</td></tr> <tr><td>0.8</td><td>168</td><td>243</td><td>427</td></tr> <tr><td>1.2</td><td>102</td><td>159</td><td>293</td></tr> <tr><td>1.6</td><td>77</td><td>118</td><td>219</td></tr> <tr><td>2.0</td><td>65</td><td>93</td><td>176</td></tr> <tr><td>2.2</td><td>65</td><td>90</td><td>165</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Time [mS]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0.0	—	—	—	0.4	293	418	718	0.8	168	243	427	1.2	102	159	293	1.6	77	118	219	2.0	65	93	176	2.2	65	90	165	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0.0	—	—	—																																																			
0.4	293	418	718																																																			
0.8	168	243	427																																																			
1.2	102	159	293																																																			
1.6	77	118	219																																																			
2.0	65	93	176																																																			
2.2	65	90	165																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間という。 (注)斜線は定格負荷電流範囲を示す。</p>																																																						

COSEL

Model	VAF1003
Item	Load Regulation 静的負荷変動
Object	+3.3V2A



Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
0.0	3.319	3.319	3.319
0.4	3.318	3.318	3.318
0.8	3.317	3.317	3.317
1.2	3.316	3.316	3.316
1.6	3.315	3.315	3.315
2.0	3.314	3.314	3.314
2.2	3.313	3.313	3.314
—	—	—	—
—	—	—	—
—	—	—	—

COSEL


Model	VAF1003	Temperature Testing Circuitry	25°C Figure A																																																									
Item	Overcurrent Protection 過電流保護																																																											
Object	+3.3V2A																																																											
1. Graph	[V]	Input Volt. 170 V Input Volt. 200 V Input Volt. 264 V	2. Values																																																									
<p>The graph plots Output Voltage [V] on the y-axis (0.0 to 5.0) against Load Current [A] on the x-axis (0 to 10). Three solid curves represent different input voltages: 170V (top), 200V (middle), and 264V (bottom). A vertical hatched line is drawn at a load current of approximately 1.8A, indicating the rated load current range. A slanted line extends from the 264V curve at low currents, showing the peak current during intermittent operation when the output voltage drops below the rated value.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>3.30</td><td>6.08</td><td>6.30</td><td>6.90</td></tr> <tr><td>3.13</td><td>6.09</td><td>6.30</td><td>6.91</td></tr> <tr><td>2.97</td><td>6.15</td><td>6.35</td><td>6.94</td></tr> <tr><td>2.64</td><td>6.40</td><td>6.65</td><td>7.14</td></tr> <tr><td>2.31</td><td>6.72</td><td>6.92</td><td>7.40</td></tr> <tr><td>1.98</td><td>7.06</td><td>7.25</td><td>7.73</td></tr> <tr><td>1.65</td><td>7.43</td><td>7.65</td><td>8.11</td></tr> <tr><td>1.32</td><td>7.89</td><td>8.12</td><td>8.55</td></tr> <tr><td>0.99</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.66</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.33</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.00</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	3.30	6.08	6.30	6.90	3.13	6.09	6.30	6.91	2.97	6.15	6.35	6.94	2.64	6.40	6.65	7.14	2.31	6.72	6.92	7.40	1.98	7.06	7.25	7.73	1.65	7.43	7.65	8.11	1.32	7.89	8.12	8.55	0.99	—	—	—	0.66	—	—	—	0.33	—	—	—	0.00	—	—	—
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																									
3.30	6.08	6.30	6.90																																																									
3.13	6.09	6.30	6.91																																																									
2.97	6.15	6.35	6.94																																																									
2.64	6.40	6.65	7.14																																																									
2.31	6.72	6.92	7.40																																																									
1.98	7.06	7.25	7.73																																																									
1.65	7.43	7.65	8.11																																																									
1.32	7.89	8.12	8.55																																																									
0.99	—	—	—																																																									
0.66	—	—	—																																																									
0.33	—	—	—																																																									
0.00	—	—	—																																																									


Note1: Slanted line shows the range of the rated load current.

Note2: The lines shows peak current of intermittent operation of power supply when output voltage drops less than rated voltage value at overcurrent.

(注1)斜線は定格負荷電流範囲を示す。

(注2)垂下部分は間欠モード時のピーク電流を示す。

COSEL

COSEL

COSEL

Model	VAF1003	Testing Circuitry Figure A																																																						
Item	Ambient Temperature Drift 周囲温度変動																																																							
Object	+3.3V2A																																																							
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	2. Values																																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>-30</td><td>3.317</td><td>3.317</td><td>3.317</td></tr> <tr> <td>-20</td><td>3.317</td><td>3.317</td><td>3.317</td></tr> <tr> <td>-10</td><td>3.316</td><td>3.316</td><td>3.317</td></tr> <tr> <td>0</td><td>3.316</td><td>3.316</td><td>3.316</td></tr> <tr> <td>10</td><td>3.315</td><td>3.315</td><td>3.315</td></tr> <tr> <td>25</td><td>3.314</td><td>3.314</td><td>3.314</td></tr> <tr> <td>30</td><td>3.312</td><td>3.312</td><td>3.313</td></tr> <tr> <td>40</td><td>3.311</td><td>3.311</td><td>3.311</td></tr> <tr> <td>55</td><td>3.308</td><td>3.308</td><td>3.308</td></tr> <tr> <td>60</td><td>3.306</td><td>3.306</td><td>3.306</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	-30	3.317	3.317	3.317	-20	3.317	3.317	3.317	-10	3.316	3.316	3.317	0	3.316	3.316	3.316	10	3.315	3.315	3.315	25	3.314	3.314	3.314	30	3.312	3.312	3.313	40	3.311	3.311	3.311	55	3.308	3.308	3.308	60	3.306	3.306	3.306	—	—	—	—			
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																					
-30	3.317	3.317	3.317																																																					
-20	3.317	3.317	3.317																																																					
-10	3.316	3.316	3.317																																																					
0	3.316	3.316	3.316																																																					
10	3.315	3.315	3.315																																																					
25	3.314	3.314	3.314																																																					
30	3.312	3.312	3.313																																																					
40	3.311	3.311	3.311																																																					
55	3.308	3.308	3.308																																																					
60	3.306	3.306	3.306																																																					
—	—	—	—																																																					

COSEL

Model	VAF1003	Testing Circuitry Figure A																																							
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧																																								
Object	+3.3V2A																																								
1. Graph	<p>[V]</p> <p>Load 50% Load 100%</p> <p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p>	2. Values																																							
			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-30</td><td>43</td><td>53</td></tr> <tr><td>-20</td><td>42</td><td>53</td></tr> <tr><td>-10</td><td>42</td><td>53</td></tr> <tr><td>0</td><td>41</td><td>53</td></tr> <tr><td>10</td><td>41</td><td>53</td></tr> <tr><td>25</td><td>41</td><td>52</td></tr> <tr><td>30</td><td>40</td><td>51</td></tr> <tr><td>40</td><td>40</td><td>52</td></tr> <tr><td>55</td><td>40</td><td>53</td></tr> <tr><td>60</td><td>40</td><td>53</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-30	43	53	-20	42	53	-10	42	53	0	41	53	10	41	53	25	41	52	30	40	51	40	40	52	55	40	53	60	40	53	—	—	—
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-30	43	53																																							
-20	42	53																																							
-10	42	53																																							
0	41	53																																							
10	41	53																																							
25	41	52																																							
30	40	51																																							
40	40	52																																							
55	40	53																																							
60	40	53																																							
—	—	—																																							

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	VAF1003	Temperature	25°C																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+3.3V2A																								
1. Graph																									
[V]																									
Output Voltage																									
Input Volt.	200V																								
Load	100%																								
2. Values																									
Time since start [H]	<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.315</td></tr> <tr><td>0.5</td><td>3.313</td></tr> <tr><td>1.0</td><td>3.313</td></tr> <tr><td>2.0</td><td>3.313</td></tr> <tr><td>3.0</td><td>3.313</td></tr> <tr><td>4.0</td><td>3.313</td></tr> <tr><td>5.0</td><td>3.313</td></tr> <tr><td>6.0</td><td>3.313</td></tr> <tr><td>7.0</td><td>3.313</td></tr> <tr><td>8.0</td><td>3.313</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	3.315	0.5	3.313	1.0	3.313	2.0	3.313	3.0	3.313	4.0	3.313	5.0	3.313	6.0	3.313	7.0	3.313	8.0	3.313
Time since start [H]	Output Voltage [V]																								
0.0	3.315																								
0.5	3.313																								
1.0	3.313																								
2.0	3.313																								
3.0	3.313																								
4.0	3.313																								
5.0	3.313																								
6.0	3.313																								
7.0	3.313																								
8.0	3.313																								



Model	VAF1003	
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry Figure A
Object	+3.3V2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~55 °C

Input Voltage : 170~264 V

Load Current : 0~2 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~55 °C

入力電圧 170~264 V

負荷電流 0~2 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	170	0	3.321		
Minimum Voltage	55	264	2	3.307	±7	±0.3

COSEL




Figure A




Figure B (DENTORI)




Figure B (IEC60950)

COSEL




Figure C




Figure D




Figure E