



## TEST DATA OF VAF503 (100V INPUT)

Regulated DC Power Supply

Nov. 9, 1999

Approved by : M. Nakata  
Design Manager

Prepared by : T. Yamashina  
Design Engineer

コーワセル株式会社  
**COSEL CO., LTD.**



## C O N T E N T S


1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流(負荷特性)	
3. Input Power (by Load Current)	3
入力電力(負荷特性)	
4. Efficiency (by Input Voltage)	4
効率(入力電圧特性)	
5. Efficiency (by Load Current)	5
効率(負荷特性)	
6. Power Factor (by Input Voltage)	6
力率(入力電圧特性)	
7. Power Factor (by Load Current)	7
力率(負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保障	
10. Load Regulation	10
静的負荷変動	
11. Overcurrent Protection	11
過電流保護	
12. Inrush Current	12
突入電流	
13. Rise and Fall Time	13
立ち上り、立下り時間	
14. Ambient Temperature Drift	14
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	15
最低レギュレーション電圧	
16. Time Lapse Drift	16
経時ドリフト	
17. Output Voltage Accuracy	17
定電圧精度	
18. Figure of Testing Circuitry	18
測定回路図	

(Final Page 19 )

**COSEL**

Model	VAF503	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation 静的入力変動																																		
Object	+3.3V1A	2. Values																																	
1. Graph	<p>Load 50%      □</p> <p>Load 100%      △</p>																																		
	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>3.327</td><td>3.325</td></tr> <tr><td>80</td><td>3.327</td><td>3.325</td></tr> <tr><td>85</td><td>3.327</td><td>3.325</td></tr> <tr><td>90</td><td>3.327</td><td>3.325</td></tr> <tr><td>100</td><td>3.327</td><td>3.325</td></tr> <tr><td>110</td><td>3.327</td><td>3.325</td></tr> <tr><td>120</td><td>3.327</td><td>3.325</td></tr> <tr><td>132</td><td>3.327</td><td>3.325</td></tr> <tr><td>140</td><td>3.327</td><td>3.325</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	3.327	3.325	80	3.327	3.325	85	3.327	3.325	90	3.327	3.325	100	3.327	3.325	110	3.327	3.325	120	3.327	3.325	132	3.327	3.325	140	3.327	3.325
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	3.327	3.325																																	
80	3.327	3.325																																	
85	3.327	3.325																																	
90	3.327	3.325																																	
100	3.327	3.325																																	
110	3.327	3.325																																	
120	3.327	3.325																																	
132	3.327	3.325																																	
140	3.327	3.325																																	
Note:	Slanted line shows the range of the rated input voltage.																																		
(注)	斜線は定格入力電圧範囲を示す。																																		

**COSEL**

Model	VAF503	Temperature	25°C																																																							
Item	Input Current (by Load Current) 入力電流（負荷特性）	Testing Circuitry	Figure A																																																							
Object																																																										
1. Graph	<p>—△— Input Volt. 85V        .....□..... Input Volt. 100V        .....○..... Input Volt. 132V</p>  <p>The graph plots Input Current [A] on the y-axis (0 to 0.2) against Load Current [A] on the x-axis (0 to 1.2). Three curves are shown for different input voltages: 85V (triangles), 100V (squares), and 132V (circles). All curves show a positive linear relationship between input current and load current. A slanted line is drawn across the graph, representing the rated load current range.</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.014</td><td>0.014</td><td>0.013</td></tr> <tr><td>0.2</td><td>0.036</td><td>0.033</td><td>0.027</td></tr> <tr><td>0.4</td><td>0.055</td><td>0.048</td><td>0.042</td></tr> <tr><td>0.6</td><td>0.073</td><td>0.067</td><td>0.056</td></tr> <tr><td>0.8</td><td>0.091</td><td>0.081</td><td>0.069</td></tr> <tr><td>1.0</td><td>0.109</td><td>0.098</td><td>0.081</td></tr> <tr><td>1.1</td><td>0.118</td><td>0.106</td><td>0.088</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.014	0.014	0.013	0.2	0.036	0.033	0.027	0.4	0.055	0.048	0.042	0.6	0.073	0.067	0.056	0.8	0.091	0.081	0.069	1.0	0.109	0.098	0.081	1.1	0.118	0.106	0.088	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	0.014	0.014	0.013																																																							
0.2	0.036	0.033	0.027																																																							
0.4	0.055	0.048	0.042																																																							
0.6	0.073	0.067	0.056																																																							
0.8	0.091	0.081	0.069																																																							
1.0	0.109	0.098	0.081																																																							
1.1	0.118	0.106	0.088																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF503	Temperature	25°C																																																							
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Testing Circuitry	Figure A																																																							
Object	<hr/>																																																									
1. Graph	<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 85V  <span style="color: gray;">—□—</span> Input Volt. 100V  <span style="color: lightgray;">—○—</span> Input Volt. 132V         </p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power 85V [W]</th> <th>Input Power 100V [W]</th> <th>Input Power 132V [W]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.42</td><td>0.47</td><td>0.55</td></tr> <tr><td>0.2</td><td>1.27</td><td>1.29</td><td>1.30</td></tr> <tr><td>0.4</td><td>2.12</td><td>2.08</td><td>2.17</td></tr> <tr><td>0.6</td><td>2.99</td><td>3.05</td><td>3.05</td></tr> <tr><td>0.8</td><td>3.94</td><td>3.87</td><td>3.98</td></tr> <tr><td>1.0</td><td>4.90</td><td>4.89</td><td>4.80</td></tr> <tr><td>1.1</td><td>5.37</td><td>5.34</td><td>5.29</td></tr> </tbody> </table>			Load Current [A]	Input Power 85V [W]	Input Power 100V [W]	Input Power 132V [W]	0.0	0.42	0.47	0.55	0.2	1.27	1.29	1.30	0.4	2.12	2.08	2.17	0.6	2.99	3.05	3.05	0.8	3.94	3.87	3.98	1.0	4.90	4.89	4.80	1.1	5.37	5.34	5.29																							
Load Current [A]	Input Power 85V [W]	Input Power 100V [W]	Input Power 132V [W]																																																							
0.0	0.42	0.47	0.55																																																							
0.2	1.27	1.29	1.30																																																							
0.4	2.12	2.08	2.17																																																							
0.6	2.99	3.05	3.05																																																							
0.8	3.94	3.87	3.98																																																							
1.0	4.90	4.89	4.80																																																							
1.1	5.37	5.34	5.29																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.42</td><td>0.47</td><td>0.55</td></tr> <tr><td>0.2</td><td>1.27</td><td>1.29</td><td>1.30</td></tr> <tr><td>0.4</td><td>2.12</td><td>2.08</td><td>2.17</td></tr> <tr><td>0.6</td><td>2.99</td><td>3.05</td><td>3.05</td></tr> <tr><td>0.8</td><td>3.94</td><td>3.87</td><td>3.98</td></tr> <tr><td>1.0</td><td>4.90</td><td>4.89</td><td>4.80</td></tr> <tr><td>1.1</td><td>5.37</td><td>5.34</td><td>5.29</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.42	0.47	0.55	0.2	1.27	1.29	1.30	0.4	2.12	2.08	2.17	0.6	2.99	3.05	3.05	0.8	3.94	3.87	3.98	1.0	4.90	4.89	4.80	1.1	5.37	5.34	5.29	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	0.42	0.47	0.55																																																							
0.2	1.27	1.29	1.30																																																							
0.4	2.12	2.08	2.17																																																							
0.6	2.99	3.05	3.05																																																							
0.8	3.94	3.87	3.98																																																							
1.0	4.90	4.89	4.80																																																							
1.1	5.37	5.34	5.29																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

# COSEL

Model	VAF503	Temperature	25°C																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																																
Object																																			
1. Graph	<p style="text-align: center;">□ Load 50%      △ Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>64.4</td> <td>67.0</td> </tr> <tr> <td>80</td> <td>63.9</td> <td>67.3</td> </tr> <tr> <td>85</td> <td>63.6</td> <td>67.4</td> </tr> <tr> <td>90</td> <td>63.6</td> <td>67.5</td> </tr> <tr> <td>100</td> <td>63.9</td> <td>67.6</td> </tr> <tr> <td>110</td> <td>64.4</td> <td>68.0</td> </tr> <tr> <td>120</td> <td>64.7</td> <td>68.5</td> </tr> <tr> <td>132</td> <td>64.7</td> <td>68.8</td> </tr> <tr> <td>140</td> <td>64.4</td> <td>68.8</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	64.4	67.0	80	63.9	67.3	85	63.6	67.4	90	63.6	67.5	100	63.9	67.6	110	64.4	68.0	120	64.7	68.5	132	64.7	68.8	140	64.4	68.8
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	64.4	67.0																																	
80	63.9	67.3																																	
85	63.6	67.4																																	
90	63.6	67.5																																	
100	63.9	67.6																																	
110	64.4	68.0																																	
120	64.7	68.5																																	
132	64.7	68.8																																	
140	64.4	68.8																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	VAF503	Temperature	25°C																																																							
Item	Efficiency (by Load Current) 効率(負荷特性)	Testing Circuitry	Figure A																																																							
Object	<hr/>																																																									
1. Graph	<p>The graph plots Efficiency [%] on the y-axis (30 to 90) against Load Current [A] on the x-axis (0 to 1.2). Three data series are shown for different input voltages: 85V (triangles), 100V (squares), and 132V (circles). All curves show efficiency increasing with load current. A slanted line on the right side of the graph indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85V [%]</th> <th>Input Volt. 100V [%]</th> <th>Input Volt. 132V [%]</th> </tr> </thead> <tbody> <tr><td>0.2</td><td>52.0</td><td>51.2</td><td>51.0</td></tr> <tr><td>0.4</td><td>62.5</td><td>63.7</td><td>61.1</td></tr> <tr><td>0.6</td><td>66.0</td><td>64.8</td><td>64.8</td></tr> <tr><td>0.8</td><td>67.0</td><td>68.2</td><td>66.3</td></tr> <tr><td>1.0</td><td>67.4</td><td>67.6</td><td>68.8</td></tr> <tr><td>1.1</td><td>67.4</td><td>67.8</td><td>68.5</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85V [%]	Input Volt. 100V [%]	Input Volt. 132V [%]	0.2	52.0	51.2	51.0	0.4	62.5	63.7	61.1	0.6	66.0	64.8	64.8	0.8	67.0	68.2	66.3	1.0	67.4	67.6	68.8	1.1	67.4	67.8	68.5																											
Load Current [A]	Input Volt. 85V [%]	Input Volt. 100V [%]	Input Volt. 132V [%]																																																							
0.2	52.0	51.2	51.0																																																							
0.4	62.5	63.7	61.1																																																							
0.6	66.0	64.8	64.8																																																							
0.8	67.0	68.2	66.3																																																							
1.0	67.4	67.6	68.8																																																							
1.1	67.4	67.8	68.5																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.2</td><td>52.0</td><td>51.2</td><td>51.0</td></tr> <tr><td>0.4</td><td>62.5</td><td>63.7</td><td>61.1</td></tr> <tr><td>0.6</td><td>66.0</td><td>64.8</td><td>64.8</td></tr> <tr><td>0.8</td><td>67.0</td><td>68.2</td><td>66.3</td></tr> <tr><td>1.0</td><td>67.4</td><td>67.6</td><td>68.8</td></tr> <tr><td>1.1</td><td>67.4</td><td>67.8</td><td>68.5</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.2	52.0	51.2	51.0	0.4	62.5	63.7	61.1	0.6	66.0	64.8	64.8	0.8	67.0	68.2	66.3	1.0	67.4	67.6	68.8	1.1	67.4	67.8	68.5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.2	52.0	51.2	51.0																																																							
0.4	62.5	63.7	61.1																																																							
0.6	66.0	64.8	64.8																																																							
0.8	67.0	68.2	66.3																																																							
1.0	67.4	67.6	68.8																																																							
1.1	67.4	67.8	68.5																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF503	Temperature	25°C																																
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)	Testing Circuitry	Figure A																																
Object																																			
1. Graph	<p style="text-align: center;">□ ..... Load 50%  <span style="margin-left: 100px;">△ ----- Load 100%</span></p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.50</td><td>0.56</td></tr> <tr><td>80</td><td>0.48</td><td>0.54</td></tr> <tr><td>85</td><td>0.48</td><td>0.53</td></tr> <tr><td>90</td><td>0.46</td><td>0.52</td></tr> <tr><td>100</td><td>0.45</td><td>0.50</td></tr> <tr><td>110</td><td>0.43</td><td>0.48</td></tr> <tr><td>120</td><td>0.42</td><td>0.47</td></tr> <tr><td>132</td><td>0.40</td><td>0.45</td></tr> <tr><td>140</td><td>0.39</td><td>0.44</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.50	0.56	80	0.48	0.54	85	0.48	0.53	90	0.46	0.52	100	0.45	0.50	110	0.43	0.48	120	0.42	0.47	132	0.40	0.45	140	0.39	0.44
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
75	0.50	0.56																																	
80	0.48	0.54																																	
85	0.48	0.53																																	
90	0.46	0.52																																	
100	0.45	0.50																																	
110	0.43	0.48																																	
120	0.42	0.47																																	
132	0.40	0.45																																	
140	0.39	0.44																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。


**COSSEL**

Model	VAF503	Temperature	25°C																																																							
Item	Power Factor (by Load Current) 力率(負荷特性)	Testing Circuitry	Figure A																																																							
Object	——																																																									
1. Graph	<p>Legend: Input Volt. 85V (triangle), Input Volt. 100V (square), Input Volt. 132V (circle).</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.36</td><td>0.34</td><td>0.32</td></tr> <tr><td>0.2</td><td>0.42</td><td>0.40</td><td>0.36</td></tr> <tr><td>0.4</td><td>0.46</td><td>0.43</td><td>0.39</td></tr> <tr><td>0.6</td><td>0.49</td><td>0.46</td><td>0.42</td></tr> <tr><td>0.8</td><td>0.51</td><td>0.48</td><td>0.44</td></tr> <tr><td>1.0</td><td>0.53</td><td>0.50</td><td>0.45</td></tr> <tr><td>1.1</td><td>0.54</td><td>0.51</td><td>0.46</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.36	0.34	0.32	0.2	0.42	0.40	0.36	0.4	0.46	0.43	0.39	0.6	0.49	0.46	0.42	0.8	0.51	0.48	0.44	1.0	0.53	0.50	0.45	1.1	0.54	0.51	0.46	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Power Factor																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	0.36	0.34	0.32																																																							
0.2	0.42	0.40	0.36																																																							
0.4	0.46	0.43	0.39																																																							
0.6	0.49	0.46	0.42																																																							
0.8	0.51	0.48	0.44																																																							
1.0	0.53	0.50	0.45																																																							
1.1	0.54	0.51	0.46																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF503	Temperature	25°C																																
Item	Hold-Up Time 出力保持時間	Testing Circuitry	Figure A																																
Object	+3.3V1A																																		
1. Graph	Load 50% 																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>35</td><td>15</td></tr> <tr><td>80</td><td>42</td><td>18</td></tr> <tr><td>85</td><td>48</td><td>22</td></tr> <tr><td>90</td><td>56</td><td>26</td></tr> <tr><td>100</td><td>72</td><td>34</td></tr> <tr><td>110</td><td>89</td><td>43</td></tr> <tr><td>120</td><td>109</td><td>53</td></tr> <tr><td>132</td><td>135</td><td>67</td></tr> <tr><td>140</td><td>154</td><td>76</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	35	15	80	42	18	85	48	22	90	56	26	100	72	34	110	89	43	120	109	53	132	135	67	140	154	76
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	35	15																																	
80	42	18																																	
85	48	22																																	
90	56	26																																	
100	72	34																																	
110	89	43																																	
120	109	53																																	
132	135	67																																	
140	154	76																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

**COSEL**

Model	VAF503	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																					
Object	+3.3V1A																																																					
1. Graph	<p>—△— Input Volt. 85 V        .....□..... Input Volt. 100 V        .....○..... Input Volt. 132 V</p>																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.2</td><td>109</td><td>157</td><td>284</td></tr> <tr><td>0.4</td><td>57</td><td>87</td><td>164</td></tr> <tr><td>0.6</td><td>39</td><td>57</td><td>111</td></tr> <tr><td>0.8</td><td>28</td><td>43</td><td>84</td></tr> <tr><td>1.0</td><td>21</td><td>32</td><td>65</td></tr> <tr><td>1.1</td><td>18</td><td>29</td><td>59</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	—	—	—	0.2	109	157	284	0.4	57	87	164	0.6	39	57	111	0.8	28	43	84	1.0	21	32	65	1.1	18	29	59	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	—	—	—																																																			
0.2	109	157	284																																																			
0.4	57	87	164																																																			
0.6	39	57	111																																																			
0.8	28	43	84																																																			
1.0	21	32	65																																																			
1.1	18	29	59																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																						


**COSEL**

Model	VAF503	Temperature	25°C																																															
Item	Load Regulation 静的負荷変動	Testing Circuitry	Figure A																																															
Object	+3.3V1A																																																	
1. Graph		2. Values																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.328</td><td>3.328</td><td>3.328</td></tr> <tr><td>0.2</td><td>3.327</td><td>3.328</td><td>3.328</td></tr> <tr><td>0.4</td><td>3.327</td><td>3.327</td><td>3.327</td></tr> <tr><td>0.6</td><td>3.326</td><td>3.326</td><td>3.326</td></tr> <tr><td>0.8</td><td>3.326</td><td>3.326</td><td>3.326</td></tr> <tr><td>1.0</td><td>3.325</td><td>3.325</td><td>3.325</td></tr> <tr><td>1.1</td><td>3.325</td><td>3.325</td><td>3.325</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	3.328	3.328	3.328	0.2	3.327	3.328	3.328	0.4	3.327	3.327	3.327	0.6	3.326	3.326	3.326	0.8	3.326	3.326	3.326	1.0	3.325	3.325	3.325	1.1	3.325	3.325	3.325	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.0	3.328	3.328	3.328																																															
0.2	3.327	3.328	3.328																																															
0.4	3.327	3.327	3.327																																															
0.6	3.326	3.326	3.326																																															
0.8	3.326	3.326	3.326																																															
1.0	3.325	3.325	3.325																																															
1.1	3.325	3.325	3.325																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																		

-COSEL

Model	VAF503
Item	Overcurrent Protection 過電流保護
Object	+3.3V1A

Temperature 25°C  
Testing Circuitry Figure A



Note: Slanted line shows the range of the rated load current.

Note2: The lines shows peak current of intermittent operation of power supply when output voltage drops less than rated voltage value at overcurrent.


(注1)斜線は定格負荷電流範囲を示す。

(注2)垂下部分は間欠モード時のピーク電流を示す。

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
3.30	3.01	3.41	3.94
3.13	3.06	3.40	3.94
2.97	3.09	3.42	3.98
2.64	3.32	3.59	4.08
2.31	3.51	3.85	4.35
1.98	3.72	4.05	4.50
1.65	3.89	4.29	4.71
1.32	4.16	4.46	4.89
0.99	—	—	—
0.66	—	—	—
0.33	—	—	—
0.00	—	—	—

COSEL

Model	VAF503	Temperature Testing Circuitry	25°C Figure A
Item	Inrush Current 突入電流		
Object	_____		



Input Voltage 100 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 15.53 [A]


② 0.39 [A]



**COSSEL**


Model	VAF503	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+3.3V1A		

## 1. Graph



## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>	[mS]
50 %		115.0	3.0	118.0	49.0	39.0	
100 %		115.0	3.3	118.3	22.0	31.5	



**COSSEL**

Model	VAF503	Testing Circuitry      Figure A																																																				
Item	Ambient Temperature Drift 周囲温度変動																																																					
Object	+3.3V1A																																																					
1. Graph																																																						
		<p>Output Voltage [V]</p> <p>Input Volt. 85V</p> <p>Input Volt. 100V</p> <p>Input Volt. 132V</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																				
		<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																				
		<p>(注) 斜線は定格周囲温度範囲を示す。</p>																																																				
2. Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>3.321</td><td>3.321</td><td>3.321</td></tr> <tr><td>-20</td><td>3.322</td><td>3.322</td><td>3.322</td></tr> <tr><td>-10</td><td>3.323</td><td>3.323</td><td>3.323</td></tr> <tr><td>0</td><td>3.324</td><td>3.324</td><td>3.324</td></tr> <tr><td>10</td><td>3.325</td><td>3.325</td><td>3.325</td></tr> <tr><td>25</td><td>3.325</td><td>3.325</td><td>3.326</td></tr> <tr><td>30</td><td>3.325</td><td>3.325</td><td>3.325</td></tr> <tr><td>40</td><td>3.326</td><td>3.325</td><td>3.326</td></tr> <tr><td>55</td><td>3.325</td><td>3.325</td><td>3.325</td></tr> <tr><td>60</td><td>3.325</td><td>3.325</td><td>3.325</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-30	3.321	3.321	3.321	-20	3.322	3.322	3.322	-10	3.323	3.323	3.323	0	3.324	3.324	3.324	10	3.325	3.325	3.325	25	3.325	3.325	3.326	30	3.325	3.325	3.325	40	3.326	3.325	3.326	55	3.325	3.325	3.325	60	3.325	3.325	3.325	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-30	3.321	3.321	3.321																																																			
-20	3.322	3.322	3.322																																																			
-10	3.323	3.323	3.323																																																			
0	3.324	3.324	3.324																																																			
10	3.325	3.325	3.325																																																			
25	3.325	3.325	3.326																																																			
30	3.325	3.325	3.325																																																			
40	3.326	3.325	3.326																																																			
55	3.325	3.325	3.325																																																			
60	3.325	3.325	3.325																																																			
—	—	—	—																																																			

COSEL

Model	VAF503		
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	Testing Circuitry Figure A	
Object	+3.3V 1A		
1. Graph			
<p>[V]</p>		Load 50%	Load 100%
2. Values			
Ambient Temperature [°C]	Input Voltage [V]		
	Load 50%	Load 100%	
-30	43	51	
-20	41	51	
-10	41	50	
0	40	48	
10	40	49	
25	40	49	
30	39	49	
40	39	48	
55	38	49	
60	39	48	
—	—	—	

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

**COSEL**

Model	VAF503	Temperature	25°C																					
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																					
Object	+3.3V1A																							
1. Graph																								
<p>[V]</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.324</td></tr> <tr><td>0.5</td><td>3.324</td></tr> <tr><td>1.0</td><td>3.324</td></tr> <tr><td>2.0</td><td>3.324</td></tr> <tr><td>3.0</td><td>3.325</td></tr> <tr><td>4.0</td><td>3.325</td></tr> <tr><td>5.0</td><td>3.324</td></tr> <tr><td>6.0</td><td>3.324</td></tr> <tr><td>7.0</td><td>3.324</td></tr> <tr><td>8.0</td><td>3.324</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	3.324	0.5	3.324	1.0	3.324	2.0	3.324	3.0	3.325	4.0	3.325	5.0	3.324	6.0	3.324	7.0	3.324	8.0	3.324
Time since start [H]	Output Voltage [V]																							
0.0	3.324																							
0.5	3.324																							
1.0	3.324																							
2.0	3.324																							
3.0	3.325																							
4.0	3.325																							
5.0	3.324																							
6.0	3.324																							
7.0	3.324																							
8.0	3.324																							
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			2. Values																					



Model	VAF503		
Item	Output Voltage Accuracy 定電圧精度	Testing Circuitry	Figure A
Object	+3.3V1A		

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~55 °C

Input Voltage : 85~132 V

Load Current : 0~1 A

\* Output Voltage Accuracy =  $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~55 °C

入力電圧 85~132 V

負荷電流 0~1 A

\* 定電圧精度(変動値) =  $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	55	100	0	3.329		
Minimum Voltage	-10	85	1	3.323	±3	±0.1

COSEL




Figure A




Figure B (DENTORI)




Figure B (IEC60950)

COSEL




Figure C




Figure D




Figure E