

COSEL

TEST DATA OF YS512A
(100V INPUT)

Regulated DC Power Supply

Sep. 22, 1999

Approved by : Yuichi Takahashi
Design Manager

Prepared by : Yuichi Takahashi
Design Engineer

コーセル株式会社


COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Current)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保障	
10. Load Regulation	10
静的負荷変動	
11. Ripple Voltage (by Load Current)	11
リップル電圧 (負荷特性)	
12. Ripple-Noise	12
リップルノイズ	
13. Overcurrent Protection	13
過電流保護	
14. Inrush Current	14
突入電流	
15. Dynamic Load Response	15
動的負荷変動	
16. Rise and Fall Time	16
立上り、立下り時間	
17. Ambient Temperature Drift	17
周囲温度変動	
18. Minimum Input Voltage for Regulated Output Voltage	18
最低レギュレーション電圧	
19. Ripple Voltage (by Ambient Temperature)	19
リップル電圧 (周囲温度特性)	
20. Time Lapse Drift	20
経時ドリフト	
21. Output Voltage Accuracy	21
定電圧精度	
22. Oscillator Frequency	22
発振周波数	
23. Condensation	23
結露特性	
24. Leakage Current	24
漏洩電流	
25. Line Noise Tolerance	25
入力雜音耐量	
26. Conducted Emission	26
雜音端子電圧	
27. Figure of Testing Circuitry	27
測定回路図	

(Final Page 28)

COSEL

Temperature 25°C
Testing Circuitry Figure A

COSEL

Model	YS512A	Temperature	25°C																																																							
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Testing Circuitry	Figure A																																																							
Output	<hr/>																																																									
1. Graph	<p>—△— Input Volt. 85V -□- Input Volt. 100V -○- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85V [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 132V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.026</td><td>0.027</td><td>0.030</td></tr> <tr><td>0.080</td><td>0.052</td><td>0.051</td><td>0.053</td></tr> <tr><td>0.160</td><td>0.074</td><td>0.070</td><td>0.068</td></tr> <tr><td>0.240</td><td>0.095</td><td>0.089</td><td>0.082</td></tr> <tr><td>0.320</td><td>0.116</td><td>0.107</td><td>0.096</td></tr> <tr><td>0.400</td><td>0.137</td><td>0.125</td><td>0.110</td></tr> <tr><td>0.450</td><td>0.151</td><td>0.136</td><td>0.119</td></tr> <tr><td>0.495</td><td>0.163</td><td>0.147</td><td>0.127</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85V [A]	Input Volt. 100V [A]	Input Volt. 132V [A]	0.00	0.026	0.027	0.030	0.080	0.052	0.051	0.053	0.160	0.074	0.070	0.068	0.240	0.095	0.089	0.082	0.320	0.116	0.107	0.096	0.400	0.137	0.125	0.110	0.450	0.151	0.136	0.119	0.495	0.163	0.147	0.127																			
Load Current [A]	Input Volt. 85V [A]	Input Volt. 100V [A]	Input Volt. 132V [A]																																																							
0.00	0.026	0.027	0.030																																																							
0.080	0.052	0.051	0.053																																																							
0.160	0.074	0.070	0.068																																																							
0.240	0.095	0.089	0.082																																																							
0.320	0.116	0.107	0.096																																																							
0.400	0.137	0.125	0.110																																																							
0.450	0.151	0.136	0.119																																																							
0.495	0.163	0.147	0.127																																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.026</td><td>0.027</td><td>0.030</td></tr> <tr><td>0.080</td><td>0.052</td><td>0.051</td><td>0.053</td></tr> <tr><td>0.160</td><td>0.074</td><td>0.070</td><td>0.068</td></tr> <tr><td>0.240</td><td>0.095</td><td>0.089</td><td>0.082</td></tr> <tr><td>0.320</td><td>0.116</td><td>0.107</td><td>0.096</td></tr> <tr><td>0.400</td><td>0.137</td><td>0.125</td><td>0.110</td></tr> <tr><td>0.450</td><td>0.151</td><td>0.136</td><td>0.119</td></tr> <tr><td>0.495</td><td>0.163</td><td>0.147</td><td>0.127</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	0.026	0.027	0.030	0.080	0.052	0.051	0.053	0.160	0.074	0.070	0.068	0.240	0.095	0.089	0.082	0.320	0.116	0.107	0.096	0.400	0.137	0.125	0.110	0.450	0.151	0.136	0.119	0.495	0.163	0.147	0.127	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.000	0.026	0.027	0.030																																																							
0.080	0.052	0.051	0.053																																																							
0.160	0.074	0.070	0.068																																																							
0.240	0.095	0.089	0.082																																																							
0.320	0.116	0.107	0.096																																																							
0.400	0.137	0.125	0.110																																																							
0.450	0.151	0.136	0.119																																																							
0.495	0.163	0.147	0.127																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	YS512A	Temperature	25°C																																																							
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Testing Circuitry	Figure A																																																							
Output	<hr/>																																																									
1. Graph	<p style="text-align: center;"> △ Input Volt. 85V □ Input Volt. 100V ○ Input Volt. 132V </p> <p>The graph plots Input Power [W] on the y-axis (0 to 10) against Load Current [A] on the x-axis (0 to 0.6). Three curves are shown for different input voltages: 85V (solid line with triangles), 100V (dashed line with squares), and 132V (dotted line with circles). All curves show a positive linear relationship between power and current. A slanted line is drawn across the graph, starting from approximately (0.05, 1.0) and ending at (0.5, 8.5), representing the rated load current range.</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.87</td><td>1.06</td><td>1.47</td></tr> <tr><td>0.080</td><td>1.98</td><td>2.22</td><td>2.84</td></tr> <tr><td>0.160</td><td>3.03</td><td>3.24</td><td>3.84</td></tr> <tr><td>0.240</td><td>4.13</td><td>4.30</td><td>4.83</td></tr> <tr><td>0.320</td><td>5.25</td><td>5.39</td><td>5.86</td></tr> <tr><td>0.400</td><td>6.41</td><td>6.50</td><td>6.91</td></tr> <tr><td>0.450</td><td>7.18</td><td>7.22</td><td>7.59</td></tr> <tr><td>0.495</td><td>7.89</td><td>7.88</td><td>8.21</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	0.87	1.06	1.47	0.080	1.98	2.22	2.84	0.160	3.03	3.24	3.84	0.240	4.13	4.30	4.83	0.320	5.25	5.39	5.86	0.400	6.41	6.50	6.91	0.450	7.18	7.22	7.59	0.495	7.89	7.88	8.21	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.000	0.87	1.06	1.47																																																							
0.080	1.98	2.22	2.84																																																							
0.160	3.03	3.24	3.84																																																							
0.240	4.13	4.30	4.83																																																							
0.320	5.25	5.39	5.86																																																							
0.400	6.41	6.50	6.91																																																							
0.450	7.18	7.22	7.59																																																							
0.495	7.89	7.88	8.21																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL


Model	YS512A																																	
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Temperature Testing Circuitry 25°C Figure A																																
Object	<hr/>																																	
1. Graph																																		
<p>[%]</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Load 50% □</p> <p>Load 100% ▲</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>70.1</td> <td>73.3</td> </tr> <tr> <td>80</td> <td>69.7</td> <td>74.1</td> </tr> <tr> <td>85</td> <td>68.3</td> <td>74.8</td> </tr> <tr> <td>90</td> <td>67.6</td> <td>74.7</td> </tr> <tr> <td>100</td> <td>65.7</td> <td>74.2</td> </tr> <tr> <td>110</td> <td>63.1</td> <td>73.3</td> </tr> <tr> <td>120</td> <td>60.6</td> <td>71.8</td> </tr> <tr> <td>132</td> <td>57.8</td> <td>70.8</td> </tr> <tr> <td>140</td> <td>55.1</td> <td>69.6</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	70.1	73.3	80	69.7	74.1	85	68.3	74.8	90	67.6	74.7	100	65.7	74.2	110	63.1	73.3	120	60.6	71.8	132	57.8	70.8	140	55.1	69.6
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	70.1	73.3																																
80	69.7	74.1																																
85	68.3	74.8																																
90	67.6	74.7																																
100	65.7	74.2																																
110	63.1	73.3																																
120	60.6	71.8																																
132	57.8	70.8																																
140	55.1	69.6																																

COSEL

Model	YS512A	Temperature	25°C																																																							
Item	Efficiency (by Load Current) 効率(負荷特性)	Testing Circuitry	Figure A																																																							
Output	—																																																									
1. Graph		2. Values																																																								
<p>The graph plots Efficiency [%] on the y-axis (0 to 80) against Load Current [A] on the x-axis (0 to 0.6). Three data series are shown for different input voltages: 85V (triangles), 100V (squares), and 132V (circles). The efficiency generally increases with both load current and input voltage. A slanted line on the graph indicates the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.080</td><td>48.0</td><td>42.9</td><td>33.7</td></tr> <tr><td>0.160</td><td>62.8</td><td>59.1</td><td>49.7</td></tr> <tr><td>0.240</td><td>69.3</td><td>66.9</td><td>59.1</td></tr> <tr><td>0.320</td><td>72.8</td><td>70.9</td><td>65.1</td></tr> <tr><td>0.400</td><td>74.3</td><td>73.2</td><td>68.9</td></tr> <tr><td>0.450</td><td>74.6</td><td>74.2</td><td>70.7</td></tr> <tr><td>0.495</td><td>74.7</td><td>74.6</td><td>71.6</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.080	48.0	42.9	33.7	0.160	62.8	59.1	49.7	0.240	69.3	66.9	59.1	0.320	72.8	70.9	65.1	0.400	74.3	73.2	68.9	0.450	74.6	74.2	70.7	0.495	74.7	74.6	71.6	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.080	48.0	42.9	33.7																																																							
0.160	62.8	59.1	49.7																																																							
0.240	69.3	66.9	59.1																																																							
0.320	72.8	70.9	65.1																																																							
0.400	74.3	73.2	68.9																																																							
0.450	74.6	74.2	70.7																																																							
0.495	74.7	74.6	71.6																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSEL


Temperature 25°C
Testing Circuitry Figure A

COSEL

Model	YS512A	Temperature	25°C																																																							
Item	Power Factor (by Load Current) 力率(負荷特性)	Testing Circuitry	Figure A																																																							
Output	—																																																									
1. Graph		2. Values																																																								
<p>Graph showing Power Factor vs Load Current for YS512A at 25°C. The graph plots Power Factor (Y-axis, 0 to 0.8) against Load Current [A] (X-axis, 0 to 0.6). Three curves are shown for Input Voltages: 85V (triangles), 100V (squares), and 132V (circles). All curves show an upward trend. A slanted line indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.39</td><td>0.39</td><td>0.37</td></tr> <tr><td>0.080</td><td>0.45</td><td>0.44</td><td>0.41</td></tr> <tr><td>0.160</td><td>0.48</td><td>0.46</td><td>0.43</td></tr> <tr><td>0.240</td><td>0.51</td><td>0.48</td><td>0.45</td></tr> <tr><td>0.320</td><td>0.53</td><td>0.50</td><td>0.46</td></tr> <tr><td>0.400</td><td>0.55</td><td>0.52</td><td>0.47</td></tr> <tr><td>0.450</td><td>0.56</td><td>0.53</td><td>0.48</td></tr> <tr><td>0.495</td><td>0.57</td><td>0.54</td><td>0.49</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	0.39	0.39	0.37	0.080	0.45	0.44	0.41	0.160	0.48	0.46	0.43	0.240	0.51	0.48	0.45	0.320	0.53	0.50	0.46	0.400	0.55	0.52	0.47	0.450	0.56	0.53	0.48	0.495	0.57	0.54	0.49	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Power Factor																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.000	0.39	0.39	0.37																																																							
0.080	0.45	0.44	0.41																																																							
0.160	0.48	0.46	0.43																																																							
0.240	0.51	0.48	0.45																																																							
0.320	0.53	0.50	0.46																																																							
0.400	0.55	0.52	0.47																																																							
0.450	0.56	0.53	0.48																																																							
0.495	0.57	0.54	0.49																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	YS512A																																		
Item	Hold-Up Time 出力保持時間	Temperature 25°C	Testing Circuitry Figure A																																
Object	+12.0V 0.45A																																		
1. Graph																																			
			2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>30</td><td>10</td></tr> <tr><td>80</td><td>36</td><td>13</td></tr> <tr><td>85</td><td>42</td><td>17</td></tr> <tr><td>90</td><td>49</td><td>21</td></tr> <tr><td>100</td><td>63</td><td>28</td></tr> <tr><td>110</td><td>78</td><td>37</td></tr> <tr><td>120</td><td>95</td><td>47</td></tr> <tr><td>132</td><td>115</td><td>59</td></tr> <tr><td>140</td><td>130</td><td>68</td></tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	30	10	80	36	13	85	42	17	90	49	21	100	63	28	110	78	37	120	95	47	132	115	59	140	130	68
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	30	10																																	
80	36	13																																	
85	42	17																																	
90	49	21																																	
100	63	28																																	
110	78	37																																	
120	95	47																																	
132	115	59																																	
140	130	68																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL


Model	YS512A	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																						
Object	+12.0V 0.45A																																																						
1. Graph	<p>Legend: Input Volt. 85 V (△), Input Volt. 100 V (□), Input Volt. 132 V (○)</p>																																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.080</td><td>111</td><td>152</td><td>245</td></tr> <tr><td>0.160</td><td>58</td><td>87</td><td>152</td></tr> <tr><td>0.240</td><td>38</td><td>58</td><td>108</td></tr> <tr><td>0.320</td><td>26</td><td>42</td><td>82</td></tr> <tr><td>0.400</td><td>17</td><td>32</td><td>65</td></tr> <tr><td>0.450</td><td>15</td><td>27</td><td>57</td></tr> <tr><td>0.495</td><td>12</td><td>23</td><td>51</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	—	—	—	0.080	111	152	245	0.160	58	87	152	0.240	38	58	108	0.320	26	42	82	0.400	17	32	65	0.450	15	27	57	0.495	12	23	51	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [ms]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.000	—	—	—																																																				
0.080	111	152	245																																																				
0.160	58	87	152																																																				
0.240	38	58	108																																																				
0.320	26	42	82																																																				
0.400	17	32	65																																																				
0.450	15	27	57																																																				
0.495	12	23	51																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																							

COSEL

Model	YS512A	Temperature Testing Circuitry	25°C Figure A																																															
Item	Load Regulation 靜的負荷変動																																																	
Object	+12.0V 0.45A																																																	
1. Graph	<p>—△— Input Volt. 85 V -□- Input Volt. 100 V -○- Input Volt. 132 V</p>																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td><td>12.071</td><td>12.072</td><td>12.071</td></tr> <tr> <td>0.080</td><td>12.068</td><td>12.069</td><td>12.069</td></tr> <tr> <td>0.160</td><td>12.067</td><td>12.067</td><td>12.068</td></tr> <tr> <td>0.240</td><td>12.066</td><td>12.067</td><td>12.067</td></tr> <tr> <td>0.320</td><td>12.065</td><td>12.066</td><td>12.067</td></tr> <tr> <td>0.400</td><td>12.065</td><td>12.065</td><td>12.066</td></tr> <tr> <td>0.450</td><td>12.064</td><td>12.066</td><td>12.065</td></tr> <tr> <td>0.495</td><td>12.064</td><td>12.065</td><td>12.065</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	12.071	12.072	12.071	0.080	12.068	12.069	12.069	0.160	12.067	12.067	12.068	0.240	12.066	12.067	12.067	0.320	12.065	12.066	12.067	0.400	12.065	12.065	12.066	0.450	12.064	12.066	12.065	0.495	12.064	12.065	12.065	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.000	12.071	12.072	12.071																																															
0.080	12.068	12.069	12.069																																															
0.160	12.067	12.067	12.068																																															
0.240	12.066	12.067	12.067																																															
0.320	12.065	12.066	12.067																																															
0.400	12.065	12.065	12.066																																															
0.450	12.064	12.066	12.065																																															
0.495	12.064	12.065	12.065																																															
—	—	—	—																																															
—	—	—	—																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																		

COSEL

Model	YS512A	Temperature Testing Circuitry 25°C Figure A																																			
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)																																				
Object	+12.0V 0.45A																																				
1. Graph	<p>Graph showing Ripple Voltage (mV) vs Load Current (A) for Input Voltages 85V and 132V. The graph shows two curves: one for 85V (squares) and one for 132V (triangles). A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Voltage [mV] (Input Volt. 85 [V])</th> <th>Ripple Output Voltage [mV] (Input Volt. 132 [V])</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>10</td><td>10</td></tr> <tr><td>0.080</td><td>15</td><td>10</td></tr> <tr><td>0.160</td><td>15</td><td>15</td></tr> <tr><td>0.240</td><td>15</td><td>15</td></tr> <tr><td>0.320</td><td>20</td><td>15</td></tr> <tr><td>0.400</td><td>20</td><td>15</td></tr> <tr><td>0.450</td><td>25</td><td>20</td></tr> <tr><td>0.495</td><td>25</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Ripple Output Voltage [mV] (Input Volt. 85 [V])	Ripple Output Voltage [mV] (Input Volt. 132 [V])	0.000	10	10	0.080	15	10	0.160	15	15	0.240	15	15	0.320	20	15	0.400	20	15	0.450	25	20	0.495	25	20	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV] (Input Volt. 85 [V])	Ripple Output Voltage [mV] (Input Volt. 132 [V])																																			
0.000	10	10																																			
0.080	15	10																																			
0.160	15	15																																			
0.240	15	15																																			
0.320	20	15																																			
0.400	20	15																																			
0.450	25	20																																			
0.495	25	20																																			
—	—	—																																			
—	—	—																																			
—	—	—																																			
2. Values																																					



Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期

— T2




Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL


Model	YS512A																																							
Item	Ripple-Noise リップルノイズ	Temperature 25°C Testing Circuitry Figure A																																						
Object	+12.0V 0.45A																																							
1. Graph																																								
		Input Volt. 85V [mV] Input Volt. 132V																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>20</td><td>15</td></tr> <tr><td>0.080</td><td>25</td><td>20</td></tr> <tr><td>0.160</td><td>30</td><td>30</td></tr> <tr><td>0.240</td><td>35</td><td>30</td></tr> <tr><td>0.320</td><td>40</td><td>35</td></tr> <tr><td>0.400</td><td>45</td><td>40</td></tr> <tr><td>0.450</td><td>50</td><td>45</td></tr> <tr><td>0.495</td><td>55</td><td>50</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.000	20	15	0.080	25	20	0.160	30	30	0.240	35	30	0.320	40	35	0.400	45	40	0.450	50	45	0.495	55	50	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.000	20	15																																						
0.080	25	20																																						
0.160	30	30																																						
0.240	35	30																																						
0.320	40	35																																						
0.400	45	40																																						
0.450	50	45																																						
0.495	55	50																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																								
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSSEL

Model	YS512A	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection 過電流保護																																																									
Object	+12.0V 0.45A																																																									
1. Graph		2. Values																																																								
<p>The graph plots Output Voltage [V] on the Y-axis (0.0 to 20.0) against Load Current [A] on the X-axis (0 to 0.8). Three curves are shown for Input Voltages of 85V, 100V, and 132V. A vertical hatched band highlights the range of load currents where the output voltage remains constant at approximately 12V.</p>																																																										
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>0.593</td><td>0.650</td><td>0.673</td></tr> <tr><td>11.40</td><td>0.586</td><td>0.645</td><td>0.671</td></tr> <tr><td>10.80</td><td>0.584</td><td>0.644</td><td>0.668</td></tr> <tr><td>9.60</td><td>0.582</td><td>0.639</td><td>0.661</td></tr> <tr><td>8.40</td><td>0.584</td><td>0.635</td><td>0.659</td></tr> <tr><td>7.20</td><td>0.575</td><td>0.625</td><td>0.650</td></tr> <tr><td>6.00</td><td>0.565</td><td>0.606</td><td>0.635</td></tr> <tr><td>4.80</td><td>0.546</td><td>0.584</td><td>0.616</td></tr> <tr><td>3.60</td><td>0.523</td><td>0.557</td><td>0.590</td></tr> <tr><td>2.40</td><td>0.492</td><td>0.520</td><td>0.555</td></tr> <tr><td>1.20</td><td>0.447</td><td>0.469</td><td>0.507</td></tr> <tr><td>0.00</td><td>0.425</td><td>0.445</td><td>0.481</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	12.00	0.593	0.650	0.673	11.40	0.586	0.645	0.671	10.80	0.584	0.644	0.668	9.60	0.582	0.639	0.661	8.40	0.584	0.635	0.659	7.20	0.575	0.625	0.650	6.00	0.565	0.606	0.635	4.80	0.546	0.584	0.616	3.60	0.523	0.557	0.590	2.40	0.492	0.520	0.555	1.20	0.447	0.469	0.507	0.00	0.425	0.445	0.481
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
12.00	0.593	0.650	0.673																																																							
11.40	0.586	0.645	0.671																																																							
10.80	0.584	0.644	0.668																																																							
9.60	0.582	0.639	0.661																																																							
8.40	0.584	0.635	0.659																																																							
7.20	0.575	0.625	0.650																																																							
6.00	0.565	0.606	0.635																																																							
4.80	0.546	0.584	0.616																																																							
3.60	0.523	0.557	0.590																																																							
2.40	0.492	0.520	0.555																																																							
1.20	0.447	0.469	0.507																																																							
0.00	0.425	0.445	0.481																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																										

COSEL

Model	YS512A	Temperature Testing Circuitry Figure A
Item	Inrush Current 突入電流	
Object	—	



Input Voltage 100 V


Frequency 50 Hz


Load 100 %


Inrush Current

① 8.97 [A]

② 1.12 [A]




COSEL

COSEL

COSEL

Model	YS512A	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+12.0V 0.45A																																																						
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2. Values																																																					
	<p>—△— Input Volt. 85V</p> <p>—□— Input Volt. 100V</p> <p>—○— Input Volt. 132V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>12.092</td><td>12.093</td><td>12.093</td></tr> <tr><td>-10</td><td>12.084</td><td>12.085</td><td>12.086</td></tr> <tr><td>0</td><td>12.077</td><td>12.077</td><td>12.077</td></tr> <tr><td>10</td><td>12.070</td><td>12.071</td><td>12.071</td></tr> <tr><td>20</td><td>12.064</td><td>12.063</td><td>12.066</td></tr> <tr><td>25</td><td>12.062</td><td>12.063</td><td>12.062</td></tr> <tr><td>30</td><td>12.061</td><td>12.060</td><td>12.060</td></tr> <tr><td>40</td><td>12.053</td><td>12.053</td><td>12.052</td></tr> <tr><td>55</td><td>12.036</td><td>12.036</td><td>12.037</td></tr> <tr><td>60</td><td>12.029</td><td>12.029</td><td>12.030</td></tr> <tr><td>70</td><td>12.017</td><td>12.017</td><td>12.017</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	12.092	12.093	12.093	-10	12.084	12.085	12.086	0	12.077	12.077	12.077	10	12.070	12.071	12.071	20	12.064	12.063	12.066	25	12.062	12.063	12.062	30	12.061	12.060	12.060	40	12.053	12.053	12.052	55	12.036	12.036	12.037	60	12.029	12.029	12.030	70	12.017	12.017	12.017
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
-20	12.092	12.093	12.093																																																				
-10	12.084	12.085	12.086																																																				
0	12.077	12.077	12.077																																																				
10	12.070	12.071	12.071																																																				
20	12.064	12.063	12.066																																																				
25	12.062	12.063	12.062																																																				
30	12.061	12.060	12.060																																																				
40	12.053	12.053	12.052																																																				
55	12.036	12.036	12.037																																																				
60	12.029	12.029	12.030																																																				
70	12.017	12.017	12.017																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						
(注)	斜線は定格周囲温度範囲を示す。																																																						

COSEL




Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	50	64
-10	48	64
0	46	62
10	46	62
20	46	61
25	46	61
30	46	61
40	45	61
55	44	61
60	44	61
70	44	61

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。


COSSEL

COSEL

Model	YS512A
Item	Time Lapse Drift 経時ドリフト
Object	+12.0V 0.45A

1. Graph

[V]



Input Volt. 100V

Load 100%

Temperature 25°C
Testing Circuitry Figure A

2. Values

Time since start [H]	Output Voltage [V]
0.0	12.058
0.5	12.057
1.0	12.057
2.0	12.057
3.0	12.057
4.0	12.057
5.0	12.057
6.0	12.057
7.0	12.057
8.0	12.057



Model	YS512A	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+12.0V 0.45A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature 0~55 °C

Input Voltage : 85~132 V

Load Current : 0~0.45 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 0~55 °C

入力電圧 85~132 V

負荷電流 0~0.45 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration)[%]
Maximum Voltage	0	132	0.00	12.085	±25	±0.3
Minimum Voltage	55	85	0.45	12.036		

COSEL

Model	YS512A	Temperature Testing Circuitry 25°C Figure A																																																		
Item	Oscillator Frequency 発振周波数																																																			
Object	+12.0V 0.45A																																																			
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V <p>Y-axis: Oscillator Frequency [KHz] (log scale: 100, 1000)</p> <p>X-axis: Load Current [A] (linear scale: 0, 0.2, 0.4, 0.6)</p>																																																			
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 100 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>926</td> <td>926</td> <td>934</td> </tr> <tr> <td>0.080</td> <td>752</td> <td>784</td> <td>829</td> </tr> <tr> <td>0.160</td> <td>604</td> <td>647</td> <td>697</td> </tr> <tr> <td>0.240</td> <td>506</td> <td>545</td> <td>607</td> </tr> <tr> <td>0.320</td> <td>437</td> <td>472</td> <td>529</td> </tr> <tr> <td>0.400</td> <td>379</td> <td>417</td> <td>465</td> </tr> <tr> <td>0.450</td> <td>351</td> <td>387</td> <td>437</td> </tr> <tr> <td>0.495</td> <td>331</td> <td>363</td> <td>413</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>				Load Current [A]	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]	0.000	926	926	934	0.080	752	784	829	0.160	604	647	697	0.240	506	545	607	0.320	437	472	529	0.400	379	417	465	0.450	351	387	437	0.495	331	363	413	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]																																																	
0.000	926	926	934																																																	
0.080	752	784	829																																																	
0.160	604	647	697																																																	
0.240	506	545	607																																																	
0.320	437	472	529																																																	
0.400	379	417	465																																																	
0.450	351	387	437																																																	
0.495	331	363	413																																																	
—	—	—	—																																																	
—	—	—	—																																																	
—	—	—	—																																																	

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。



Model	YS512A	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+12.0V 0.45A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	12.064	Input Volt.: 100V, Load Current:0.45A
Line Regulation [mV]	2	Input Volt.: 85~132V, Load Current:0.45A
Load Regulation [mV]	7	Input Volt.: 100V, Load Current:0.00~0.45A



Model	YS512A	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	—	—	—

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.16	0.19	0.25
(B) IEC60950	0.15	0.18	0.24

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	YS512A	Temperature Testing Circuitry Figure C	25°C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+12.0V 0.45A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	YS512A	Testing Circuitry Figure D
Item	Conducted Emission 雑音端子電圧	
Object	_____	

1. Graph

Remarks


Input Volt. 120 V

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注) 斜線は許容値を示す。

NO	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/ μ V]
1	FCC class A		0.45~1.6	60
			1.6~30	69.5
2	FCC class B	○	0.45~30	48
3	VCCI class A		0.15~0.5	79
			0.5~30	73
4	VCCI class B		0.15~0.5	66~56
			0.5~5	56
			5~30	60
5	CISPR Pub. 22 class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR Pub. 22 class B (EN55022)		0.15~0.5	66~56
			0.5~5	56
			5~30	60



COSEL





Figure B (DENTORI)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E