



## TEST DATA OF YW515A (100V INPUT)

Regulated DC Power Supply

Oct. 1, 1999

Approved by : Koji Takemoto  
Design Manager

Prepared by : Yuichi Yokohashi  
Design Engineer

コーセル株式会社

**COSEL CO., LTD.**



## C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Current)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	10
瞬時停電保障	
10. Load Regulation	12
静的負荷変動	
11. Ripple Voltage (by Load Current)	13
リップル電圧 (負荷特性)	
12. Ripple-Noise	15
リップルノイズ	
13. Overcurrent Protection	17
過電流保護	
14. Inrush Current	18
突入電流	
15. Dynamic Load Response	19
動的負荷変動	
16. Rise and Fall Time	21
立上り、立下り時間	
17. Ambient Temperature Drift	23
周囲温度変動	
18. Minimum Input Voltage for Regulated Output Voltage	24
最低レギュレーション電圧	
19. Ripple Voltage (by Ambient Temperature)	25
リップル電圧 (周囲温度特性)	
20. Time Lapse Drift	26
経時ドリフト	
21. Output Voltage Accuracy	27
定電圧精度	
22. Oscillator Frequency	28
発振周波数	
23. Condensation	29
結露特性	
24. Leakage Current	30
漏洩電流	
25. Line Noise Tolerance	31
入力雜音耐量	
26. Conducted Emission	32
雜音端子電圧	
27. Figure of Testing Circuitry	33
測定回路図	

(Final Page 34 )

**COSEL**

Model YW515A		Temperature 25°C Testing Circuitry Figure A																																	
Item Line Regulation 静的入力変動																																			
Object +15.0V0.17A																																			
1. Graph		2. Values																																	
<p style="text-align: center;">----- □ ----- Load 50%  ----- △ ----- Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>15.078</td><td>15.001</td></tr> <tr><td>80</td><td>15.077</td><td>15.001</td></tr> <tr><td>85</td><td>15.070</td><td>15.000</td></tr> <tr><td>90</td><td>15.068</td><td>15.000</td></tr> <tr><td>100</td><td>15.064</td><td>15.000</td></tr> <tr><td>110</td><td>15.063</td><td>15.000</td></tr> <tr><td>120</td><td>15.061</td><td>15.000</td></tr> <tr><td>132</td><td>15.059</td><td>15.000</td></tr> <tr><td>140</td><td>15.059</td><td>15.000</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	15.078	15.001	80	15.077	15.001	85	15.070	15.000	90	15.068	15.000	100	15.064	15.000	110	15.063	15.000	120	15.061	15.000	132	15.059	15.000	140	15.059	15.000
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	15.078	15.001																																	
80	15.077	15.001																																	
85	15.070	15.000																																	
90	15.068	15.000																																	
100	15.064	15.000																																	
110	15.063	15.000																																	
120	15.061	15.000																																	
132	15.059	15.000																																	
140	15.059	15.000																																	
Object -15.0V0.17A		2. Values																																	
<p style="text-align: center;">----- □ ----- Load 50%  ----- △ ----- Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>-15.060</td><td>-14.976</td></tr> <tr><td>80</td><td>-15.057</td><td>-14.976</td></tr> <tr><td>85</td><td>-15.055</td><td>-14.979</td></tr> <tr><td>90</td><td>-15.051</td><td>-14.980</td></tr> <tr><td>100</td><td>-15.048</td><td>-14.980</td></tr> <tr><td>110</td><td>-15.046</td><td>-14.981</td></tr> <tr><td>120</td><td>-15.045</td><td>-14.982</td></tr> <tr><td>132</td><td>-15.043</td><td>-14.982</td></tr> <tr><td>140</td><td>-15.043</td><td>-14.982</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	-15.060	-14.976	80	-15.057	-14.976	85	-15.055	-14.979	90	-15.051	-14.980	100	-15.048	-14.980	110	-15.046	-14.981	120	-15.045	-14.982	132	-15.043	-14.982	140	-15.043	-14.982
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	-15.060	-14.976																																	
80	-15.057	-14.976																																	
85	-15.055	-14.979																																	
90	-15.051	-14.980																																	
100	-15.048	-14.980																																	
110	-15.046	-14.981																																	
120	-15.045	-14.982																																	
132	-15.043	-14.982																																	
140	-15.043	-14.982																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																			

**COSEL**

Model	YW515A																																																										
Item	Input Current (by Load Current) 入力電流 (負荷特性)	Temperature Testing Circuitry      25°C Figure A																																																									
Output	—																																																										
1. Graph	<p>—△— Input Volt. 85V        —□— Input Volt. 100V        —○— Input Volt. 132V</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.031</td><td>0.033</td><td>0.036</td></tr> <tr><td>0.030</td><td>0.053</td><td>0.052</td><td>0.053</td></tr> <tr><td>0.060</td><td>0.073</td><td>0.069</td><td>0.066</td></tr> <tr><td>0.090</td><td>0.092</td><td>0.086</td><td>0.079</td></tr> <tr><td>0.120</td><td>0.112</td><td>0.103</td><td>0.092</td></tr> <tr><td>0.150</td><td>0.131</td><td>0.119</td><td>0.105</td></tr> <tr><td>0.170</td><td>0.144</td><td>0.130</td><td>0.114</td></tr> <tr><td>0.187</td><td>0.156</td><td>0.140</td><td>0.121</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	0.031	0.033	0.036	0.030	0.053	0.052	0.053	0.060	0.073	0.069	0.066	0.090	0.092	0.086	0.079	0.120	0.112	0.103	0.092	0.150	0.131	0.119	0.105	0.170	0.144	0.130	0.114	0.187	0.156	0.140	0.121	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
0.000	0.031	0.033	0.036																																																								
0.030	0.053	0.052	0.053																																																								
0.060	0.073	0.069	0.066																																																								
0.090	0.092	0.086	0.079																																																								
0.120	0.112	0.103	0.092																																																								
0.150	0.131	0.119	0.105																																																								
0.170	0.144	0.130	0.114																																																								
0.187	0.156	0.140	0.121																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								


Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

**COSEL**

Model	YW515A																																																										
Item	Input Power (by Load Current) 入力電力 (負荷特性)	Temperature 25°C Testing Circuitry Figure A																																																									
Output	—																																																										
1. Graph	<p>Graph showing Input Power [W] vs Load Current [A] for YW515A at 25°C. Three curves are plotted for Input Voltages 85V (solid line with triangles), 100V (dashed line with squares), and 132V (dotted line with circles). A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85V [W]</th> <th>Input Volt. 100V [W]</th> <th>Input Volt. 132V [W]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>1.09</td><td>1.31</td><td>1.81</td></tr> <tr><td>0.030</td><td>2.03</td><td>2.25</td><td>2.86</td></tr> <tr><td>0.060</td><td>2.98</td><td>3.18</td><td>3.75</td></tr> <tr><td>0.090</td><td>3.97</td><td>4.14</td><td>4.64</td></tr> <tr><td>0.120</td><td>4.99</td><td>5.12</td><td>5.57</td></tr> <tr><td>0.150</td><td>6.07</td><td>6.13</td><td>6.53</td></tr> <tr><td>0.170</td><td>6.80</td><td>6.81</td><td>7.17</td></tr> <tr><td>0.187</td><td>7.47</td><td>7.41</td><td>7.74</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85V [W]	Input Volt. 100V [W]	Input Volt. 132V [W]	0.000	1.09	1.31	1.81	0.030	2.03	2.25	2.86	0.060	2.98	3.18	3.75	0.090	3.97	4.14	4.64	0.120	4.99	5.12	5.57	0.150	6.07	6.13	6.53	0.170	6.80	6.81	7.17	0.187	7.47	7.41	7.74	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—				
Load Current [A]	Input Volt. 85V [W]	Input Volt. 100V [W]	Input Volt. 132V [W]																																																								
0.000	1.09	1.31	1.81																																																								
0.030	2.03	2.25	2.86																																																								
0.060	2.98	3.18	3.75																																																								
0.090	3.97	4.14	4.64																																																								
0.120	4.99	5.12	5.57																																																								
0.150	6.07	6.13	6.53																																																								
0.170	6.80	6.81	7.17																																																								
0.187	7.47	7.41	7.74																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>1.09</td><td>1.31</td><td>1.81</td></tr> <tr><td>0.030</td><td>2.03</td><td>2.25</td><td>2.86</td></tr> <tr><td>0.060</td><td>2.98</td><td>3.18</td><td>3.75</td></tr> <tr><td>0.090</td><td>3.97</td><td>4.14</td><td>4.64</td></tr> <tr><td>0.120</td><td>4.99</td><td>5.12</td><td>5.57</td></tr> <tr><td>0.150</td><td>6.07</td><td>6.13</td><td>6.53</td></tr> <tr><td>0.170</td><td>6.80</td><td>6.81</td><td>7.17</td></tr> <tr><td>0.187</td><td>7.47</td><td>7.41</td><td>7.74</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	1.09	1.31	1.81	0.030	2.03	2.25	2.86	0.060	2.98	3.18	3.75	0.090	3.97	4.14	4.64	0.120	4.99	5.12	5.57	0.150	6.07	6.13	6.53	0.170	6.80	6.81	7.17	0.187	7.47	7.41	7.74	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
0.000	1.09	1.31	1.81																																																								
0.030	2.03	2.25	2.86																																																								
0.060	2.98	3.18	3.75																																																								
0.090	3.97	4.14	4.64																																																								
0.120	4.99	5.12	5.57																																																								
0.150	6.07	6.13	6.53																																																								
0.170	6.80	6.81	7.17																																																								
0.187	7.47	7.41	7.74																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
Note: Slanted line shows the range of the rated load current																																																											
(注)斜線は定格負荷電流範囲を示す。																																																											

COSEL



**COSEL**

Model	YW515A																																																										
Item	Efficiency (by Load Current) 効率(負荷特性)	Temperature 25°C Testing Circuitry Figure A																																																									
Output	—																																																										
1. Graph	<p>The graph plots Efficiency [%] on the y-axis (0 to 80) against Load Current [A] on the x-axis (0 to 0.2). Three data series are shown for different input voltages: 85V (triangles), 100V (squares), and 132V (circles). All three curves show an increasing trend of efficiency with load current. A slanted line is drawn across the graph, representing the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency 85V [%]</th> <th>Efficiency 100V [%]</th> <th>Efficiency 132V [%]</th> </tr> </thead> <tbody> <tr> <td>0.030</td> <td>44.5</td> <td>40.0</td> <td>31.6</td> </tr> <tr> <td>0.060</td> <td>60.7</td> <td>56.7</td> <td>48.4</td> </tr> <tr> <td>0.090</td> <td>68.0</td> <td>65.5</td> <td>58.5</td> </tr> <tr> <td>0.120</td> <td>72.3</td> <td>70.4</td> <td>64.6</td> </tr> <tr> <td>0.150</td> <td>74.2</td> <td>73.6</td> <td>68.9</td> </tr> <tr> <td>0.170</td> <td>75.0</td> <td>74.8</td> <td>71.1</td> </tr> <tr> <td>0.187</td> <td>75.0</td> <td>75.7</td> <td>72.5</td> </tr> </tbody> </table>			Load Current [A]	Efficiency 85V [%]	Efficiency 100V [%]	Efficiency 132V [%]	0.030	44.5	40.0	31.6	0.060	60.7	56.7	48.4	0.090	68.0	65.5	58.5	0.120	72.3	70.4	64.6	0.150	74.2	73.6	68.9	0.170	75.0	74.8	71.1	0.187	75.0	75.7	72.5																								
Load Current [A]	Efficiency 85V [%]	Efficiency 100V [%]	Efficiency 132V [%]																																																								
0.030	44.5	40.0	31.6																																																								
0.060	60.7	56.7	48.4																																																								
0.090	68.0	65.5	58.5																																																								
0.120	72.3	70.4	64.6																																																								
0.150	74.2	73.6	68.9																																																								
0.170	75.0	74.8	71.1																																																								
0.187	75.0	75.7	72.5																																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.030</td> <td>44.5</td> <td>40.0</td> <td>31.6</td> </tr> <tr> <td>0.060</td> <td>60.7</td> <td>56.7</td> <td>48.4</td> </tr> <tr> <td>0.090</td> <td>68.0</td> <td>65.5</td> <td>58.5</td> </tr> <tr> <td>0.120</td> <td>72.3</td> <td>70.4</td> <td>64.6</td> </tr> <tr> <td>0.150</td> <td>74.2</td> <td>73.6</td> <td>68.9</td> </tr> <tr> <td>0.170</td> <td>75.0</td> <td>74.8</td> <td>71.1</td> </tr> <tr> <td>0.187</td> <td>75.0</td> <td>75.7</td> <td>72.5</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.030	44.5	40.0	31.6	0.060	60.7	56.7	48.4	0.090	68.0	65.5	58.5	0.120	72.3	70.4	64.6	0.150	74.2	73.6	68.9	0.170	75.0	74.8	71.1	0.187	75.0	75.7	72.5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
0.030	44.5	40.0	31.6																																																								
0.060	60.7	56.7	48.4																																																								
0.090	68.0	65.5	58.5																																																								
0.120	72.3	70.4	64.6																																																								
0.150	74.2	73.6	68.9																																																								
0.170	75.0	74.8	71.1																																																								
0.187	75.0	75.7	72.5																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								
—	—	—	—																																																								

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

**COSEL**

Model	YW515A	Temperature	25°C
Item	Power Factor (by Input Voltage) 力率(入力電圧特性)	Testing Circuitry	Figure A
Object			
1. Graph			
2. Values			
Input Voltage [V]	Power Factor		
	Load 50%	Load 100%	
75	0.52	0.58	
80	0.51	0.57	
85	0.50	0.55	
90	0.49	0.54	
100	0.48	0.52	
110	0.46	0.51	
120	0.45	0.49	
132	0.44	0.48	
140	0.44	0.47	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	YW515A	Temperature	25°C																																																							
Item	Power Factor (by Load Current) 力率 (負荷特性)	Testing Circuitry	Figure A																																																							
Output	<hr/>																																																									
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85V</li> <li>Input Volt. 100V</li> <li>Input Volt. 132V</li> </ul>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.41</td><td>0.40</td><td>0.38</td></tr> <tr><td>0.030</td><td>0.45</td><td>0.43</td><td>0.41</td></tr> <tr><td>0.060</td><td>0.48</td><td>0.46</td><td>0.43</td></tr> <tr><td>0.090</td><td>0.51</td><td>0.48</td><td>0.44</td></tr> <tr><td>0.120</td><td>0.53</td><td>0.50</td><td>0.46</td></tr> <tr><td>0.150</td><td>0.54</td><td>0.51</td><td>0.47</td></tr> <tr><td>0.170</td><td>0.55</td><td>0.52</td><td>0.48</td></tr> <tr><td>0.187</td><td>0.56</td><td>0.53</td><td>0.48</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	0.41	0.40	0.38	0.030	0.45	0.43	0.41	0.060	0.48	0.46	0.43	0.090	0.51	0.48	0.44	0.120	0.53	0.50	0.46	0.150	0.54	0.51	0.47	0.170	0.55	0.52	0.48	0.187	0.56	0.53	0.48	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Power Factor																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.000	0.41	0.40	0.38																																																							
0.030	0.45	0.43	0.41																																																							
0.060	0.48	0.46	0.43																																																							
0.090	0.51	0.48	0.44																																																							
0.120	0.53	0.50	0.46																																																							
0.150	0.54	0.51	0.47																																																							
0.170	0.55	0.52	0.48																																																							
0.187	0.56	0.53	0.48																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
Note:	Slanted line shows the range of the rated load current																																																									
(注)	斜線は定格負荷電流範囲を示す。																																																									

**COSEL**

Model	YW515A	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+15.0 V 0.17 A																																		
1. Graph																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>18</td><td>11</td></tr> <tr> <td>80</td><td>22</td><td>14</td></tr> <tr> <td>85</td><td>27</td><td>18</td></tr> <tr> <td>90</td><td>32</td><td>22</td></tr> <tr> <td>100</td><td>42</td><td>30</td></tr> <tr> <td>110</td><td>54</td><td>39</td></tr> <tr> <td>120</td><td>67</td><td>49</td></tr> <tr> <td>132</td><td>83</td><td>62</td></tr> <tr> <td>140</td><td>95</td><td>72</td></tr> </tbody> </table>			Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	18	11	80	22	14	85	27	18	90	32	22	100	42	30	110	54	39	120	67	49	132	83	62	140	95	72
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	18	11																																	
80	22	14																																	
85	27	18																																	
90	32	22																																	
100	42	30																																	
110	54	39																																	
120	67	49																																	
132	83	62																																	
140	95	72																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	YW515A	Temperature Testing Circuitry 25°C Figure A
Item	Hold-Up Time 出力保持時間	
Object	-15.0V 0.17A	

1. Graph

Input Voltage [V]	Hold-up Time [mS]	
	Load 50%	Load 100%
80	20	15
90	40	30
100	60	45
110	80	65
120	100	85
130	120	105
140	140	115

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

## 2. Values

Input Voltage [V]	Hold-up Time [mS]	
	Load 50%	Load 100%
75	18	11
80	22	14
85	26	18
90	31	21
100	42	30
110	54	39
120	66	49
132	82	62
140	94	71

# COSEL

Model	YW515A																																																						
Item	Instantaneous Interruption Compensation 瞬時停電保障	Temperature 25°C Testing Circuitry Figure A																																																					
Object	+15.0V 0.17A																																																						
1. Graph																																																							
		—▲— Input Volt. 85 V -□- Input Volt. 100 V ○ Input Volt. 132 V																																																					
		2. Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.030</td><td>36</td><td>56</td><td>106</td></tr> <tr><td>0.060</td><td>28</td><td>48</td><td>93</td></tr> <tr><td>0.090</td><td>26</td><td>41</td><td>82</td></tr> <tr><td>0.120</td><td>22</td><td>36</td><td>73</td></tr> <tr><td>0.150</td><td>17</td><td>32</td><td>66</td></tr> <tr><td>0.170</td><td>16</td><td>27</td><td>62</td></tr> <tr><td>0.187</td><td>15</td><td>26</td><td>58</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	—	—	—	0.030	36	56	106	0.060	28	48	93	0.090	26	41	82	0.120	22	36	73	0.150	17	32	66	0.170	16	27	62	0.187	15	26	58	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.000	—	—	—																																																				
0.030	36	56	106																																																				
0.060	28	48	93																																																				
0.090	26	41	82																																																				
0.120	22	36	73																																																				
0.150	17	32	66																																																				
0.170	16	27	62																																																				
0.187	15	26	58																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注) 斜線は定格負荷電流範囲を示す。

**COSEL**

Model	YW515A	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																					
Object	-15.0V 0.17A	2. Values																																																				
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85 V</li> <li>Input Volt. 100 V</li> <li>Input Volt. 132 V</li> </ul>																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.030</td><td>35</td><td>56</td><td>106</td></tr> <tr><td>0.060</td><td>27</td><td>47</td><td>92</td></tr> <tr><td>0.090</td><td>25</td><td>41</td><td>81</td></tr> <tr><td>0.120</td><td>21</td><td>36</td><td>73</td></tr> <tr><td>0.150</td><td>17</td><td>31</td><td>66</td></tr> <tr><td>0.170</td><td>16</td><td>27</td><td>61</td></tr> <tr><td>0.187</td><td>15</td><td>26</td><td>58</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.000	—	—	—	0.030	35	56	106	0.060	27	47	92	0.090	25	41	81	0.120	21	36	73	0.150	17	31	66	0.170	16	27	61	0.187	15	26	58	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.000	—	—	—																																																			
0.030	35	56	106																																																			
0.060	27	47	92																																																			
0.090	25	41	81																																																			
0.120	21	36	73																																																			
0.150	17	31	66																																																			
0.170	16	27	61																																																			
0.187	15	26	58																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
	<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																					

COSEL


Model YW515A

Item Load Regulation 靜的負荷変動

Object +15.0V 0.17A

1. Graph

—△— Input Volt. 85 V  
 —□— Input Volt. 100 V  
 —○— Input Volt. 132 V

Temperature 25°C  
Testing Circuitry Figure A


2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
0.000	15.280	15.281	15.272
0.030	15.136	15.134	15.131
0.060	15.090	15.084	15.080
0.090	15.063	15.058	15.053
0.120	15.039	15.033	15.031
0.150	15.014	15.011	15.009
0.170	14.998	14.998	14.997
0.187	14.985	14.984	14.986
—	—	—	—
—	—	—	—

Object -15.0V 0.17A

1. Graph

—△— Input Volt. 85 V  
 —□— Input Volt. 100 V  
 —○— Input Volt. 132 V



2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
0.000	-15.236	-15.233	-15.229
0.030	-15.118	-15.113	-15.108
0.060	-15.076	-15.072	-15.066
0.090	-15.049	-15.043	-15.039
0.120	-15.023	-15.020	-15.017
0.150	-14.997	-14.994	-14.995
0.170	-14.979	-14.981	-14.981
0.187	-14.964	-14.967	-14.970
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	YW515A	Temperature Testing Circuitry      25°C      Figure A																																								
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)																																									
Object	+15.0V 0.17A																																									
1. Graph	<p>—△— Input Volt. 85V —○— Input Volt. 132V</p>																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15</td><td>10</td></tr> <tr><td>0.030</td><td>15</td><td>10</td></tr> <tr><td>0.060</td><td>15</td><td>10</td></tr> <tr><td>0.090</td><td>15</td><td>10</td></tr> <tr><td>0.120</td><td>15</td><td>10</td></tr> <tr><td>0.150</td><td>20</td><td>10</td></tr> <tr><td>0.170</td><td>25</td><td>10</td></tr> <tr><td>0.187</td><td>30</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.000	15	10	0.030	15	10	0.060	15	10	0.090	15	10	0.120	15	10	0.150	20	10	0.170	25	10	0.187	30	10	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																									
	Input Volt. 85 [V]	Input Volt. 132 [V]																																								
0.000	15	10																																								
0.030	15	10																																								
0.060	15	10																																								
0.090	15	10																																								
0.120	15	10																																								
0.150	20	10																																								
0.170	25	10																																								
0.187	30	10																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Ripple Voltage is shown as p-p in the figure below.																																										
Note: Slanted line shows the range of the rated load current.																																										
リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。																																										
T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期																																										
Ripple [mVp-p]																																										
Fig. Complex Ripple Wave Form 図 リップル波形詳細図																																										

COSEL

Model	YW515A	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷特性)	Testing Circuitry	Figure A																																						
Object	-15.0V 0.17A																																								
1. Graph	<p style="text-align: center;">△ Input Volt. 85V [mV]      ○ Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Voltage [mV] (Input Volt. 85V)</th> <th>Ripple Output Voltage [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>10</td></tr> <tr><td>0.030</td><td>15</td><td>10</td></tr> <tr><td>0.060</td><td>15</td><td>10</td></tr> <tr><td>0.090</td><td>15</td><td>10</td></tr> <tr><td>0.120</td><td>15</td><td>10</td></tr> <tr><td>0.150</td><td>20</td><td>10</td></tr> <tr><td>0.170</td><td>25</td><td>10</td></tr> <tr><td>0.187</td><td>30</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV] (Input Volt. 85V)	Ripple Output Voltage [mV] (Input Volt. 132V)	0.00	15	10	0.030	15	10	0.060	15	10	0.090	15	10	0.120	15	10	0.150	20	10	0.170	25	10	0.187	30	10	—	—	—	—	—	—	—	—	—		
Load Current [A]	Ripple Output Voltage [mV] (Input Volt. 85V)	Ripple Output Voltage [mV] (Input Volt. 132V)																																							
0.00	15	10																																							
0.030	15	10																																							
0.060	15	10																																							
0.090	15	10																																							
0.120	15	10																																							
0.150	20	10																																							
0.170	25	10																																							
0.187	30	10																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15</td><td>10</td></tr> <tr><td>0.030</td><td>15</td><td>10</td></tr> <tr><td>0.060</td><td>15</td><td>10</td></tr> <tr><td>0.090</td><td>15</td><td>10</td></tr> <tr><td>0.120</td><td>15</td><td>10</td></tr> <tr><td>0.150</td><td>20</td><td>10</td></tr> <tr><td>0.170</td><td>25</td><td>10</td></tr> <tr><td>0.187</td><td>30</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.000	15	10	0.030	15	10	0.060	15	10	0.090	15	10	0.120	15	10	0.150	20	10	0.170	25	10	0.187	30	10	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Output Voltage [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.000	15	10																																							
0.030	15	10																																							
0.060	15	10																																							
0.090	15	10																																							
0.120	15	10																																							
0.150	20	10																																							
0.170	25	10																																							
0.187	30	10																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p> <p>Fig. Complex Ripple Wave Form</p> <p>図 リップル波形詳細図</p>																																									

COSEL

Model	YW515A	Temperature	25°C																											
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																											
Object	+15.0V 0.17A	2. Values																												
1. Graph	<p>Input Volt. 85V [mV]      □      Input Volt. 132V [mV]      ▲</p> <table border="1"> <caption>Data points estimated from Figure 1 graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise at 85V [mV]</th> <th>Ripple-Noise at 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>30</td><td>20</td></tr> <tr><td>0.030</td><td>30</td><td>20</td></tr> <tr><td>0.060</td><td>30</td><td>20</td></tr> <tr><td>0.090</td><td>30</td><td>20</td></tr> <tr><td>0.120</td><td>35</td><td>25</td></tr> <tr><td>0.150</td><td>40</td><td>30</td></tr> <tr><td>0.170</td><td>40</td><td>30</td></tr> <tr><td>0.187</td><td>45</td><td>30</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise at 85V [mV]	Ripple-Noise at 132V [mV]	0.000	30	20	0.030	30	20	0.060	30	20	0.090	30	20	0.120	35	25	0.150	40	30	0.170	40	30	0.187	45	30
Load Current [A]	Ripple-Noise at 85V [mV]	Ripple-Noise at 132V [mV]																												
0.000	30	20																												
0.030	30	20																												
0.060	30	20																												
0.090	30	20																												
0.120	35	25																												
0.150	40	30																												
0.170	40	30																												
0.187	45	30																												
		Load Current [A]	Ripple-Noise [mV]																											
		Input Volt. 85 [V]	Input Volt. 132 [V]																											
		0.000	30																											
		0.030	30																											
		0.060	30																											
		0.090	30																											
		0.120	35																											
		0.150	40																											
		0.170	40																											
		0.187	45																											
		—	—																											
		—	—																											
		—	—																											

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line  
入力商用周期

T2: Due to Switching  
スイッチング周期




Fig. Complex Ripple Wave Form

図 リップル波形詳細図

**COSCEL**


Model	YW515A	Temperature	25°C																																						
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																																						
Object	-15.0V 0.17A																																								
1. Graph		2. Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>30</td><td>20</td></tr> <tr><td>0.030</td><td>30</td><td>20</td></tr> <tr><td>0.060</td><td>30</td><td>20</td></tr> <tr><td>0.090</td><td>30</td><td>25</td></tr> <tr><td>0.120</td><td>30</td><td>25</td></tr> <tr><td>0.150</td><td>35</td><td>25</td></tr> <tr><td>0.170</td><td>40</td><td>30</td></tr> <tr><td>0.187</td><td>45</td><td>30</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.000	30	20	0.030	30	20	0.060	30	20	0.090	30	25	0.120	30	25	0.150	35	25	0.170	40	30	0.187	45	30	--	--	--	--	--	--	--	--	--
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.000	30	20																																							
0.030	30	20																																							
0.060	30	20																																							
0.090	30	25																																							
0.120	30	25																																							
0.150	35	25																																							
0.170	40	30																																							
0.187	45	30																																							
--	--	--																																							
--	--	--																																							
--	--	--																																							
<p>Ripple-Noise is shown as p-p in the figure below.  Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。  (注)斜線は定格負荷電流範囲を示す。</p>		<p>T1: Due to AC Input Line  T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form  図 リップル波形詳細図</p>																																							

**COSEL**

Model	YW515A																																																										
Item	Overcurrent Protection 過電流保護	Temperature 25°C Testing Circuitry Figure A																																																									
Object	+15.0V 0.17A																																																										
1. Graph	<p>[V]                          Input Volt. 85 V                                   Input Volt. 100 V                                   Input Volt. 132 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>15.00</td><td>0.257</td><td>0.286</td><td>0.304</td></tr> <tr><td>14.25</td><td>0.264</td><td>0.293</td><td>0.308</td></tr> <tr><td>13.50</td><td>0.272</td><td>0.295</td><td>0.315</td></tr> <tr><td>12.00</td><td>0.281</td><td>0.304</td><td>0.324</td></tr> <tr><td>10.50</td><td>0.289</td><td>0.313</td><td>0.333</td></tr> <tr><td>9.00</td><td>0.294</td><td>0.316</td><td>0.338</td></tr> <tr><td>7.50</td><td>0.297</td><td>0.319</td><td>0.342</td></tr> <tr><td>6.00</td><td>0.297</td><td>0.316</td><td>0.341</td></tr> <tr><td>4.50</td><td>0.293</td><td>0.309</td><td>0.334</td></tr> <tr><td>3.00</td><td>0.281</td><td>0.295</td><td>0.322</td></tr> <tr><td>1.50</td><td>0.262</td><td>0.273</td><td>0.306</td></tr> <tr><td>0.00</td><td>0.285</td><td>0.302</td><td>0.335</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	15.00	0.257	0.286	0.304	14.25	0.264	0.293	0.308	13.50	0.272	0.295	0.315	12.00	0.281	0.304	0.324	10.50	0.289	0.313	0.333	9.00	0.294	0.316	0.338	7.50	0.297	0.319	0.342	6.00	0.297	0.316	0.341	4.50	0.293	0.309	0.334	3.00	0.281	0.295	0.322	1.50	0.262	0.273	0.306	0.00	0.285	0.302	0.335
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
15.00	0.257	0.286	0.304																																																								
14.25	0.264	0.293	0.308																																																								
13.50	0.272	0.295	0.315																																																								
12.00	0.281	0.304	0.324																																																								
10.50	0.289	0.313	0.333																																																								
9.00	0.294	0.316	0.338																																																								
7.50	0.297	0.319	0.342																																																								
6.00	0.297	0.316	0.341																																																								
4.50	0.293	0.309	0.334																																																								
3.00	0.281	0.295	0.322																																																								
1.50	0.262	0.273	0.306																																																								
0.00	0.285	0.302	0.335																																																								
Object	-15.0V 0.17A																																																										
1. Graph	<p>[V]                          Input Volt. 85 V                                   Input Volt. 100 V                                   Input Volt. 132 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-15.00</td><td>0.256</td><td>0.291</td><td>0.308</td></tr> <tr><td>-14.25</td><td>0.270</td><td>0.297</td><td>0.312</td></tr> <tr><td>-13.50</td><td>0.272</td><td>0.301</td><td>0.318</td></tr> <tr><td>-12.00</td><td>0.285</td><td>0.309</td><td>0.329</td></tr> <tr><td>-10.50</td><td>0.291</td><td>0.314</td><td>0.336</td></tr> <tr><td>-9.00</td><td>0.296</td><td>0.320</td><td>0.344</td></tr> <tr><td>-7.50</td><td>0.302</td><td>0.321</td><td>0.345</td></tr> <tr><td>-6.00</td><td>0.301</td><td>0.320</td><td>0.345</td></tr> <tr><td>-4.50</td><td>0.298</td><td>0.313</td><td>0.339</td></tr> <tr><td>-3.00</td><td>0.286</td><td>0.300</td><td>0.328</td></tr> <tr><td>-1.50</td><td>0.268</td><td>0.281</td><td>0.312</td></tr> <tr><td>0.00</td><td>0.297</td><td>0.314</td><td>0.349</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-15.00	0.256	0.291	0.308	-14.25	0.270	0.297	0.312	-13.50	0.272	0.301	0.318	-12.00	0.285	0.309	0.329	-10.50	0.291	0.314	0.336	-9.00	0.296	0.320	0.344	-7.50	0.302	0.321	0.345	-6.00	0.301	0.320	0.345	-4.50	0.298	0.313	0.339	-3.00	0.286	0.300	0.328	-1.50	0.268	0.281	0.312	0.00	0.297	0.314	0.349
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
-15.00	0.256	0.291	0.308																																																								
-14.25	0.270	0.297	0.312																																																								
-13.50	0.272	0.301	0.318																																																								
-12.00	0.285	0.309	0.329																																																								
-10.50	0.291	0.314	0.336																																																								
-9.00	0.296	0.320	0.344																																																								
-7.50	0.302	0.321	0.345																																																								
-6.00	0.301	0.320	0.345																																																								
-4.50	0.298	0.313	0.339																																																								
-3.00	0.286	0.300	0.328																																																								
-1.50	0.268	0.281	0.312																																																								
0.00	0.297	0.314	0.349																																																								
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																											

**COSSEL**

Model	YW515A	Temperature Testing Circuitry 25°C Figure A
Item	Inrush Current 突入電流	
Object	_____	



Input Voltage 100 V


Frequency 50 Hz


Load 100 %


Inrush Current

① 8.06 [A]

② 1.33 [A]




**COSSEL**

**COSEL**

**COSEL**


Model	YW515A	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time 立上り、立下り時間		
Object	+15.0V 0.17A		

## 1. Graph



## 2. Values


Load	Time	$T_d$	$T_r$	$T_s$	$T_h$	$T_f$	[mS]
50 %		60.3	2.0	62.3	27.3	20.4	
100 %		60.5	2.3	62.8	17.6	21.8	



COSEL


Model	YW515A	Temperature Testing Circuitry Figure A	25°C Figure A
Item	Rise and Fall Time 立上り、立下り時間		
Object	-15.0V 0.17A		

## 1. Graph



## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>	[mS]
50 %		60.5	2.0	62.5	26.4	20.6	
100 %		60.5	2.0	62.5	17.8	22.0	



**COSEL**


Model	YW515A	Testing Circuitry Figure A																																																				
Item	Ambient Temperature Drift 周囲温度変動																																																					
Object	+15.0V 0.17A																																																					
1. Graph	<p>[V]</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend: ▲ Input Volt. 85V, ■ Input Volt. 100V, ○ Input Volt. 132V</p>	2. Values																																																				
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>14.954</td><td>14.956</td><td>14.956</td></tr> <tr><td>-10</td><td>14.962</td><td>14.965</td><td>14.965</td></tr> <tr><td>0</td><td>14.973</td><td>14.973</td><td>14.974</td></tr> <tr><td>10</td><td>14.983</td><td>14.983</td><td>14.984</td></tr> <tr><td>20</td><td>14.994</td><td>14.994</td><td>14.994</td></tr> <tr><td>25</td><td>14.997</td><td>14.997</td><td>14.998</td></tr> <tr><td>30</td><td>15.003</td><td>15.002</td><td>15.001</td></tr> <tr><td>40</td><td>15.007</td><td>15.006</td><td>15.006</td></tr> <tr><td>55</td><td>15.008</td><td>15.006</td><td>15.005</td></tr> <tr><td>60</td><td>15.006</td><td>15.004</td><td>15.003</td></tr> <tr><td>70</td><td>15.002</td><td>15.002</td><td>15.001</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	14.954	14.956	14.956	-10	14.962	14.965	14.965	0	14.973	14.973	14.974	10	14.983	14.983	14.984	20	14.994	14.994	14.994	25	14.997	14.997	14.998	30	15.003	15.002	15.001	40	15.007	15.006	15.006	55	15.008	15.006	15.005	60	15.006	15.004	15.003	70	15.002	15.002	15.001
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	14.954	14.956	14.956																																																			
-10	14.962	14.965	14.965																																																			
0	14.973	14.973	14.974																																																			
10	14.983	14.983	14.984																																																			
20	14.994	14.994	14.994																																																			
25	14.997	14.997	14.998																																																			
30	15.003	15.002	15.001																																																			
40	15.007	15.006	15.006																																																			
55	15.008	15.006	15.005																																																			
60	15.006	15.004	15.003																																																			
70	15.002	15.002	15.001																																																			
Object	-15.0V 0.17A																																																					
1. Graph	<p>[V]</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend: ▲ Input Volt. 85V, ■ Input Volt. 100V, ○ Input Volt. 132V</p>	2. Values																																																				
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>-14.949</td><td>-14.949</td><td>-14.949</td></tr> <tr><td>-10</td><td>-14.953</td><td>-14.954</td><td>-14.955</td></tr> <tr><td>0</td><td>-14.958</td><td>-14.959</td><td>-14.960</td></tr> <tr><td>10</td><td>-14.966</td><td>-14.966</td><td>-14.968</td></tr> <tr><td>20</td><td>-14.973</td><td>-14.974</td><td>-14.976</td></tr> <tr><td>25</td><td>-14.977</td><td>-14.977</td><td>-14.979</td></tr> <tr><td>30</td><td>-14.980</td><td>-14.982</td><td>-14.983</td></tr> <tr><td>40</td><td>-14.981</td><td>-14.984</td><td>-14.986</td></tr> <tr><td>55</td><td>-14.981</td><td>-14.982</td><td>-14.984</td></tr> <tr><td>60</td><td>-14.977</td><td>-14.979</td><td>-14.982</td></tr> <tr><td>70</td><td>-14.972</td><td>-14.976</td><td>-14.978</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	-20	-14.949	-14.949	-14.949	-10	-14.953	-14.954	-14.955	0	-14.958	-14.959	-14.960	10	-14.966	-14.966	-14.968	20	-14.973	-14.974	-14.976	25	-14.977	-14.977	-14.979	30	-14.980	-14.982	-14.983	40	-14.981	-14.984	-14.986	55	-14.981	-14.982	-14.984	60	-14.977	-14.979	-14.982	70	-14.972	-14.976	-14.978
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
-20	-14.949	-14.949	-14.949																																																			
-10	-14.953	-14.954	-14.955																																																			
0	-14.958	-14.959	-14.960																																																			
10	-14.966	-14.966	-14.968																																																			
20	-14.973	-14.974	-14.976																																																			
25	-14.977	-14.977	-14.979																																																			
30	-14.980	-14.982	-14.983																																																			
40	-14.981	-14.984	-14.986																																																			
55	-14.981	-14.982	-14.984																																																			
60	-14.977	-14.979	-14.982																																																			
70	-14.972	-14.976	-14.978																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																																						

COSEL

Model	YW515A
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+15.0V 0.17A

1. Graph

[V] 




Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	57	64
-10	56	63
0	55	62
10	54	62
20	54	62
25	54	61
30	53	61
40	53	60
55	52	60
60	52	60
70	51	60

Object | -15.0V 0.17A

[V] 



## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	57	64
-10	56	63
0	55	62
10	54	62
20	54	62
25	54	61
30	53	61
40	53	60
55	52	60
60	52	60
70	51	60

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

**COSEL**

Model	YW515A																																								
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry      Figure A																																							
Object	+15.0V 0.17A																																								
1. Graph																																									
<p>[mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100 V</p>		2. Values																																							
<p>[mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100 V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>20</td><td>30</td></tr> <tr><td>-10</td><td>15</td><td>25</td></tr> <tr><td>0</td><td>15</td><td>20</td></tr> <tr><td>10</td><td>15</td><td>20</td></tr> <tr><td>20</td><td>15</td><td>20</td></tr> <tr><td>25</td><td>15</td><td>20</td></tr> <tr><td>30</td><td>15</td><td>20</td></tr> <tr><td>40</td><td>15</td><td>20</td></tr> <tr><td>55</td><td>15</td><td>20</td></tr> <tr><td>60</td><td>15</td><td>20</td></tr> <tr><td>70</td><td>15</td><td>20</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Output Voltage [mV]		Load 50%	Load 100%	-20	20	30	-10	15	25	0	15	20	10	15	20	20	15	20	25	15	20	30	15	20	40	15	20	55	15	20	60	15	20	70	15	20
Ambient Temperature [°C]	Ripple Output Voltage [mV]																																								
	Load 50%	Load 100%																																							
-20	20	30																																							
-10	15	25																																							
0	15	20																																							
10	15	20																																							
20	15	20																																							
25	15	20																																							
30	15	20																																							
40	15	20																																							
55	15	20																																							
60	15	20																																							
70	15	20																																							
<p>[mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100 V</p>		2. Values																																							
<p>[mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100 V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Output Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-20</td><td>20</td><td>30</td></tr> <tr><td>-10</td><td>15</td><td>25</td></tr> <tr><td>0</td><td>15</td><td>20</td></tr> <tr><td>10</td><td>15</td><td>20</td></tr> <tr><td>20</td><td>15</td><td>20</td></tr> <tr><td>25</td><td>15</td><td>20</td></tr> <tr><td>30</td><td>15</td><td>20</td></tr> <tr><td>40</td><td>15</td><td>20</td></tr> <tr><td>55</td><td>15</td><td>20</td></tr> <tr><td>60</td><td>15</td><td>20</td></tr> <tr><td>70</td><td>15</td><td>20</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Output Voltage [mV]		Load 50%	Load 100%	-20	20	30	-10	15	25	0	15	20	10	15	20	20	15	20	25	15	20	30	15	20	40	15	20	55	15	20	60	15	20	70	15	20
Ambient Temperature [°C]	Ripple Output Voltage [mV]																																								
	Load 50%	Load 100%																																							
-20	20	30																																							
-10	15	25																																							
0	15	20																																							
10	15	20																																							
20	15	20																																							
25	15	20																																							
30	15	20																																							
40	15	20																																							
55	15	20																																							
60	15	20																																							
70	15	20																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									
(注)斜線は定格周囲温度範囲を示す。																																									

**COSEL**

Model	YW515A	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift 経時ドリフト																								
Object	+15.0V 0.17A																								
1. Graph			2. Values																						
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.975</td></tr> <tr><td>0.5</td><td>14.982</td></tr> <tr><td>1.0</td><td>14.982</td></tr> <tr><td>2.0</td><td>14.982</td></tr> <tr><td>3.0</td><td>14.982</td></tr> <tr><td>4.0</td><td>14.982</td></tr> <tr><td>5.0</td><td>14.982</td></tr> <tr><td>6.0</td><td>14.982</td></tr> <tr><td>7.0</td><td>14.982</td></tr> <tr><td>8.0</td><td>14.982</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	14.975	0.5	14.982	1.0	14.982	2.0	14.982	3.0	14.982	4.0	14.982	5.0	14.982	6.0	14.982	7.0	14.982	8.0	14.982
Time since start [H]	Output Voltage [V]																								
0.0	14.975																								
0.5	14.982																								
1.0	14.982																								
2.0	14.982																								
3.0	14.982																								
4.0	14.982																								
5.0	14.982																								
6.0	14.982																								
7.0	14.982																								
8.0	14.982																								
Object -15.0V 0.17A			2. Values																						
<p>1. Graph</p> <p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.964</td></tr> <tr><td>0.5</td><td>-14.967</td></tr> <tr><td>1.0</td><td>-14.967</td></tr> <tr><td>2.0</td><td>-14.967</td></tr> <tr><td>3.0</td><td>-14.967</td></tr> <tr><td>4.0</td><td>-14.967</td></tr> <tr><td>5.0</td><td>-14.967</td></tr> <tr><td>6.0</td><td>-14.967</td></tr> <tr><td>7.0</td><td>-14.967</td></tr> <tr><td>8.0</td><td>-14.967</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-14.964	0.5	-14.967	1.0	-14.967	2.0	-14.967	3.0	-14.967	4.0	-14.967	5.0	-14.967	6.0	-14.967	7.0	-14.967	8.0	-14.967
Time since start [H]	Output Voltage [V]																								
0.0	-14.964																								
0.5	-14.967																								
1.0	-14.967																								
2.0	-14.967																								
3.0	-14.967																								
4.0	-14.967																								
5.0	-14.967																								
6.0	-14.967																								
7.0	-14.967																								
8.0	-14.967																								



Model	YW515A	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

### 1 Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : 0~55 °C

Input Voltage : 85~132 V

Load Current (AVR 1) : 0~0.17 A

(AVR 2) : 0~0.17 A

\* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

#### 1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 0~55 °C

入力電圧 85~132 V

負荷電流 (AVR 1) 0~0.17 A

(AVR 2) 0~0.17 A

\* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2


$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

#### 2. Values

Object	+15.0V 0.17A					
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ratio) [%]
Maximum Voltage	25	100	0.00	15.282	±153	±1.1
Minimum Voltage	0	85	0.17	14.976		
Object	-15.0V 0.17A					
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ratio) [%]
Maximum Voltage	25	85	0.00	-15.231	±135	±0.9
Minimum Voltage	0	85	0.17	-14.961		

**COSEL**

Model	YW515A
Item	Oscillator Frequency 発振周波数
Object	+15.0V 0.17A



Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Input Volt. 85[V] [kHz]	Input Volt. 100[V] [kHz]	Input Volt. 132[V] [kHz]
0.000	909	928	931
0.030	743	776	817
0.060	610	645	687
0.090	519	557	610
0.120	455	485	543
0.150	395	432	483
0.170	365	399	449
0.187	341	378	426
—	—	—	—
—	—	—	—
—	—	—	—



Model	YW515A	
Item	Condensation 結露特性	Testing Circuitry Figure A

### 1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

### 1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

### 2. Values

Object	+15.0V 0.17A	
<hr/>		
Item	Data	Testing Conditions
Output Voltage [V]	15.000	Input Volt.: 100V, Load Current:0.17A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:0.17A
Load Regulation [mV]	283	Input Volt.: 100V, Load Current:0~0.17A

Object	-15.0V 0.17A	
<hr/>		
Item	Data	Testing Conditions
Output Voltage [V]	-14.980	Input Volt.: 100V, Load Current:0.17A
Line Regulation [mV]	3	Input Volt.: 85~132V, Load Current:0.17A
Load Regulation [mV]	252	Input Volt.: 100V, Load Current:0~0.17A



Model	YW515A	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	—	—	—

### 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.16	0.19	0.25
(B) IEC60950	0.15	0.18	0.24

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	YW515A	Temperature	25°C
Item	Line Noise Tolerance 入力雑音耐量	Testing Circuitry	Figure C
Object	+15.0V 0.17A		

## 1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動	Conditions
50	COMMON	OK	no fluctuation	Input Voltage : 100 V
	NORMAL	OK	no fluctuation	Pulse Voltage : 2000 V
1000	COMMON	OK	no fluctuation	Pulse Cycle : 10 mS
	NORMAL	OK	no fluctuation	Pulse Input Duration: 1 min. or more Load : 100 %

Object	-15.0V 0.17A
--------	--------------

## 1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動	Conditions
50	COMMON	OK	no fluctuation	Input Voltage : 100 V
	NORMAL	OK	no fluctuation	Pulse Voltage : 2000 V
1000	COMMON	OK	no fluctuation	Pulse Cycle : 10 mS
	NORMAL	OK	no fluctuation	Pulse Input Duration: 1 min. or more Load : 100 %

**COSEL**

Model	YW515A
Item	Conducted Emission 雜音端子電圧
Object	_____

Testing Circuitry

Figure D

## 1. Graph

## Remarks


Input Volt. 120 V

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注) 斜線は許容値を示す。

No	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/μV]
1	FCC class A		0.45~1.6	60
			1.6~30	69.5
2	FCC class B	○	0.45~30	48
3	VCCI class A		0.15~0.5	79
			0.5~30	73
4	VCCI class B		0.15~0.5	66~56
			0.5~5	56
			5~30	60
5	CISPR Pub. 22 class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR Pub. 22 class B (EN55022)		0.15~0.5	66~56
			0.5~5	56
			5~30	60



COSEL





Figure B (DENTOR1)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E