

COSEL

TEST DATA OF ZTS1R50512
(5.0V INPUT)

Regulated DC Power Supply

Date : Mar. 5. 1998

Approved by : N. Shioishi
Design Manager

Prepared by : T. Iwai
Design Engineer

コーセル株式会社

COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	5
リップルノイズ	
6. Overcurrent Protection	6
過電流保護	
7. Dynamic Load Response	7
動的負荷変動	
8. Rise and Fall Time	8
立ち上り、立下がり時間	
9. Ambient Temperature Drift	9
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage	10
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	11
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	12
経時ドリフト	
13. Output Voltage Accuracy	13
定電圧精度	
14. Condensation	14
結露特性	
15. Figure of Testing Circuitry	15
測定回路図	

(Final Page 15)

COSEL

Model	ZTS1R50512																																										
Item	Line Regulation 静的入力変動	Temperature Testing Circuitry 25°C Figure A																																									
Object	+12V 0.13A																																										
1. Graph																																											
		2. Values																																									
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>12.007</td><td>12.005</td></tr> <tr><td>4.5</td><td>12.007</td><td>12.005</td></tr> <tr><td>5.0</td><td>12.006</td><td>12.005</td></tr> <tr><td>6.0</td><td>12.006</td><td>12.004</td></tr> <tr><td>7.0</td><td>12.006</td><td>12.004</td></tr> <tr><td>8.0</td><td>12.006</td><td>12.004</td></tr> <tr><td>9.0</td><td>12.006</td><td>12.004</td></tr> <tr><td>9.5</td><td>12.006</td><td>12.004</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	4.0	12.007	12.005	4.5	12.007	12.005	5.0	12.006	12.005	6.0	12.006	12.004	7.0	12.006	12.004	8.0	12.006	12.004	9.0	12.006	12.004	9.5	12.006	12.004	-	-	-	-	-	-	-	-	-	-	-	-
Input Voltage [V]	Load 50%	Load 100%																																									
	Output Volt. [V]	Output Volt. [V]																																									
4.0	12.007	12.005																																									
4.5	12.007	12.005																																									
5.0	12.006	12.005																																									
6.0	12.006	12.004																																									
7.0	12.006	12.004																																									
8.0	12.006	12.004																																									
9.0	12.006	12.004																																									
9.5	12.006	12.004																																									
-	-	-																																									
-	-	-																																									
-	-	-																																									
-	-	-																																									

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL


Model ZTS1R50512

Item Efficiency 効率

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph

-----□----- Load 50%
-----△----- Load 100%

2. Values


Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
4.0	63.7	67.4
4.5	62.5	68.3
5.0	61.0	68.3
6.0	57.5	67.3
7.0	54.3	65.5
8.0	50.8	63.2
9.0	47.4	60.6
9.5	45.8	59.4
-	-	-
-	-	-
-	-	-
-	-	-

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	ZTS1R50512
Item	Load Regulation 靜的負荷変動
Object	+12V 0.13A



Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。


Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
0.00	12.006	12.006	12.006
0.02	12.006	12.006	12.006
0.04	12.005	12.006	12.006
0.06	12.005	12.005	12.005
0.08	12.005	12.005	12.005
0.10	12.005	12.005	12.005
0.12	12.004	12.005	12.004
0.13	12.004	12.004	12.004
0.14	12.004	12.004	12.004
-	-	-	-

COSSEL

Model	ZTS1R50512	Temperature	25°C																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry	Figure A																																						
Object	+12V 0.13A																																								
1. Graph	<p>-----□----- Input Volt. 4.5V [mV]</p> <p>——△—— Input Volt. 9.0V</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9.0 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>5</td><td>8</td></tr> <tr> <td>0.02</td><td>5</td><td>8</td></tr> <tr> <td>0.04</td><td>5</td><td>8</td></tr> <tr> <td>0.06</td><td>5</td><td>10</td></tr> <tr> <td>0.08</td><td>8</td><td>10</td></tr> <tr> <td>0.10</td><td>10</td><td>10</td></tr> <tr> <td>0.12</td><td>10</td><td>15</td></tr> <tr> <td>0.13</td><td>15</td><td>15</td></tr> <tr> <td>0.14</td><td>15</td><td>15</td></tr> <tr> <td>—</td><td>—</td><td>—</td></tr> <tr> <td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	5	8	0.02	5	8	0.04	5	8	0.06	5	10	0.08	8	10	0.10	10	10	0.12	10	15	0.13	15	15	0.14	15	15	—	—	—	—	—	—
Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.00	5	8																																							
0.02	5	8																																							
0.04	5	8																																							
0.06	5	10																																							
0.08	8	10																																							
0.10	10	10																																							
0.12	10	15																																							
0.13	15	15																																							
0.14	15	15																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.00	15	25
0.02	15	25
0.04	20	25
0.06	30	25
0.08	35	25
0.10	40	35
0.12	40	40
0.13	45	40
0.14	45	40
—	—	—
—	—	—

COSEL

Model	ZTS1R50512	Temperature 25°C Testing Circuitry Figure A																																																									
Item	Overcurrent Protection 過電流保護																																																										
Object	+12V 0.13A																																																										
1. Graph	<p>Input Volt. 4.5V Input Volt. 5.0V Input Volt. 9.0V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> <tr> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>0.19</td><td>0.20</td><td>0.19</td></tr> <tr><td>11.40</td><td>0.19</td><td>0.20</td><td>0.19</td></tr> <tr><td>10.80</td><td>0.20</td><td>0.20</td><td>0.19</td></tr> <tr><td>9.60</td><td>0.21</td><td>0.21</td><td>0.19</td></tr> <tr><td>8.40</td><td>0.22</td><td>0.22</td><td>0.19</td></tr> <tr><td>7.20</td><td>0.22</td><td>0.22</td><td>0.19</td></tr> <tr><td>6.00</td><td>0.23</td><td>0.23</td><td>0.19</td></tr> <tr><td>4.80</td><td>0.24</td><td>0.23</td><td>0.19</td></tr> <tr><td>3.60</td><td>0.24</td><td>0.23</td><td>0.19</td></tr> <tr><td>2.40</td><td>0.24</td><td>0.23</td><td>0.18</td></tr> <tr><td>1.20</td><td>0.25</td><td>0.23</td><td>0.19</td></tr> <tr><td>0.00</td><td>0.11</td><td>0.13</td><td>0.21</td></tr> </tbody> </table>				Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	12.00	0.19	0.20	0.19	11.40	0.19	0.20	0.19	10.80	0.20	0.20	0.19	9.60	0.21	0.21	0.19	8.40	0.22	0.22	0.19	7.20	0.22	0.22	0.19	6.00	0.23	0.23	0.19	4.80	0.24	0.23	0.19	3.60	0.24	0.23	0.19	2.40	0.24	0.23	0.18	1.20	0.25	0.23	0.19	0.00	0.11	0.13	0.21
Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																								
	Load Current [A]	Load Current [A]	Load Current [A]																																																								
12.00	0.19	0.20	0.19																																																								
11.40	0.19	0.20	0.19																																																								
10.80	0.20	0.20	0.19																																																								
9.60	0.21	0.21	0.19																																																								
8.40	0.22	0.22	0.19																																																								
7.20	0.22	0.22	0.19																																																								
6.00	0.23	0.23	0.19																																																								
4.80	0.24	0.23	0.19																																																								
3.60	0.24	0.23	0.19																																																								
2.40	0.24	0.23	0.18																																																								
1.20	0.25	0.23	0.19																																																								
0.00	0.11	0.13	0.21																																																								
Note:	Slanted line shows the range of the rated load current.																																																										
(注)	斜線は定格負荷電流範囲を示す。																																																										


COSEL

Model	ZTS1R50512
Item	Dynamic Load Response 動的負荷變動
Object	+12V 0.13A

Temperature 25°C
Testing Circuitry Figure A

Input Volt. 5.0 V



Cycle 100 mS



Min. Load →

Load 100 %



200 mV/div



Min. Load →

Load 50 %



200 mV/div



Load 50%→

Load 100 %

200 mV/div



1 mS/div

COSEL


Model ZTS1R50512

Item Rise and Fall Time 立上り、立下り時間

Object +12V 0.13A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

Load \ Time	T d	T r	T s	T h	T f
50 %	1.00	2.50	3.50	0.95	2.00
100 %	0.90	2.60	3.50	0.40	1.35

[mS]



COSEL


Model ZTS1R50512

Item Ambient Temperature Drift
周囲温度変動

Object +12V 0.13A

1. Graph

—△— Input Volt. 4.5V
 - - -□- Input Volt. 5.0V
 - - -○- Input Volt. 9.0V



Load 100%

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values



Temperature [°C]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
-30	12.013	12.013	12.013
-20	12.011	12.011	12.011
-10	12.009	12.009	12.009
0	12.008	12.008	12.008
10	12.007	12.007	12.007
25	12.004	12.004	12.004
30	12.005	12.005	12.004
40	11.998	11.998	11.998
55	11.986	11.986	11.986
60	11.981	11.980	11.980
—	—	—	—

COSEL

Model ZTS1R50512

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +12V 0.13A

1. Graph
[V] 

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	2.6	3.6
-20	2.5	3.5
-10	2.4	3.5
0	2.4	3.4
10	2.3	3.4
25	2.3	3.3
30	2.3	3.3
40	2.3	3.2
55	2.3	3.1
60	2.3	3.1
—	—	—


COSEL

Model ZTS1R50512

Item Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object +12V 0.13A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.
Input Volt. 4.5 V

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values


Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]
-30	10	20
-20	10	20
-10	8	15
0	8	15
10	8	15
25	8	15
30	8	15
40	8	15
55	8	15
60	8	15
—	—	—

COSEL

Model	ZTSIR50512
Item	Time Lapse Drift 経時ドリフト
Object	+12V 0.13A

Temperature 25 °C
 Testing Circuitry Figure A

1. Graph



2. Values

Time since start [H]	Output Voltage [V]
0.0	12.003
0.5	11.998
1.0	11.998
2.0	11.998
3.0	11.998
4.0	11.998
5.0	11.998
6.0	11.998
7.0	11.998
8.0	11.998

COSEL

Model	ZTS1R50512	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+12V 0.13A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 4.5~9.0 V

Load Current : 0.00~0.13 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~55 °C

入力電圧 4.5~9.0 V

負荷電流 0.00~0.13 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	9.0	0.00	12.013	±15	±0.2
Minimum Voltage	55	9.0	0.13	11.983		



Model	ZTS1R50512		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+12V 0.13A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	11.863	Input Volt.: 5V, Load Current: 0.13A
Line Regulation [mV]	1	Input Volt.: 4.5~9V, Load Current: 0.13A
Load Regulation [mV]	3	Input Volt.: 5V, Load Current: 0~0.13A

COSEL




Figure A