



TEST DATA OF ZTS31215

(12.0V INPUT)

Regulated DC Power Supply

Date : Mar. 5. 1998

Approved by : N. Shiraishi
Design Manager

Prepared by : J. Tsun
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	5
リップルノイズ	
6. Overcurrent Protection	6
過電流保護	
7. Dynamic Load Responce	7
動的負荷変動	
8. Rise and Fall Time	8
立上り、立下がり時間	
9. Ambient Temperature Drift	9
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage	10
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	11
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	12
経時ドリフト	
13. Output Voltage Accuracy	13
定電圧精度	
14. Condensation	14
結露特性	
15. Figure of Testing Circuitry	15
測定回路図	


(Final Page 15)

COSEL

Model	ZTS31215
Item	Line Regulation 静的入力変動
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure A

1. Graph
- Load 50%
-----△----- Load 100%



Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Load 50%	Load 100%
	Output Volt. [V]	Output Volt. [V]
8.0	15.016	15.014
9.0	15.017	15.014
10.0	15.017	15.014
12.0	15.017	15.014
15.0	15.016	15.014
18.0	15.016	15.014
20.0	15.016	15.013
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

COSEL

Model		ZTS31215	
Item		Efficiency 効率	
Object			

1. Graph

-----□----- Load 50%

-----△----- Load 100%

[%]

80

72

64

56

48

0

0

10

15

20

Input Voltage

[V]

Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]
8.0	73.5	78.1
9.0	73.1	78.5
10.0	72.3	78.2
12.0	70.6	77.7
15.0	67.1	76.2
18.0	63.1	73.8
20.0	60.5	72.2
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]
8.0	73.5	78.1
9.0	73.1	78.5
10.0	72.3	78.2
12.0	70.6	77.7
15.0	67.1	76.2
18.0	63.1	73.8
20.0	60.5	72.2
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—


COSEL

Model		ZTS31215		Temperature		25℃																																																
Item		Load Regulation 静的負荷変動		Testing Circuitry		Figure A																																																
Object		+15V0.2A																																																				
1. Graph				2. Values																																																		
<div><div><div>—△—</div><div>—□—</div><div>—○—</div></div><div>Input Volt. 9.0V</div><div>Input Volt. 12.0V</div><div>Input Volt. 18.0V</div></div> <div><div><div>Output Voltage [V]</div><div><div></div><div>15.16</div><div>15.12</div><div>15.08</div><div>15.04</div><div>15.00</div><div>14.96</div><div>14.92</div><div>0</div></div><div><div></div><div>0</div><div>0.05</div><div>0.1</div><div>0.15</div><div>0.2</div><div>0.25</div></div><div>Load Current [A]</div></div><div></div></div> <div><div>Note: Slanted line shows the range of the rated load current.</div><div>(注)斜線は定格負荷電流範囲を示す。</div></div>				<table><tr><th rowspan="2">Load Current [A]</th><th>Input Volt. 9.0[V]</th><th>Input Volt. 12.0[V]</th><th>Input Volt. 18.0[V]</th></tr><tr><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr><tr><td>0.00</td><td>15.018</td><td>15.018</td><td>15.019</td></tr><tr><td>0.04</td><td>15.018</td><td>15.018</td><td>15.017</td></tr><tr><td>0.08</td><td>15.017</td><td>15.017</td><td>15.016</td></tr><tr><td>0.12</td><td>15.016</td><td>15.016</td><td>15.016</td></tr><tr><td>0.16</td><td>15.016</td><td>15.016</td><td>15.015</td></tr><tr><td>0.20</td><td>15.015</td><td>15.015</td><td>15.014</td></tr><tr><td>0.22</td><td>15.015</td><td>15.015</td><td>15.014</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>				Load Current [A]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.00	15.018	15.018	15.019	0.04	15.018	15.018	15.017	0.08	15.017	15.017	15.016	0.12	15.016	15.016	15.016	0.16	15.016	15.016	15.015	0.20	15.015	15.015	15.014	0.22	15.015	15.015	15.014	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]																																																			
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																			
0.00	15.018	15.018	15.019																																																			
0.04	15.018	15.018	15.017																																																			
0.08	15.017	15.017	15.016																																																			
0.12	15.016	15.016	15.016																																																			
0.16	15.016	15.016	15.015																																																			
0.20	15.015	15.015	15.014																																																			
0.22	15.015	15.015	15.014																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

COSEL

Model		ZTS31215	Temperature		25℃
Item		Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry		Figure A
Object		+15V0.2A			
1. Graph		2.Values			
[mV]					
50					
40					
30					
20					
10					
0					
0					
0.05					
0.1					
0.15					
0.2					
0.25					
Ripple Voltage					
Load Current					
[A]					
-----□-----		Input Volt. 9.0V			
-----△-----		Input Volt. 18.0V			
Ripple Voltage is shown as p-p in the figure below.					
Note: Slanted line shows the range of the rated load current.					
リップル電圧は、下図 p-p 値で示される。					
(注)斜線は定格負荷電流範囲を示す。					
T1: Due to AC Input Line 入力商用周期					
T2: Due to Switching スイッチング周期					
Ripple [mVp-p]					
T1					
T2					
Fig. Complex Ripple Wave Form					
図 リップル波形詳細図					

COSEL



COSEL

Model		ZTS31215	Temperature		25℃																																																							
Item		Overcurrent Protection 過電流保護	Testing Circuitry		Figure A																																																							
Object		+15V0.2A																																																										
1. Graph			2. Values																																																									
<div><div>[V]</div><div><div>Output Voltage [V]</div><div>Load Current [A]</div></div></div>			<div><div>~~~~~</div>Input Volt. 9.0V</div> <div><div>————</div>Input Volt. 12.0V</div> <div><div>————</div>Input Volt. 18.0V</div>																																																									
<div>Note: Slanted line shows the range of the rated load current.</div> <div>(注)斜線は定格負荷電流範囲を示す。</div>			<table><tr><th rowspan="2">Output Voltage [V]</th><th>Input Volt. 9.0[V]</th><th>Input Volt. 12.0[V]</th><th>Input Volt. 18.0[V]</th></tr><tr><th>Load Curr-ent [A]</th><th>Load Curr-ent [A]</th><th>Load Curr-ent [A]</th></tr><tr><td>15.00</td><td>0.29</td><td>0.32</td><td>0.28</td></tr><tr><td>14.25</td><td>0.29</td><td>0.32</td><td>0.28</td></tr><tr><td>13.50</td><td>0.29</td><td>0.32</td><td>0.28</td></tr><tr><td>12.00</td><td>0.30</td><td>0.32</td><td>0.27</td></tr><tr><td>10.50</td><td>0.30</td><td>0.32</td><td>0.26</td></tr><tr><td>9.00</td><td>0.30</td><td>0.31</td><td>0.25</td></tr><tr><td>7.50</td><td>0.29</td><td>0.30</td><td>0.24</td></tr><tr><td>6.00</td><td>0.29</td><td>0.29</td><td>0.22</td></tr><tr><td>4.50</td><td>0.27</td><td>0.26</td><td>0.20</td></tr><tr><td>3.00</td><td>0.25</td><td>0.23</td><td>0.17</td></tr><tr><td>1.50</td><td>0.22</td><td>0.20</td><td>0.16</td></tr><tr><td>0.00</td><td>0.21</td><td>0.19</td><td>0.17</td></tr></table>			Output Voltage [V]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]	Load Curr-ent [A]	Load Curr-ent [A]	Load Curr-ent [A]	15.00	0.29	0.32	0.28	14.25	0.29	0.32	0.28	13.50	0.29	0.32	0.28	12.00	0.30	0.32	0.27	10.50	0.30	0.32	0.26	9.00	0.30	0.31	0.25	7.50	0.29	0.30	0.24	6.00	0.29	0.29	0.22	4.50	0.27	0.26	0.20	3.00	0.25	0.23	0.17	1.50	0.22	0.20	0.16	0.00	0.21	0.19	0.17
Output Voltage [V]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]																																																									
	Load Curr-ent [A]	Load Curr-ent [A]	Load Curr-ent [A]																																																									
15.00	0.29	0.32	0.28																																																									
14.25	0.29	0.32	0.28																																																									
13.50	0.29	0.32	0.28																																																									
12.00	0.30	0.32	0.27																																																									
10.50	0.30	0.32	0.26																																																									
9.00	0.30	0.31	0.25																																																									
7.50	0.29	0.30	0.24																																																									
6.00	0.29	0.29	0.22																																																									
4.50	0.27	0.26	0.20																																																									
3.00	0.25	0.23	0.17																																																									
1.50	0.22	0.20	0.16																																																									
0.00	0.21	0.19	0.17																																																									

COSEL

Model	ZTS31215	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	+15V0.2A	

Input Volt. 12.0 V


Cycle 100 mS

Load Current

Min. Load ↔

Load 100 %


200 mV/div



Min. Load ↔

Load 50 %


200 mV/div



Load 50% ↔

Load 100 %

200 mV/div




1 mS/div

COSEL

Model	ZTS31215	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+15V0.2A		

1. Graph


Input Volt. 9.0 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.10	3.50	3.60	0.30	5.68
100 %	0.10	3.55	3.65	0.14	2.13




COSEL

Model	ZTS31215
Item	Ambient Temperature Drift 周囲温度変動
Object	+15V0.2A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


2. Values

Temperature [°C]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
-30	15.024	15.024	15.024
-20	15.023	15.024	15.023
-10	15.022	15.022	15.022
0	15.020	15.020	15.019
10	15.017	15.017	15.017
25	15.012	15.012	15.011
30	15.013	15.012	15.011
40	15.004	15.004	15.003
55	14.990	14.989	14.988
60	14.984	14.983	14.982
—	—	—	—

COSEL

Model	ZTS31215
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+15V0.2A

1. Graph
- [V]
- Load 50%
- △----- Load 100%



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values


Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	5.4	7.1
-20	5.3	7.0
-10	5.3	6.7
0	5.1	6.6
10	5.1	6.6
25	5.0	6.3
30	4.9	6.3
40	4.9	6.2
55	4.8	6.2
60	4.8	6.2
—	—	—

COSEL

Model	ZTS31215
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+15V0.2A

1. Graph

-----□----- Load 50%
 ————△——— Load 100%



Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-30	5	20
-20	5	20
-10	5	10
0	5	10
10	5	10
25	5	10
30	5	10
40	5	10
55	5	5
60	5	5
—	—	—

COSEL

Model	ZTS31215	Temperature	25 ℃																						
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																						
Object	+15V0.2A																								
1. Graph		2.Values																							
<div>[V]</div> <div></div> <div>Output Voltage</div> <div>Time</div> <div>[H]</div> <div>Input Volt. 12V</div> <div>Load 100%</div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>15.014</td></tr><tr><td>0.5</td><td>15.009</td></tr><tr><td>1.0</td><td>15.009</td></tr><tr><td>2.0</td><td>15.009</td></tr><tr><td>3.0</td><td>15.010</td></tr><tr><td>4.0</td><td>15.009</td></tr><tr><td>5.0</td><td>15.009</td></tr><tr><td>6.0</td><td>15.010</td></tr><tr><td>7.0</td><td>15.009</td></tr><tr><td>8.0</td><td>15.009</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	15.014	0.5	15.009	1.0	15.009	2.0	15.009	3.0	15.010	4.0	15.009	5.0	15.009	6.0	15.010	7.0	15.009	8.0	15.009
Time since start [H]	Output Voltage [V]																								
0.0	15.014																								
0.5	15.009																								
1.0	15.009																								
2.0	15.009																								
3.0	15.010																								
4.0	15.009																								
5.0	15.009																								
6.0	15.010																								
7.0	15.009																								
8.0	15.009																								

COSEL

Model	ZTS31215	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+15V0.2A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 9.0~18.0 V

Load Current : 0.0~0.2 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) = $\frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -20~55 °C

入力電圧 : 9.0~18.0 V

負荷電流 : 0.0~0.2 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ratio) [%]
Maximum Voltage	-20	18.0	0.0	15.028	±20	±0.2
Minimum Voltage	55	18.0	0.2	14.988		

COSEL

