



TEST DATA OF ZTS34815

(48.0V INPUT)

Regulated DC Power Supply

Date : Mar. 5. 1998

Approved by : N. Shirashi
Design Manager

Prepared by : J. Iwari
Design Engineer

コーセル株式会社


COSEL CO., LTD.



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	5
リップルノイズ	
6. Overcurrent Protection	6
過電流保護	
7. Dynamic Load Responce	7
動的負荷変動	
8. Rise and Fall Time	8
立ち上り、立下がり時間	
9. Ambient Temperature Drift	9
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage	10
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	11
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	12
経時ドリフト	
13. Output Voltage Accuracy	13
定電圧精度	
14. Condensation	14
結露特性	
15. Figure of Testing Circuitry	15
測定回路図	

(Final Page 15)

COSEL

 Temperature 25°C
 Testing Circuitry Figure A

COSEL

Model	ZTS34815	Temperature Testing Circuitry	25°C Figure A
Item	Efficiency 効率		
Object	—		
1. Graph			
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>			2. Values
Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]	
33.0	74.0	76.8	
36.0	72.8	77.6	
42.0	70.2	77.3	
48.0	67.9	76.4	
54.0	65.3	74.9	
60.0	63.3	73.4	
66.0	61.3	72.0	
72.0	59.3	70.6	
75.0	58.3	69.9	
—	—	—	
—	—	—	
—	—	—	

COSEL

Model	ZTS34815	Temperature 25°C Testing Circuitry Figure A
Item	Load Regulation 静的負荷変動	
Object	+15V 0.2A	

1. Graph

2. Values

Load Current [A]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
0.00	15.141	15.142	15.146
0.04	15.140	15.141	15.141
0.08	15.140	15.140	15.140
0.12	15.139	15.140	15.140
0.16	15.139	15.139	15.139
0.20	15.139	15.139	15.138
0.22	15.138	15.139	15.138
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	ZTS34815	Temperature Testing Circuitry 25°C Figure A																																							
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																								
Object	+15V 0.2A																																								
1. Graph	<p style="text-align: center;">□ Input Volt. 36.0V △ Input Volt. 72.0V</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 36.0 [V]</th> <th>Input Volt. 72.0 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>8</td><td>10</td></tr> <tr><td>0.08</td><td>8</td><td>10</td></tr> <tr><td>0.12</td><td>8</td><td>15</td></tr> <tr><td>0.16</td><td>8</td><td>15</td></tr> <tr><td>0.20</td><td>10</td><td>15</td></tr> <tr><td>0.22</td><td>15</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 36.0 [V]	Input Volt. 72.0 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	5	5	0.04	8	10	0.08	8	10	0.12	8	15	0.16	8	15	0.20	10	15	0.22	15	15	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 36.0 [V]	Input Volt. 72.0 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.00	5	5																																							
0.04	8	10																																							
0.08	8	10																																							
0.12	8	15																																							
0.16	8	15																																							
0.20	10	15																																							
0.22	15	15																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
Ripple Voltage is shown as p-p in the figure below.																																									
Note: Slanted line shows the range of the rated load current.																																									
リップル電圧は、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。																																									
T1: Due to AC Input Line T2: Due to Switching																																									
Fig. Complex Ripple Wave Form 図 リップル波形詳細図																																									

COSEL

Model	ZTS34815																																							
Item	Ripple-Noise リップルノイズ	Temperature Testing Circuitry 25°C Figure A																																						
Object	+15V 0.2A																																							
1. Graph																																								
[mV]		Input Volt. 36.0V Input Volt. 72.0V																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 36.0 [V]</th> <th>Input Volt. 72.0 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>20</td></tr> <tr><td>0.04</td><td>20</td><td>20</td></tr> <tr><td>0.08</td><td>25</td><td>25</td></tr> <tr><td>0.12</td><td>35</td><td>35</td></tr> <tr><td>0.16</td><td>40</td><td>35</td></tr> <tr><td>0.20</td><td>40</td><td>40</td></tr> <tr><td>0.22</td><td>45</td><td>45</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load current [A]	Input Volt. 36.0 [V]	Input Volt. 72.0 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	15	20	0.04	20	20	0.08	25	25	0.12	35	35	0.16	40	35	0.20	40	40	0.22	45	45	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 36.0 [V]	Input Volt. 72.0 [V]																																						
	Ripple-Noise [mV]	Ripple-Noise [mV]																																						
0.00	15	20																																						
0.04	20	20																																						
0.08	25	25																																						
0.12	35	35																																						
0.16	40	35																																						
0.20	40	40																																						
0.22	45	45																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL

Model	ZTS34815
Item	Overcurrent Protection 過電流保護
Object	+15V 0.2A
1. Graph	<p>Input Volt. 36.0V Input Volt. 48.0V Input Volt. 72.0V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>
Note:	Slanted line shows the range of the rated load current.
(注)	斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
15.00	0.28	0.32	0.29
14.25	0.28	0.32	0.29
13.50	0.28	0.32	0.29
12.00	0.29	0.32	0.28
10.50	0.29	0.31	0.27
9.00	0.29	0.31	0.26
7.50	0.29	0.29	0.25
6.00	0.28	0.27	0.24
4.50	0.26	0.25	0.22
3.00	0.24	0.22	0.21
1.50	0.22	0.20	0.20
0.00	0.21	0.21	0.22

COSEL

Model	ZTS34815	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response 動的負荷變動		
Object	+15V 0.2A		


Input Volt. 48.0 V

Cycle 100 mS


Load Current

Min. Load ↔
Load 100 %


200 mV/div

Min. Load ↔
Load 50 %

200 mV/div

Load 50%↔
Load 100 %

200 mV/div




1 mS/div

COSEL


Model	ZTS34815	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+15V 0.2A		

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f
50 %		0.10	3.30	3.40	0.59	5.96
100 %		0.10	3.30	3.40	0.26	2.27




COSEL

Model	ZTS34815
Item	Ambient Temperature Drift 周囲温度変動
Object	+15V 0.2A
1. Graph	
<p style="text-align: center;"> △ Input Volt. 36.0V □ Input Volt. 48.0V ○ Input Volt. 72.0V </p>	
<p style="text-align: center; margin-top: 10px;"> [V] [°C] </p>	
Load 100%	
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>	
<p>(注)斜線は定格周囲温度範囲を示す。</p>	

Testing Circuitry Figure A

2. Values

Temperature [°C]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
-30	15.160	15.161	15.160
-20	15.157	15.157	15.157
-10	15.154	15.154	15.154
0	15.151	15.151	15.151
10	15.148	15.148	15.148
25	15.141	15.141	15.140
30	15.136	15.136	15.136
40	15.127	15.128	15.127
55	15.111	15.111	15.110
60	15.104	15.103	15.103
—	—	—	—

COSEL



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	21.9	27.4
-20	21.4	26.9
-10	20.9	26.4
0	20.4	25.9
10	20.4	25.4
25	19.4	25.4
30	19.4	25.4
40	18.9	25.4
55	18.4	25.4
60	18.4	25.9
—	—	—

COSEL


Testing Circuitry Figure A

COSEL

Model	ZTS34815
Item	Time Lapse Drift 経時ドリフト
Object	+15V 0.2A

1. Graph

[V]



Input Volt. 48V
Load 100%

Temperature 25 °C
Testing Circuitry Figure A

2. Values

Time since start [H]	Output Voltage [V]
0.0	15.139
0.5	15.133
1.0	15.133
2.0	15.133
3.0	15.133
4.0	15.134
5.0	15.134
6.0	15.134
7.0	15.134
8.0	15.134

COSEL

Model	ZTS34815	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+15V0.2A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 36.0~72.0 V

Load Current : 0.0~0.2 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~55 °C

入力電圧 36.0~72.0 V

負荷電流 0.0~0.2 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$\text{* 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	-20	72.0	0.0	15.167	±30	±0.3
Minimum Voltage	55	72.0	0.2	15.107		



Model	ZTS34815		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+15V0.2A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	14.997	Input Volt.: 48V, Load Current:0.2A
Line Regulation [mV]	1	Input Volt.: 36~72V, Load Current:0.2A
Load Regulation [mV]	6	Input Volt.: 48V, Load Current:0~0.2A

COSEL




Figure A