

COSEL

TEST DATA OF ZTW1R51212
(12.0V INPUT)

Regulated DC Power Supply

Date : Mar. 5. 1998

Approved by : N. Shibaishi
Design Manager

Prepared by : J. Teuri
Design Engineer

コーワセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	6
リップルノイズ	
6. Overcurrent Protection	8
過電流保護	
7. Dynamic Load Responce	9
動的負荷変動	
8. Rise and Fall Time	11
立上り、立下がり時間	
9. Ambient Temperature Drift	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	16
経時ドリフト	
13. Output Voltage Accuracy	17
定電圧精度	
14. Condensation	18
結露特性	
15. Figure of Testing Circuitry	20
測定回路図	

(Final Page 20)

COSEL


Model ZTW1R51212

Item Line Regulation 静的入力変動

Object +12V 0.065A

1. Graph

Load 50%
Load 100%

Temperature
Testing Circuitry25°C
Figure A


2. Values

Input Voltage [V]	Load 50%	Load 100%
	Output Volt. [V]	Output Volt. [V]
8.0	12.017	11.884
9.0	12.008	11.887
10.0	12.002	11.889
12.0	11.993	11.891
15.0	11.984	11.889
18.0	11.977	11.886
20.0	11.973	11.884
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

Object -12V 0.065A

1. Graph

Load 50%
Load 100%



2. Values

Input Voltage [V]	Load 50%	Load 100%
	Output Volt. [V]	Output Volt. [V]
8.0	-11.994	-11.861
9.0	-11.984	-11.864
10.0	-11.977	-11.865
12.0	-11.968	-11.865
15.0	-11.958	-11.863
18.0	-11.951	-11.859
20.0	-11.947	-11.857
-	-	-
-	-	-
-	-	-
-	-	-

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL


Model ZTW1R51212

Item Efficiency 効率

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
8.0	67.2	71.5
9.0	67.3	72.2
10.0	66.1	72.5
12.0	64.8	72.5
15.0	60.6	70.7
18.0	56.5	68.2
20.0	54.4	66.4
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	ZTW1R51212	Temperature 25°C	Testing Circuitry Figure A																																												
Item	Load Regulation 靜的負荷変動																																														
Object	+12V0.065A																																														
1. Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9.0V Input Volt. 12.0V Input Volt. 18.0V</p>	2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 9.0[V]</th> <th>Input Volt. 12.0[V]</th> <th>Input Volt. 18.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.172</td><td>12.157</td><td>12.144</td></tr> <tr><td>0.010</td><td>12.100</td><td>12.081</td><td>12.063</td></tr> <tr><td>0.020</td><td>12.057</td><td>12.039</td><td>12.021</td></tr> <tr><td>0.030</td><td>12.020</td><td>12.004</td><td>11.987</td></tr> <tr><td>0.040</td><td>11.983</td><td>11.971</td><td>11.956</td></tr> <tr><td>0.050</td><td>11.947</td><td>11.940</td><td>11.928</td></tr> <tr><td>0.060</td><td>11.910</td><td>11.909</td><td>11.901</td></tr> <tr><td>0.065</td><td>11.891</td><td>11.893</td><td>11.888</td></tr> <tr><td>0.072</td><td>11.865</td><td>11.873</td><td>11.871</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]	0.000	12.172	12.157	12.144	0.010	12.100	12.081	12.063	0.020	12.057	12.039	12.021	0.030	12.020	12.004	11.987	0.040	11.983	11.971	11.956	0.050	11.947	11.940	11.928	0.060	11.910	11.909	11.901	0.065	11.891	11.893	11.888	0.072	11.865	11.873	11.871	-	-	-	-
Load Current [A]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]																																												
0.000	12.172	12.157	12.144																																												
0.010	12.100	12.081	12.063																																												
0.020	12.057	12.039	12.021																																												
0.030	12.020	12.004	11.987																																												
0.040	11.983	11.971	11.956																																												
0.050	11.947	11.940	11.928																																												
0.060	11.910	11.909	11.901																																												
0.065	11.891	11.893	11.888																																												
0.072	11.865	11.873	11.871																																												
-	-	-	-																																												
Object	-12V0.065A	2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 9.0[V]</th> <th>Input Volt. 12.0[V]</th> <th>Input Volt. 18.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.130</td><td>-12.116</td><td>-12.102</td></tr> <tr><td>0.010</td><td>-12.065</td><td>-12.047</td><td>-12.030</td></tr> <tr><td>0.020</td><td>-12.023</td><td>-12.006</td><td>-11.989</td></tr> <tr><td>0.030</td><td>-11.986</td><td>-11.971</td><td>-11.955</td></tr> <tr><td>0.040</td><td>-11.950</td><td>-11.938</td><td>-11.924</td></tr> <tr><td>0.050</td><td>-11.913</td><td>-11.907</td><td>-11.896</td></tr> <tr><td>0.060</td><td>-11.878</td><td>-11.877</td><td>-11.870</td></tr> <tr><td>0.065</td><td>-11.858</td><td>-11.861</td><td>-11.856</td></tr> <tr><td>0.072</td><td>-11.832</td><td>-11.840</td><td>-11.838</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]	0.000	-12.130	-12.116	-12.102	0.010	-12.065	-12.047	-12.030	0.020	-12.023	-12.006	-11.989	0.030	-11.986	-11.971	-11.955	0.040	-11.950	-11.938	-11.924	0.050	-11.913	-11.907	-11.896	0.060	-11.878	-11.877	-11.870	0.065	-11.858	-11.861	-11.856	0.072	-11.832	-11.840	-11.838	-	-	-	-
Load Current [A]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]																																												
0.000	-12.130	-12.116	-12.102																																												
0.010	-12.065	-12.047	-12.030																																												
0.020	-12.023	-12.006	-11.989																																												
0.030	-11.986	-11.971	-11.955																																												
0.040	-11.950	-11.938	-11.924																																												
0.050	-11.913	-11.907	-11.896																																												
0.060	-11.878	-11.877	-11.870																																												
0.065	-11.858	-11.861	-11.856																																												
0.072	-11.832	-11.840	-11.838																																												
-	-	-	-																																												
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																															

COSEL

Model	ZTW1R51212	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																								
Object	+12V 0.065A																																								
1. Graph			2. Values																																						
<p style="text-align: center;">-----□----- Input Volt. 9.0V [mV] -----△----- Input Volt. 18.0V</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 9.0 [V]</th> <th>Input Volt. 18.0 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>10</td><td>15</td></tr> <tr><td>0.010</td><td>10</td><td>15</td></tr> <tr><td>0.020</td><td>15</td><td>15</td></tr> <tr><td>0.030</td><td>20</td><td>20</td></tr> <tr><td>0.040</td><td>25</td><td>20</td></tr> <tr><td>0.060</td><td>45</td><td>20</td></tr> <tr><td>0.065</td><td>50</td><td>20</td></tr> <tr><td>0.072</td><td>60</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 9.0 [V]	Input Volt. 18.0 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.000	10	15	0.010	10	15	0.020	15	15	0.030	20	20	0.040	25	20	0.060	45	20	0.065	50	20	0.072	60	20	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 9.0 [V]	Input Volt. 18.0 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.000	10	15																																							
0.010	10	15																																							
0.020	15	15																																							
0.030	20	20																																							
0.040	25	20																																							
0.060	45	20																																							
0.065	50	20																																							
0.072	60	20																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	ZTW1R51212	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																							
Object	-12V 0.065A																																							
1. Graph	<p style="text-align: center;">-----□----- Input Volt. 9.0V [mV] -----△----- Input Volt. 18.0V</p>	2. Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 9.0 [V]</th> <th>Input Volt. 18.0 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>8</td><td>15</td></tr> <tr><td>0.010</td><td>10</td><td>15</td></tr> <tr><td>0.020</td><td>15</td><td>15</td></tr> <tr><td>0.030</td><td>15</td><td>15</td></tr> <tr><td>0.040</td><td>25</td><td>20</td></tr> <tr><td>0.060</td><td>40</td><td>20</td></tr> <tr><td>0.065</td><td>45</td><td>20</td></tr> <tr><td>0.072</td><td>55</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 9.0 [V]	Input Volt. 18.0 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.000	8	15	0.010	10	15	0.020	15	15	0.030	15	15	0.040	25	20	0.060	40	20	0.065	45	20	0.072	55	20	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 9.0 [V]	Input Volt. 18.0 [V]																																						
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																						
0.000	8	15																																						
0.010	10	15																																						
0.020	15	15																																						
0.030	15	15																																						
0.040	25	20																																						
0.060	40	20																																						
0.065	45	20																																						
0.072	55	20																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期

T2: Due to Switching
スイッチング周期




Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSEL

Model	ZTW1R51212	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																							
Object	+12V 0.065A																																							
1. Graph	<p>Input Volt. 9.0V [mV] □</p> <p>Input Volt. 18.0V △</p>	2. Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 9.0 [V]</th> <th>Input Volt. 18.0 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>25</td><td>20</td></tr> <tr><td>0.010</td><td>30</td><td>25</td></tr> <tr><td>0.020</td><td>30</td><td>25</td></tr> <tr><td>0.030</td><td>35</td><td>25</td></tr> <tr><td>0.040</td><td>40</td><td>25</td></tr> <tr><td>0.060</td><td>55</td><td>30</td></tr> <tr><td>0.065</td><td>65</td><td>35</td></tr> <tr><td>0.072</td><td>70</td><td>40</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load current [A]	Input Volt. 9.0 [V]	Input Volt. 18.0 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.000	25	20	0.010	30	25	0.020	30	25	0.030	35	25	0.040	40	25	0.060	55	30	0.065	65	35	0.072	70	40	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 9.0 [V]	Input Volt. 18.0 [V]																																						
	Ripple-Noise [mV]	Ripple-Noise [mV]																																						
0.000	25	20																																						
0.010	30	25																																						
0.020	30	25																																						
0.030	35	25																																						
0.040	40	25																																						
0.060	55	30																																						
0.065	65	35																																						
0.072	70	40																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																								
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p>																																								
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL

Model	ZTW1R51212
Item	Ripple-Noise リップルノイズ
Object	-12V 0.065A
1. Graph	<p style="text-align: center;">-----□----- Input Volt. 9.0V -----△----- Input Volt. 18.0V</p>
2. Ripple-Noise	<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load current [A]	Input Volt. 9.0 [V]	Input Volt. 18.0 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.000	30	25
0.010	35	25
0.020	40	30
0.030	45	30
0.040	50	35
0.060	60	35
0.065	60	35
0.072	65	35
—	—	—
—	—	—
—	—	—


COSEL

Model ZTW1R51212

Item Overcurrent Protection
過電流保護

Object +12V 0.065A

1. Graph


Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
12.00	0.075	0.097	0.103
11.40	0.132	0.145	0.117
10.80	0.137	0.148	0.118
9.60	0.145	0.153	0.120
8.40	0.152	0.157	0.120
7.20	0.159	0.160	0.121
6.00	0.166	0.160	0.120
4.80	0.171	0.161	0.118
3.60	0.176	0.158	0.119
2.40	0.183	0.161	0.124
1.20	0.165	0.168	0.111
0.00	0.164	0.176	0.138

Object -12V 0.065A

1. Graph



2. Values

Output Voltage [V]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
-12.00	0.080	0.103	0.109
-11.40	0.136	0.149	0.120
-10.80	0.140	0.151	0.121
-9.60	0.148	0.156	0.123
-8.40	0.156	0.161	0.125
-7.20	0.164	0.164	0.125
-6.00	0.170	0.165	0.124
-4.80	0.176	0.164	0.123
-3.60	0.181	0.164	0.123
-2.40	0.188	0.165	0.128
-1.20	0.196	0.173	0.116
0.00	0.156	0.165	0.130

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model ZTW1R51212

Item Dynamic Load Response
動的負荷変動

Object +12V 0.065A

Temperature 25°C
Testing Circuitry Figure A

Input Volt. 12.0 V



Cycle 100 mS

Load Current

Min. Load →

Load 100 %



200 mV/div



Min. Load →

Load 50 %



200 mV/div



Load 50%→

Load 100 %

200 mV/div



1 mS/div

COSEL

Model	ZTW1R51212
Item	Dynamic Load Response 動的負荷變動
Object	-12V 0.065A

Temperature 25°C
Testing Circuitry Figure A

Input Volt. 12.0 V



Cycle 100 mS

Load Current

Min. Load →

Load 100 %



200 mV/div



Min. Load →

Load 50 %



200 mV/div



Load 50%→

Load 100 %

200 mV/div



1 mS/div

COSEL



Model ZTW1R51212

Item Rise and Fall Time 立上り、立下り時間

Object +12V 0.065A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f
50 %		0.05	1.55	1.60	0.97	2.58
100 %		0.05	1.65	1.70	0.59	2.66



COSEL


Model ZTW1R51212

Item Rise and Fall Time 立上り、立下り時間

Object -12V 0.065A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

Load \ Time	T d	T r	T s	T h	T f
50 %	0.70	0.95	1.65	0.96	2.45
100 %	0.70	1.00	1.70	0.59	2.60

[mS]




COSEL

Model ZTW1R51212

Item Ambient Temperature Drift
周围温度変動

Object +12V0.065A

1. Graph




Testing Circuitry Figure A

2. Values

Temperature [°C]	Input Volt.	Input Volt.	Input Volt.
	9.0[V]	12.0[V]	18.0[V]
-30	11.890	11.893	11.889
-20	11.889	11.892	11.889
-10	11.889	11.892	11.889
0	11.889	11.892	11.888
10	11.889	11.892	11.888
25	11.889	11.892	11.888
30	11.889	11.893	11.888
40	11.889	11.893	11.888
55	11.889	11.893	11.888
60	11.888	11.892	11.887
—	—	—	—

Object -12V0.065A

1. Graph



2. Values

Temperature [°C]	Input Volt.	Input Volt.	Input Volt.
	9.0[V]	12.0[V]	18.0[V]
-30	-11.870	-11.870	-11.865
-20	-11.869	-11.869	-11.863
-10	-11.867	-11.868	-11.862
0	-11.867	-11.867	-11.862
10	-11.866	-11.867	-11.862
25	-11.866	-11.868	-11.862
30	-11.866	-11.868	-11.862
40	-11.867	-11.869	-11.863
55	-11.867	-11.870	-11.864
60	-11.867	-11.869	-11.863
—	—	—	—

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model ZTW1R512.12

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +12V 0.065A


1. Graph
[V] 

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	6.1	7.1
-20	5.9	7.0
-10	5.8	6.8
0	5.6	6.6
10	5.6	6.5
25	5.5	6.4
30	5.4	6.3
40	5.4	6.2
55	5.3	6.1
60	5.3	6.1
-	-	-

Object -12V 0.065A

[V] 

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	6.1	7.1
-20	5.9	7.0
-10	5.8	6.8
0	5.6	6.6
10	5.6	6.5
25	5.5	6.4
30	5.4	6.3
40	5.4	6.2
55	5.3	6.1
60	5.3	6.1
-	-	-

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL


Model ZTW1R51212

Item Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object +12V 0.065A

1. Graph

—□— Load 50%
 —△— Load 100%




Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]
-30	35	80
-20	30	70
-10	30	70
0	25	60
10	25	55
25	20	50
30	20	50
40	20	45
55	15	40
60	15	35
—	—	—

1. Graph

—□— Load 50%
 —△— Load 100%



2. Values

Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]
-30	30	70
-20	25	65
-10	25	60
0	25	55
10	20	45
25	20	45
30	20	45
40	15	40
55	15	35
60	15	35
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.


(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	ZTW1R51212
Item	Time Lapse Drift 経時ドリフト
Object	+12V 0.065A

Temperature 25 °C
Testing Circuitry Figure A

1. Graph




2. Values

Time since start [H]	Output Voltage [V]
0.0	11.899
0.5	11.897
1.0	11.897
2.0	11.897
3.0	11.897
4.0	11.897
5.0	11.897
6.0	11.897
7.0	11.897
8.0	11.897

Object	-12V 0.065A
--------	-------------

1. Graph



2. Values

Time since start [H]	Output Voltage [V]
0.0	-11.865
0.5	-11.860
1.0	-11.860
2.0	-11.859
3.0	-11.860
4.0	-11.859
5.0	-11.860
6.0	-11.860
7.0	-11.860
8.0	-11.860

COSEL

Model	ZTW1R51212	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 9.0~18.0 V

Load Current (AVR 1) : 0.000~0.065 A

(AVR 2) : 0.000~0.065 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~55 °C

入力電圧 9.0~18.0 V

負荷電流 (AVR 1) 0.000~0.065 A

(AVR 2) 0.000~0.065 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object +12V 0.065A

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	25	12.0	0.065	11.891		
Minimum Voltage	55	9.0	0.000	11.634	±129	±1.1

Object -12V 0.065A

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	55	12.0	0.065	-11.869		
Minimum Voltage	55	9.0	0.000	-11.603	±133	±1.2



Model	ZTW1R51212		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+12V 0.065A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	12.147	Input Volt.: 12V, Load Current: 0.065A
Line Regulation [mV]	4	Input Volt.: 9~18V, Load Current: 0.065A
Load Regulation [mV]	275	Input Volt.: 12V, Load Current: 0~0.065A



Model	ZTW1R51212		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	-12V 0.065A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	-12.129	Input Volt.: 12V, Load Current:0.065A
Line Regulation [mV]	4	Input Volt.: 9~18V, Load Current:0.065A
Load Regulation [mV]	139	Input Volt.: 12V, Load Current:0~0.065A

COSEL




Figure A