



TEST DATA OF ZUW100512

(5.0V INPUT)

Regulated DC Power Supply

Date : Sep 21. 1996

Approved by : T. Sugimori
Design Manager

Prepared by : M. Takashima
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	6
リップルノイズ	
6. Overcurrent Protection	8
過電流保護	
7. Dynamic Load Responce	9
動的負荷変動	
8. Rise and Fall Time	11
立上り、立下がり時間	
9. Ambient Temperature Drift	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage . . .	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	16
経時ドリフト	
13. Output Voltage Accuracy	17
定電圧精度	
14. Condensation	18
結露特性	
15. Figure of Testing Circuitry	20
測定回路図	

(Final Page 20)

COSEL


Model ZUW100512

Item Efficiency 効率

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph



(注) 斜線は定格入力電圧範囲を示す。


2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
4.0	76.3	74.2
4.5	76.7	75.1
5.0	76.8	76.5
6.0	76.9	78.2
7.0	77.1	79.0
8.0	77.7	79.2
9.0	77.4	79.4
9.5	76.9	79.3
—	—	—
—	—	—
—	—	—
—	—	—

COSEL

Model		ZUW100512																																																																																																					
Item	Load Regulation 静的負荷変動																																																																																																						
Object	+12V0.35A																																																																																																						
1. Graph		2. Values																																																																																																					
<div><div><div>—△—</div><div>—□—</div><div>—○—</div></div><div>Input Volt. 4.5V</div><div>Input Volt. 5.0V</div><div>Input Volt. 9.0V</div></div> <div><table><thead><tr><th>Load Current [A]</th><th>Input Volt. 4.5V [V]</th><th>Input Volt. 5.0V [V]</th><th>Input Volt. 9.0V [V]</th></tr></thead><tbody><tr><td>0.000</td><td>12.466</td><td>12.466</td><td>12.465</td></tr><tr><td>0.060</td><td>12.338</td><td>12.335</td><td>12.329</td></tr><tr><td>0.120</td><td>12.286</td><td>12.281</td><td>12.267</td></tr><tr><td>0.180</td><td>12.244</td><td>12.239</td><td>12.223</td></tr><tr><td>0.240</td><td>12.204</td><td>12.200</td><td>12.188</td></tr><tr><td>0.300</td><td>12.164</td><td>12.162</td><td>12.156</td></tr><tr><td>0.350</td><td>12.131</td><td>12.131</td><td>12.129</td></tr><tr><td>0.385</td><td>12.108</td><td>12.108</td><td>12.111</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></tbody></table></div> <tr><td colspan="2">Object</td><td colspan="2">-12V0.35A</td></tr> <tr><td colspan="2">1. Graph</td><td colspan="2">2. Values</td></tr> <tr><td colspan="2"><div><div><div>—△—</div><div>—□—</div><div>—○—</div></div><div>Input Volt. 4.5V</div><div>Input Volt. 5.0V</div><div>Input Volt. 9.0V</div></div><div><table><thead><tr><th>Load Current [A]</th><th>Input Volt. 4.5V [V]</th><th>Input Volt. 5.0V [V]</th><th>Input Volt. 9.0V [V]</th></tr></thead><tbody><tr><td>0.000</td><td>-12.498</td><td>-12.498</td><td>-12.499</td></tr><tr><td>0.060</td><td>-12.358</td><td>-12.355</td><td>-12.350</td></tr><tr><td>0.120</td><td>-12.305</td><td>-12.300</td><td>-12.287</td></tr><tr><td>0.180</td><td>-12.261</td><td>-12.257</td><td>-12.242</td></tr><tr><td>0.240</td><td>-12.221</td><td>-12.218</td><td>-12.207</td></tr><tr><td>0.300</td><td>-12.180</td><td>-12.179</td><td>-12.174</td></tr><tr><td>0.350</td><td>-12.147</td><td>-12.147</td><td>-12.147</td></tr><tr><td>0.385</td><td>-12.123</td><td>-12.124</td><td>-12.128</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></tbody></table></div><tr><td colspan="4">Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。</td></tr></td></tr>		Load Current [A]	Input Volt. 4.5V [V]	Input Volt. 5.0V [V]	Input Volt. 9.0V [V]	0.000	12.466	12.466	12.465	0.060	12.338	12.335	12.329	0.120	12.286	12.281	12.267	0.180	12.244	12.239	12.223	0.240	12.204	12.200	12.188	0.300	12.164	12.162	12.156	0.350	12.131	12.131	12.129	0.385	12.108	12.108	12.111	—	—	—	—	—	—	—	—	Object		-12V0.35A		1. Graph		2. Values		<div><div><div>—△—</div><div>—□—</div><div>—○—</div></div><div>Input Volt. 4.5V</div><div>Input Volt. 5.0V</div><div>Input Volt. 9.0V</div></div> <div><table><thead><tr><th>Load Current [A]</th><th>Input Volt. 4.5V [V]</th><th>Input Volt. 5.0V [V]</th><th>Input Volt. 9.0V [V]</th></tr></thead><tbody><tr><td>0.000</td><td>-12.498</td><td>-12.498</td><td>-12.499</td></tr><tr><td>0.060</td><td>-12.358</td><td>-12.355</td><td>-12.350</td></tr><tr><td>0.120</td><td>-12.305</td><td>-12.300</td><td>-12.287</td></tr><tr><td>0.180</td><td>-12.261</td><td>-12.257</td><td>-12.242</td></tr><tr><td>0.240</td><td>-12.221</td><td>-12.218</td><td>-12.207</td></tr><tr><td>0.300</td><td>-12.180</td><td>-12.179</td><td>-12.174</td></tr><tr><td>0.350</td><td>-12.147</td><td>-12.147</td><td>-12.147</td></tr><tr><td>0.385</td><td>-12.123</td><td>-12.124</td><td>-12.128</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></tbody></table></div> <tr><td colspan="4">Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。</td></tr>		Load Current [A]	Input Volt. 4.5V [V]	Input Volt. 5.0V [V]	Input Volt. 9.0V [V]	0.000	-12.498	-12.498	-12.499	0.060	-12.358	-12.355	-12.350	0.120	-12.305	-12.300	-12.287	0.180	-12.261	-12.257	-12.242	0.240	-12.221	-12.218	-12.207	0.300	-12.180	-12.179	-12.174	0.350	-12.147	-12.147	-12.147	0.385	-12.123	-12.124	-12.128	—	—	—	—	—	—	—	—	Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。			
Load Current [A]	Input Volt. 4.5V [V]	Input Volt. 5.0V [V]	Input Volt. 9.0V [V]																																																																																																				
0.000	12.466	12.466	12.465																																																																																																				
0.060	12.338	12.335	12.329																																																																																																				
0.120	12.286	12.281	12.267																																																																																																				
0.180	12.244	12.239	12.223																																																																																																				
0.240	12.204	12.200	12.188																																																																																																				
0.300	12.164	12.162	12.156																																																																																																				
0.350	12.131	12.131	12.129																																																																																																				
0.385	12.108	12.108	12.111																																																																																																				
—	—	—	—																																																																																																				
—	—	—	—																																																																																																				
Object		-12V0.35A																																																																																																					
1. Graph		2. Values																																																																																																					
<div><div><div>—△—</div><div>—□—</div><div>—○—</div></div><div>Input Volt. 4.5V</div><div>Input Volt. 5.0V</div><div>Input Volt. 9.0V</div></div> <div><table><thead><tr><th>Load Current [A]</th><th>Input Volt. 4.5V [V]</th><th>Input Volt. 5.0V [V]</th><th>Input Volt. 9.0V [V]</th></tr></thead><tbody><tr><td>0.000</td><td>-12.498</td><td>-12.498</td><td>-12.499</td></tr><tr><td>0.060</td><td>-12.358</td><td>-12.355</td><td>-12.350</td></tr><tr><td>0.120</td><td>-12.305</td><td>-12.300</td><td>-12.287</td></tr><tr><td>0.180</td><td>-12.261</td><td>-12.257</td><td>-12.242</td></tr><tr><td>0.240</td><td>-12.221</td><td>-12.218</td><td>-12.207</td></tr><tr><td>0.300</td><td>-12.180</td><td>-12.179</td><td>-12.174</td></tr><tr><td>0.350</td><td>-12.147</td><td>-12.147</td><td>-12.147</td></tr><tr><td>0.385</td><td>-12.123</td><td>-12.124</td><td>-12.128</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></tbody></table></div> <tr><td colspan="4">Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。</td></tr>		Load Current [A]	Input Volt. 4.5V [V]	Input Volt. 5.0V [V]	Input Volt. 9.0V [V]	0.000	-12.498	-12.498	-12.499	0.060	-12.358	-12.355	-12.350	0.120	-12.305	-12.300	-12.287	0.180	-12.261	-12.257	-12.242	0.240	-12.221	-12.218	-12.207	0.300	-12.180	-12.179	-12.174	0.350	-12.147	-12.147	-12.147	0.385	-12.123	-12.124	-12.128	—	—	—	—	—	—	—	—	Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。																																																									
Load Current [A]	Input Volt. 4.5V [V]	Input Volt. 5.0V [V]	Input Volt. 9.0V [V]																																																																																																				
0.000	-12.498	-12.498	-12.499																																																																																																				
0.060	-12.358	-12.355	-12.350																																																																																																				
0.120	-12.305	-12.300	-12.287																																																																																																				
0.180	-12.261	-12.257	-12.242																																																																																																				
0.240	-12.221	-12.218	-12.207																																																																																																				
0.300	-12.180	-12.179	-12.174																																																																																																				
0.350	-12.147	-12.147	-12.147																																																																																																				
0.385	-12.123	-12.124	-12.128																																																																																																				
—	—	—	—																																																																																																				
—	—	—	—																																																																																																				
Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。																																																																																																							

COSEL




COSEL

Model	ZUW100512
Item	Ripple Voltage (by Load Current) リップル電圧 (負荷電流特性)
Object	-12V 0.35A

Temperature 25°C
Testing Circuitry Figure A

1. Graph
- Input Volt. 4.5V
-----△----- Input Volt. 9.0V



Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p-p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期




Fig. Complex Ripple Wave Form
図 リップル波形詳細図

2. Values

Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	5	5
0.06	5	5
0.12	5	5
0.18	5	5
0.24	6	6
0.30	6	7
0.35	8	8
0.39	9	10
—	—	—
—	—	—
—	—	—

COSEL

Model	ZUW100512	Temperature	25°C
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A
Object	+12V0.350A		

1. Graph

[mV]

-----□----- Input Volt. 4.5V

-----△----- Input Volt. 9.0V

Ripple-Noise

Load Current [A]

2. Values

Load current [A]	Input Volt. 4.5 [V] Ripple-Noise [mV]	Input Volt. 9.0 [V] Ripple-Noise [mV]
0.00	15	20
0.06	15	20
0.12	15	20
0.18	20	25
0.24	20	25
0.30	20	30
0.35	25	30
0.39	30	35
—	—	—
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p-p 値で示される。
(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期

T2: Due to Switching
スイッチング周期

Ripple-Noise [mVp-p]

Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSEL


Model ZUW100512

Item Ripple-Noise リップルノイズ

Object -12V0.350A

Temperature 25°C
Testing Circuitry Figure A

1. Graph
- Input Volt. 4.5V
 -----△----- Input Volt. 9.0V



Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p-p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
 入力商用周期
 T2: Due to Switching
 スイッチング周期




Fig. Complex Ripple Wave Form

図 リップル波形詳細図

2. Values

Load current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.00	20	25
0.06	20	25
0.12	30	30
0.18	30	35
0.24	30	40
0.30	35	40
0.35	35	40
0.39	40	40
—	—	—
—	—	—
—	—	—

COSEL

Model		ZUW100512		Temperature		25℃	
Item		Overcurrent Protection 過電流保護		Testing Circuitry Figure A			
Object		+12V0.350A		2. Values			
1. Graph		<div><div>~~~~~ Input Volt. 4.5 V</div><div>_____ Input Volt. 5.0 V</div><div>_____ Input Volt. 9.0 V</div></div> <div><div>[V]</div><div>20.0</div><div>15.0</div><div>10.0</div><div>5.0</div><div>0.0</div><div>00.2.0.4.0.6.0.8.1.01.2</div><div>Load Current</div><div>[A]</div></div>					
Object		-12V0.350A		2. Values			
1. Graph		<div><div>~~~~~ Input Volt. 4.5 V</div><div>_____ Input Volt. 5.0 V</div><div>_____ Input Volt. 9.0 V</div></div> <div><div>[V]</div><div>-20.0</div><div>-15.0</div><div>-10.0</div><div>-5.0</div><div>0.0</div><div>00.2.0.4.0.6.0.8.1.01.2</div><div>Load Current</div><div>[A]</div></div>					
Note: Slanted line shows the range of the rated load current.							
(注)斜線は定格負荷電流範囲を示す。							

COSEL

Model	ZUW100512	Temperature	25°C
Item	Dynamic Load Responce 動的負荷変動	Testing Circuitry	Figure A
Object	+12V0.350A		

Input Volt. 5 V



Cycle 100 mS

Load Current

Min. Load ↔

Load 100 %



200 mV/div



Min. Load ↔

Load 50 %



200 mV/div



Load 50% ↔

Load 100 %

200 mV/div



1 mS/div

COSEL

Model	ZUW100512	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response 動的負荷変動	
Object	-12V0.350A	



Input Volt. 5 V
Cycle 100 mS

Load Current

Min. Load ←→

Load 100 %



200 mV/div



Min. Load ←→

Load 50 %



200 mV/div



Load 50%←→

Load 100 %

200 mV/div




1 mS/div

COSEL

Model	ZUW100512		
Item	Rise and Fall Time 立上り、立下り時間	Temperature	25°C
Object	+12V0.350A	Testing Circuitry	Figure A

1. Graph


Input Volt. 4.5 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.35	1.95	2.30	0.28	4.68
100 %	0.35	2.15	2.50	0.15	2.33




COSEL

Model	ZUW100512	Temperature	25℃
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	-12V0.35A		

1. Graph


Input Volt. 4.5 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.40	1.80	2.20	0.28	4.68
100 %	0.40	2.10	2.50	0.15	2.33



COSEL

Model		ZUW100512																																																					
Item		Ambient Temperature Drift 周囲温度変動																																																					
Object		+12V0.350A																																																					
1. Graph		2. Values																																																					
<div><div><div>—△—</div><div>Input Volt. 4.5V</div></div><div><div>- -□- -</div><div>Input Volt. 5.0V</div></div><div><div>- -○- -</div><div>Input Volt. 9.0V</div></div></div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table><tr><th>Temperature</th><th>Input Volt. 4.5[V]</th><th>Input Volt. 5.0[V]</th><th>Input Volt. 9.0[V]</th></tr><tr><th>[°C]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr><tr><td>-30</td><td>12.142</td><td>12.141</td><td>12.140</td></tr><tr><td>-20</td><td>12.139</td><td>12.139</td><td>12.138</td></tr><tr><td>-10</td><td>12.137</td><td>12.136</td><td>12.135</td></tr><tr><td>0</td><td>12.135</td><td>12.134</td><td>12.133</td></tr><tr><td>10</td><td>12.133</td><td>12.133</td><td>12.132</td></tr><tr><td>25</td><td>12.130</td><td>12.129</td><td>12.128</td></tr><tr><td>30</td><td>12.128</td><td>12.128</td><td>12.126</td></tr><tr><td>40</td><td>12.125</td><td>12.123</td><td>12.121</td></tr><tr><td>55</td><td>12.113</td><td>12.111</td><td>12.109</td></tr><tr><td>60</td><td>12.107</td><td>12.105</td><td>12.104</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>		Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	12.142	12.141	12.140	-20	12.139	12.139	12.138	-10	12.137	12.136	12.135	0	12.135	12.134	12.133	10	12.133	12.133	12.132	25	12.130	12.129	12.128	30	12.128	12.128	12.126	40	12.125	12.123	12.121	55	12.113	12.111	12.109	60	12.107	12.105	12.104	—	—	—	—
Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																				
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	12.142	12.141	12.140																																																				
-20	12.139	12.139	12.138																																																				
-10	12.137	12.136	12.135																																																				
0	12.135	12.134	12.133																																																				
10	12.133	12.133	12.132																																																				
25	12.130	12.129	12.128																																																				
30	12.128	12.128	12.126																																																				
40	12.125	12.123	12.121																																																				
55	12.113	12.111	12.109																																																				
60	12.107	12.105	12.104																																																				
—	—	—	—																																																				
Object		-12V0.350A																																																					
1. Graph		2. Values																																																					
<div><div><div>—△—</div><div>Input Volt. 4.5V</div></div><div><div>- -□- -</div><div>Input Volt. 5.0V</div></div><div><div>- -○- -</div><div>Input Volt. 9.0V</div></div></div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table><tr><th>Temperature</th><th>Input Volt. 4.5[V]</th><th>Input Volt. 5.0[V]</th><th>Input Volt. 9.0[V]</th></tr><tr><th>[°C]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr><tr><td>-30</td><td>-12.161</td><td>-12.160</td><td>-12.160</td></tr><tr><td>-20</td><td>-12.158</td><td>-12.157</td><td>-12.157</td></tr><tr><td>-10</td><td>-12.155</td><td>-12.154</td><td>-12.155</td></tr><tr><td>0</td><td>-12.153</td><td>-12.152</td><td>-12.153</td></tr><tr><td>10</td><td>-12.151</td><td>-12.150</td><td>-12.151</td></tr><tr><td>25</td><td>-12.147</td><td>-12.147</td><td>-12.147</td></tr><tr><td>30</td><td>-12.145</td><td>-12.144</td><td>-12.145</td></tr><tr><td>40</td><td>-12.141</td><td>-12.140</td><td>-12.139</td></tr><tr><td>55</td><td>-12.129</td><td>-12.128</td><td>-12.128</td></tr><tr><td>60</td><td>-12.123</td><td>-12.122</td><td>-12.122</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>		Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	-12.161	-12.160	-12.160	-20	-12.158	-12.157	-12.157	-10	-12.155	-12.154	-12.155	0	-12.153	-12.152	-12.153	10	-12.151	-12.150	-12.151	25	-12.147	-12.147	-12.147	30	-12.145	-12.144	-12.145	40	-12.141	-12.140	-12.139	55	-12.129	-12.128	-12.128	60	-12.123	-12.122	-12.122	—	—	—	—
Temperature	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																				
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	-12.161	-12.160	-12.160																																																				
-20	-12.158	-12.157	-12.157																																																				
-10	-12.155	-12.154	-12.155																																																				
0	-12.153	-12.152	-12.153																																																				
10	-12.151	-12.150	-12.151																																																				
25	-12.147	-12.147	-12.147																																																				
30	-12.145	-12.144	-12.145																																																				
40	-12.141	-12.140	-12.139																																																				
55	-12.129	-12.128	-12.128																																																				
60	-12.123	-12.122	-12.122																																																				
—	—	—	—																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							
(注)斜線は定格周囲温度範囲を示す。																																																							


COSEL

Model ZUW100512

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +12V0.350A

1. Graph




Testing Circuitry Figure A

2. Values

Ambient Temp.	Load 50%	Load 100%
[°C]	Input Volt. [V]	Input Volt. [V]
-30	3.5	3.8
-20	3.5	3.8
-10	3.6	3.8
0	3.6	3.9
10	3.6	3.9
25	3.7	3.9
30	3.7	3.9
40	3.7	3.9
55	3.7	4.0
60	3.7	4.0
—	—	—

Object -12V0.350A



2. Values


Ambient Temp.	Load 50%	Load 100%
[°C]	Input Volt. [V]	Input Volt. [V]
-30	3.5	3.8
-20	3.5	3.8
-10	3.6	3.8
0	3.6	3.9
10	3.6	3.9
25	3.7	3.9
30	3.7	3.9
40	3.7	3.9
55	3.7	4.0
60	3.7	4.0
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

2. Values



Object	-12 V 0.350 A
--------	---------------

2. Values



Note: Slanted line shows the range of the rated ambient temperature.

- 15 -

COSEL

COSEL	
Model	ZUW100512
Item	Time Lapse Drift 経時ドリフト
Object	+12V0.350A
1. Graph	
<div><div><div>Output Voltage [V]</div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div></div>	

COSEL

COSEL

Model	ZUW100512		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+12V0.350A		

1. Condensation test

Testing procedure is as follows.

① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off.

② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.

③ Testing electrical characteristics of the unit to confirm there be no fault.

④ Repeating ①,② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で－10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values				
	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	12.230	5	25
	2	12.235	5	25
	3	12.230	5	25
Load 100 %	1	12.136	10	40
	2	12.138	10	40
	3	12.131	15	40

Input Volt. 5.0 V

COSEL

LOCEL

Model	ZUW100512
Item	Condensation 結露特性
Object	−12V0.350A

Testing Circuitry Figure A

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at −10℃ for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.


1. 結露特性試験

入力を切った状態で、恒温槽で−10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電氣的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	12.252	10	30
	2	12.248	10	30
	3	12.251	10	30
Load 100 %	1	12.143	15	30
	2	12.139	15	30
	3	12.145	15	30

Input Volt. 5.0 V



Data Acquisition/Control Unit
データ集録システム

Figure A