



TEST DATA OF ZUW150512
(5.0V INPUT)

Regulated DC Power Supply

Date : Feb. 23. 1998

Approved by : Nagai Design Manager

Prepared by : Hanaka Design Engineer

コーセル株式会社
COSEL CO.,LTD.



CONTENTS

1.	Line Regulation	1
	静的入力変動	
2.	Efficiency (by Input Voltage)	2
	効率 (入力電圧特性)	
3.	Load Regulation	3
	静的負荷変動	
4.	Ripple Voltage (by Load Current)	4
	リップル電圧 (負荷特性)	
5.	Ripple-Noise	6
	リップルノイズ	
6.	Overcurrent Protection	8
	過電流保護	
7.	Overvoltage Protection	9
	過電圧保護	
8.	Dynamic Load Responce	10
	動的負荷変動	
9.	Rise and Fall Time	12
	立上り、立下がり時間	
10.	Ambient Temperature Drift	14
	周囲温度変動	
11.	Minimum Input Voltage for Regulated Output Voltage	15
	最低レギュレーション電圧	
12.	Ripple Voltage (by Ambient Temperature)	16
	リップル電圧 (周囲温度特性)	
13.	Time Lapse Drift	17
	経時ドリフト	
14.	Output Voltage Accuracy	18
	定電圧精度	
15.	Condensation	19
	結露特性	
16.	Figure of Testing Circuitry	21
	測定回路図	

(Final Page 22)



Model		ZUW150512	Temperature		25°C																																									
Item		Line Regulation 静的入力変動	Testing Circuitry		Figure A																																									
Object		+12.0V0.60A																																												
1. Graph			2. Values																																											
<p>---○--- Load 50%</p> <p>—×— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>12.003</td><td>11.307</td></tr> <tr><td>4.1</td><td>12.008</td><td>11.762</td></tr> <tr><td>4.2</td><td>12.011</td><td>12.004</td></tr> <tr><td>4.3</td><td>12.012</td><td>12.009</td></tr> <tr><td>4.4</td><td>12.014</td><td>12.011</td></tr> <tr><td>4.5</td><td>12.015</td><td>12.013</td></tr> <tr><td>5.0</td><td>12.020</td><td>12.020</td></tr> <tr><td>6.0</td><td>12.025</td><td>12.026</td></tr> <tr><td>7.0</td><td>12.029</td><td>12.030</td></tr> <tr><td>8.0</td><td>12.031</td><td>12.032</td></tr> <tr><td>9.0</td><td>12.033</td><td>12.034</td></tr> <tr><td>9.5</td><td>12.034</td><td>12.035</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	4.0	12.003	11.307	4.1	12.008	11.762	4.2	12.011	12.004	4.3	12.012	12.009	4.4	12.014	12.011	4.5	12.015	12.013	5.0	12.020	12.020	6.0	12.025	12.026	7.0	12.029	12.030	8.0	12.031	12.032	9.0	12.033	12.034	9.5	12.034	12.035
Input Voltage [V]	Load 50%	Load 100%																																												
	Output Volt. [V]	Output Volt. [V]																																												
4.0	12.003	11.307																																												
4.1	12.008	11.762																																												
4.2	12.011	12.004																																												
4.3	12.012	12.009																																												
4.4	12.014	12.011																																												
4.5	12.015	12.013																																												
5.0	12.020	12.020																																												
6.0	12.025	12.026																																												
7.0	12.029	12.030																																												
8.0	12.031	12.032																																												
9.0	12.033	12.034																																												
9.5	12.034	12.035																																												


Object		-12V0.60A	2. Values																																										
1. Graph																																													
<p>---○--- Load 50%</p> <p>—×— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-12.001</td><td>-11.302</td></tr> <tr><td>4.1</td><td>-12.006</td><td>-11.756</td></tr> <tr><td>4.2</td><td>-12.009</td><td>-11.996</td></tr> <tr><td>4.3</td><td>-12.011</td><td>-12.001</td></tr> <tr><td>4.4</td><td>-12.012</td><td>-12.003</td></tr> <tr><td>4.5</td><td>-12.013</td><td>-12.005</td></tr> <tr><td>5.0</td><td>-12.019</td><td>-12.013</td></tr> <tr><td>6.0</td><td>-12.025</td><td>-12.020</td></tr> <tr><td>7.0</td><td>-12.028</td><td>-12.024</td></tr> <tr><td>8.0</td><td>-12.031</td><td>-12.027</td></tr> <tr><td>9.0</td><td>-12.033</td><td>-12.029</td></tr> <tr><td>9.5</td><td>-12.034</td><td>-12.030</td></tr> </tbody> </table>		Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	4.0	-12.001	-11.302	4.1	-12.006	-11.756	4.2	-12.009	-11.996	4.3	-12.011	-12.001	4.4	-12.012	-12.003	4.5	-12.013	-12.005	5.0	-12.019	-12.013	6.0	-12.025	-12.020	7.0	-12.028	-12.024	8.0	-12.031	-12.027	9.0	-12.033	-12.029	9.5	-12.034	-12.030
Input Voltage [V]	Load 50%	Load 100%																																											
	Output Volt. [V]	Output Volt. [V]																																											
4.0	-12.001	-11.302																																											
4.1	-12.006	-11.756																																											
4.2	-12.009	-11.996																																											
4.3	-12.011	-12.001																																											
4.4	-12.012	-12.003																																											
4.5	-12.013	-12.005																																											
5.0	-12.019	-12.013																																											
6.0	-12.025	-12.020																																											
7.0	-12.028	-12.024																																											
8.0	-12.031	-12.027																																											
9.0	-12.033	-12.029																																											
9.5	-12.034	-12.030																																											
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																													

COSEL

Model	ZUW150512	Temperature	25°C
Item	Efficiency 効率	Testing Circuitry	Figure A
Object			

1. Graph

[%]



Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
4.0	81.2	78.6
4.1	81.9	79.0
4.2	82.3	78.8
4.3	82.4	79.4
4.4	82.7	79.8
4.5	82.9	80.1
5.0	82.7	81.3
6.0	82.2	82.0
7.0	81.9	82.5
8.0	80.8	82.2
9.0	80.1	82.1
9.5	79.4	82.1

COSEL

Model		ZUW150512		Temperature		25°C																																																				
Item		Load Regulation 静的負荷変動		Testing Circuitry		Figure A																																																				
Object		+12.0V0.60A																																																								
1. Graph				2. Values																																																						
<p> ○ Input Volt. 4.5V × Input Volt. 5.0V ▲ Input Volt. 9.0V </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> <tr> <th colspan="3">Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.280</td><td>12.284</td><td>12.304</td></tr> <tr><td>0.070</td><td>12.212</td><td>12.214</td><td>12.219</td></tr> <tr><td>0.140</td><td>12.180</td><td>12.182</td><td>12.187</td></tr> <tr><td>0.210</td><td>12.152</td><td>12.155</td><td>12.161</td></tr> <tr><td>0.280</td><td>12.126</td><td>12.130</td><td>12.137</td></tr> <tr><td>0.350</td><td>12.100</td><td>12.105</td><td>12.113</td></tr> <tr><td>0.420</td><td>12.076</td><td>12.081</td><td>12.091</td></tr> <tr><td>0.490</td><td>12.051</td><td>12.057</td><td>12.069</td></tr> <tr><td>0.560</td><td>12.026</td><td>12.033</td><td>12.047</td></tr> <tr><td>0.600</td><td>12.013</td><td>12.020</td><td>12.035</td></tr> <tr><td>0.630</td><td>12.002</td><td>12.010</td><td>12.025</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	Output Volt. [V]			0.000	12.280	12.284	12.304	0.070	12.212	12.214	12.219	0.140	12.180	12.182	12.187	0.210	12.152	12.155	12.161	0.280	12.126	12.130	12.137	0.350	12.100	12.105	12.113	0.420	12.076	12.081	12.091	0.490	12.051	12.057	12.069	0.560	12.026	12.033	12.047	0.600	12.013	12.020	12.035	0.630	12.002	12.010	12.025
Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																							
	Output Volt. [V]																																																									
0.000	12.280	12.284	12.304																																																							
0.070	12.212	12.214	12.219																																																							
0.140	12.180	12.182	12.187																																																							
0.210	12.152	12.155	12.161																																																							
0.280	12.126	12.130	12.137																																																							
0.350	12.100	12.105	12.113																																																							
0.420	12.076	12.081	12.091																																																							
0.490	12.051	12.057	12.069																																																							
0.560	12.026	12.033	12.047																																																							
0.600	12.013	12.020	12.035																																																							
0.630	12.002	12.010	12.025																																																							
Object		-12V0.60A																																																								
1. Graph				2. Values																																																						
<p> ○ Input Volt. 4.5V × Input Volt. 5.0V ▲ Input Volt. 9.0V </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> <tr> <th colspan="3">Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.278</td><td>-12.282</td><td>-12.300</td></tr> <tr><td>0.070</td><td>-12.211</td><td>-12.214</td><td>-12.219</td></tr> <tr><td>0.140</td><td>-12.178</td><td>-12.181</td><td>-12.187</td></tr> <tr><td>0.210</td><td>-12.150</td><td>-12.153</td><td>-12.160</td></tr> <tr><td>0.280</td><td>-12.122</td><td>-12.127</td><td>-12.135</td></tr> <tr><td>0.350</td><td>-12.096</td><td>-12.101</td><td>-12.111</td></tr> <tr><td>0.420</td><td>-12.070</td><td>-12.076</td><td>-12.088</td></tr> <tr><td>0.490</td><td>-12.045</td><td>-12.051</td><td>-12.065</td></tr> <tr><td>0.560</td><td>-12.019</td><td>-12.027</td><td>-12.042</td></tr> <tr><td>0.600</td><td>-12.004</td><td>-12.012</td><td>-12.029</td></tr> <tr><td>0.630</td><td>-11.993</td><td>-12.001</td><td>-12.019</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	Output Volt. [V]			0.000	-12.278	-12.282	-12.300	0.070	-12.211	-12.214	-12.219	0.140	-12.178	-12.181	-12.187	0.210	-12.150	-12.153	-12.160	0.280	-12.122	-12.127	-12.135	0.350	-12.096	-12.101	-12.111	0.420	-12.070	-12.076	-12.088	0.490	-12.045	-12.051	-12.065	0.560	-12.019	-12.027	-12.042	0.600	-12.004	-12.012	-12.029	0.630	-11.993	-12.001	-12.019
Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																																							
	Output Volt. [V]																																																									
0.000	-12.278	-12.282	-12.300																																																							
0.070	-12.211	-12.214	-12.219																																																							
0.140	-12.178	-12.181	-12.187																																																							
0.210	-12.150	-12.153	-12.160																																																							
0.280	-12.122	-12.127	-12.135																																																							
0.350	-12.096	-12.101	-12.111																																																							
0.420	-12.070	-12.076	-12.088																																																							
0.490	-12.045	-12.051	-12.065																																																							
0.560	-12.019	-12.027	-12.042																																																							
0.600	-12.004	-12.012	-12.029																																																							
0.630	-11.993	-12.001	-12.019																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																										

COSEL

Model	ZUW150512	Temperature	25°C
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry	Figure A
Object	+12.0V0.60A		

1. Graph

Legend:
 ---○--- Input Volt. 4.5V
 ---×--- Input Volt. 9.0V

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple Output Volt. [mV]	
0.000	10	10
0.070	30	40
0.140	30	40
0.210	30	40
0.280	30	40
0.350	30	40
0.420	30	40
0.490	20	40
0.560	20	40
0.600	20	40
0.630	20	40

COSEL

Model		ZUW150512	Temperature		25°C																																					
Item		Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry		Figure A																																					
Object		-12.0V 0.60A																																								
1. Graph		<p>---○--- Input Volt. 4.5V</p> <p>---×--- Input Volt. 9.0V</p>	2. Values																																							
<p>[mV]</p> <p>Ripple Voltage</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9.0 [V]</th> </tr> <tr> <th colspan="2">Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>10</td><td>10</td></tr> <tr><td>0.070</td><td>30</td><td>30</td></tr> <tr><td>0.140</td><td>30</td><td>40</td></tr> <tr><td>0.210</td><td>30</td><td>40</td></tr> <tr><td>0.280</td><td>30</td><td>40</td></tr> <tr><td>0.350</td><td>30</td><td>40</td></tr> <tr><td>0.420</td><td>30</td><td>40</td></tr> <tr><td>0.490</td><td>30</td><td>40</td></tr> <tr><td>0.560</td><td>30</td><td>40</td></tr> <tr><td>0.600</td><td>20</td><td>40</td></tr> <tr><td>0.630</td><td>20</td><td>40</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]	Ripple Output Volt. [mV]		0.000	10	10	0.070	30	30	0.140	30	40	0.210	30	40	0.280	30	40	0.350	30	40	0.420	30	40	0.490	30	40	0.560	30	40	0.600	20	40	0.630	20	40
Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]																																								
	Ripple Output Volt. [mV]																																									
0.000	10	10																																								
0.070	30	30																																								
0.140	30	40																																								
0.210	30	40																																								
0.280	30	40																																								
0.350	30	40																																								
0.420	30	40																																								
0.490	30	40																																								
0.560	30	40																																								
0.600	20	40																																								
0.630	20	40																																								
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>mVp-p</p>																																										


COSEL

Model	ZUW150512
Item	Ripple-Noise リップルノイズ
Object	+12.0V0.60A

Temperature 25°C
Testing Circuitry Figure A

1. Graph
[mV]


---○--- Input Volt. 4.5V
—×— Input Volt. 9.0V



2. Values

Load current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple-Noise [mV]	
0.000	30	60
0.070	40	60
0.140	40	70
0.210	40	70
0.280	40	70
0.350	40	70
0.420	40	70
0.490	40	70
0.560	40	70
0.600	40	70
0.630	40	70

Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.



COSEL

Model		ZUW150512	Temperature		25°C																																						
Item		Ripple-Noise リップルノイズ	Testing Circuitry		Figure A																																						
Object		-12.0V0.60A																																									
1. Graph			2. Values																																								
<p>---○--- Input Volt. 4.5V</p> <p>—×— Input Volt. 9.0V</p> <p>[mV]</p> <p>Ripple-Noise</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9.0 [V]</th> </tr> <tr> <th colspan="2">Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>30</td><td>50</td></tr> <tr><td>0.070</td><td>30</td><td>50</td></tr> <tr><td>0.140</td><td>40</td><td>50</td></tr> <tr><td>0.210</td><td>40</td><td>60</td></tr> <tr><td>0.280</td><td>40</td><td>60</td></tr> <tr><td>0.350</td><td>40</td><td>60</td></tr> <tr><td>0.420</td><td>40</td><td>60</td></tr> <tr><td>0.490</td><td>40</td><td>60</td></tr> <tr><td>0.560</td><td>40</td><td>60</td></tr> <tr><td>0.600</td><td>30</td><td>60</td></tr> <tr><td>0.630</td><td>30</td><td>60</td></tr> </tbody> </table>			Load current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]	Ripple-Noise [mV]		0.000	30	50	0.070	30	50	0.140	40	50	0.210	40	60	0.280	40	60	0.350	40	60	0.420	40	60	0.490	40	60	0.560	40	60	0.600	30	60	0.630	30	60
Load current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]																																									
	Ripple-Noise [mV]																																										
0.000	30	50																																									
0.070	30	50																																									
0.140	40	50																																									
0.210	40	60																																									
0.280	40	60																																									
0.350	40	60																																									
0.420	40	60																																									
0.490	40	60																																									
0.560	40	60																																									
0.600	30	60																																									
0.630	30	60																																									
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																											

COSEL

Model	ZUW150512	Temperature	25°C																																																																			
Item	Overcurrent Protection 過電流保護	Testing Circuitry	Figure A																																																																			
Object	+12.0V0.60A																																																																					
1. Graph	<p>----- Input Volt. 4.5 V</p> <p>————— Input Volt. 5.0 V</p> <p>..... Input Volt. 9.0 V</p>	2. Values																																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> <tr> <th colspan="3">Load Current [A]</th> </tr> </thead> <tbody> <tr><td>11.99</td><td>0.66</td><td>0.66</td><td>0.72</td></tr> <tr><td>11.40</td><td>0.80</td><td>0.80</td><td>0.77</td></tr> <tr><td>10.80</td><td>0.83</td><td>0.83</td><td>0.80</td></tr> <tr><td>9.60</td><td>0.90</td><td>0.90</td><td>0.87</td></tr> <tr><td>8.40</td><td>0.96</td><td>0.96</td><td>0.94</td></tr> <tr><td>7.20</td><td>1.03</td><td>1.03</td><td>1.02</td></tr> <tr><td>6.00</td><td>1.11</td><td>1.11</td><td>1.10</td></tr> <tr><td>4.80</td><td>1.18</td><td>1.18</td><td>1.16</td></tr> <tr><td>3.60</td><td>1.26</td><td>1.26</td><td>1.25</td></tr> <tr><td>2.40</td><td>1.33</td><td>1.33</td><td>1.28</td></tr> <tr><td>1.20</td><td>1.41</td><td>1.41</td><td>1.34</td></tr> <tr><td>0.00</td><td>1.49</td><td>1.49</td><td>1.42</td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	Load Current [A]			11.99	0.66	0.66	0.72	11.40	0.80	0.80	0.77	10.80	0.83	0.83	0.80	9.60	0.90	0.90	0.87	8.40	0.96	0.96	0.94	7.20	1.03	1.03	1.02	6.00	1.11	1.11	1.10	4.80	1.18	1.18	1.16	3.60	1.26	1.26	1.25	2.40	1.33	1.33	1.28	1.20	1.41	1.41	1.34	0.00	1.49	1.49	1.42													
Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]		Input Volt. 9.0[V]																																																																		
	Load Current [A]																																																																					
11.99	0.66	0.66	0.72																																																																			
11.40	0.80	0.80	0.77																																																																			
10.80	0.83	0.83	0.80																																																																			
9.60	0.90	0.90	0.87																																																																			
8.40	0.96	0.96	0.94																																																																			
7.20	1.03	1.03	1.02																																																																			
6.00	1.11	1.11	1.10																																																																			
4.80	1.18	1.18	1.16																																																																			
3.60	1.26	1.26	1.25																																																																			
2.40	1.33	1.33	1.28																																																																			
1.20	1.41	1.41	1.34																																																																			
0.00	1.49	1.49	1.42																																																																			


Object	-12V0.60A	2. Values																																																																				
1. Graph	<p>----- Input Volt. 4.5 V</p> <p>————— Input Volt. 5.0 V</p> <p>..... Input Volt. 9.0 V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> <tr> <th colspan="3">Load Current [A]</th> </tr> </thead> <tbody> <tr><td>-11.99</td><td>0.65</td><td>0.65</td><td>0.70</td></tr> <tr><td>-11.40</td><td>0.80</td><td>0.80</td><td>0.76</td></tr> <tr><td>-10.80</td><td>0.83</td><td>0.83</td><td>0.80</td></tr> <tr><td>-9.60</td><td>0.89</td><td>0.89</td><td>0.87</td></tr> <tr><td>-8.40</td><td>0.96</td><td>0.96</td><td>0.94</td></tr> <tr><td>-7.20</td><td>1.04</td><td>1.04</td><td>1.03</td></tr> <tr><td>-6.00</td><td>1.11</td><td>1.11</td><td>1.10</td></tr> <tr><td>-4.80</td><td>1.18</td><td>1.18</td><td>1.20</td></tr> <tr><td>-3.60</td><td>1.26</td><td>1.26</td><td>1.25</td></tr> <tr><td>-2.40</td><td>1.34</td><td>1.33</td><td>1.28</td></tr> <tr><td>-1.20</td><td>1.42</td><td>1.42</td><td>1.35</td></tr> <tr><td>0.00</td><td>1.50</td><td>1.50</td><td>1.43</td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	Load Current [A]			-11.99	0.65	0.65	0.70	-11.40	0.80	0.80	0.76	-10.80	0.83	0.83	0.80	-9.60	0.89	0.89	0.87	-8.40	0.96	0.96	0.94	-7.20	1.04	1.04	1.03	-6.00	1.11	1.11	1.10	-4.80	1.18	1.18	1.20	-3.60	1.26	1.26	1.25	-2.40	1.34	1.33	1.28	-1.20	1.42	1.42	1.35	0.00	1.50	1.50	1.43													
Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]		Input Volt. 9.0[V]																																																																		
	Load Current [A]																																																																					
-11.99	0.65	0.65	0.70																																																																			
-11.40	0.80	0.80	0.76																																																																			
-10.80	0.83	0.83	0.80																																																																			
-9.60	0.89	0.89	0.87																																																																			
-8.40	0.96	0.96	0.94																																																																			
-7.20	1.04	1.04	1.03																																																																			
-6.00	1.11	1.11	1.10																																																																			
-4.80	1.18	1.18	1.20																																																																			
-3.60	1.26	1.26	1.25																																																																			
-2.40	1.34	1.33	1.28																																																																			
-1.20	1.42	1.42	1.35																																																																			
0.00	1.50	1.50	1.43																																																																			
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																																						

COSEL

Model	ZUW150512
Item	Overvoltage Protection 過電圧保護
Object	±12.0V0.60A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temp. [°C]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Operating Point [V]		
-20	29.40	29.40	29.40
-10	29.60	29.60	29.60
0	29.80	29.80	29.80
10	30.00	30.00	30.00
25	30.40	30.40	30.40
30	30.50	30.50	30.50
40	30.70	30.70	30.70
55	31.00	31.00	31.00
60	31.10	31.10	31.10
70	31.30	31.30	31.30

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Overvoltage protection is measured at between +Vo-Pin and -Vo-Pin.

COSEL

Model	ZUW150512	Temperature	25°C
Item	Dynamic Load Responce 動的負荷変動	Testing Circuitry	Figure A
Object	+12.0V0.60A		


Input Volt. 5.0 V
Cycle 10 mS

Load Current




Load 0% ↔
Load 100 %


100[mV/div]



Load 0% ↔
Load 50 %



Load 50 % ↔
Load 100 %



0.5[mS/div]

COSEL


Model	ZUW150512	Temperature	25°C
Item	Dynamic Load Responce 動的負荷変動	Testing Circuitry	Figure A
Object	-12.0V0.60A		

Input Volt. 5.0 V
Cycle 10 mS


Load Current




Load 0% ↔ 100[mV/div]
Load 100 %



Load 0% ↔
Load 50 %



Load 50 % ↔
Load 100 %




0.5[mS/div]

COSEL

Model	ZUW150512	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+12.0V0.60A		

1. Graph


Input Volt. 4.5 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.30	0.65	0.95	0.10	0.72
100 %	0.30	0.65	0.95	0.10	0.43




COSEL

Model	ZUW150512	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	-12.0V0.60A		

1. Graph


Input Volt. 4.5 V




2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.32	0.66	0.98	0.10	0.75
100 %	0.32	0.66	0.98	0.10	0.43




COSEL



Testing Circuitry Figure A

2. Values

Temperature [°C]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Output Volt. [V]		
-20	12.023	12.023	12.035
-10	12.021	12.021	12.034
0	12.021	12.021	12.034
10	12.021	12.021	12.034
25	12.019	12.019	12.033
30	12.019	12.019	12.034
40	12.015	12.015	12.032
55	12.013	12.013	12.031
60	12.013	12.013	12.032
70	12.008	12.008	12.030



2. Values


Temperature [°C]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Output Volt. [V]		
-20	-12.021	-12.021	-12.034
-10	-12.019	-12.019	-12.033
0	-12.019	-12.019	-12.033
10	-12.016	-12.016	-12.030
25	-12.015	-12.015	-12.031
30	-12.014	-12.014	-12.031
40	-12.012	-12.012	-12.030
55	-12.008	-12.008	-12.028
60	-12.004	-12.004	-12.026
70	-12.001	-12.001	-12.025



Model	ZUW150512
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+12.0V0.60A

Testing Circuitry Figure A


1. Graph
 [V]
 ---○--- Load 50%
 ---×--- Load 100%



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-20	3.9	4.0
-10	3.9	4.0
0	3.9	4.0
10	3.9	4.0
25	3.9	4.0
30	3.9	4.1
40	3.9	4.1
55	3.9	4.1
60	3.9	4.1
70	3.9	4.1

Object	-12V0.60A
--------	-----------



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-20	3.9	4.0
-10	3.9	4.0
0	3.9	4.0
10	3.9	4.0
25	3.9	4.0
30	3.9	4.1
40	3.9	4.1
55	3.9	4.1
60	3.9	4.1
70	3.9	4.1

Note: Slanted line shows the range of the rated ambient temperature.


(注) 斜線は定格周囲温度範囲を示す。



Model	ZUW150512
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+12V0.60A

Testing Circuitry Figure A

1. Graph




Input Volt. 4.5V

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	40	40
-10	30	30
0	30	30
10	30	30
25	30	30
30	30	30
40	30	30
55	30	30
60	30	30
70	30	30

Object	-12V0.60A
--------	-----------

1. Graph



Input Volt. 4.5V

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

2. Values


Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	40	40
-10	30	40
0	30	40
10	30	30
25	30	30
30	30	30
40	30	30
55	30	30
60	30	30
70	30	30

COSEL

Model	ZUW150512
Item	Time Lapse Drift 経時ドリフト
Object	+12.0V0.60A

Temperature 25 °C
Testing Circuitry Figure A

1. Graph




Input Volt. 5.0V
Load 100%

2. Values

Time since start [H]	Output Voltage [V]
0.0	12.019
0.5	12.017
1.0	12.017
2.0	12.017
3.0	12.017
4.0	12.017
5.0	12.017
6.0	12.017
7.0	12.017
8.0	12.017

Object	-12V0.60A
--------	-----------

1. Graph



Input Volt. 5.0V
Load 100%

2. Values

Time since start [H]	Output Voltage [V]
0.0	-12.015
0.5	-12.013
1.0	-12.013
2.0	-12.013
3.0	-12.013
4.0	-12.013
5.0	-12.013
6.0	-12.013
7.0	-12.013
8.0	-12.013



Model		ZUW150512	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度		

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : 0~55 °C

Input Voltage : 4.5~9.0 V

Load Current (AVR 1) : 0.00~0.60 A

(AVR 2) : 0.00~0.60 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{ Output Voltage Accuracy (Ration) } = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 0~55 °C

入力電圧 4.5~9.0 V

負荷電流 (AVR 1) 0.00~0.60 A

(AVR 2) 0.00~0.60 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{ 定電圧精度(変動率) } = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object +12.0V0.60A

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	55	9.0	0.00	12.337	±167	±1.4
Minimum Voltage	55	4.5	0.60	12.003		

Object -12V0.60A

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	55	9.0	0.00	-12.332	±170	±1.5
Minimum Voltage	55	4.5	0.60	-11.992		

COSEL

Model	ZUW150512	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+12.0V0.60A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で-10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50%	1	11.902	30	50
	2	11.908	30	50
	3	11.898	30	50
Load 100%	1	11.901	30	50
	2	11.899	30	50
	3	11.897	30	50

Input Volt. 5.0 V

COSEL

Model		ZUW150512	Testing Circuitry Figure A
Item		Condensation 結露特性	
Object		-12.0V0.60A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で -10°C に冷却しておき、約1時間後に恒温槽から取り出し、室温 25°C 、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	-11.901	30	40
	2	-11.908	30	40
	3	-11.903	30	50
Load 100 %	1	-11.913	30	40
	2	-11.898	30	40
	3	-11.906	30	40

Input Volt. 5.0 V

COSEL

