



TEST DATA OF ZUW30512 (5.0V INPUT)

Regulated DC Power Supply

Date : Nov. 5. 1996

Approved by : T. Sugimori
Design Manager

Prepared by : Y. Nagai
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	6
リップルノイズ	
6. Overcurrent Protection	8
過電流保護	
7. Dynamic Load Responce	9
動的負荷変動	
8. Rise and Fall Time	11
立ち上り、立下がり時間	
9. Ambient Temperature Drift	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	16
経時ドリフト	
13. Output Voltage Accuracy	17
定電圧精度	
14. Condensation	18
結露特性	
15. Figure of Testing Circuitry	20
測定回路図	

(Final Page 20)

COSEL

Model	ZUW30512	Temperature Testing Circuitry	25°C Figure A																																							
Item	Line Regulation 静的入力変動																																									
Object	+12V0.13A																																									
1. Graph	<p style="text-align: center;">-----□----- Load 50% -----△----- Load 100%</p>	2. Values																																								
		<table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Output Volt. [V]</th> <th>Load 100% Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>11.978</td><td>11.869</td></tr> <tr><td>4.5</td><td>11.976</td><td>11.877</td></tr> <tr><td>5.0</td><td>11.975</td><td>11.881</td></tr> <tr><td>6.0</td><td>11.972</td><td>11.885</td></tr> <tr><td>7.0</td><td>11.969</td><td>11.884</td></tr> <tr><td>8.0</td><td>11.966</td><td>11.882</td></tr> <tr><td>9.0</td><td>11.963</td><td>11.879</td></tr> <tr><td>9.5</td><td>11.961</td><td>11.878</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	4.0	11.978	11.869	4.5	11.976	11.877	5.0	11.975	11.881	6.0	11.972	11.885	7.0	11.969	11.884	8.0	11.966	11.882	9.0	11.963	11.879	9.5	11.961	11.878	-	-	-	-	-	-	-	-	-	-	-	-	
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
4.0	11.978	11.869																																								
4.5	11.976	11.877																																								
5.0	11.975	11.881																																								
6.0	11.972	11.885																																								
7.0	11.969	11.884																																								
8.0	11.966	11.882																																								
9.0	11.963	11.879																																								
9.5	11.961	11.878																																								
-	-	-																																								
-	-	-																																								
-	-	-																																								
-	-	-																																								
Object	-12V0.13A	2. Values																																								
1. Graph	<p style="text-align: center;">-----□----- Load 50% -----△----- Load 100%</p>	<table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Output Volt. [-V]</th> <th>Load 100% Output Volt. [-V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-12.009</td><td>-11.901</td></tr> <tr><td>4.5</td><td>-12.007</td><td>-11.907</td></tr> <tr><td>5.0</td><td>-12.005</td><td>-11.911</td></tr> <tr><td>6.0</td><td>-12.002</td><td>-11.913</td></tr> <tr><td>7.0</td><td>-11.999</td><td>-11.912</td></tr> <tr><td>8.0</td><td>-11.996</td><td>-11.910</td></tr> <tr><td>9.0</td><td>-11.993</td><td>-11.908</td></tr> <tr><td>9.5</td><td>-11.992</td><td>-11.906</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 50% Output Volt. [-V]	Load 100% Output Volt. [-V]	4.0	-12.009	-11.901	4.5	-12.007	-11.907	5.0	-12.005	-11.911	6.0	-12.002	-11.913	7.0	-11.999	-11.912	8.0	-11.996	-11.910	9.0	-11.993	-11.908	9.5	-11.992	-11.906	-	-	-	-	-	-	-	-	-	-	-	-	
Input Voltage [V]	Load 50% Output Volt. [-V]	Load 100% Output Volt. [-V]																																								
4.0	-12.009	-11.901																																								
4.5	-12.007	-11.907																																								
5.0	-12.005	-11.911																																								
6.0	-12.002	-11.913																																								
7.0	-11.999	-11.912																																								
8.0	-11.996	-11.910																																								
9.0	-11.993	-11.908																																								
9.5	-11.992	-11.906																																								
-	-	-																																								
-	-	-																																								
-	-	-																																								
-	-	-																																								
			Note: Slanted line shows the range of the rated input voltage. (注)斜線は定格入力電圧範囲を示す。																																							

COSEL


Model ZUW30512

Item Efficiency 効率

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
4.0	66.3	70.7
4.5	67.1	71.4
5.0	65.5	71.8
6.0	63.5	71.0
7.0	61.1	70.3
8.0	59.2	68.7
9.0	56.2	67.0
9.5	55.5	66.3
—	—	—
—	—	—
—	—	—
—	—	—

Note: Slanted line shows the range of the rated input voltage.


(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	ZUW30512	Temperature 25°C Testing Circuitry Figure A																																															
Item	Load Regulation 靜的負荷変動																																																
Object	+12V0.13A																																																
1. Graph	<p>Output Voltage [V] vs Load Current [A]. The graph shows three curves for input voltages 4.5V, 5.0V, and 9.0V. The output voltage decreases as load current increases. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.146</td><td>12.147</td><td>12.145</td></tr> <tr><td>0.020</td><td>12.055</td><td>12.054</td><td>12.043</td></tr> <tr><td>0.040</td><td>12.014</td><td>12.012</td><td>12.000</td></tr> <tr><td>0.060</td><td>11.981</td><td>11.980</td><td>11.969</td></tr> <tr><td>0.080</td><td>11.952</td><td>11.951</td><td>11.941</td></tr> <tr><td>0.100</td><td>11.923</td><td>11.923</td><td>11.916</td></tr> <tr><td>0.120</td><td>11.892</td><td>11.894</td><td>11.890</td></tr> <tr><td>0.130</td><td>11.876</td><td>11.880</td><td>11.878</td></tr> <tr><td>0.143</td><td>11.855</td><td>11.861</td><td>11.862</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	0.000	12.146	12.147	12.145	0.020	12.055	12.054	12.043	0.040	12.014	12.012	12.000	0.060	11.981	11.980	11.969	0.080	11.952	11.951	11.941	0.100	11.923	11.923	11.916	0.120	11.892	11.894	11.890	0.130	11.876	11.880	11.878	0.143	11.855	11.861	11.862	—	—	—	—	
Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																														
0.000	12.146	12.147	12.145																																														
0.020	12.055	12.054	12.043																																														
0.040	12.014	12.012	12.000																																														
0.060	11.981	11.980	11.969																																														
0.080	11.952	11.951	11.941																																														
0.100	11.923	11.923	11.916																																														
0.120	11.892	11.894	11.890																																														
0.130	11.876	11.880	11.878																																														
0.143	11.855	11.861	11.862																																														
—	—	—	—																																														
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.146</td><td>12.147</td><td>12.145</td></tr> <tr><td>0.020</td><td>12.055</td><td>12.054</td><td>12.043</td></tr> <tr><td>0.040</td><td>12.014</td><td>12.012</td><td>12.000</td></tr> <tr><td>0.060</td><td>11.981</td><td>11.980</td><td>11.969</td></tr> <tr><td>0.080</td><td>11.952</td><td>11.951</td><td>11.941</td></tr> <tr><td>0.100</td><td>11.923</td><td>11.923</td><td>11.916</td></tr> <tr><td>0.120</td><td>11.892</td><td>11.894</td><td>11.890</td></tr> <tr><td>0.130</td><td>11.876</td><td>11.880</td><td>11.878</td></tr> <tr><td>0.143</td><td>11.855</td><td>11.861</td><td>11.862</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	0.000	12.146	12.147	12.145	0.020	12.055	12.054	12.043	0.040	12.014	12.012	12.000	0.060	11.981	11.980	11.969	0.080	11.952	11.951	11.941	0.100	11.923	11.923	11.916	0.120	11.892	11.894	11.890	0.130	11.876	11.880	11.878	0.143	11.855	11.861	11.862	—	—	—	—	
Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																														
0.000	12.146	12.147	12.145																																														
0.020	12.055	12.054	12.043																																														
0.040	12.014	12.012	12.000																																														
0.060	11.981	11.980	11.969																																														
0.080	11.952	11.951	11.941																																														
0.100	11.923	11.923	11.916																																														
0.120	11.892	11.894	11.890																																														
0.130	11.876	11.880	11.878																																														
0.143	11.855	11.861	11.862																																														
—	—	—	—																																														
Object	-12V0.13A	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.224</td><td>-12.228</td><td>-12.237</td></tr> <tr><td>0.020</td><td>-12.085</td><td>-12.084</td><td>-12.076</td></tr> <tr><td>0.040</td><td>-12.041</td><td>-12.039</td><td>-12.029</td></tr> <tr><td>0.060</td><td>-12.008</td><td>-12.006</td><td>-11.996</td></tr> <tr><td>0.080</td><td>-11.977</td><td>-11.976</td><td>-11.967</td></tr> <tr><td>0.100</td><td>-11.948</td><td>-11.949</td><td>-11.941</td></tr> <tr><td>0.120</td><td>-11.918</td><td>-11.920</td><td>-11.916</td></tr> <tr><td>0.130</td><td>-11.902</td><td>-11.906</td><td>-11.904</td></tr> <tr><td>0.143</td><td>-11.881</td><td>-11.886</td><td>-11.888</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	0.000	-12.224	-12.228	-12.237	0.020	-12.085	-12.084	-12.076	0.040	-12.041	-12.039	-12.029	0.060	-12.008	-12.006	-11.996	0.080	-11.977	-11.976	-11.967	0.100	-11.948	-11.949	-11.941	0.120	-11.918	-11.920	-11.916	0.130	-11.902	-11.906	-11.904	0.143	-11.881	-11.886	-11.888	—	—	—	—
Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																														
0.000	-12.224	-12.228	-12.237																																														
0.020	-12.085	-12.084	-12.076																																														
0.040	-12.041	-12.039	-12.029																																														
0.060	-12.008	-12.006	-11.996																																														
0.080	-11.977	-11.976	-11.967																																														
0.100	-11.948	-11.949	-11.941																																														
0.120	-11.918	-11.920	-11.916																																														
0.130	-11.902	-11.906	-11.904																																														
0.143	-11.881	-11.886	-11.888																																														
—	—	—	—																																														
1. Graph	<p>Output Voltage [V] vs Load Current [A]. The graph shows three curves for input voltages 4.5V, 5.0V, and 9.0V. The output voltage decreases as load current increases. A slanted line indicates the rated load current range.</p>																																																
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5.0[V]</th> <th>Input Volt. 9.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.224</td><td>-12.228</td><td>-12.237</td></tr> <tr><td>0.020</td><td>-12.085</td><td>-12.084</td><td>-12.076</td></tr> <tr><td>0.040</td><td>-12.041</td><td>-12.039</td><td>-12.029</td></tr> <tr><td>0.060</td><td>-12.008</td><td>-12.006</td><td>-11.996</td></tr> <tr><td>0.080</td><td>-11.977</td><td>-11.976</td><td>-11.967</td></tr> <tr><td>0.100</td><td>-11.948</td><td>-11.949</td><td>-11.941</td></tr> <tr><td>0.120</td><td>-11.918</td><td>-11.920</td><td>-11.916</td></tr> <tr><td>0.130</td><td>-11.902</td><td>-11.906</td><td>-11.904</td></tr> <tr><td>0.143</td><td>-11.881</td><td>-11.886</td><td>-11.888</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]	0.000	-12.224	-12.228	-12.237	0.020	-12.085	-12.084	-12.076	0.040	-12.041	-12.039	-12.029	0.060	-12.008	-12.006	-11.996	0.080	-11.977	-11.976	-11.967	0.100	-11.948	-11.949	-11.941	0.120	-11.918	-11.920	-11.916	0.130	-11.902	-11.906	-11.904	0.143	-11.881	-11.886	-11.888	—	—	—	—	
Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]																																														
0.000	-12.224	-12.228	-12.237																																														
0.020	-12.085	-12.084	-12.076																																														
0.040	-12.041	-12.039	-12.029																																														
0.060	-12.008	-12.006	-11.996																																														
0.080	-11.977	-11.976	-11.967																																														
0.100	-11.948	-11.949	-11.941																																														
0.120	-11.918	-11.920	-11.916																																														
0.130	-11.902	-11.906	-11.904																																														
0.143	-11.881	-11.886	-11.888																																														
—	—	—	—																																														
Note: Slanted line shows the range of the rated load current.																																																	
(注)斜線は定格負荷電流範囲を示す。																																																	

COSEL

Model	ZUW30512
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)
Object	+12V 0.13A

 Temperature 25°C
 Testing Circuitry Figure A


2. Values

Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	5	5
0.02	5	5
0.04	5	5
0.06	5	5
0.08	5	5
0.10	10	5
0.12	15	5
0.13	15	10
0.14	20	10
—	—	—
—	—	—

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

- T1: Due to AC Input Line
入力商用周期
- T2: Due to Switching
スイッチング周期





Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSEL

Model	ZUW30512
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)
Object	-12V 0.13A



Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

- T1: Due to AC Input Line
入力商用周期
- T2: Due to Switching
スイッチング周期





Fig. Complex Ripple Wave Form
図 リップル波形詳細図

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.00	5	5
0.02	5	5
0.04	5	5
0.06	5	5
0.08	10	5
0.10	10	5
0.12	15	5
0.13	15	5
0.14	20	5
—	—	—
—	—	—

COSEL

Model	ZUW30512	Temperature Testing Circuitry	25°C Figure A
Item	Ripple-Noise リップルノイズ		
Object	+12V 0.13A		
1. Graph		-----□----- Input Volt. 4.5V [mV] -----△----- Input Volt. 9.0V 	
2. Values			
Load Current [A]	Input Volt. 4.5 [V] Ripple Output Volt. [mV]	Input Volt. 9.0 [V] Ripple Output Volt. [mV]	
0.00	10	10	
0.02	10	10	
0.04	10	10	
0.06	10	10	
0.08	10	10	
0.10	15	10	
0.12	20	10	
0.13	20	15	
0.14	25	15	
—	—	—	
—	—	—	

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。





Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSEL

Model	ZUW30512	Temperature Testing Circuitry	25°C Figure A
Item	Ripple-Noise リップルノイズ		
Object	-12V 0.13A		
1. Graph		-----□----- Input Volt. 4.5V [mV] -----△----- Input Volt. 9.0V 	
2. Values			
Load Current [A]	Input Volt. 4.5 [V] Ripple Output Volt. [mV]	Input Volt. 9.0 [V] Ripple Output Volt. [mV]	
0.00	10	10	
0.02	10	10	
0.04	10	10	
0.06	10	10	
0.08	15	15	
0.10	15	15	
0.12	20	15	
0.13	20	20	
0.14	30	20	
—	—	—	
—	—	—	

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。




Fig. Complex Ripple Wave Form
図 リップル波形詳細図


COSEL

Model ZUW30512

Item Overcurrent Protection
過電流保護

Object +12V0.13A

1. Graph


Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
12.00	0.068	0.065	0.058
11.40	0.210	0.226	0.222
10.80	0.220	0.235	0.225
9.60	0.234	0.248	0.228
8.40	0.248	0.258	0.226
7.20	0.259	0.266	0.222
6.00	0.265	0.268	0.215
4.80	0.263	0.265	0.201
3.60	0.256	0.255	0.184
2.40	0.239	0.233	0.167
1.20	0.216	0.205	0.155
0.00	0.189	0.180	0.163

Object -12V0.13A

1. Graph



2. Values

Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
-12.00	0.084	0.084	0.077
-11.40	0.216	0.232	0.227
-10.80	0.223	0.238	0.229
-9.60	0.237	0.251	0.231
-8.40	0.252	0.263	0.231
-7.20	0.263	0.271	0.227
-6.00	0.269	0.274	0.218
-4.80	0.269	0.271	0.206
-3.60	0.261	0.259	0.189
-2.40	0.245	0.238	0.171
-1.20	0.223	0.211	0.162
0.00	0.196	0.187	0.167

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model ZUW30512

Item Dynamic Load Response
動的負荷變動

Object +12V 0.13A

Temperature 25°C
Testing Circuitry Figure A


Input Volt. 5.0 V

Cycle 100 mS


Load Current

Min. Load ↔
Load 100 %


200 mV/div

Min. Load ↔
Load 50 %

200 mV/div

Load 50%↔
Load 100 %

200 mV/div



1 mS/div

COSEL

Model	ZUW30512	Temperature Testing Circuitry	25°C
Item	Dynamic Load Response 動的負荷變動		Figure A
Object	-12V 0.13A		


Input Volt. 5.0 V

Cycle 100 mS


Load Current

Min. Load ↔
Load 100 %


200 mV/div

Min. Load ↔
Load 50 %

200 mV/div

Load 50%↔
Load 100 %

200 mV/div



1 mS/div

COSEL


Model ZUW30512

Item Rise and Fall Time 立上り、立下り時間

Object +12V 0.13A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f
50 %		0.60	0.70	1.30	0.10	1.86
100 %		0.60	0.80	1.40	0.06	0.86

[mS]



COSEL



Model ZUW30512

Item Rise and Fall Time 立上り、立下り時間

Object -12V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph





2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f
50 %		0.60	0.75	1.35	0.10	1.67
100 %		0.60	0.85	1.45	0.06	0.67




COSEL



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


Testing Circuitry Figure A

COSEL

Testing Circuitry Figure A



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	3.2	3.6
-20	3.2	3.5
-10	3.1	3.5
0	3.0	3.4
10	3.0	3.4
25	2.9	3.3
30	2.9	3.3
40	2.9	3.3
55	2.8	3.3
60	2.8	3.3
—	—	—



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	3.2	3.6
-20	3.2	3.5
-10	3.1	3.5
0	3.0	3.4
10	3.0	3.4
25	2.9	3.3
30	2.9	3.3
40	2.9	3.3
55	2.8	3.3
60	2.8	3.3
—	—	—


COSEL


COSEL

Model	ZUW30512
Item	Time Lapse Drift 経時ドリフト
Object	+12V0.13A

Temperature 25 °C
Testing Circuitry Figure A

1. Graph


Input Volt. 5.0V
Load 100%

2. Values

Time since start [H]	Output Voltage [V]
0.0	11.896
0.5	11.890
1.0	11.890
2.0	11.891
3.0	11.891
4.0	11.891
5.0	11.891
6.0	11.891
7.0	11.891
8.0	11.891

Object	-12V0.13A
--------	-----------

1. Graph

Input Volt. 5.0V
Load 100%

2. Values

Time since start [H]	Output Voltage [V]
0.0	-11.919
0.5	-11.910
1.0	-11.910
2.0	-11.910
3.0	-11.910
4.0	-11.910
5.0	-11.910
6.0	-11.910
7.0	-11.910
8.0	-11.910



Model	ZUW30512	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 4.5~9.0 V

Load Current (AVR 1) : 0.00~0.13 A

(AVR 2) : 0.00~0.13 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~55 °C

入力電圧 4.5~9.0 V

負荷電流 (AVR 1) 0.00~0.13 A

(AVR 2) 0.00~0.13 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object +12V0.13A

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	5.0	0.13	11.905		
Minimum Voltage	25	9.0	0.00	11.558	±174	±1.5

Object -12V0.13A

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	5.0	0.13	-11.939		
Minimum Voltage	55	4.5	0.00	-11.675	±132	±1.1



Model	ZUW30512		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+12V 0.13A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	11.986	5	15
	2	11.978	5	15
	3	11.982	5	15
Load 100 %	1	11.897	10	20
	2	11.885	10	20
	3	11.888	10	20

Input Volt. 5.0 V



Model	ZUW30512		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	-12V 0.13A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	-12.009	5	15
	2	-12.012	5	15
	3	-12.013	5	15
Load 100 %	1	-11.921	10	30
	2	-11.924	10	30
	3	-11.928	10	35

Input Volt. 5.0 V




Figure A