

**COSEL**

TEST DATA OF ZUW32415  
(24.0V INPUT)

Regulated DC Power Supply

Date : Nov. 5. 1996

Approved by : T. Sugimori  
Design Manager

Prepared by : Y. Nagai  
Design Engineer

コーセル株式会社  
**COSEL CO., LTD.**



## C O N T E N T S

1. Line Regulation . . . . .	1
静的入力変動	
2. Efficiency . . . . .	2
効率	
3. Load Regulation . . . . .	3
静的負荷変動	
4. Ripple Voltage (by Load Current) . . . . .	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise . . . . .	6
リップルノイズ	
6. Overcurrent Protection . . . . .	8
過電流保護	
7. Dynamic Load Response . . . . .	9
動的負荷変動	
8. Rise and Fall Time . . . . .	11
立ち上り、立下がり時間	
9. Ambient Temperature Drift . . . . .	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage . . . . .	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature) . . . . .	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift . . . . .	16
経時ドリフト	
13. Output Voltage Accuracy . . . . .	17
定電圧精度	
14. Condensation . . . . .	18
結露特性	
15. Figure of Testing Circuitry . . . . .	20
測定回路図	

(Final Page 20 )

**COSEL**

Model	ZUW32415	Temperature Testing Circuitry	25°C Figure A																																									
Item	Line Regulation 靜的入力変動																																											
Object	+15V 0.1A																																											
1. Graph	<p style="text-align: center;">-----□----- Load 50% -----△----- Load 100%</p> <p style="text-align: center;">[V]</p>	2. Values																																										
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>16.0</td><td>14.982</td><td>14.866</td></tr> <tr><td>18.0</td><td>14.980</td><td>14.873</td></tr> <tr><td>20.0</td><td>14.979</td><td>14.877</td></tr> <tr><td>24.0</td><td>14.976</td><td>14.882</td></tr> <tr><td>30.0</td><td>14.972</td><td>14.881</td></tr> <tr><td>36.0</td><td>14.966</td><td>14.874</td></tr> <tr><td>40.0</td><td>14.962</td><td>14.870</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	16.0	14.982	14.866	18.0	14.980	14.873	20.0	14.979	14.877	24.0	14.976	14.882	30.0	14.972	14.881	36.0	14.966	14.874	40.0	14.962	14.870	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
Input Voltage [V]	Load 50%	Load 100%																																										
	Output Volt. [V]	Output Volt. [V]																																										
16.0	14.982	14.866																																										
18.0	14.980	14.873																																										
20.0	14.979	14.877																																										
24.0	14.976	14.882																																										
30.0	14.972	14.881																																										
36.0	14.966	14.874																																										
40.0	14.962	14.870																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
Object	-15V 0.1A	2. Values																																										
1. Graph	<p style="text-align: center;">-----□----- Load 50% -----△----- Load 100%</p> <p style="text-align: center;">[V]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>16.0</td><td>-14.974</td><td>-14.858</td></tr> <tr><td>18.0</td><td>-14.973</td><td>-14.864</td></tr> <tr><td>20.0</td><td>-14.971</td><td>-14.868</td></tr> <tr><td>24.0</td><td>-14.969</td><td>-14.872</td></tr> <tr><td>30.0</td><td>-14.964</td><td>-14.871</td></tr> <tr><td>36.0</td><td>-14.958</td><td>-14.865</td></tr> <tr><td>40.0</td><td>-14.955</td><td>-14.860</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	16.0	-14.974	-14.858	18.0	-14.973	-14.864	20.0	-14.971	-14.868	24.0	-14.969	-14.872	30.0	-14.964	-14.871	36.0	-14.958	-14.865	40.0	-14.955	-14.860	—	—	—	—	—	—	—	—	—	—	—	—				
Input Voltage [V]	Load 50%	Load 100%																																										
	Output Volt. [V]	Output Volt. [V]																																										
16.0	-14.974	-14.858																																										
18.0	-14.973	-14.864																																										
20.0	-14.971	-14.868																																										
24.0	-14.969	-14.872																																										
30.0	-14.964	-14.871																																										
36.0	-14.958	-14.865																																										
40.0	-14.955	-14.860																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	ZUW32415	Temperature Testing Circuitry	25°C Figure A																																							
Item	Efficiency 効率																																									
Object	<hr/>																																									
1. Graph	<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Load 50% (dashed line with squares)</p> <p>Load 100% (solid line with triangles)</p>																																									
2. Values	<table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Efficiency [%]</th> <th>Load 100% Efficiency [%]</th> </tr> </thead> <tbody> <tr><td>16.0</td><td>70.9</td><td>76.8</td></tr> <tr><td>18.0</td><td>70.0</td><td>76.4</td></tr> <tr><td>20.0</td><td>68.5</td><td>76.2</td></tr> <tr><td>24.0</td><td>66.3</td><td>74.8</td></tr> <tr><td>30.0</td><td>64.1</td><td>73.2</td></tr> <tr><td>36.0</td><td>61.5</td><td>71.1</td></tr> <tr><td>40.0</td><td>59.6</td><td>70.1</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]	16.0	70.9	76.8	18.0	70.0	76.4	20.0	68.5	76.2	24.0	66.3	74.8	30.0	64.1	73.2	36.0	61.5	71.1	40.0	59.6	70.1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]																																								
16.0	70.9	76.8																																								
18.0	70.0	76.4																																								
20.0	68.5	76.2																																								
24.0	66.3	74.8																																								
30.0	64.1	73.2																																								
36.0	61.5	71.1																																								
40.0	59.6	70.1																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

**COSEL**

Model	ZUW32415	Temperature 25°C Testing Circuitry Figure A																																														
Item	Load Regulation 靜的負荷変動																																															
Object	+15V 0.1A																																															
1. Graph																																																
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 18.0[V]</th> <th>Input Volt. 24.0[V]</th> <th>Input Volt. 36.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.147</td><td>15.149</td><td>15.150</td></tr> <tr><td>0.020</td><td>15.049</td><td>15.045</td><td>15.037</td></tr> <tr><td>0.040</td><td>14.996</td><td>14.993</td><td>14.983</td></tr> <tr><td>0.060</td><td>14.952</td><td>14.951</td><td>14.942</td></tr> <tr><td>0.080</td><td>14.910</td><td>14.913</td><td>14.905</td></tr> <tr><td>0.100</td><td>14.868</td><td>14.877</td><td>14.871</td></tr> <tr><td>0.110</td><td>14.846</td><td>14.859</td><td>14.854</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]	0.000	15.147	15.149	15.150	0.020	15.049	15.045	15.037	0.040	14.996	14.993	14.983	0.060	14.952	14.951	14.942	0.080	14.910	14.913	14.905	0.100	14.868	14.877	14.871	0.110	14.846	14.859	14.854	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]																																													
0.000	15.147	15.149	15.150																																													
0.020	15.049	15.045	15.037																																													
0.040	14.996	14.993	14.983																																													
0.060	14.952	14.951	14.942																																													
0.080	14.910	14.913	14.905																																													
0.100	14.868	14.877	14.871																																													
0.110	14.846	14.859	14.854																																													
—	—	—	—																																													
—	—	—	—																																													
—	—	—	—																																													
Object	-15V 0.1A																																															
1. Graph																																																
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 18.0[V]</th> <th>Input Volt. 24.0[V]</th> <th>Input Volt. 36.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.142</td><td>-15.144</td><td>-15.144</td></tr> <tr><td>0.020</td><td>-15.041</td><td>-15.036</td><td>-15.028</td></tr> <tr><td>0.040</td><td>-14.986</td><td>-14.983</td><td>-14.974</td></tr> <tr><td>0.060</td><td>-14.942</td><td>-14.941</td><td>-14.932</td></tr> <tr><td>0.080</td><td>-14.897</td><td>-14.901</td><td>-14.893</td></tr> <tr><td>0.100</td><td>-14.854</td><td>-14.864</td><td>-14.858</td></tr> <tr><td>0.110</td><td>-14.832</td><td>-14.845</td><td>-14.841</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]	0.000	-15.142	-15.144	-15.144	0.020	-15.041	-15.036	-15.028	0.040	-14.986	-14.983	-14.974	0.060	-14.942	-14.941	-14.932	0.080	-14.897	-14.901	-14.893	0.100	-14.854	-14.864	-14.858	0.110	-14.832	-14.845	-14.841	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]																																													
0.000	-15.142	-15.144	-15.144																																													
0.020	-15.041	-15.036	-15.028																																													
0.040	-14.986	-14.983	-14.974																																													
0.060	-14.942	-14.941	-14.932																																													
0.080	-14.897	-14.901	-14.893																																													
0.100	-14.854	-14.864	-14.858																																													
0.110	-14.832	-14.845	-14.841																																													
—	—	—	—																																													
—	—	—	—																																													
—	—	—	—																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																

**COSEL**

Model	ZUW32415	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																								
Object	+15V 0.1A																																								
1. Graph	<p>-----□----- Input Volt. 18.0V [mV]            -----△----- Input Volt. 36.0V [mV]</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 18.0V [mV] (Input 18.0V)</th> <th>Ripple Output Volt. 36.0V [mV] (Input 36.0V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.02</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.06</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>15</td><td>5</td></tr> <tr><td>0.10</td><td>25</td><td>5</td></tr> <tr><td>0.11</td><td>30</td><td>5</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Volt. 18.0V [mV] (Input 18.0V)	Ripple Output Volt. 36.0V [mV] (Input 36.0V)	0.00	5	5	0.02	5	5	0.04	5	5	0.06	5	5	0.08	15	5	0.10	25	5	0.11	30	5														
Load Current [A]	Ripple Output Volt. 18.0V [mV] (Input 18.0V)	Ripple Output Volt. 36.0V [mV] (Input 36.0V)																																							
0.00	5	5																																							
0.02	5	5																																							
0.04	5	5																																							
0.06	5	5																																							
0.08	15	5																																							
0.10	25	5																																							
0.11	30	5																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 18.0 [V]</th> <th>Input Volt. 36.0 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.02</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.06</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>15</td><td>5</td></tr> <tr><td>0.10</td><td>25</td><td>5</td></tr> <tr><td>0.11</td><td>30</td><td>5</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 18.0 [V]	Input Volt. 36.0 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	5	5	0.02	5	5	0.04	5	5	0.06	5	5	0.08	15	5	0.10	25	5	0.11	30	5	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Input Volt. 18.0 [V]	Input Volt. 36.0 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.00	5	5																																							
0.02	5	5																																							
0.04	5	5																																							
0.06	5	5																																							
0.08	15	5																																							
0.10	25	5																																							
0.11	30	5																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	ZUW32415	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)																																							
Object	-15V 0.1A																																							
1. Graph	<p>-----□----- Input Volt. 18.0V [mV]</p> <p>-----△----- Input Volt. 36.0V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 18.0V [mV] (□)</th> <th>Ripple Output Volt. 36.0V [mV] (△)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.02</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.06</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>10</td><td>5</td></tr> <tr><td>0.10</td><td>20</td><td>5</td></tr> <tr><td>0.11</td><td>25</td><td>5</td></tr> </tbody> </table>	Load Current [A]	Ripple Output Volt. 18.0V [mV] (□)	Ripple Output Volt. 36.0V [mV] (△)	0.00	5	5	0.02	5	5	0.04	5	5	0.06	5	5	0.08	10	5	0.10	20	5	0.11	25	5	2. Values														
Load Current [A]	Ripple Output Volt. 18.0V [mV] (□)	Ripple Output Volt. 36.0V [mV] (△)																																						
0.00	5	5																																						
0.02	5	5																																						
0.04	5	5																																						
0.06	5	5																																						
0.08	10	5																																						
0.10	20	5																																						
0.11	25	5																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 18.0 [V]</th> <th>Input Volt. 36.0 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.02</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.06</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>10</td><td>5</td></tr> <tr><td>0.10</td><td>20</td><td>5</td></tr> <tr><td>0.11</td><td>25</td><td>5</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 18.0 [V]	Input Volt. 36.0 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	5	5	0.02	5	5	0.04	5	5	0.06	5	5	0.08	10	5	0.10	20	5	0.11	25	5	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 18.0 [V]	Input Volt. 36.0 [V]																																						
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																						
0.00	5	5																																						
0.02	5	5																																						
0.04	5	5																																						
0.06	5	5																																						
0.08	10	5																																						
0.10	20	5																																						
0.11	25	5																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

- T1: Due to AC Input Line  
入力商用周期
- T2: Due to Switching  
スイッチング周期




Fig. Complex Ripple Wave Form  
図 リップル波形詳細図

**COSEL**

Model	ZUW32415																																							
Item	Ripple-Noise リップルノイズ																																							
Object	+15V 0.1A																																							
1. Graph																																								
<p>Temperature Testing Circuitry 25°C Figure A</p> <p>2. Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 18.0 [V]</th> <th>Input Volt. 36.0 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.02</td><td>15</td><td>15</td></tr> <tr><td>0.04</td><td>15</td><td>15</td></tr> <tr><td>0.06</td><td>20</td><td>20</td></tr> <tr><td>0.08</td><td>25</td><td>25</td></tr> <tr><td>0.10</td><td>35</td><td>25</td></tr> <tr><td>0.11</td><td>40</td><td>25</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 18.0 [V]	Input Volt. 36.0 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	15	15	0.02	15	15	0.04	15	15	0.06	20	20	0.08	25	25	0.10	35	25	0.11	40	25	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 18.0 [V]	Input Volt. 36.0 [V]																																						
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																						
0.00	15	15																																						
0.02	15	15																																						
0.04	15	15																																						
0.06	20	20																																						
0.08	25	25																																						
0.10	35	25																																						
0.11	40	25																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						
—	—	—																																						

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p – p 値で示される。  
(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form  
図 リップル波形詳細図

**COSEL**

Model	ZUW32415	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	-15V 0.1A																																								
1. Graph	<p>-----□----- Input Volt. 18.0V [mV]            -----△----- Input Volt. 36.0V [mV]</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 18.0 [V]</th> <th>Input Volt. 36.0 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.02</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>10</td><td>5</td></tr> <tr><td>0.06</td><td>10</td><td>10</td></tr> <tr><td>0.08</td><td>20</td><td>10</td></tr> <tr><td>0.10</td><td>30</td><td>15</td></tr> <tr><td>0.11</td><td>35</td><td>15</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 18.0 [V]	Input Volt. 36.0 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	5	5	0.02	5	5	0.04	10	5	0.06	10	10	0.08	20	10	0.10	30	15	0.11	35	15	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 18.0 [V]	Input Volt. 36.0 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.00	5	5																																							
0.02	5	5																																							
0.04	10	5																																							
0.06	10	10																																							
0.08	20	10																																							
0.10	30	15																																							
0.11	35	15																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below.            Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p – p 値で示される。            (注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line            入力商用周期            T2: Due to Switching            スイッチング周期</p>																																									
<p>Fig. Complex Ripple Wave Form            図 リップル波形詳細図</p>																																									

COSEL

Model	ZUW32415
Item	Overcurrent Protection 過電流保護
Object	+15V 0.1A

1. Graph

	Input Volt. 18.0 V	Input Volt. 24.0 V	Input Volt. 36.0 V
[V]			

Output Voltage [V]

Load Current [A]

Object	-15V 0.1A								
1. Graph	<table border="1"> <tr> <td></td> <td>Input Volt. 18.0 V</td> <td>Input Volt. 24.0 V</td> <td>Input Volt. 36.0 V</td> </tr> <tr> <td>[V]</td> <td></td> <td></td> <td></td> </tr> </table> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		Input Volt. 18.0 V	Input Volt. 24.0 V	Input Volt. 36.0 V	[V]			
	Input Volt. 18.0 V	Input Volt. 24.0 V	Input Volt. 36.0 V						
[V]									
Note:	Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。								

Temperature 25°C  
Testing Circuitry Figure A


## 2. Values


Output Voltage [V]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
15.00	0.021	0.020	0.018
14.25	0.215	0.244	0.199
13.50	0.220	0.248	0.201
12.00	0.235	0.259	0.204
10.50	0.245	0.266	0.205
9.00	0.254	0.269	0.203
7.50	0.258	0.269	0.198
6.00	0.258	0.262	0.189
4.50	0.249	0.245	0.175
3.00	0.233	0.219	0.158
1.50	0.212	0.193	0.145
0.00	0.272	0.263	0.232

## 2. Values

Output Voltage [V]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
-15.00	0.001	0.001	0.001
-14.25	0.218	0.246	0.201
-13.50	0.224	0.251	0.203
-12.00	0.237	0.261	0.206
-10.50	0.249	0.268	0.208
-9.00	0.257	0.272	0.206
-7.50	0.262	0.272	0.202
-6.00	0.261	0.266	0.193
-4.50	0.254	0.250	0.180
-3.00	0.239	0.226	0.164
-1.50	0.218	0.198	0.151
0.00	0.261	0.251	0.219

COSEL



**COSEL**

COSEL


Model ZUW32415

Item Rise and Fall Time 立上り、立下り時間

Object +15V 0.1A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>	[mS]
50 %		0.45	2.30	2.75	0.28	2.90	
100 %		0.45	2.45	2.90	0.19	1.45	



**COSEL**



Model ZUW32415

Item Rise and Fall Time 立上り、立下り時間

Object -15V0.1A


Temperature 25°C  
Testing Circuitry  
Figure A

## 1. Graph



## 2. Values

Load	Time	T <sub>d</sub>	T <sub>r</sub>	T <sub>s</sub>	T <sub>h</sub>	T <sub>f</sub>	[mS]
50 %		0.50	2.30	2.80	0.28	2.62	
100 %		0.50	2.45	2.95	0.19	1.17	



COSEL


Model	ZUW32415	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift 周囲温度変動																																																						
Object	+15V0.1A																																																						
1. Graph	<p style="text-align: center;"> <span style="color: black;">△</span> Input Volt. 18.0V  <span style="color: gray;">□</span> Input Volt. 24.0V  <span style="color: gray;">○</span> Input Volt. 36.0V         </p>	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Temperature [°C]</th> <th>Input Volt. 18.0[V]</th> <th>Input Volt. 24.0[V]</th> <th>Input Volt. 36.0[V]</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>14.907</td><td>14.910</td><td>14.904</td></tr> <tr><td>-20</td><td>14.900</td><td>14.905</td><td>14.898</td></tr> <tr><td>-10</td><td>14.894</td><td>14.899</td><td>14.893</td></tr> <tr><td>0</td><td>14.889</td><td>14.894</td><td>14.888</td></tr> <tr><td>10</td><td>14.884</td><td>14.890</td><td>14.883</td></tr> <tr><td>25</td><td>14.876</td><td>14.883</td><td>14.876</td></tr> <tr><td>30</td><td>14.874</td><td>14.881</td><td>14.873</td></tr> <tr><td>40</td><td>14.867</td><td>14.875</td><td>14.867</td></tr> <tr><td>55</td><td>14.856</td><td>14.866</td><td>14.857</td></tr> <tr><td>60</td><td>14.852</td><td>14.861</td><td>14.853</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	14.907	14.910	14.904	-20	14.900	14.905	14.898	-10	14.894	14.899	14.893	0	14.889	14.894	14.888	10	14.884	14.890	14.883	25	14.876	14.883	14.876	30	14.874	14.881	14.873	40	14.867	14.875	14.867	55	14.856	14.866	14.857	60	14.852	14.861	14.853	—	—	—	—
Temperature [°C]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]																																																				
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	14.907	14.910	14.904																																																				
-20	14.900	14.905	14.898																																																				
-10	14.894	14.899	14.893																																																				
0	14.889	14.894	14.888																																																				
10	14.884	14.890	14.883																																																				
25	14.876	14.883	14.876																																																				
30	14.874	14.881	14.873																																																				
40	14.867	14.875	14.867																																																				
55	14.856	14.866	14.857																																																				
60	14.852	14.861	14.853																																																				
—	—	—	—																																																				
Object	-15V0.1A	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Temperature [°C]</th> <th>Input Volt. 18.0[V]</th> <th>Input Volt. 24.0[V]</th> <th>Input Volt. 36.0[V]</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>-14.890</td><td>-14.896</td><td>-14.890</td></tr> <tr><td>-20</td><td>-14.886</td><td>-14.892</td><td>-14.885</td></tr> <tr><td>-10</td><td>-14.882</td><td>-14.887</td><td>-14.880</td></tr> <tr><td>0</td><td>-14.877</td><td>-14.883</td><td>-14.876</td></tr> <tr><td>10</td><td>-14.873</td><td>-14.879</td><td>-14.872</td></tr> <tr><td>25</td><td>-14.866</td><td>-14.873</td><td>-14.865</td></tr> <tr><td>30</td><td>-14.864</td><td>-14.871</td><td>-14.863</td></tr> <tr><td>40</td><td>-14.857</td><td>-14.866</td><td>-14.858</td></tr> <tr><td>55</td><td>-14.847</td><td>-14.856</td><td>-14.848</td></tr> <tr><td>60</td><td>-14.842</td><td>-14.852</td><td>-14.844</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-30	-14.890	-14.896	-14.890	-20	-14.886	-14.892	-14.885	-10	-14.882	-14.887	-14.880	0	-14.877	-14.883	-14.876	10	-14.873	-14.879	-14.872	25	-14.866	-14.873	-14.865	30	-14.864	-14.871	-14.863	40	-14.857	-14.866	-14.858	55	-14.847	-14.856	-14.848	60	-14.842	-14.852	-14.844	—	—	—	—
Temperature [°C]	Input Volt. 18.0[V]	Input Volt. 24.0[V]	Input Volt. 36.0[V]																																																				
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-30	-14.890	-14.896	-14.890																																																				
-20	-14.886	-14.892	-14.885																																																				
-10	-14.882	-14.887	-14.880																																																				
0	-14.877	-14.883	-14.876																																																				
10	-14.873	-14.879	-14.872																																																				
25	-14.866	-14.873	-14.865																																																				
30	-14.864	-14.871	-14.863																																																				
40	-14.857	-14.866	-14.858																																																				
55	-14.847	-14.856	-14.848																																																				
60	-14.842	-14.852	-14.844																																																				
—	—	—	—																																																				
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																																							

**COSEL**

Model	ZUW32415
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+15V0.1A

1. Graph

[V]      -----□----- Load 50%  
               -----△----- Load 100%




Testing Circuitry Figure A

## 2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	10.3	11.9
-20	10.2	11.6
-10	10.0	11.4
0	9.8	11.2
10	9.7	10.9
25	9.5	10.7
30	9.5	10.7
40	9.4	10.7
55	9.2	10.6
60	9.1	10.7
—	—	—

Object -15V0.1A

[V]      -----□----- Load 50%  
               -----△----- Load 100%



## 2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	10.3	11.9
-20	10.2	11.6
-10	10.0	11.4
0	9.8	11.2
10	9.7	10.9
25	9.5	10.7
30	9.5	10.7
40	9.4	10.7
55	9.2	10.6
60	9.1	10.7
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

# COSEL

<p>Model      ZUW32415</p> <p>Item      Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)</p> <p>Object    +15V 0.1A</p>	Testing Circuitry      Figure A																																				
	1. Graph	2. Values																																			
<p>1. Graph</p> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 18 V</p>	<table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-30</td><td>10</td><td>60</td></tr> <tr><td>-20</td><td>10</td><td>45</td></tr> <tr><td>-10</td><td>5</td><td>35</td></tr> <tr><td>0</td><td>5</td><td>30</td></tr> <tr><td>10</td><td>5</td><td>25</td></tr> <tr><td>25</td><td>5</td><td>25</td></tr> <tr><td>30</td><td>5</td><td>25</td></tr> <tr><td>40</td><td>5</td><td>25</td></tr> <tr><td>55</td><td>5</td><td>25</td></tr> <tr><td>60</td><td>5</td><td>25</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temp. [°C]	Load 50%	Load 100%	-30	10	60	-20	10	45	-10	5	35	0	5	30	10	5	25	25	5	25	30	5	25	40	5	25	55	5	25	60	5	25	—	—	—
Ambient Temp. [°C]	Load 50%	Load 100%																																			
-30	10	60																																			
-20	10	45																																			
-10	5	35																																			
0	5	30																																			
10	5	25																																			
25	5	25																																			
30	5	25																																			
40	5	25																																			
55	5	25																																			
60	5	25																																			
—	—	—																																			
<p>Object    -15V 0.1A</p> <p>1. Graph</p> <p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 18 V</p>	<p>2. Values</p> <table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-30</td><td>10</td><td>45</td></tr> <tr><td>-20</td><td>10</td><td>40</td></tr> <tr><td>-10</td><td>5</td><td>30</td></tr> <tr><td>0</td><td>5</td><td>25</td></tr> <tr><td>10</td><td>5</td><td>20</td></tr> <tr><td>25</td><td>5</td><td>20</td></tr> <tr><td>30</td><td>5</td><td>20</td></tr> <tr><td>40</td><td>5</td><td>20</td></tr> <tr><td>55</td><td>5</td><td>20</td></tr> <tr><td>60</td><td>5</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Ambient Temp. [°C]	Load 50%	Load 100%	-30	10	45	-20	10	40	-10	5	30	0	5	25	10	5	20	25	5	20	30	5	20	40	5	20	55	5	20	60	5	20	—	—	—
Ambient Temp. [°C]	Load 50%	Load 100%																																			
-30	10	45																																			
-20	10	40																																			
-10	5	30																																			
0	5	25																																			
10	5	20																																			
25	5	20																																			
30	5	20																																			
40	5	20																																			
55	5	20																																			
60	5	20																																			
—	—	—																																			

Note: Slanted line shows the range of the rated ambient temperature.


(注)斜線は定格周囲温度範囲を示す。

**COSEL**

Model	ZUW32415
Item	Time Lapse Drift 経時ドリフト
Object	+15V 0.1A

Temperature 25 °C  
Testing Circuitry Figure A

## 1. Graph




## 2. Values

Time since start [H]	Output Voltage [V]
0.0	14.897
0.5	14.891
1.0	14.892
2.0	14.891
3.0	14.892
4.0	14.892
5.0	14.892
6.0	14.892
7.0	14.892
8.0	14.891

Object	-15V 0.1A
--------	-----------

## 1. Graph



## 2. Values

Time since start [H]	Output Voltage [V]
0.0	-14.880
0.5	-14.870
1.0	-14.869
2.0	-14.869
3.0	-14.869
4.0	-14.869
5.0	-14.869
6.0	-14.869
7.0	-14.869
8.0	-14.869



Model	ZUW32415	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

#### Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 18.0~36.0 V

Load Current (AVR 1) : 0.0~0.1 A

(AVR 2) : 0.0~0.1 A

\* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage)/2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

#### 定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~55 °C

入力電圧 18.0~36.0 V

負荷電流 (AVR 1) 0.0~0.1 A

(AVR 2) 0.0~0.1 A

\* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値)/2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object +15V 0.1A

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	24.0	0.1	14.904		
Minimum Voltage	25	18.0	0.0	14.628	±138	±1.0

Object -15V 0.1A

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	24.0	0.1	-14.892		
Minimum Voltage	55	18.0	0.0	-14.626	±133	±0.9



Model	ZUW32415		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+15V 0.1A		

### 1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

### 1. 結露特性試験

入力を切った状態で、恒温槽で-10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

### 2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	14.989	5	15
	2	14.991	5	15
	3	14.991	5	15
Load 100 %	1	14.895	10	20
	2	14.901	10	20
	3	14.904	10	20

Input Volt. 24.0 V

**COSEL**

Model	ZUW32415	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	-15V 0.1A	

## 1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

## 1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

## 2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	-14.972	5	20
	2	-14.972	5	20
	3	-14.968	5	20
Load 100 %	1	-14.879	10	20
	2	-14.879	10	25
	3	-14.878	10	25

Input Volt. 24.0 V




Figure A