



TEST DATA OF ZUW64812

(48.0V INPUT)

Regulated DC Power Supply

Date : Sep. 21. 1996

Approved by : 7. Sugimori
Design Manager

Prepared by : H. Ise
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	6
リップルノイズ	
6. Overcurrent Protection	8
過電流保護	
7. Dynamic Load Responce	9
動的負荷変動	
8. Rise and Fall Time	11
立上り、立下がり時間	
9. Ambient Temperature Drift	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage . . .	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	16
経時ドリフト	
13. Output Voltage Accuracy	17
定電圧精度	
14. Condensation	18
結露特性	
15. Figure of Testing Circuitry	20
測定回路図	

(Final Page 20)

COSEL

Model		ZUW64812																																								
Item	Line Regulation 静的入力変動																																									
Object	+12V0.25A																																									
1. Graph		2. Values																																								
<div><div>-----□----- Load 50%</div><div>-----△----- Load 100%</div></div> <div><div>[V]</div><div>Output Voltage</div><div>Input Voltage [V]</div></div>		<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>33.0</td><td>12.070</td><td>11.969</td></tr><tr><td>36.0</td><td>12.064</td><td>11.970</td></tr><tr><td>42.0</td><td>12.055</td><td>11.970</td></tr><tr><td>48.0</td><td>12.049</td><td>11.969</td></tr><tr><td>54.0</td><td>12.044</td><td>11.967</td></tr><tr><td>60.0</td><td>12.040</td><td>11.965</td></tr><tr><td>66.0</td><td>12.036</td><td>11.962</td></tr><tr><td>72.0</td><td>12.033</td><td>11.960</td></tr><tr><td>75.0</td><td>12.031</td><td>11.959</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	33.0	12.070	11.969	36.0	12.064	11.970	42.0	12.055	11.970	48.0	12.049	11.969	54.0	12.044	11.967	60.0	12.040	11.965	66.0	12.036	11.962	72.0	12.033	11.960	75.0	12.031	11.959	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
33.0	12.070	11.969																																								
36.0	12.064	11.970																																								
42.0	12.055	11.970																																								
48.0	12.049	11.969																																								
54.0	12.044	11.967																																								
60.0	12.040	11.965																																								
66.0	12.036	11.962																																								
72.0	12.033	11.960																																								
75.0	12.031	11.959																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Object		-12V0.25A																																								
1. Graph		2. Values																																								
<div><div>-----□----- Load 50%</div><div>-----△----- Load 100%</div></div> <div><div>[V]</div><div>Output Voltage</div><div>Input Voltage [V]</div></div>		<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>33.0</td><td>-12.053</td><td>-11.942</td></tr><tr><td>36.0</td><td>-12.049</td><td>-11.946</td></tr><tr><td>42.0</td><td>-12.042</td><td>-11.949</td></tr><tr><td>48.0</td><td>-12.037</td><td>-11.951</td></tr><tr><td>54.0</td><td>-12.033</td><td>-11.950</td></tr><tr><td>60.0</td><td>-12.029</td><td>-11.950</td></tr><tr><td>66.0</td><td>-12.026</td><td>-11.948</td></tr><tr><td>72.0</td><td>-12.023</td><td>-11.946</td></tr><tr><td>75.0</td><td>-12.021</td><td>-11.945</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	33.0	-12.053	-11.942	36.0	-12.049	-11.946	42.0	-12.042	-11.949	48.0	-12.037	-11.951	54.0	-12.033	-11.950	60.0	-12.029	-11.950	66.0	-12.026	-11.948	72.0	-12.023	-11.946	75.0	-12.021	-11.945	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
33.0	-12.053	-11.942																																								
36.0	-12.049	-11.946																																								
42.0	-12.042	-11.949																																								
48.0	-12.037	-11.951																																								
54.0	-12.033	-11.950																																								
60.0	-12.029	-11.950																																								
66.0	-12.026	-11.948																																								
72.0	-12.023	-11.946																																								
75.0	-12.021	-11.945																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Note: Slanted line shows the range of the rated input voltage. (注)斜線は定格入力電圧範囲を示す。																																										

COSEL


Model ZUW64812

Item Efficiency 効率

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
33.0	78.2	81.1
36.0	77.7	82.0
42.0	75.8	82.3
48.0	73.6	81.9
54.0	71.6	80.8
60.0	70.6	80.0
66.0	68.9	78.5
72.0	67.3	77.4
75.0	66.7	76.9
—	—	—
—	—	—
—	—	—

COSEL

Model ZUW64812


Item Load Regulation 静的負荷変動

Temperature 25°C
Testing Circuitry Figure A

Object +12V0.25A

1. Graph

—△— Input Volt. 36.0V
 - - -□- - - Input Volt. 48.0V
 - - -○- - - Input Volt. 72.0V




2. Values

Load Current [A]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
0.000	12.303	12.307	12.308
0.040	12.128	12.113	12.099
0.080	12.094	12.078	12.062
0.120	12.064	12.049	12.034
0.160	12.036	12.023	12.009
0.200	12.007	11.999	11.987
0.240	11.976	11.974	11.964
0.250	11.968	11.967	11.958
0.275	11.947	11.951	11.945
—	—	—	—

Object -12V0.25A

1. Graph

—△— Input Volt. 36.0V
 - - -□- - - Input Volt. 48.0V
 - - -○- - - Input Volt. 72.0V




2. Values

Load Current [A]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
0.000	-12.312	-12.313	-12.312
0.040	-12.118	-12.104	-12.091
0.080	-12.080	-12.067	-12.053
0.120	-12.048	-12.037	-12.023
0.160	-12.017	-12.010	-11.998
0.200	-11.986	-11.983	-11.974
0.240	-11.952	-11.956	-11.951
0.250	-11.943	-11.948	-11.945
0.275	-11.921	-11.931	-11.930
—	—	—	—

Note: Slanted line shows the range of the rated
load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL



LOVEL

Model	ZUW64812
Item	Ripple-Noise リップルノイズ
Object	+12V0.25A

Temperature	25℃
Testing Circuitry	Figure A

1. Graph

-----□----- Input Volt. 36.0V
 -----△----- Input Volt. 72.0V

[mV]

Ripple-Noise

Load Current [A]

2. Values

Load current [A]	Input Volt. 36.0 [V]	Input Volt. 72.0 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.000	15	15
0.040	15	15
0.080	20	15
0.120	20	20
0.160	20	20
0.200	25	20
0.240	25	20
0.250	25	20
0.275	25	20
—	—	—
—	—	—


Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p-p 値で示される。
 (注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
 入力商用周期
 T2: Due to Switching
 スイッチング周期

Fig. Complex Ripple Wave Form
 図 リップル波形詳細図

COSEL



COSEL

Model ZUW64812		Temperature 25°C																																																								
Item Overcurrent Protection 過電流保護		Testing Circuitry Figure A																																																								
Object +12V0.25A																																																										
1. Graph <div> </div>		2. Values <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th><th>Input Volt. 36.0[V]</th><th>Input Volt. 48.0[V]</th><th>Input Volt. 72.0[V]</th></tr> <tr> <th>Load Current [A]</th><th>Load Current [A]</th><th>Load Current [A]</th></tr> </thead> <tbody> <tr><td>12.00</td><td>0.194</td><td>0.183</td><td>0.161</td></tr> <tr><td>11.40</td><td>0.480</td><td>0.537</td><td>0.438</td></tr> <tr><td>10.80</td><td>0.497</td><td>0.545</td><td>0.435</td></tr> <tr><td>9.60</td><td>0.531</td><td>0.561</td><td>0.421</td></tr> <tr><td>8.40</td><td>0.558</td><td>0.569</td><td>0.402</td></tr> <tr><td>7.20</td><td>0.584</td><td>0.569</td><td>0.376</td></tr> <tr><td>6.00</td><td>0.600</td><td>0.553</td><td>0.343</td></tr> <tr><td>4.80</td><td>0.605</td><td>0.526</td><td>0.314</td></tr> <tr><td>3.60</td><td>0.594</td><td>0.477</td><td>0.293</td></tr> <tr><td>2.40</td><td>0.574</td><td>0.427</td><td>0.292</td></tr> <tr><td>1.20</td><td>0.561</td><td>0.405</td><td>0.327</td></tr> <tr><td>0.00</td><td>0.661</td><td>0.498</td><td>0.444</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	12.00	0.194	0.183	0.161	11.40	0.480	0.537	0.438	10.80	0.497	0.545	0.435	9.60	0.531	0.561	0.421	8.40	0.558	0.569	0.402	7.20	0.584	0.569	0.376	6.00	0.600	0.553	0.343	4.80	0.605	0.526	0.314	3.60	0.594	0.477	0.293	2.40	0.574	0.427	0.292	1.20	0.561	0.405	0.327	0.00	0.661	0.498	0.444
Output Voltage [V]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]																																																							
	Load Current [A]	Load Current [A]	Load Current [A]																																																							
12.00	0.194	0.183	0.161																																																							
11.40	0.480	0.537	0.438																																																							
10.80	0.497	0.545	0.435																																																							
9.60	0.531	0.561	0.421																																																							
8.40	0.558	0.569	0.402																																																							
7.20	0.584	0.569	0.376																																																							
6.00	0.600	0.553	0.343																																																							
4.80	0.605	0.526	0.314																																																							
3.60	0.594	0.477	0.293																																																							
2.40	0.574	0.427	0.292																																																							
1.20	0.561	0.405	0.327																																																							
0.00	0.661	0.498	0.444																																																							
Object -12V0.25A																																																										
1. Graph <div> </div>		2. Values <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th><th>Input Volt. 36.0[V]</th><th>Input Volt. 48.0[V]</th><th>Input Volt. 72.0[V]</th></tr> <tr> <th>Load Current [A]</th><th>Load Current [A]</th><th>Load Current [A]</th></tr> </thead> <tbody> <tr><td>-12.00</td><td>0.165</td><td>0.090</td><td>0.072</td></tr> <tr><td>-11.40</td><td>0.491</td><td>0.548</td><td>0.450</td></tr> <tr><td>-10.80</td><td>0.508</td><td>0.558</td><td>0.445</td></tr> <tr><td>-9.60</td><td>0.541</td><td>0.571</td><td>0.433</td></tr> <tr><td>-8.40</td><td>0.571</td><td>0.579</td><td>0.412</td></tr> <tr><td>-7.20</td><td>0.594</td><td>0.579</td><td>0.387</td></tr> <tr><td>-6.00</td><td>0.611</td><td>0.564</td><td>0.354</td></tr> <tr><td>-4.80</td><td>0.615</td><td>0.535</td><td>0.325</td></tr> <tr><td>-3.60</td><td>0.604</td><td>0.487</td><td>0.303</td></tr> <tr><td>-2.40</td><td>0.584</td><td>0.434</td><td>0.302</td></tr> <tr><td>-1.20</td><td>0.571</td><td>0.415</td><td>0.340</td></tr> <tr><td>0.00</td><td>0.683</td><td>0.517</td><td>0.460</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	-12.00	0.165	0.090	0.072	-11.40	0.491	0.548	0.450	-10.80	0.508	0.558	0.445	-9.60	0.541	0.571	0.433	-8.40	0.571	0.579	0.412	-7.20	0.594	0.579	0.387	-6.00	0.611	0.564	0.354	-4.80	0.615	0.535	0.325	-3.60	0.604	0.487	0.303	-2.40	0.584	0.434	0.302	-1.20	0.571	0.415	0.340	0.00	0.683	0.517	0.460
Output Voltage [V]	Input Volt. 36.0[V]	Input Volt. 48.0[V]	Input Volt. 72.0[V]																																																							
	Load Current [A]	Load Current [A]	Load Current [A]																																																							
-12.00	0.165	0.090	0.072																																																							
-11.40	0.491	0.548	0.450																																																							
-10.80	0.508	0.558	0.445																																																							
-9.60	0.541	0.571	0.433																																																							
-8.40	0.571	0.579	0.412																																																							
-7.20	0.594	0.579	0.387																																																							
-6.00	0.611	0.564	0.354																																																							
-4.80	0.615	0.535	0.325																																																							
-3.60	0.604	0.487	0.303																																																							
-2.40	0.584	0.434	0.302																																																							
-1.20	0.571	0.415	0.340																																																							
0.00	0.683	0.517	0.460																																																							
Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。																																																										

COSEL

Model	ZUW64812	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	+12V0.25A	

Input Volt. 48.0 V


Cycle 100 mS

Load Current

Min. Load ←→

Load 100 %


200 mV/div



Min. Load ←→

Load 50 %


200 mV/div



Load 50%←→

Load 100 %

200 mV/div



1 mS/div

COSEL

Model	ZUW64812	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	-12V0.25A	

Input Volt. 48.0 V


Cycle 100 mS

Load Current

Min. Load ←→

Load 100 %


200 mV/div



Min. Load ←→

Load 50 %


200 mV/div



Load 50% ←→

Load 100 %

200 mV/div




1 mS/div

COSEL

Model	ZUW64812	Temperature	25℃
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+12V0.25A		

1. Graph


Input Volt. 36.0 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.05	0.95	1.00	0.20	1.95
100 %	0.05	1.05	1.10	0.14	1.10




COSEL

Model	ZUW64812	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	-12V0.25A		

1. Graph


Input Volt. 36.0 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.05	0.90	0.95	0.21	1.89
100 %	0.05	1.00	1.05	0.15	1.06



COSEL


Model	ZUW64812	Testing Circuitry Figure A																																																	
Item	Ambient Temperature Drift 周囲温度変動																																																		
Object	+12V0.25A																																																		
1. Graph	<div> <div> <div>△</div> <div>Input Volt. 36.0V</div> </div> <div> <div>□</div> <div>Input Volt. 48.0V</div> </div> <div> <div>○</div> <div>Input Volt. 72.0V</div> </div> </div>	2. Values	<table> <tr> <th>Temperature [°C]</th><th>Input Volt. 36.0[V] Output Volt. [V]</th><th>Input Volt. 48.0[V] Output Volt. [V]</th><th>Input Volt. 72.0[V] Output Volt. [V]</th></tr> <tr><td>-30</td><td>11.982</td><td>11.979</td><td>11.970</td></tr> <tr><td>-20</td><td>11.979</td><td>11.977</td><td>11.968</td></tr> <tr><td>-10</td><td>11.977</td><td>11.975</td><td>11.966</td></tr> <tr><td>0</td><td>11.975</td><td>11.973</td><td>11.965</td></tr> <tr><td>10</td><td>11.973</td><td>11.972</td><td>11.964</td></tr> <tr><td>25</td><td>11.972</td><td>11.970</td><td>11.961</td></tr> <tr><td>30</td><td>11.972</td><td>11.970</td><td>11.961</td></tr> <tr><td>40</td><td>11.971</td><td>11.970</td><td>11.961</td></tr> <tr><td>55</td><td>11.971</td><td>11.971</td><td>11.962</td></tr> <tr><td>60</td><td>11.971</td><td>11.971</td><td>11.962</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </table>	Temperature [°C]	Input Volt. 36.0[V] Output Volt. [V]	Input Volt. 48.0[V] Output Volt. [V]	Input Volt. 72.0[V] Output Volt. [V]	-30	11.982	11.979	11.970	-20	11.979	11.977	11.968	-10	11.977	11.975	11.966	0	11.975	11.973	11.965	10	11.973	11.972	11.964	25	11.972	11.970	11.961	30	11.972	11.970	11.961	40	11.971	11.970	11.961	55	11.971	11.971	11.962	60	11.971	11.971	11.962	—	—	—	—
Temperature [°C]	Input Volt. 36.0[V] Output Volt. [V]	Input Volt. 48.0[V] Output Volt. [V]	Input Volt. 72.0[V] Output Volt. [V]																																																
-30	11.982	11.979	11.970																																																
-20	11.979	11.977	11.968																																																
-10	11.977	11.975	11.966																																																
0	11.975	11.973	11.965																																																
10	11.973	11.972	11.964																																																
25	11.972	11.970	11.961																																																
30	11.972	11.970	11.961																																																
40	11.971	11.970	11.961																																																
55	11.971	11.971	11.962																																																
60	11.971	11.971	11.962																																																
—	—	—	—																																																
Object	-12V0.25A	Testing Circuitry Figure A																																																	
1. Graph	<div> <div>△</div> <div>Input Volt. 36.0V</div> </div> <div> <div>□</div> <div>Input Volt. 48.0V</div> </div> <div> <div>○</div> <div>Input Volt. 72.0V</div> </div>	2. Values	<table> <tr> <th>Temperature [°C]</th><th>Input Volt. 36.0[V] Output Volt. [V]</th><th>Input Volt. 48.0[V] Output Volt. [V]</th><th>Input Volt. 72.0[V] Output Volt. [V]</th></tr> <tr><td>-30</td><td>-11.941</td><td>-11.948</td><td>-11.949</td></tr> <tr><td>-20</td><td>-11.942</td><td>-11.949</td><td>-11.949</td></tr> <tr><td>-10</td><td>-11.944</td><td>-11.950</td><td>-11.950</td></tr> <tr><td>0</td><td>-11.945</td><td>-11.951</td><td>-11.950</td></tr> <tr><td>10</td><td>-11.946</td><td>-11.952</td><td>-11.950</td></tr> <tr><td>25</td><td>-11.947</td><td>-11.952</td><td>-11.948</td></tr> <tr><td>30</td><td>-11.948</td><td>-11.952</td><td>-11.948</td></tr> <tr><td>40</td><td>-11.947</td><td>-11.952</td><td>-11.947</td></tr> <tr><td>55</td><td>-11.947</td><td>-11.952</td><td>-11.947</td></tr> <tr><td>60</td><td>-11.946</td><td>-11.952</td><td>-11.947</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </table>	Temperature [°C]	Input Volt. 36.0[V] Output Volt. [V]	Input Volt. 48.0[V] Output Volt. [V]	Input Volt. 72.0[V] Output Volt. [V]	-30	-11.941	-11.948	-11.949	-20	-11.942	-11.949	-11.949	-10	-11.944	-11.950	-11.950	0	-11.945	-11.951	-11.950	10	-11.946	-11.952	-11.950	25	-11.947	-11.952	-11.948	30	-11.948	-11.952	-11.948	40	-11.947	-11.952	-11.947	55	-11.947	-11.952	-11.947	60	-11.946	-11.952	-11.947	—	—	—	—
Temperature [°C]	Input Volt. 36.0[V] Output Volt. [V]	Input Volt. 48.0[V] Output Volt. [V]	Input Volt. 72.0[V] Output Volt. [V]																																																
-30	-11.941	-11.948	-11.949																																																
-20	-11.942	-11.949	-11.949																																																
-10	-11.944	-11.950	-11.950																																																
0	-11.945	-11.951	-11.950																																																
10	-11.946	-11.952	-11.950																																																
25	-11.947	-11.952	-11.948																																																
30	-11.948	-11.952	-11.948																																																
40	-11.947	-11.952	-11.947																																																
55	-11.947	-11.952	-11.947																																																
60	-11.946	-11.952	-11.947																																																
—	—	—	—																																																
Note: Slanted line shows the range of the rated ambient temperature. (注)斜線は定格周囲温度範囲を示す。																																																			

COSEL

Model ZUW64812

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +12V0.25A


1. Graph
[V]
-----□----- Load 50%
-----△----- Load 100%

Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	26.6	28.1
-20	25.6	27.6
-10	25.1	26.6
0	24.6	26.1
10	24.1	25.6
25	23.1	25.1
30	23.1	24.6
40	22.5	24.1
55	21.5	24.0
60	21.5	24.0
—	—	—

Object -12V0.25A

[V]
-----□----- Load 50%
-----△----- Load 100%

2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	26.6	28.1
-20	25.6	27.6
-10	25.1	26.6
0	24.6	26.1
10	24.1	25.6
25	23.1	25.1
30	23.1	24.6
40	22.5	24.1
55	21.5	24.0
60	21.5	24.0
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model		ZUW64812																																					
Item		Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)																																					
Object		+12V0.25A																																					
1. Graph		2. Values																																					
<div><div><div>-----□-----</div><div>Load 50%</div></div><div><div>-----△-----</div><div>Load 100%</div></div></div> <div><div>[mV]</div><div>50</div><div>40</div><div>30</div><div>20</div><div>10</div><div>0</div></div> <div><div>Ripple Voltage</div></div> <div><div>-40</div><div>-20</div><div>0</div><div>20</div><div>40</div><div>60</div></div> <div><div>Ambient Temperature</div><div>[°C]</div></div> <div>Input Volt. 36.0 V</div>		<table><tr><th>Ambient Temp. [°C]</th><th>Load 50% Ripple Output Volt. [mV]</th><th>Load 100% Ripple Output Volt. [mV]</th></tr><tr><td>-30</td><td>10</td><td>20</td></tr><tr><td>-20</td><td>10</td><td>15</td></tr><tr><td>-10</td><td>5</td><td>15</td></tr><tr><td>0</td><td>5</td><td>15</td></tr><tr><td>10</td><td>5</td><td>10</td></tr><tr><td>25</td><td>5</td><td>10</td></tr><tr><td>30</td><td>5</td><td>10</td></tr><tr><td>40</td><td>5</td><td>10</td></tr><tr><td>55</td><td>5</td><td>10</td></tr><tr><td>60</td><td>5</td><td>10</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-30	10	20	-20	10	15	-10	5	15	0	5	15	10	5	10	25	5	10	30	5	10	40	5	10	55	5	10	60	5	10	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																					
-30	10	20																																					
-20	10	15																																					
-10	5	15																																					
0	5	15																																					
10	5	10																																					
25	5	10																																					
30	5	10																																					
40	5	10																																					
55	5	10																																					
60	5	10																																					
—	—	—																																					
Object		-12V0.25A																																					
1. Graph		2. Values																																					
<div><div><div>-----□-----</div><div>Load 50%</div></div><div><div>-----△-----</div><div>Load 100%</div></div></div> <div><div>50</div><div>40</div><div>30</div><div>20</div><div>10</div><div>0</div></div> <div><div>Ripple Voltage</div></div> <div><div>-40</div><div>-20</div><div>0</div><div>20</div><div>40</div><div>60</div></div> <div><div>Ambient Temperature</div><div>[°C]</div></div> <div>Input Volt. 36.0 V</div> <div>Note: Slanted line shows the range of the rated ambient temperature.</div> <div>(注)斜線は定格周囲温度範囲を示す。</div>		<table><tr><th>Ambient Temp. [°C]</th><th>Load 50% Ripple Output Volt. [mV]</th><th>Load 100% Ripple Output Volt. [mV]</th></tr><tr><td>-30</td><td>10</td><td>20</td></tr><tr><td>-20</td><td>10</td><td>20</td></tr><tr><td>-10</td><td>5</td><td>15</td></tr><tr><td>0</td><td>5</td><td>10</td></tr><tr><td>10</td><td>5</td><td>10</td></tr><tr><td>25</td><td>5</td><td>10</td></tr><tr><td>30</td><td>5</td><td>10</td></tr><tr><td>40</td><td>5</td><td>10</td></tr><tr><td>55</td><td>5</td><td>10</td></tr><tr><td>60</td><td>5</td><td>10</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-30	10	20	-20	10	20	-10	5	15	0	5	10	10	5	10	25	5	10	30	5	10	40	5	10	55	5	10	60	5	10	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																					
-30	10	20																																					
-20	10	20																																					
-10	5	15																																					
0	5	10																																					
10	5	10																																					
25	5	10																																					
30	5	10																																					
40	5	10																																					
55	5	10																																					
60	5	10																																					
—	—	—																																					

COSEL

COSEL																							
Model	ZUW64812																						
Item	Time Lapse Drift 経時ドリフト																						
Object	+12V0.25A																						
1. Graph																							
<div><div><div>Output Voltage</div><div>[V]</div><div><div>12.04</div><div>12.02</div><div>12.00</div><div>11.98</div><div>11.96</div><div>11.94</div><div>11.92</div><div>0</div></div><div><div>0</div><div>1</div><div>2</div><div>3</div><div>4</div><div>5</div><div>6</div><div>7</div><div>8</div><div>9</div><div>10</div></div><div>Time</div><div>[H]</div></div><div><div>Input Volt.</div><div>48.0V</div><div>Load</div><div>100%</div></div></div>																							
2. Values																							
<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>11.972</td></tr><tr><td>0.5</td><td>11.971</td></tr><tr><td>1.0</td><td>11.971</td></tr><tr><td>2.0</td><td>11.971</td></tr><tr><td>3.0</td><td>11.971</td></tr><tr><td>4.0</td><td>11.971</td></tr><tr><td>5.0</td><td>11.971</td></tr><tr><td>6.0</td><td>11.971</td></tr><tr><td>7.0</td><td>11.971</td></tr><tr><td>8.0</td><td>11.971</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	11.972	0.5	11.971	1.0	11.971	2.0	11.971	3.0	11.971	4.0	11.971	5.0	11.971	6.0	11.971	7.0	11.971	8.0	11.971
Time since start [H]	Output Voltage [V]																						
0.0	11.972																						
0.5	11.971																						
1.0	11.971																						
2.0	11.971																						
3.0	11.971																						
4.0	11.971																						
5.0	11.971																						
6.0	11.971																						
7.0	11.971																						
8.0	11.971																						
Object-12V0.25A																							
1. Graph																							
<div><div><div>Output Voltage</div><div>[V]</div><div><div>-12.02</div><div>-12.00</div><div>-11.98</div><div>-11.96</div><div>-11.94</div><div>-11.92</div><div>-11.90</div><div>0</div></div><div><div>0</div><div>1</div><div>2</div><div>3</div><div>4</div><div>5</div><div>6</div><div>7</div><div>8</div><div>9</div><div>10</div></div><div>Time</div><div>[H]</div></div><div><div>Input Volt.</div><div>48.0V</div><div>Load</div><div>100%</div></div></div>																							
2. Values																							
<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-11.953</td></tr><tr><td>0.5</td><td>-11.951</td></tr><tr><td>1.0</td><td>-11.951</td></tr><tr><td>2.0</td><td>-11.951</td></tr><tr><td>3.0</td><td>-11.951</td></tr><tr><td>4.0</td><td>-11.951</td></tr><tr><td>5.0</td><td>-11.951</td></tr><tr><td>6.0</td><td>-11.951</td></tr><tr><td>7.0</td><td>-11.951</td></tr><tr><td>8.0</td><td>-11.951</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-11.953	0.5	-11.951	1.0	-11.951	2.0	-11.951	3.0	-11.951	4.0	-11.951	5.0	-11.951	6.0	-11.951	7.0	-11.951	8.0	-11.951
Time since start [H]	Output Voltage [V]																						
0.0	-11.953																						
0.5	-11.951																						
1.0	-11.951																						
2.0	-11.951																						
3.0	-11.951																						
4.0	-11.951																						
5.0	-11.951																						
6.0	-11.951																						
7.0	-11.951																						
8.0	-11.951																						

COSEL

LOREL

Model		ZUW64812	Testing Circuitry Figure A	
Item		Condensation 結露特性		
Object		+12V 0.25A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 26℃ and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で－１０℃に冷却しておき、約１時間後に恒温槽から取り出し、室温２６℃、湿度４０％RHの状態におき結露させ、その電気的特性の測定を３度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	12.098	5	30
	2	12.095	5	30
	3	12.098	5	30
Load 100 %	1	12.005	10	35
	2	12.003	10	35
	3	12.008	10	35

Input Volt. 48.0 V

- 18 -

BC-2061

COSEL

LOREL

Model	ZUW64812		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	-12V 0.25A		

1. Condensation test

Testing procedure is as follows.

① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off.

② Taking it out of the tank and dewing itself in a room where the temperature is 26℃ and the humidity is 40%RH.

③ Testing electrical characteristics of the unit to confirm there be no fault.

④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で- 1 0℃に冷却しておき、約1時間後に恒温槽から取り出し、室温2 6℃、湿度4 0 %RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	-12.097	5	30
	2	-12.104	5	30
	3	-12.101	5	30
Load 100 %	1	-12.005	10	35
	2	-12.007	10	35
	3	-12.001	10	35

Input Volt. 48.0 V

COSEL

